

THE DISPLAY CHOICE OF PROFESSIONALS

LA-Series LCD Monitor 22" | 24" | 27"



Eye comfort characterises the LA-Series, an array of displays crafted to accommodate daily usage. Multiple connectivity options—DisplayPort, HDMI, and VGA—and hence diverse multimedia applications are complemented by the flexibility of settling for a 4:3 or 16:9 aspect ratio. Also featuring a wide viewing angle, an outstanding contrast ratio, and exceptional colour performance, they promise to deliver a pleasantly rewarding visual experience either at work or at home.








Eye Comfort

Eye comfort figures high on the list of strengths that define the LA-Series. The flicker-free backlight and blue light filter of the LA-Series ensure a comfortable viewing experience by reducing eyestrain after long periods of use. A finely tuned overdrive circuit greatly reduces ghosting and blurring to ensure videos look clean and sharp.

Flexible Connectivity and Multimedia Options

Connectivity versatility brings immense flexibility. Given its HDMI, DisplayPort, and VGA input options, you can easily connect an LA-Series display to your current or older peripherals, like PCs, laptops, or media players at the workplace or home.







Audiovisual Multimedia Enjoyment

A 20,000,000:1 contrast ratio, precise colour temperature and preset picture mode settings for reading texts, browsing webpages, or watching videos make the LA-Series a competent multimedia platform. Whether watching videos or listening to music, you can either count on its built-in speakers or plug in your earphones.

Features

- Full HD 1920 x 1080 resolution
- Crisp 20,000,000:1 dynamic contrast ratio
- DisplayPort and HDMI inputs for Full HD connectivity with a variety of devices
- Blue-light filter and Flicker-free display technology reduces eye discomfort
- Selectable aspect ratio
- Built-in speakers and audio mini-jack in/out connection
- VESA mount compatibility for flexible installation



THE DISPLAY CHOICE OF PROFESSIONALS

| Specifications | |
|----------------|--|
| D1 | |

Panel

Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time Frequency Frequency (H) Frequency (V) Signal Input DisplayPort HDMI VGA Audio Audio In Audio Out Internal Speakers Power Power Supply Power Requirements On Mode Standby Mode Off Mode **Operating Conditions** Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Stand Tilt Security Kensington Security Slot Dimensions

Product with Base (W x H x D)

Product w/o Base (W x H x D)

Packaging (W x H x D)

Product with Base

Regulation Approval Certifications & Compliance

Wall Mount (Landscape only)

Desk Mount (Landscape only)

Weight Product w/o Base

Packaging

Accessories

Supplied **Optional Accessories** Ceiling Mount (Landscape only)

LA-22 LED 21.5 FHD 0.24 300 20.0 170° 16.7 3 ms 30 k 56 H x 1 1.3 15-F Ster Ster 2W Inte AC 16W < 0. < 0.3 5°C-20% -20° 5%-Yes -5° t

LA-24

LA-27

| LED-Backlit TFT LCD (TN Technology) | LED-Backlit TFT LCD (IPS Technology) | LED-Backlit TFT LCD (IPS Technology) |
|---|---|---|
| 21.5" | 23.8" | 27.0" |
| FHD 1920 x 1080 | FHD 1920 x 1080 | FHD 1920 x 1080 |
| 0.248 mm | 0.275 mm | 0.314 mm |
| 300 cd/m ² | 270 cd/m² | 250 cd/m ² |
| 20,000,000:1 (DCR) | 20,000,000:1 (DCR) | 20,000,000:1 (DCR) |
| 170°/160° | 178°/178° | 178°/178° |
| 16.7M | 16.7M | 16.7M |
| 3 ms | 5 ms | 5 ms |
| | | |
| 30 kHz-83 KHz | 30 kHz-83 KHz | 30 kHz-83 KHz |
| 56 Hz-75 Hz | 56 Hz-75 Hz | 56 Hz-75 Hz |
| | | |
| x 1 | x 1 | x 1 |
| 1.3 x 1 | 1.3 x 1 | 1.3 x 1 |
| 15-Pin D-Sub x 1 | 15-Pin D-Sub x 1 | 15-Pin D-Sub x 1 |
| | | |
| Stereo Audio Jack (3.5 mm) | Stereo Audio Jack (3.5 mm) | Stereo Audio Jack (3.5 mm) |
| Stereo Audio Jack (3.5 mm) | Stereo Audio Jack (3.5 mm) | Stereo Audio Jack (3.5 mm) |
| 2W x 2 | 2W x 2 | 2W x 2 |
| I-4 | I-+ | Indowe al |
| Internal AC 100-240V, 50/60 Hz | Internal | Internal |
| 16W (On) | AC 100-240V, 50/60 Hz 18W (On) | AC 100-240V, 50/60 Hz 17W (On) |
| < 0.5W | < 0.5W | < 0.5W |
| < 0.3W | < 0.3W | < 0.3W |
| < 0.5 W | < 0.5W | < 0.5W |
| 5°C- 35°C (41°F-95°F) | 5°C- 35°C (41°F-95°F) | 0°C- 40°C (32°F-104°F) |
| 20%-85% (non-condensing) | 20%-85% (non-condensing) | 10%-85% (non-condensing) |
| | | |
| -20°C-60°C (-4°F-140°F) | -20°C-60°C (-4°F-140°F) | -20°C-60°C (-4°F-140°F) |
| 5%-85% (non-condensing) | 5%-85% (non-condensing) | 5%-85% (non-condensing) |
| | | |
| Yes (100 x 100 mm) | Yes (100 x 100 mm) | Yes (100 x 100 mm) |
| | | |
| -5° to 15° | -5° to 20° | -5° to 20° |
| | | |
| Yes | Yes | Yes |
| | | |
| 511.0 x 377.0 x 183.0 mm (20.1" x 14.8" x 7.2") | 555.0 x 433.0 x 226.0 mm (21.9" x 17.0" x 8.9") | 612.0 x 452.0 x 226.0 mm (24.1" x 17.8" x 8.9") |
| 511.0 x 313.0 x 46.0 mm (20.1" x 12.3" x 1.8") | 555.0 x 339.0 x 46.0 mm (21.9" x 13.3" x 1.8") | 612.0 x 365.0 x 46.0 mm (24.1" x 14.4" x 1.8") |
| 561.0 x 426.0 x 103.0 mm (22.1" x 16.8" x 4.1") | 620.0 x 418.0 x 157.0 mm (24.4" x 16.5" x 6.2") | 678.0 x 545.0 x 134 mm (26.7" x 21.5" x 5.3") |
| | | |
| 3.1 kg (6.8 lb) | 3.1 kg (6.8 lb) | 3.8 kg (8.4 lb) |
| 3.4 kg (7.5 lb) | 3.5 kg (7.7 lb) | 4.3 kg (9.5 lb) |
| 4.6 kg (10.1 lb) | 5.0 kg (11.0 lb) | 5.9 kg (13.0 lb) |
| OF LUD FOO WEFE D-UO DELOU DOUT | CE LUD FOC DOM WEEP D VC DEACH | OF LUD WEEF D-UC DEACH OCO ON TOO |
| CE, LVD, FCC, WEEE, RoHS, REACH, BSMI | CE, LVD, FCC, BSMI, WEEE, RoHS, REACH | CE, LVD, WEEE, RoHS, REACH, CCC, CEL, FCC |
| Power Cord VCA Cable Audio Cable Ouist Start | Power Cord VCA Cable Audio Cable Ouigh Start | Power Cord, VGA Cable, Audio Cable, Quick Start |
| Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card | Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card | Guide, Warranty Card |
| | | |
| CMP-01+WMK-03 | CMP-01+WMK-03 | CMP-01+WMK-03 |
| WMA-01, WMK-01, WMK-03, PMK-01 | WMA-01, WMK-01, WMK-03, PMK-01 | WMA-01, WMK-01, WMK-03, PMK-01 |
| DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 | DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 | DMC-01, ES-02 |



Global Headquarters Taipei, Taiwan

EMEA Regional Headquarters Capelle a/d Ijssel, The Netherlands

North & South America Regional Headquarters San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters Taipei, Taiwan

Canada Sales Office Vancouver, B.C., Canada

China Sales Office Shanghai, China

Czech Republic Sales Office Brno, Czech Republic

Denmark Sales Office Støvring, Denmark

Germany Sales Office Mechernich, Germany

Italy Sales Office Livorno, Italy

Poland Sales Office Warsaw, Poland

Spain Sales Office Barcelona, Spain

Ukraine Sales Office Lviv, Ukraine

www.agneovo.com

