

G2260VWQ6

21.5 inch (54.6 cm) LCD MONITOR

No stuttering, no tearing, just gaming.





1ms Response Time

A pixel response time of 1ms GTG means speed without the smear for an enhanced experience. Fast-moving action and dramatic transitions will be rendered smoothly without the effects of ghosting.



FreeSync

Whatever your setup, achieve the highest framerate and smoothest display possible via AMD Free-Sync Technology. Whether you're dashing through explosions or screeching around rain slicked bends, wave goodbye to screen tearing and lag – and leave your opponents in your smoothly rendered dust.



DisplayPort Connection

The most recent display interface standard from VESA, DisplayPort can also transfer audio, USB and other forms of data. DisplayPort version 1.2-1.2a support up to 165 Hz@1440p, 75 Hz@2160p, version 1.3 supports up to 240Hz@1440p, 120 Hz@2160p and the version 1.4 supports HDR10 specifications.



Display Port

The most recent display interface standard from VESA, DisplayPort can also transfer audio, USB and other forms of data. DisplayPort version 1.2-1.2a support up to 165 Hz@1440p, 75 Hz@2160p, version 1.3 supports up to 240Hz@1440p, 120 Hz@2160p and the version 1.4 supports HDR10 specifications.

General

Carton Dimensions (mm)

693x127x435 mm

Screen Details

Color	Black
Resolution	1920x1080 PX
Refresh rate	75Hz
Response time	1 ms
Panel	TN
Backlight	WLED
flickerfree	1
Aspect ratio	16:9
Brightness (typical)	250 cd/m ²
Contrast (dynamic)	20M:1
Contrast (static)	1000:1
Pixel Pitch (H) (V)	0.248
Diagonal (inch)	21.5 inch
Active Screen Area (WxH) (mm)	477,5x268,5 mm mm
Viewing angle (CR10)	170/160 ^o
Display Colours	16.7 Million
Scanning Frequency	30-83khz/48-76Hz
OSD languages	EN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN (S), JP

Connections

Signal Input

HDMI 1.4 x 1, VGA, DisplayPort 1.2 x 1

What's in the box

Sustainability

• Environmental and energy: RoHS, Lead-free, Mercury Free

Recyclable packaging material: 100 %

Ergonomics

Tilt	-5/20 °
Vesa Wallmount	100x100

Power details

Powersupply	Internal
Powersource	100 - 240V 50/60Hz
Power Consumption	On 20 watt, Off 0.3 watt Standby 0.5 watt,

Dimensions

Product Dimensions (incl base) (mm)	511.8x376.9x184.4 mm
Carton Dimensions (mm)	693x127x435 mm
Net Weight (excl package) (kg)	3.03 Kg
Gross Weight (incl package) (kg)	4.15 Kg

Warranty

Warranty Period	3 Years
EAN	4038986125314
MTBF	50.000 hours

Regulations

TUV-GS 1, TUV-Bauart 1, CE 1, TCO 6, energystar 1, FCC 1, EAC 1, ISO 9241-307 class I 1, Rohs compliant 1,

