

DHI-LM32-P301A

31.5" QHD Monitor



Features:

- The 2560*1440 resolution produces clearer and more vivid pictures:
- \cdot IPS panel for wide viewing angles with 3-sided frameless design;
- \cdot 178°H/178°V extra-wide viewing angle for overall viewing performance;
- \cdot The 10bit(1.70B colors) panel has 99% sRGB, 100% NTSC, 95% DCI-P3, 92% Adobe RGB color gamut. It meets the designer's pursuit of image texture;
- · Rich interfaces, 65W type-C can support reverse charging;
- \cdot 4ms fast response time with no image blurring or ghosting.
- \cdot Supporting PIP/PBP to display the screens of two devices on the display simultaneously.
- \cdot The angle can be adjusted to meet different needs.

Technical Specification

V	0	d	е	l
---	---	---	---	---

Model	DHI-LM32-P301A	
Display		
Screen Size	31.5"	
Panel type	IPS	
Aspect Ratio	16:9	
Resolution	2560x1440	
Backlight	E-LED	
Brightness/Luminance	350nits(typ)	
Contrast Ratio	1200:1	
Color Support	99% sRGB, 100% NTSC, 95% DCI-P3, 92% Adobe RGB	
Viewing Angle(H/V)	178°(H)/178°(V)	
Response time	4ms (OD)	
Refresh Rate	75Hz	
Signals		
Interface	DP1.4×1, HDMI 2.1×1, Type C 65W×1, Audio out×1	
General		
Power Supply	DC 19V 7.89A	

Power Type	Adapter			
Consumption (Standard)	Typ. 52W, Max. 145W			
Consumption (Standby)	≤0.5W			
Net Weight	7.7kg			
Gross Weight	10.69kg			
Tilt Angles	-5° ±2° ~15° ±2°			
Swivel(angle)	15°			
Pivot(angle/direction)	0°~180°			
Height Adjustment	100+/-5mm			
VESA	75x75mm			
Dimension(W×H×D)	718.59*422.07*45.10mm(without stand)			
Package(W×H×D)	821x183x530mm			
Work Environment	Temperature	0°~40°(32°F~104°F)		
work environment	Humidity	10%~85%		
Accessory				
Standard	HDMI 1.5m Cable, Power cable,			

Standard HDMI 1.5m Cable, Power cable, Adapter, Stand, Base