

Data Sheet FUJITSU Display B24T-1L

Advanced Display: 61 cm (24-inch) widescreen display Ergonomic height adjustable display for office applications

The FUJITSU Display B24T-1L combines comfortable ergonomics with best-in-class energy saving technology.

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Proven eco-friendliness with TCO Display 6.0, ENERGY STAR® 6.0 and EPEAT® Silver certificate

Representative design providing a slender housing in ergonomic matt black, integrated speakers and power supply





Technical details

Consist features	
Special features	4-in-1 Stand, LED backlight panel, Pivot
Ergonomic stand	4-111-1 Jeanu, LLD Dackilghe panel, Fivol
Stand	4-in-1 Stand
Height adjust range	130 mm
Picture height over desk (min)	95 mm
Rotation to portrait	90°
Tilt angle	-5° / +22°
Swivel angle	320°
Picture performance	
Panel and backlit	TN/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1000:1
Contrast - advanced	20,000,000:1
Response time typical	5 ms
Viewing angle (h/v) - typical	170°/160°
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2
Size and resolution	
Aspect ratio	16:9
Diagonal Size	61 cm (24-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,360 x 768 pixel, 1,280 x 1,024 pixel, 1,280 x 768 pixel, 1,152 x 870 pixel, 1,024 x 768 pixel, 832 x 624 pixel, 800 x 600 pixel, 720 x 400 pixel, 640 x 480 pixel
Picture size	531 x 299 mm
Pixel Pitch	0.277 mm
Frequencies	
Horizontal	30 - 83 kHz
Vertical	55 - 76 Hz
Connectivity	
HDMI	1 x HDMI
DVI	1 x DVI-D (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 2.0 W
HDMI audio	Yes
Ease-of-use menu	
Languages	Arabic, Chinese simply, Czech, Danish, Dutch, English, Finnish, French, German, Hebrew, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Brightness / Contrast	Brightness, Contrast
Mode	General
Color	6500K, 7500K, Custom Color
Image adjust	H-Position, V-Position, Clock, Phase
Audio	Mute, Volume
Information	Model name, Serial number, Resolution/mode, Signal input
Power consumption (typical, w/o sound	
Soft switch off	0.2 W
Power save mode	0.2 W
Operating with EPA settings	18.3 W
Operating maximum brightness	23.2 W

Power supply	integrated			
Power notes	Speakers off			
Electrical values				
Rated voltage range	100 V - 240 V			
Rated frequency range	50 Hz - 60 Hz			
Protection class				
Compliance				
Europe	Energy Efficiency Class: A+, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration			
Model	W2413			
Germany	TÜV GS			
Russia	EAC			
USA/Canada	FCC Class B, cUL, CSA			
Saudi Arabia	SASO			
Global	TCO Displays 6.0, ENERGY STAR® 6.0, ISO9241-307 (Pixel fault class I)			
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates			
Quality and Reliability				
MTBF (demonstrated)	50.000 h			
Dimensions / Weight / Environmental				
Dimension without stand (W x D x H)	565.4 x 56.5 x 339.9 mm			
	22.26 x 2.22 x 13.38 inch			
Dimension with stand (W x D x H)	565.4 x 244.5 x 512.4 mm			
(22.26 inch x 9.63 x 20.17 inch			
Weight (packed)	6.78			
reigne (packed)	14.95 lbs			
Weight (unpacked)	5.26 kg			
reight (unpacked)	11.6 lbs			
Weight (Monitor only)	2.9 kg			
weight (Monitor only)	6.63 lbs			
Operating ambient temperature	0 - 40 °C			
Miscellaneous	0-40 (
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared			
Color	Black			
	DIDLK			
Package content	D#DD + 11 10			
Display delivered accessories	DVI-D Data cable 1.8 m D-SUB Data cable 1.8 m Audio cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Utility CD Warranty booklet Safety booklet			
Display delivered accessories notes	Data cables and audio cable detachable on display			
Order information				
Order Code	S26361-K1558-V160			
EAN Code	4053026802659			
Accessories information	Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf			
Warranty				
Warranty period	3 years (depending on country)			
Warranty type	Collect & Return Service (depending on country specific requirements)			
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty			
Spare Parts availability	5 years after end of product life			
Service Weblink	http://www.fujitsu.com/fts/services/support			
	**			

Data	Sheet	FUJITSU	Display	B24T-1L
Data	Jileet	10)1130	Display	DZTI IL

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display B24T-1L, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display B24T-1L, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/qlobal/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2016-06-22 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2016 Fujitsu Technology Solutions GmbH