

# Data Sheet

## FUJITSU Display B24-8 TE Pro

Advanced display: 60.5 cm (23.8-inch) widescreen  
Best ergonomic and energy saving solutions for office applications

The FUJITSU Display B24-8 TE Pro is made for intensive office work. With visual and mechanical ergonomics this marble-grey display enables fatigue-free working for hours in front of the screen. The large 60.5 cm (23.8-inch) screen allows you to keep always track of all open applications. This high-quality display works unfailingly around the clock. Easy connectivity, manageability and usability help you increase your productivity.

Excellent visual performance with wide viewing angle panel technology

Convenient and fatigue-proof longtime-usage with outstanding visual ergonomics for the office

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Flexible connectivity with DisplayPort, DVI, Analog and USB

Smart design with space saving front frame and smart details like discretely integrated speakers and cable guide for a clean desk

Environment-friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby



# Technical details

## Special features

Low blue light mode, 4-in-1 Stand, cable guide, Eco button for Eco mode and 3-coloured Eco status LED, Pivot, DisplayView™ IT Suite, 24/7 usage

## Ergonomic stand

Stand	4-in-1 Stand
Height adjust range	150 mm
Picture height over desk (min)	40 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	340°

## Picture performance

Panel and backlight	Wide viewing angle technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2

## Size and resolution

Aspect ratio	16:9
Diagonal Size	60.5 cm (23.8-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,366 x 768 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	527 x 296 mm
Pixel Pitch	0.2745 mm

## Frequencies

Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz

## Connectivity

DisplayPort	1 x DisplayPort
DVI	1 x DVI-D (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack for head phone
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 2.0 W
USB downstream	2x USB 2.0
USB upstream	1 x USB

## Ease-of-use menu

Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Mode	D-Mode, sRGB, Office, Photo, Video, Low Blue Light
Color	sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position, Expansion
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Resolution/mode, Signal input
Setup	Input select, Language, DDC-CI, OSD-Timeout, Factory preset

## Power consumption (typical, w/o sound)

Soft switch off	0.16 W
-----------------	--------

Power save mode	0.21 W
Operating with EPA settings	18.3 W
Operating maximum brightness	23 W
Power supply display	integrated
Power notes	Speakers off, without USB
<b>Electrical values</b>	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
<b>Compliance</b>	
Europe	Energy Efficiency Class: A+, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration
Model	B24-8 T
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cTÜVus
Australia/New Zealand	RCM
South Korea	KC
Argentina	TÜV-S
Singapore	S-Mark
Taiwan	BSMI
China	CCC
Saudi Arabia	SASO
Global	TCO Displays 7.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions) (planned), ISO9241-307 (Pixel fault class I)
Compliance link	<a href="http://globalsp.ts.fujitsu.com/sites/certificates">http://globalsp.ts.fujitsu.com/sites/certificates</a>
<b>Quality and Reliability</b>	
MTBF (demonstrated)	70,000 h
<b>Dimensions / Weight / Environmental</b>	
Dimension without stand (W x D x H)	553 x 63.5 x 330.2 mm
	21.77 x 2.5 x 13.00 inch
Dimension with stand (W x D x H)	553 x 229.4 x 347 mm
	21.77 x 9.03 x 13.65 inch
Weight (packed)	7.4 kg
	16.20 lbs
Weight (unpacked)	5.6 kg
	12.35 lbs
Weight (Monitor only)	3.5 kg
	7.74 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
<b>Miscellaneous</b>	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
<b>Package content</b>	
Display delivered accessories	DisplayPort data cable 1.8 m DVI-D Data cable 1.8 m Audio cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Data cables and audio cable detachable on display
<b>Order information</b>	
Order Code	S26361-K1577-V140

**Order information**

<b>EAN Code</b>	4054681927114
<b>Country specific order code</b>	BDL:K1577V140-UK - with UK power cable, mandatory for Arabian countries BDL:K1577V140-CHN - with China power cable and CEL, mandatory for China BDL:K1577V140-ID - with Import label, mandatory for Indonesia (on demand) BDL:K1577V140-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed

<b>Accessories information</b>	Further helpful options: Available Privacy Filters: <a href="http://globalsp.ts.fujitsu.com/dmsp/Publications/public/ds-Privacy-Filter.pdf">http://globalsp.ts.fujitsu.com/dmsp/Publications/public/ds-Privacy-Filter.pdf</a> Available Adapters: <a href="http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf">http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf</a>
--------------------------------	---

**Warranty**

<b>Warranty period</b>	3 years (depending on country)
<b>Warranty type</b>	Collect & Return Service (depending on country specific requirements)
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>
<b>Spare Parts availability</b>	5 years after end of product life
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>

# More information

## Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display B24-8 TE Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Display B24-8 TE Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/fts/displays>

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2016 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2016-03-29 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2016 Fujitsu Technology Solutions GmbH