

# Data Sheet FUJITSU Display E24-8 TS Pro

Best-in-class wide screen office monitor that combines performance with energy savings

The FUJITSU Display E24-8 TS Pro combines robust business performance with cost savings. It has Integrated speakers, In-Plane Switching (IPS) technology with Full HD for supreme audio visual experience required by business professionals. The E24-8 TS Pro comes with the DisplayPort, DVI (HDCP), VGA interfaces and is an extremely energy efficient monitor for demanding business environments.

In-Plane Switching (IPS) technology with FHD resolution that delivers accurate and sharp picture quality

Ergonomic design in a matt black slender housing that helps you save on desk space and have a clean working area

Direct access keys on the monitor housing for brightness, mode, input, audio, menu and ECO savings

Five lighting modes that help users switch from sRGB, Office applications, Photo, Video and Low Blue Light for varied lighting conditions

Anti-glare and flicker-free backlight feature for working without straining your eyes















## Technical details

Special features	
	In-Plane Switching (IPS) technology, LED backlight panel, Keep aspect ratio option, headset connector, Eco control button, Integrated speakers
Ergonomic stand	
Stand	removable
Picture height over desk (min)	63 mm
Tilt angle	-5° / +22°
Picture performance	
Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in video mode)
Viewing angle (h/v) - typical	178°/178°
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2
Size and resolution	
Aspect ratio	16:9
Diagonal Size	60.5 cm (23.8-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	527 x 296 mm
Pixel Pitch	0.2745 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz
Connectivity	
DisplayPort	1 x DisplayPort
DVI	1 x DVI-D (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 2 W
Ease-of-use menu	
Direct Access Keys	Brightness, ECO, Input, Mode, Audio, Menu
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Mode	sRGB, Office, Photo, Video, Low Blue Light
Color	sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position, Expansion
Audio	Mute, Volume, Input for DP interface
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status
Advanced settings	Overdrive, DDC/CI, Factory Recall
Power consumption (typical, w/o sour	
Soft switch off	0.1 W
Power save mode	0.2 W
	14.95 W

Power supply	integrated
Power notes	Speakers off
	ETEC and EPA refer to ENERGY STAR® 7.0
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	Energy Efficiency Class: A+, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration
Model	B24-8T
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cTUVus
Australia/New Zealand	(on customer request)
South Korea	KC#E-Standby
Singapore	S-Mark
Taiwan	BSMI
China	CCC
Saudi Arabia	SASO
Global	ENERGY STAR® 7.0, TCO Certified Displays 7.0, EPEAT® Gold (dedicated regions), Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Low Blue Light Certified, TÜV Flicker Free Certified
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Quality and Reliability	
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	553 x 63.5 x 330.2 mm
· ,	21.77 x 2.5 x 13.00 inch
Dimension with stand (W x D x H)	553 x 209 x 372 mm
	21.77 inch x 8.24 x 14.65 inch
Weight (packed)	4.84 kg
	10.67 lbs
Weight (unpacked)	3.6 kg
	7.94 lbs
Weight (Monitor only)	3.3 kg
·	7.28 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Black
Package content	
Display delivered accessories	DVI-D Data cable 1.8 m Audio cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Data cables and audio cable detachable on display Please note: cable length may vary by +/- 5 cm.
Order information	
Order Code	S26361-K1598-V160
EAN Code	4057185668828

Order information	
Country specific order code	BDL:K1598V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1598V160-CHN - with China power cable and CEL, mandatory for China BDL:K1598V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed BDL:K1598V160-ID - with Import label, mandatory for Indonesia (on demand)
Accessories information	Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/ dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

### More information

#### Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display E24-8 TS Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### **Computing Products**

www.fujitsu.com/global/products/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about FUJITSU Display E24-8 TS Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



#### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

© 2017 Fujitsu Technology Solutions GmbH

#### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2017-08-18 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH