


Open Frame Touch Monitor

HO 275 PTB

27" / 68,58cm Diagonal

LED Backlight – Format 16:9

- 1920 x 1080 Full HD 1080P Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- Triple Input: DP + HDMI + VGA
- Built-in Speakers
- IP65 (front) Rating Level
- Display Protection: Thickness 3mm
- 7H Toughened Hard Panel Surface
- Built for 24/7
- VESA Mount and Multiple Mounting Options
- Edge to Edge glass without raised frame
- Orientation: Landscape, Portrait, Face-Up



27" / 68,58 cm

Part. No.: HO 275 PTB

SIZE, RESOLUTION



27" Display Size
16:9 Aspect Ratio



Full HD
1920 x 1080

CONNECTIVITY, IP LEVEL



DP
HDMI
VGA



IP 65
Water & Dust
Protection

VIEWING ANGLE, VESA



178 Ultra-Wide
Viewing Angle



VESA
Wall-Mountable

OTHER FEATURES



10 Points
Touch



Built for 24/7
Operation

Display Size	68,58 cm / 27" Diagonal
Panel Type	TFT – LED Backlight, ADS Panel (**)
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	300cd/m ² Panel / 260 cd/m ² Monitor
Contrast	1.000:1 (Typical); 80.000.000:1 (Active Contrast)
Viewing Angle L/R; U/D	178° H / 178° V
Response Time	5 msec
Pixel Pitch	0,311 (H) x 0,311 (V) mm
Touch Type	Projected Capacitive – 10 Point Touch Type: Cover Glass + LOCA + ITO Glass
Display Colors	16.7M Colors
Horizontal Frequency	30 ~ 83 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	VGA
Input 2	HDMI
Input 3	Display Port
Input 4	USB 2.0 Type B (Touch)
Speakers	Yes, 2W x 2, Earphone jack
Power Consumption	On: 40W; Stand-by: ≤0,5W; Off: ≤0,3W (TBC)
Power Range	Built-In Power Supply AC 100 ~ 240 Volt; 50 ~ 60 Hz
Product Dimensions	649,2 x 47 x 387 mm (W x D x H)
Packing Dimensions	735 x 146 x 480 mm (W x D x H) TBC
Net / Gross Weight	- Kg / - Kg TBC

VESA Mounting	100 x 100 mm. Screws: M4, 12mm (Max), pitch 0.7
Display Protection	Thickness 3 mm
Hardness / Transmittance	≥7H Toughened hard panel surface / ≥ 86%
IP Rating Level	IP 65 (Front), Water and Dust Protection (*)
Controls	Power, Auto, (+), (-), Menu
Color	5500K, 6500K, 9300K, User Mode
Preset Mode	PC, Movie, Game, ECO Modes
On Screen Display	11 Languages
Accessory	Power Cable (1.5m); HDMI Cable (1.5m); USB 2.0 (B-A) Cable, for Touch (1.5m).
Orientation	Landscape, Portrait, Face-Up
24 / 7	Yes

PART. NO.:
HO 275 PTB

* IP65: The IP Code classifies how resistant a device is to foreign objects and moisture.
IP65 means that the monitor is protected from total dust ingress and it is protected against low pressure water jets from any direction. Limited ingress permitted.

** "ADS" word mark / trademark and related patents
on technologies belong to their respective owners.

Display Solutions

HO 275 PTB 27" Open Frame Touch Monitor

