

HP 246 PDB

60,96 cm / 24" Diagonal
LED Backlight – Format 16:10

- 24" 16:10 LED Backlight Monitor
- 1920 x 1200 WUXGA Resolution
- 178° / 178° Ultra Wide Viewing Angle
- Digital Inputs: Display Port + HDMI
- Daisy Chain, DP out
- Picture In Picture / Picture by Picture
- USB 3.0 HUB, 1 up - 4 down
- Built-In Stereo Speakers
- Tilt and Wall-Mountable (VESA)
- Multi-Functional Height Adjustable Stand
- Pivot Function (90° Rotation) and Swivel
- Low Power Consumption & Multi-Video Modes
- Flicker Free and Low Blue Light Mode



60,96 cm / 24"

Part. No.: HP 246 PDB

SIZE, RESOLUTION



24"
16:10 Aspect Ratio



WUXGA
1920 x 1200

CONNECTIVITY



DP
HDMI



Daisy Chain
DP Out

VIEWING ANGLE, PIP




178 Ultra-Wide
Viewing Angle



Picture In Picture

ERGONOMIC FEATURES



Height
Adjust.
Stand



Pivot



Tilt



Swivel

| | |
|------------------------|--|
| Display Size | 60,96cm / 24" Diagonal |
| Panel Type | TFT – LED Backlight, ADS Panel (*) |
| Aspect Ratio | 16:10 |
| Resolution (H x V) | 1920 x 1200 WUXGA |
| Brightness | 300cd/m ² |
| Contrast (Typ.) | 1.000:1 (Typical) |
| Contrast (Active) | 80.000.000:1 (Active) |
| Viewing Angle L/R; U/D | 178° H – 178° V (CR > 10) |
| Response Time | 4 msec (with OD) |
| Pixel Pitch | 0.274 (H) x 0.274 (V) mm |
| Panel Surface | Anti-Glare, Haze-level 25%; 3H Hardness Coating |
| Display Colors | 16.7M Colors |
| Horizontal Frequency | 30 ~ 83 kHz |
| Vertical Frequency | 56 ~ 75 Hz |
| Max Display Frequency | 1920 x 1200 @ 60Hz |
| Input 1 | HDMI |
| Input 2 | DP 1.2 |
| Output | DP (for Daisy Chain) |
| Buil-in Speakers | Yes, 1.5W x 2; Audio Out Earphone Jack |
| Power Consumption | On: 13,59W; Stand-by: 0,3W; Off: 0,28W (Energy Consumption related to EPA Energy Star Version 8.0) |
| AC Power Range | AC 100 ~ 240 Volt; 50 ~ 65 Hz |
| Product Dimensions | 556,8 x 245 x 562,9 mm including stand (W x D x H) |
| Packing Dimensions | 630 x 209 x 438 mm (W x D x H) |
| Net / Gross Weight | 7,2 Kg / 9,2 Kg (±0.3KG) |
| Bezel & Color Plan | Bezel /Arm / Base / Rear Cover Matt |

| | |
|------------------------|---|
| VESA Mounting | 100 x 100 mm |
| Monitor Stand | Height Adjustable Stand (117 mm lift) |
| Tilt / Kensington Lock | -5° ~ 30° / Yes |
| Pivot / Swivel | Yes 90° Clockwise / Left: 170° - Right: 170° |
| Controls | 1,2, ▼, ▲, Power |
| Color | 9300, 6500, 5500, User Mode |
| Preset Mode | PC, Movie, Game, ECO Modes |
| On Screen Display | 11 OSD Languages |
| Built-in USB Hub | USB 3.0: 1 upstream, 4 downstream ** |
| Other Features | Flicker Free / Low Blue Light Mode Picture In Picture / Picture by Picture |
| Accessory | Power Cable (1,5m); HDMI Cable (1,5m); Warranty Card; Quick Start Guide |



| | |
|--|--------------|
| Supplier's Name | HANNspree |
| Model Name | HP246PDB |
| Energy efficiency class for standard Dynamic Range (SDR) | F |
| Annual Energy Power Consumption (kWh/1000h) | 22 kWh/1000h |
| On mode power demand for Standard Dynamic Range (SDR) | 22 W |
| Off mode power demand (W) | 0,3 W |
| Standby mode power demand (W) | 0,4 W |
| Screen Diagonal (cm / inches) | 61cm / 24" |
| Resolution | 1920 x 1200 |

PART. NO.:
HP 246 PDB

