

HP 24es 60.45 cm (23.8") Monitor



**Impossibly thin.
Irresistibly priced.**

Our thinnest LCD display yet¹ has a sleek design that's easy on the eyes. And the crisp, vibrant view from almost any angle comes at an ultra-affordable price.



Our thinnest LCD display yet

- Pushing the limits of thin in an eye-catching design. With our innovative use of high-strength, lightweight metal, we've created our thinnest LCD display yet.¹

Stunning from edge-to-edge

- With ultra-wide viewing angles and vivid 1920 x 1080² resolution, this edge-to-edge display delivers an expansive entertainment experience for seamless multiple display setups.

True-to-life color

- When the colors on your display are indistinguishable from real life, the result is a beautifully vivid picture. With Technicolor Color Certification, color accuracy is assured every time.

Featuring

- With no bezel encircling the display, an ultra-wide viewing experience provides for seamless multi-monitor set-ups.
- Vibrant detail from practically any position with consistent color and image clarity maintained across an ultra-wide 178° horizontal and vertical viewing angles.
- Be prepared for brilliant visuals and crisp images with the unforgettable quality of this stunning FHD display.²
- HP Enhance+ resolution improves image quality with advanced noise reduction for crisper, cleaner images. By reducing overexposure, this advanced noise filter amplifies your images for crisper photos, videos and games.³

¹ 7.0 mm at its thinnest point.

² Full high-definition (FHD) content required to view FHD images.

³ Results may vary based on the viewing quality of the original image (picture, photo or video) and the difference between the monitor's previous settings compared to the new HP Enhance+ mode.

Datasheet

HP 24es 60.45 cm (23.8") Monitor



Display Size	60.45 cm (23.8")
Aspect Ratio	16:9
Display type	IPS w/ LED backlight
Pixel pitch	0.274 mm
Refresh response time	7 ms gray to gray
Brightness	250 cd/m²
Contrast ratio	1000:1 static; 1000000:1 dynamic
Viewing angle	178° horizontal; 178° vertical
Video input signal	1 VGA; 1 HDMI (with HDCP support)
Resolution	1920 x 1080 @ 60 Hz
Display Scan Frequency (horizontal)	Up to 80 kHz
Display Scan Frequency (vertical)	Up to 60 Hz
Display features	Anti-glare; In plane switching; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable
Physical security features	Security lock-ready (lock is sold separately)
Display moving angle	Tilt: -5 to +25°
Environmental Specifications	Mercury-free LED backlighting; Arsenic-Free Display Glass
Power Supply and Power Requirements	Input voltage: 100-240 VAC at 50 - 60 Hz; Power consumption: 25W maximum, 21W typical; Standby mode: < 0.3W
Energy Efficiency	Energy Efficiency class: A; Visible Screen Diagonal: 60.45 cm (23.8"); On-mode power consumption: 19 W; Annual energy consumption: 28 kWh; Standby: 0,2 W; Power consumption (off-mode): 0,12 W; Screen Resolution: 1920 x 1080 @ 60 Hz
Display User Control Options	Menu/ok; Information/"; Input/"; Auto/QV/Exit; Power
Dimensions (W x D x H)	53.98 x 18.35 x 40.88 cm (with stand); 53.98 x 3.57 x 32.29 cm (without stand)
Weight	3.04 kg (with stand); 2.65 kg (without stand)
Operating Temperature Range	5 to 35 C
Operating Humidity Range	20 to 80 %
Storage Temperature Range	-20 to 60 C
Non-operating Humidity Range	5% ~95 %
Certifications and compliances	CB; CE; TUV-BAUART; ISO9241; CSA; CSA-NRTL; FCC; ICES; S-Mark; VCCI; CCC; China CEL; BSMI; KCC; KC; E-standby; EUP Lot 6 and Lot 5; GEMS; MEPS; UKRAINIA; HRN N NO.201; EAC; IEC60950:1999; IS 1121; SASO; SABS IEC 60950-1; NOM; PSB; ISC; C-Tick
Product colour	Natural silver (front and stand) and black (rear)
Warranty	1 year HP Commercial Guarantee
Box Content	A/C power cable 1.9 m, Power adapter 1.0 m, CD (include U.G., warranty, drivers), QSP(Quick Setup Poster), Telephone Card, HDMI Cable 1.8m (In selected sku/region)
VESA Mount	No
Ordering info	T3M78AA#A2N: 889899004333; T3M78AA#ABB: 889899004258; T3M78AA#ABT: 889899004296; T3M78AA#ABU: 889899004265; T3M78AA#ABV: 889899004319; T3M78AA#ABY: 889899004289; T3M78AA#ACQ: 889899004302; T3M78AA#UUG: 889899004326; T3M78AA#UUZ: 889899004272

