



## 24" IPS technology panel with USB-C dock

Equipped with a USB-C dock connector, the XUB2492HSN allows you to simplify your workspace by using a single cable to both send signal from your notebook to your monitor and power and charge the notebook from the monitor. Additionally, if your monitor is connected to the Internet with a LAN cable, your notebook will automatically be connected to the network as well. Thanks to a DisplayPort output you can easily extend your desktop by creating a double-monitor set-up.



### USB-C dock

The dock allows you to connect your laptop with a single cable to the monitor to both make sure it is charged and connected to a wired network and signal from the laptop is sent to the monitor. A second monitor can be connected to the DisplayPort (MST) output to create a multi-monitor set-up. With additional USB-ports, your mouse, keyboard or webcam can also be connected to the monitor. All thanks to a single cable connecting your laptop\* to the USB C dock in the monitor.

\*Functions vary depending on your laptop USB-C support.



### IPS Technology

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

## 01 DISPLAY CHARACTERISTICS

|                     |                                                                       |
|---------------------|-----------------------------------------------------------------------|
| Design              | ultra slim                                                            |
| Diagonal            | 23.8", 60.5cm                                                         |
| Panel               | IPS Panel Technology LED, matte finish                                |
| Native resolution   | 1920 x 1080 @75Hz (2.1 megapixel Full HD)                             |
| Aspect ratio        | 16:9                                                                  |
| Brightness          | 250 cd/m² typical                                                     |
| Static contrast     | 1000:1 typical                                                        |
| Advanced contrast   | 80M:1                                                                 |
| Response time (GTG) | 4ms                                                                   |
| Viewing zone        | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support      | 16.7mIn (sRGB: 99%; NTSC: 72%)                                        |
| Horizontal Sync     | 30 - 85kHz                                                            |
| Vertical Sync       | 55 - 75Hz                                                             |
| Viewable area W x H | 527 x 296.5mm, 20.7 x 11.7"                                           |
| Pixel pitch         | 0.275mm                                                               |
| Colour              | matte, black                                                          |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                     |                                                                   |
|---------------------|-------------------------------------------------------------------|
| Signal input        | HDMI x1 (1920 x 1080@ 75Hz)<br>DisplayPort x1 (1920 x 1080@ 75Hz) |
| Signal output       | DisplayPort x1 (Daisy Chain MST max. 1920 x 1080)                 |
| USB HUB             | x2 (v.3.0)                                                        |
| USB C dock          | x1 (Power delivery 65W, LAN, DP out, USB 3.0)                     |
| HDCP                | yes                                                               |
| Headphone connector | yes                                                               |

## 03 FEATURES

|                    |                                                                                                                                                                                                                                                                                                                                                              |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Blue light reducer | yes                                                                                                                                                                                                                                                                                                                                                          |
| Flicker free       | yes                                                                                                                                                                                                                                                                                                                                                          |
| OSD languages      | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL                                                                                                                                                                                                                                                                                                                       |
| Control buttons    | Power, Menu/ Select, Up/ Volume, Down/ ECO, Exit, Input                                                                                                                                                                                                                                                                                                      |
| User controls      | picture adjust (brightness, contrast, Eco, blue light reducer, ACR, OD), colour settings (colour temp., user preset, i-Style colour), OSD (OSD H. position, OSD V. position, OSD rotate, OSD time), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, USB BC, MST, information), input select, audio settings (volume, mute) |
| Speakers           | 2 x 2W                                                                                                                                                                                                                                                                                                                                                       |
| Convenience        | Kensington-lock™ prepared, DDC2B                                                                                                                                                                                                                                                                                                                             |

## 04 MECHANICAL

|                              |                                                   |
|------------------------------|---------------------------------------------------|
| Display position adjustments | height, swivel, tilt, pivot (rotation both sides) |
| Height adjustment            | 130mm                                             |
| Rotation (PIVOT function)    | 90°                                               |
| Swivel stand                 | 90°; 45° left; 45° right                          |
| Tilt angle                   | 22° up; 5° down                                   |

|                             |             |
|-----------------------------|-------------|
| VESA mounting               | 100 x 100mm |
| Cable management system     | yes         |
| Operation temperature range | 5°C - 35°C  |

## 05 ACCESSORIES INCLUDED

|        |                                 |
|--------|---------------------------------|
| Cables | power (1.5m), HDMI (1.5m)       |
| USB-C  | 1m (on)                         |
| Other  | quick start guide, safety guide |

## 06 POWER MANAGEMENT

|                   |                                           |
|-------------------|-------------------------------------------|
| Power supply unit | internal                                  |
| Power supply      | AC 100 - 240V, 50/60Hz                    |
| Power usage       | 19W typical, 0.5W stand by, 0.5W off mode |

## 07 SUSTAINABILITY

|                         |                                                                   |
|-------------------------|-------------------------------------------------------------------|
| Regulations             | TCO, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH |
| Energy efficiency class | A+                                                                |
| Other                   | REACH SVHC above 0.1%: Lead                                       |

## 08 DIMENSIONS / WEIGHT

|                              |                               |
|------------------------------|-------------------------------|
| Product dimensions W x H x D | 539.5 x 366.5 (496.5) x 210mm |
| Box dimensions W x H x D     | 688 x 401 x 206mm             |
| Weight (without box)         | 5.4kg                         |
| EAN code                     | 4948570117864                 |

