



27" IPS panel Technology, edge-to-edge monitor featuring WQHD resolution

The elegant 3-side borderless design makes the ProLite XU2792QSU perfect for multi-monitor set-ups. The IPS panel offers accurate and consistent colour reproduction with wide viewing angles and the WQHD (2560 x 1440) resolution means the XU2792QSU can accommodate almost 77% more information on the screen than a Full HD display. High contrast and brightness values guarantee the monitor will provide excellent performance for photographic and web design. It is a great choice for both multi-monitor office applications and more specific design applications.

Available also with height adjustable stand: ProLite XUB2792QSU-B1 (2560x1440), ProLite XUB2792UHSU-B1 (3840x2160) and ProLite XUB2792HSU-B1 (1920x1080)





WQHD

With true WQHD 2560 x 1440p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen, i.e. over 76% more in comparison to a 1920 x 1080 monitor.

IPS Technology

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

DISPLAY CHARACTERISTICS

Design	ultra slim
Diagonal	27", 68.5cm
Panel	IPS LED, matte finish
Native resolution	2560 x 1440 @70Hz (DisplayPort, 3.7 megapixel WQHD)
Aspect ratio	16:9
Brightness	350 cd/m² typical
Static contrast	1000:1 typical
Advanced contrast	80M:1
Response time (GTG)	5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 100%, NTSC 77%)
Horizontal Sync	30 - 89kHz
Viewable area W x H	596.7 x 335.7mm, 23.5 x 13.2"
Pixel pitch	0.233mm
Colour	matte,

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	DVI x1 (max. 2560 x 1440 @60Hz) HDMI x1 (max. 2560 x 1440 @60Hz) DisplayPort x1 (max. 2560 x 1440 @70Hz)
USB HUB	x2 (v.3.0 DC5V, 900mA)
HDCP	yes
Headphone connector	yes



FEATURES

Blue light reducer	yes
Flicker free	yes
FreeSync support	DisplayPort: 2560x1440 @70Hz
OSD languages	EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL
Control buttons	Power, Menu / Select, + / Volume, - / ECO, Exit, Input
User controls	picture adjust (contrast, brightness, OD, ACR, ECO, blue light reducer), input select, audio adjust (volume, mute, digital audio), colour adjust (cool, normal, warm, user colour, i-Style colour), image adjust (sharpness, video mode adjust), language, setup (OSD position, OSD time out, opening logo, auto power off, FreeSync), display information, reset
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX



04 MECHANICAL

Display position adjustments	tilt
Tilt angle	22° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes



ACCESSORIES INCLUDED



POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	33W typical, 0.5W stand by, 0.5W off mode




SUSTAINABILITY

Regulations	TCO, CE, TÜV-GS, EAC, RoHS support, ErP, WEEE, REACH
Energy efficiency class	A
Other	REACH SVHC above 0.1%; Lead



DIMENSIONS / WEIGHT

Product dimensions W x H x D	611 x 441.5 x 197mm
Box dimensions W x H x D	690 x 140 x 451mm
Weight (without box)	5kg
Weight (with box)	7kg
EAN code	4948570115204



09

EU ENERGY EFFICIENCY LABEL

Manufacturer	iiyama
Model	ProLite XU2792QSU-B1

Energy efficiency class	A
Visible screen diagonal	68cm; 27"; (27" segment)
Annual energy consumption	44kWh/annum*
Power in Standby	0.5W stand by
Power in OFF Mode	0.5W off mode
Resolution	2560 x 1440

This is information under Regulation (EU) No 1062/2010.*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED