



- Advanced infra-red touch technology
- Anti-Glare coating
- Fanless design
- Integrated speakers
- Automatic brightness adjustment
- Low energy consumption
- Ultra slim design
- Unique EasyFix® mounting solutions
- Comes complete with Tango Software



e-Screen STX-6500 Black

- The STX range displays offers razor sharp, high quality images in Full-HD and Ultra-HD
- The build-in Automatic Brightness Sensor guarantees an optimal picture under all light circumstances and significantly reduces energy consumption
- The anti-glare coated glass guarantees perfect readability and a comfortable touch experience
- The advanced infra-red touch screen technology uses infra-red sensors to detect the touch point. Any pointing device (finger, stylus, or any other pen-shaped object) can be used
- Multi-touch with up to 10 simultaneous touches for multi user requirements (Windows 7, 8, 8.1 and 10)
- Easy to set up, plug and play functionality for Windows
- Dual USB input for touch, allows simultaneous connection of two computers to the e-screen
- The durable, ultra slim design with laser cut bezels, creates a non-intrusive, minimalistic and professional timeless design that fits in any surrounding
- The unique EasyFix® Mounting Solutions for easy, quick and flexible mounting of whiteboard side panels, control button of Legamaster electrical height adjustable solutions, VESA 100 PC and SP3700 Active Sound System
- The unique EasyFix® Cable Management system guarantees quickly securing and fastening of cables, neatly routed on the back of the screen.


Ref.: **7-801100-65**

EAN: **8713797081757**



Recommended accessories

- Column system electrical height adjustable Ref.:7-194261
- Freestanding column system electrical height adjustable XL Ref.:7-194272
- Flipbox Software Suite Ref.:7-197002



Signal source input 65" Connector

1	Touch USB 2
2	Touch USB 1
3	RS-232
4	Ethernet
5	DisplayPort
6	HDMI
7	DVI
8	VGA
9	Audio Out
10	IR Extender
11	PC audio In
12	Power

Product specifications

Color	Black
Product dimensions	W: 1483 x H: 851 x D: 90 (mm)
Bezel size	16,1 mm
Viewing angle max	H: 178° / V: 178°
Size diagonal	65"
Brightness	350 cd/m ²
Contrast ratio	4000:1
Response time	8ms
Supported colors	1073,3M
Display resolution / frame rate	1920x1080 / 60 Hz
Input resolution / frame rate	1920x1080 / 60 Hz
Ops slot	No
Fanless design	Yes
Display control	RS232C, IR remote controller, keypad
Automatic brightness adjustment	Yes
Speaker	2x10W@4Ω
Mounting interface accessories	VESA 100x100
Power consumption / Stand by	≤225 / ≤0,5 (Watt)
Durability / Lifespan	16/7 / -
Input connectors	DisplayPort,HDMI,VGA,DVI-D,PC Audio-in,IR extender
Output connectors	Audio-Out
Touch technology	High-resolution Infrared Touch Technology
Touch operation	finger, glove, stylus
Number of touch points	10
Driver	Win: plug and play (optional driver) / Mac: driver
Sup. operating systems	Windows XP, Vista, 7, 8, 8.1, 10,Mac OSX, Linux
Product warranty	3 years

Product logistics

Product SAP / EAN / KEA	867659000 / 8713797081757 / 7-801100-65
Packing Unit	Piece
Quantity	1
Weight net	51.80 kg



We make communication visible

For more information:
www.legamaster.com