

LENOVO® THINKVISION® T2254p

UNCOMPROMISED PERFORMANCE.
EXCEPTIONAL DISPLAY THAT FUELS PRODUCTIVITY.



Outstanding visuals are just the beginning with this sleek, high-performance monitor. 22-inch wide monitor delivers exceptional resolution, brightness and contrast across a wide-view screen that enhances productivity. Multiple connectivity options, ergonomic full-function stand and Green certifications make it an excellent all-around monitor for virtually any business environment.

WHY BUY
THE
THINKVISION®
T2254p?

1 OUTSTANDING VISUALS



The 22"16:10 screen is perfect for any business content, displayed with 250 nits brightness and 1000:1 contrast for the darkest blacks and brightest colours, with an anti-glare finish.

2 MULTIPLE CONNECTIVITY OPTIONS



Ideal for multimonitor settings with VGA, HDMI 1.4 and DP 1.2 connectivity options, perfect for connecting a wide range of PCs and notebooks.

3 ERGONOMIC DESIGN



The ergonomic full-function stand is perfect for collaboration. It supports the new ThinkCentre® Tiny Clamp bracket for easy set-up of ThinkCentre® Tiny at the back of the monitor. Practical cable management effectively manages desktop clutter.

4 GREEN-CERTIFIED



This Green monitor minimizes the carbon footprint with ENERGY STAR 6.0, EPEAT® Gold, TCO Edge 2.0, ULE Gold and CEL Tier 1 certifications.

WHO
NEEDS A
THINKVISION®
T2254p?

1 Professionals in the fields of finance, healthcare, education and office administration.

2 Any enterprise or individual who is seeking a high-performance monitor with multiple connectivity options.

3 Organizations that require professional quality monitors that also deliver a green advantage.



0800 123 1234

WWW.LENOVO.COM

SPECIFICATIONS

DISPLAY

Panel Size	22-inch Wide
Panel Type	TN
Backlight	WLED
Viewable Area (Diagonal)	22" (558.8 mm)
Screen Dimensions (W x H)	473.76 mm x 296.1 mm
Resolution	1680 x 1050
Aspect Ratio	16:10
Viewing Angle (H/V at CR 10:1)	170°/160°
Maximum Brightness (Typical)	250 cd/m²
Contrast Ratio (Typical)	1000:1
Dynamic Contrast Ratio	3M:1
Pixel Pitch (mm)	0.282 (H) x 0.282 (V)
Dot/Pixel Per Inch (DP / PPI)	90
Color Gamut (CIE 1931)	72%
Color Gamut (CIE 1976)	86%
Number of Colors	16.7 M
Response Time	5 ms (On/Off)
Anti-Glare	Yes

SIGNAL INPUT

Video Input Signals	VGA, HDMI 1.4, DP 1.2
Video Cables Supplied	VGA
Video Cable Length	1.8 m
USB Hub	None
USB Cable Supplied	None
Audio Out	Yes

SIGNAL INTERFACE / PERFORMANCE

Horizontal Frequency	30 to 83 kHz
Vertical Frequency	50 to 75 Hz
Native Resolution	1680 x 1050
Maximum Pixel Clock Speed / Bandwidth	146.25 MHz
Default Color Temperature	7200 K
Preset Display Modes	28
User-defined Display Modes	20
OSD Buttons	5
OSD Languages	8

COMPLIANCE

EPEAT®	Toggle case (i.e. Gold)
ENERGY STAR Rating	6.0
ULE	Gold
TCO	Display 6.0
TCO Edge	2.0
TUV	Yes
GREENGUARD	No
RoHS (EU 2002/95/EC)	Yes
Windows Certification	Windows 7, Windows 8.0, Windows 8.1
China Energy Efficiency Standard	Tier 1

WARRANTY

Warranty	3 Years
Geography Availability	World Wide

MECHANICAL

Tilt Angle (Front / Back)	-5° to 30°
Swivel Angle (left / right)	-45° to 45°
Lift	110 mm
Pivot	0° to 90°, clockwise
VESA® Mount	100 mm x 100 mm
Kensington® Lock Slot	Yes
Cable Management	Yes
Ambient Light sensor	No
Bezel Color	Raven Black
Bezel Width (Side)	0.67" (17.1 mm)
Bezel Width (Top / Bottom)	0.67" (17.1 mm)

POWER CONSUMPTION

Power Consumption	
Typical	20 W
Max.	25 W
Sleep	0.5 W
Off-Mode	0.5 W
Heat Dissipation	
Typical	68.2 Btu/h
Max.	85.22 Btu/h
Power Supply	Internal
Power Voltage	1.5A, 90–264 V AC
Voltage Dynamic Frequency	47–63 Hz

DIMENSIONS (W x D x H)

Size Packed	22.44" x 6.93" x 16.22" (570 mm x 176 mm x 412 mm)
Size Unpacked with stand	20.01" x 9.55" x 14.63" (509.3 mm x 242.6 mm x 371.7 mm)
Size Unpacked without stand (Head Only)	20.05" x 1.73" x 13.06" (509.3 mm x 44 mm x 331.7 mm)
Min. Distance from Table to Panel (lowest pixel at bottom of screen)	2.28" (57.78 mm)
Max. Distance from Table to Panel (highest pixel at top of screen)	13.93" (353.88 mm)
Stand Base Footprint Area	9.35" (240 mm) (diameter)
Weight Packed	6.3 kg (13.9 lbs)
Weight Unpacked	4.6 kg (10.37 lbs)
Weight (Monitor Head Only)	2.85 kg (6.28 lbs)

ENVIRONMENTAL

Temperature – Operating	0 °C to 45 °C
Temperature – Non-operating	-20 °C to 60 °C (non-condensing)
Humidity – Operating	10% to 80%
Humidity – Non-operating	5% to 95% (non-condensing)
Altitude – Operating	5000 m
Altitude – Non-operating	40,000 ft
Arsenic-free Glass	Yes
PVC free	Yes
Mercury free	Yes
PCC % of plastic resins	85%
Low Halogen	No

