



ThinkVision T24m-20

Exceptional Display Performance. Extended Capabilities.

POWERING WORKDAY WITH EFFECTUAL DISPLAY PERFORMANCE

A monitor that's more than just another screen, ThinkVision T24m-20 renders easy connectivity and manageability to businesses. Enjoy the generous screen space of 23.8 inches on this FHD In-Plane Switching panel. With 3-side NearEdgeless bezels and daisy-chaining capability via the DP-out port, enjoy an unrestricted view and multitasking in a multi-monitor setup. It is equipped with USB Type-C¹ technology that provides rapid transfer speeds via a one-cable solution. For secure and reliable connectivity and remote management, an Ethernet port lets the user work uninterrupted. Ergonomic features with a clutter-free, space-saving design can't go unnoticed on the T24m, which makes for a comfortable work experience wherever the users are. The monitor minimizes eye strain with Natural Low Blue Light technology without creating yellow-skewed images. With sustainable packaging using pulp cushion, the T24m monitor remains environmentally friendly throughout its life cycle.

FEATURES OF THINKVISION T24m-20 MONITOR



Daisy chain for a multiple-monitor setup

Optimized for Efficient Multitasking

Clear visuals and consistent colors are what users get to see on its 1920 x 1080 FHD resolution display. An In-Plane Switching panel provides a wide-viewing angle (up to 178°) for a comfortable and distortion-free view. 3-side NearEdgeless bezels ensure a seamless multitasking experience when daisy-chaining multiple screens for an expanded display setup. When multiple devices are plugged into the monitor like a tablet, a laptop, or any other USB-powered peripheral, Smart Power² function dynamically detects and optimizes the distribution of power.



User Convenience and Comfort

ThinkVision T24m adjusts to users' workstyle—its ergonomic stand offers increased lift range and tilt angle with a design that keeps wobble to a minimum. Its square base occupies comparatively lesser desk space and also comes with a phone holder for added convenience—making it the perfect display for offices with limited workspace. Cable management keeps the clutter in check, enabling a minimalist and clean workspace. Lenovo ThinkColour³, an exclusive Lenovo software, offers access to advanced display settings with a simple and snappy user interface.



Connectivity That Adapts to Business Needs

Full-function USB Type-C¹ port provides single-cable connectivity to transfer data, video, audio, and power. The Ethernet port (RJ45) offers fast and secure remote management with PXE, WOL, and Mac Address Pass Through (MAPT) support. USB Type-C solution with DP out provides simple and clean deskspace for users who need a multi-screen setup. Additionally, this docking monitor with USB Type-C, HDMI, and DisplayPort offers a multitude of connectivity options.

ThinkVision T24m-20

DISPLAY

Panel Size 23.8-inch

Screen Dimensions 535.1 mm x 313.1 mm

Panel Type 3-side NearEdgeless In-Plane Switching

Active Area 527.0 mm x 296.5 mm

Backlight WLED

Aspect Ratio 16:9

Resolution 1920 x 1080

Pixel Pitch 0.2745 mm x 0.2745 mm

Dot/Pixel Per Inch (DPI/PPI) 93

Viewing angle (H x V @ CR 10:1) 178° / 178°

Response Time 4ms (Extreme Mode) 6ms (Normal Mode)

Refresh Rate 60 Hz

Brightness (typical) 250 cd/m²

Contrast Ratio (typical) 1000:1

Dynamic Contrast Ratio (typical) 3M:1

Color Gamut 72% NTSC (CIE 1931)

Color Support (typical) 16.7 Million

Color Depth 8-bit (6+FRC)

> Anti-glare Yes

CONNECTIVITY

Video Signal 1 x USB Type-C¹ Gen1 (DP1.2 Alt Mode) 1 x HDMI 1.4 1 x DP 1.2 1 x DP Out

Audio Signal 1 x Audio Out (3.5mm)

USB Hub Yes

Ethernet Yes (10M/100M/1000M)

USB Upstream 1 x USB3.2 Gen1 (1 by USB Type-C¹)

USB Downstream 4 x USB3.2 Gen1 (1 x BC1.2)

SPECIAL FEATURES

Software Lenovo ThinkColour³ (Lenovo Display Control Center)

POWFR

Power Consumption (Tvp./Max) 22W / 140W

Power Consumption Sleep/Off Mode < 0.5W⁴

Power Consumption Switch-Off Mode < 0.3W

Energystar Power Consumption (Pon/E_{rrc}) 15W / 49kWh

Power Supply Internal

USB Type-C1 (DP Alt Mode) power delivery Up to 90W⁵

Smart Power² Yes

Voltage Required AC 90 to 264 V (50-60 Hz)

MECHANICAL

Tilt Angle (front/back) -5° / 35°

Swivel Angle (left/right) -45° / 45°

Lift (Max range) 150 mm

Pivot -90° / 90°

VESA Mount Capability

ThinkCentre M Series Tiny support Yes, by Tiny monitor clamp II (PN: 4XH0Z42451) & Tiny VESA mount II

ThinkCentre M Series Nano support

Yes, by Nano monitor clamp II

& Nano VESA mount (PN: 4XE0V81630) Kensington Lock Slot

(PN: 4XF0N03161)

(PN: 4XH0Z42451)

Yes

Cable Management Yes

Bezel Color Raven Black Bezel Width(side) 2.0 mm

Bezel Width(top/bottom) 2.0 / 22.0 mm

DIMENSION

Size Packed $(D \times H \times W. mm/inch)$ 161.0 x 480.0 x 604.0 mm 6.34 X 18.89 X 23.78 inches

Size Unpacked w/stand (D x H x W)(mm/inch)(Lowest position) 204.9 x 417.1 x 539.8 mm 8 09 x 16 42 x 21 25 inches

Size Unpacked w/stand (D x H x W)(mm/inch)(Highest position) 204.9 x 567.1 x 539.8 mm 8.09 x 22.33 x 21.25 inches

Size Unpacked w/o stand (Head Only) (D x H x W) (mm/inch) 44.4 x 325.9 x 539.8 mm 1.75 x 12.83 x 21.25 inches

Weight Packed (kg/lb) 8.9 kg / 19.7 lbs.

Weight Unpacked (kg/lb) 6.1 kg / 13.5 lbs.

Weight (Monitor Head Only) (kg/lb) 3.6 kg / 8.0 lbs.

WHAT'S IN THE BOX

Monitor with stand 1 x Power cable (1.8m) 1 x DP cable (1.8m) for US, Canada 1 x USB Type-C to Type-A cable (1.8m) for US. Canada 1 x USB Type-C to Type-C cable (1.8m) Quick setup quide

CERTIFICATION

ENERGY STAR Certification

Yes CCC

Yes

тсо 8.0

TCO Edge 2.0

EPEAT Gold

EU(2011/65/EC) Yes

Windows Certification Windows 7. Windows 10

China Energy Efficiency Standard Tier 1

TÜV Rheinland Eye Comfort Vac

TÜV Rheinland Flicker Free Vac

TÜV Low Blue Light (Hardware Solution) Yes

Eyesafe Display Certification Yes



¹ USB Type-C* and USB-C* are registered trademarks of USB Implementers Forum. ² The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device. Up to 90W power delivery to compatible devices by USB Type-C, typical power delivery is 65W.³ This software can only be used with Windows 10.⁴ For DP/HDMI mode.⁵ Listed as maximum capacity of power delivery. Actual capacity of power delivery may vary depending upon devices connected or monitor configuration, and may decline with downstream USB ports connected or higher brightness setting.

Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications; 5 Gbit/s for USB 3.2 Gen 1: 10 Gbit/s for USB 3.2 Gen 2 & 20 Gbit/s for USB 3.2 Gen2x2.

© 2021 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, and ThinkVision are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others.

Specifications may vary depending upon region.

Yes (100 x 100 mm)