

OWNER'S MANUAL

LG Digital Signage

(MONITOR SIGNAGE)

Please read the user manual before using this product to ensure safe and convenient use.

43UH7J 49UH7J 55UH7J 65UH7J 43UH5J 49UH5J 55UH5J 65UH5J

TABLE OF CONTENTS

BASIC3
- Checking the Accessories3
- Checking the Optional Accessories4
- Learning the Buttons5
GETTING READY6
- Connecting the IR Sensors6
- Mounting and Removing the
LG Logo Bracket7
- Kensington Lock Device8
CHECKING BEFORE
INSTALLATION9
- Installation Orientation9
- Installation Location10
- Wall Mount Holder11
PRECAUTIONS FOR USE 12
- Dust12
- Afterimage12
PRODUCT SPECIFICATIONS 14
LICENCE 19


WARNING - This equipment is compliant with Class A of CISPR 32. In a residential environment this equipment may cause radio interference.

BASIC



- The accessories provided with your product may vary depending on the model or region.
- Product specifications or contents in this manual may be changed without prior notice due to upgrade of product functions.
- · SuperSign Software & Manual
 - Visit https://partner.lge.com to download the latest SuperSign software and manual.


Checking the Accessories



Checking the Optional Accessories

In order to improve product performance, optional accessories are subject to change without prior notice. The illustrations in this manual may differ from the actual product and its accessories.

Refer to the product manual for the components of the optional accessories.






• Before you attach the OPS (Open Pluggable Specification) PC, connect the cable to the port.

Learning the Buttons

The illustrations may differ depending on the model.





Power On (Press)
Quick Menu (Press ¹)
Menu Selection (Press ²)
Power Off ³ (Press and Hold)





- 1 When the monitor is turned on, press the 🖰 button one time.
- 2 You can use the function when you control menu.
- 3 All running apps will close.

Quick Menu

(') Turns the power off.



Accesses the main menu.



Changes the input source.

X

Close the quick menu.


GETTING READY

Connecting the IR Sensors


Connecting the cable to the product allows it to receive signals from the remote control. Rotate the IR sensor according to horizontal or vertical use.

- The illustrations may differ depending on the model.

Default Mount - Horizontal Use



Vertical Use




Mounting and Removing the LG Logo Bracket

- Applies only to some models.
- The illustrations may differ depending on the model.


Removing the LG Logo Bracket

Place a clean cloth on the floor, and remove one screw from the LG logo bracket on the lower back of the monitor with a screwdriver.



Mounting the LG Logo Bracket on the Right

Screw the LG logo bracket into the hole on the right.



Kensington Lock Device

(This feature applies only to some models.)

The Kensington lock device connector is located on the back of the monitor. For more information on installation and use, refer to the user manual provided with the locking device.

Connect the Kensington security system cable between the monitor and a table.





NOTE

- The Kensington lock device is an optional specification.
- This is a general illustration of installation and may look different from the product held by the customer.

CHECKING BEFORE INSTALLATION

We are not responsible for product damage caused by failure to follow the guide.

Installation Orientation

Using Vertically


When installing vertically, rotate the monitor 90 degrees anti-clockwise while facing the front of the screen.



Tilt Angle



Ceiling, Floor Orientation




Installation Location

We are not responsible for product damage caused by failure to follow the guide.

Indoor

Installing on a Wall






A: 40 mm (1.5 inches)or more

 The warranty will not cover any damage caused by using the product in direct sunlight on the front panel.

Installing on a Recessed Wall





A: 40 mm (1.5 inches) or more

- B:50 mm (1.9 inches) or more
- C: 70 mm (2.7 inches) or more
- The warranty will not cover any damage caused by using the product in direct sunlight on the front panel.

Outdoor

Outdoor Enclosed




Wall Mount Holder

To install the monitor on a wall, attach a wall mount holder (optional) to the back of the monitor.

Take caution, and ensure that the wall mount holder (optional) is securely fixed to the monitor and to the wall.

The VESA dimensions of the wall mount by model are as follows.



Model	VESA Dimensions (A x B) (mm)	Standard Dimensions	Length (Maximum) (mm)	Quantity
43UH5J	200 x 200	M6	15.6	4
43UH7J	200 X 200	IVIO	13.0	4
49UH5J	200 200	MC	15.6	4
49UH7J	300 x 300	M6	15.6	4
55UH5J	300 x 300	M6	15.6	4
55UH7J	300 x 300	IVIO	15.0	4
65UH5J	200 v 200	MC	15.6	4
65UH7J	300 x 300	M6	15.6	4

Model	VESA Dimensions (A x B) (inches)	Standard Dimensions	Length (Maximum) (inches)	Quantity
43UH5J	7.8 x 7.8	M6	0.6	4
43UH7J	7.0 X 7.0	IVIO	0.6	4
49UH5J	11.8 x 11.8	M6	0.6	4
49UH7J	11.0 X 11.0	IVIO	0.0	4
55UH5J	11.8 x 11.8	M6	0.6	4
55UH7J	11.0 X 11.0	IVIO	0.0	4
65UH5J	11.8 x 11.8	M6	0.6	4
65UH7J	11.0 X 11.0	IVIO	0.6	4

CAUTION

- Disconnect the power cord first, and then move or install the monitor. Otherwise, it may result in electric shock.
- If the monitor is installed on a ceiling or inclined wall, it may fall and result in injury.
- · Damage to the monitor by tightening the screws too tightly may void your warranty.
- Use screws and wall mount plates conforming to VESA standards. Breakage or personal injury due to use or misuse
 of inappropriate components is not covered by the warranty of this product.



- · Using screws longer than the indicated depth may damage the inside of the product. Be sure to use the proper length.
- For more information on installation, please refer to the user manual for the wall mount.

PRECAUTIONS FOR USE

Dust


The warranty will not cover any damage caused by using the product in an excessively dusty environment.

Afterimage

- · After-image appears when the product is turned off.
 - Pixels may be damaged rapidly if a still image is displayed on the screen for a long period of time. Use the screensaver function.
 - Switching from a screen with high differences in luminance (black and white or grey) to a darker screen may cause an afterimage. This is normal due to the display characteristics of this product.
- When the LCD screen is in a still pattern for extended periods of use, a slight voltage difference may occur between
 the electrodes that operate the liquid crystal (LC). The voltage difference between the electrodes increases over time
 and tends to keep the liquid crystal aligned in one direction. At this time, the previous image remains, which is called
 an afterimage.
- Afterimages do not occur when continuously changing images are used but take place when a certain screen is fixed
 for a long time. The following are operational recommendations for reducing the occurrence of afterimages when
 using a fixed screen. The maximum recommended time for switching the screen is 12 hours. Shorter cycles are better
 for preventing afterimages.
- · Recommended Usage Condition

- 1 Change the background color and text color at equal intervals.
- Afterimages occur less when the colors to be changed are complementary to one another.





ITO or MoTi Pixel Layer

- 2 Switch the screen at equal time intervals.
- Take caution, and ensure that text or images from before the screen change are not left in the same location after the screen change.



PRODUCT SPECIFICATIONS

Without prior notice, all product information and specifications contained in this manual are subject to change to improve the performance of the product.

land Outrat Date	43/49/55/65UH5J	HDMI IN 1, HDMI IN 2, HDMI IN 3, DP IN, HDMI OUT, DVI-D IN, RS-232C IN/OUT, LAN, IR & LIGHT SENSOR, USB 2.0 IN, AUDIO IN/OUT, OPS	
Input/Output Ports	43/49/55/65UH7J	HDMI IN 1, HDMI IN 2, DP IN/OUT, DVI-D IN, RS-232C IN/OUT, USB Type-C, LAN, IR & LIGHT SENSOR, USB 2.0 IN, AUDIO IN/OUT, OPS	
	Recommended Resolution	HDMI1,2/ DisplayPort: 3840 x 2160 @ 60 Hz	
		USB Type-C: 3840 x 2160 @ 60 Hz (43/49/55/65UH7J) HDMI3: 3840 x 2160 @ 30 Hz (43/49/55/65UH5J)	
Resolution	Max Resolution	OPS: 3840 x 2160 @ 30 Hz	
		DVI-D: 1920 x 1080 @ 60 Hz	
		- This may not be supported on some OS or graphics card	
		types.	
Embedded battery	Applied		
	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)	
	Operating Humidity	10 % to 80 % (Condition for preventing condensation)	
Environmental Conditions	Storage Temperature	-20 °C to 60°C (-4 °F to 140 °F)	
	Storage Humidity	5 % to 85 % (Condition for preventing condensation)	
		* Product box packaging storage conditions	
Audio	Input Sensitivity	0.7 Vrms	



- USB-C does not support fast charging. Gender converters for fast charging is also not supported.
- Use a certified USB-C cable (1.5 M (4.9 feet) or less). If you do not do so, the screen may not be displayed or a connection error may occur.
- USB-C port is not supported to DPM (Sleep mode).

43UH5J, 43UH7J

Power Voltage	100-240 V ~ 50/60 Hz 1.2 A	
	On Mode	80 W (Typ.)
Power Consumption	Sleep Mode / Standby Mode ≤ 0.5 W	
Dimensions (Width x Height x	Head	962.5 mm x 568.0 mm x 39.9 mm / 11.2 kg
Depth) / Weight		(37.8 inches x 22.3 inches x 1.5 inches / 24.6 lbs)
	Head + Stand	962.5 mm x 613.1 mm x 290.0 mm / 11.8 kg
		(37.8 inches x 24.1 inches x 11.4 inches / 26.0 lbs)

49UH5J, 49UH7J

Power Voltage	100-240 V ~ 50/60 Hz 1.6 A	
	On Mode 100 W (Typ.)	
Power Consumption	Sleep Mode / Standby	< 0.5 W
	Mode	S 0.5 W
Dimensions (Width x Height x	Head	1098.6 mm x 644.5 mm x 39.9 mm / 15.4 kg
Depth) / Weight		(43.2 inches x 25.3 inches x 1.5 inches / 33.9 lbs)
	Head + Stand	1098.6 mm x 694.3 mm x 290.0 mm / 16.0 kg
		(43.2 inches x 27.3 inches x 11.4 inches / 35.2 lbs)

55UH5J, 55UH7J

Power Voltage	100-240 V ~ 50/60 Hz 1.7 A		
	On Mode	110 W (Typ.)	
Power Consumption	Sleep Mode / Standby	< 0.5 W	
	Mode	0.5 W	
	Head	1234.4 mm x 720.9 mm x 39.9 mm / 19.0 kg	
Dimensions (Width x Height x Depth) / Weight		(48.5 inches x 28.3 inches x 1.5 inches / 41.8 lbs)	
	Head + Stand	1234.4 mm x 770.7 mm x 290.0 mm / 19.6 kg	
		(48.5 inches x 30.3 inches x 11.4 inches / 43.2 lbs)	

65UH5J, 65UH7J

Power Voltage	100-240 V ~ 50/60 Hz 1.9 A		
	On Mode	130 W (Typ.)	
Power Consumption	Sleep Mode / Standby Mode	≤ 0.5 W	
Dimensions (Width x Height x Depth) / Weight	Head	1453.3 mm x 844.0 mm x 39.9 mm / 28.2 kg	
		(57.2 inches x 33.2 inches x 1.5 inches / 62.1 lbs)	
	Head + Stand	1453.3 mm x 893.1 mm x 290.0 mm / 28.8 kg	
		(57.2 inches x 35.1 inches x 11.4 inches / 63.4 lbs)	

HDMI/ DVI-D/ DisplayPort/ USB-C/ OPS (PC) Support mode

Resolution	Horizontal frequency (kHz)	Vertical frequency (Hz)	Remark
800 x 600	37.879	60.317	
1024 x 768	48.363	60	
1280 x 720	44.772	59.855	
1280 x 1024	63.981	60.02	
1680 x 1050	65.29	59.954	
1920 x 1080	67.5	60	
3840 x 2160	67.5	30	HDMI1/2/3, DisplayPort, USB-C, OPS
3840 x 2160	135	60	HDMI1/2, DisplayPort, USB-C

HDMI/ DisplayPort/ OPS (DTV) Support mode

Resolution	Horizontal frequency (kHz)	Vertical frequency (Hz)	Remark
480/60p	31.5	60	
576/50p	31.25	50	
720/50p	37.5	50	
720/60p	45	60	
1080/50i	28.1	50	
1080/60i	33.75	60	
1080/50p	56.25	50	
1080/60p	67.432	59.94	
1080/60p	67.5	60	
2160/30p	67.5	30	HDMI1/2/3, DisplayPort, OPS
2160/50p	112.5	50	HDMI1/2, DisplayPort
2160/60p	135	60	HDMI1/2, DisplayPort



- Horizontal frequency: The horizontal interval is the time taken to display one horizontal line. When 1 is divided by the horizontal interval, the number of horizontal lines displayed every second can be tabulated as the horizontal frequency. The unit is kHz.
- Vertical frequency: The product display functions by the screen image changing dozens of times every second like a fluorescent lamp. The vertical frequency or refresh rate is the number of image displays per second. The unit is Hz.

vvireless module (LGSBvvAC92) Specifications				
Wireless LAN (IEEE 802.11a/b/g/n/ac)				
Frequency range (MHz) Output power (Max.) (dBm)				
2400 to 2483.5				
5150 to 5725				
5725 to 5850 18				
Bluetooth				
Frequency range (MHz) Output power (Max) (dBm)				

dula (LCCDMACOS) Caa

As band channels can vary per country, the user cannot change or adjust the operating frequency. This product is configured for the regional frequency table.

- For consideration of the user, this device should be installed and operated with a minimum distance of 20 cm (7.8 inches) between the device and the body.
- FCC ID: BEJLGSBWAC92 / IC: 2703H-LGSBWAC92

2400 to 2483.5

LICENCE

Supported licenses may differ by model. For more information of the licenses, visit www.lg.com.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Manufactured under license from Dolby Laboratories. Dolby, Dolby Vision, Dolby Vision IQ, Dolby Audio, Dolby Atmos, and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation.

For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Licensing Limited. DTS, the Symbol, & DTS and the Symbol together, DTS 2.0 Channel, DTS 2.0+Digital Out, DTS-HD, and DTS Virtual:X are registered trademarks or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.



The Bluetooth[®] word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by LG Electronics Inc. is under license. Other trademarks and trade names are those of their respective owners.



Supplier's Declaration of Conformity

Trade Name LG

Responsible Party LG Electronics USA, Inc.

Address 111 Sylvan Avenue, North Building,

Englewood Cliffs, NJ 07632

E-mail lg.environmental@lge.com

The model and serial number of the product are located on the back and on one side of the product. Record them below in case you ever need service.



SERIAL NO.



This product qualifies for ENERGY STAR®.

Changing the factory default configuration and settings or enabling certain optional features and functionalities may increase energy consumption beyond the limits required for ENERGY STAR® certification.

Refer to ENERGYSTAR.gov for more information on the ENERGY STAR® program.

Temporary noise is normal when powering ON or OFF this device