

Owner's Manual



* LG LED Monitor applies LCD screen with LED backlights.

Please read this manual carefully before operating your set and retain it for future reference.

32GR93U

www.lg.com

Copyright © 2022 LG Electronics Inc. All Rights Reserved.

TABLE OF CONTENTS

	L	C

LICENSE......3

OPEN SOURCE SOFTWARE NOTICE INFORMATION4

ASSEMBLING AND PREPARING 4

- Supported Drivers and Software5
- Product and Button Description......5
- How to Use the Joystick Button
- Moving and Lifting the Monitor......6
- Installing on a Table
- Adjusting the Stand Height
- Adjusting the Angle
- Pivot Feature
- Using the Kensington Lock
- Installing the Wall Mount Plate
- Installing on the Wall

USING THE MONITOR...... 15

- Connecting to a PC......15 HDMI Connection DisplayPort Connection
- Connecting AV Devices......16 HDMI Connection
- Connecting Peripherals......17 USB Device connection

Connecting Headphones

USER SETTINGS 18

Menu Settings

TROUBLESHOOTING...... 30

PRODUCT SPECIFICATION 34

LICENSE

Each model has different licenses. Visit www.lg.com for more information on the license.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



The SuperSpeed USB Trident logo is a registered trademark of USB Implementers Forum, Inc.



VESA, VESA logo, DisplayPort compliance logo and DisplayPort compliance logo for dual-mode source devices are all registered trademarks of the Video Electronics Standards Association.



For DTS patents, see http://patents.dts.com.

Manufactured under license from DTS Licensing Limited. DTS, the Symbol, & DTS and the Symbol together, Headphone:X, and the DTS Headphone:X logo are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

OPEN SOURCE SOFTWARE NOTICE INFORMATION

To obtain the source code that is contained in this product, under GPL, LGPL, MPL, and other open source licenses that have the obligation to disclose source code, and to access all referred license terms, copyright notices and other relevant documents, please visit https://opensource.lge.com.

LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping, and handling) upon email request to opensource@lge.com.

This offer is valid to anyone in receipt of this information for a period of three years after our last shipment of this product.

ASSEMBLING AND PREPARING

CAUTION

- · Always use genuine LG components to ensure safety and product performance.
- The product warranty will not cover damage or injury caused by the use of unauthorized components.
- It is recommended that use the supplied components.
- If you use generic cables not certified by LG, the screen may not display or there may be image noises.
- Illustrations in this document represent typical procedures, so they may look different from the actual product.
- Do not apply foreign substances (oils, lubricants, etc.) to the screw parts when assembling the product. (Doing so may damage the product.)

- Applying excessive force when tightening screws may cause damage to the monitor. Damage caused in this way will not be covered by the product warranty.
- Do not carry the monitor upside down by just holding the base. This may cause the monitor to fall off the stand and could result in personal injury.
- When lifting or moving the monitor do not touch the monitor screen. The force applied to the monitor screen may cause damage to it.
- For wave pattern on appearance, unlike the general method of coating, it's applied to added glittering material in raw material. With no peeled-off appearance, it has good durability. Please use it with confidence because there is no problem in using the product at all.

NOTE

- The components may look different from those illustrated here.
- · Without prior notice, all product information and specifications contained in this manual are subject to change to improve the performance of the product.
- To purchase optional accessories, visit an electronics store or an online shopping site, or contact the retailer from where you purchased the product.
- The power cord provided may differ depending upon the region.

Supported Drivers and Software

You can download and install the latest version from the LGE website (*www.lg.com*).

Drivers and Software	Installation Priority
Monitor Driver	Recommended
OnScreen Control	Recommended
LG Calibration Studio	Optional

Product and Button Description





Joystick Button

How to Use the Joystick Button

You can easily control the functions of the monitor by pressing the joystick button or moving it left/right/up/down with your finger.


Basic Functions

		Power on	Press the joystick button once with your finger to turn on the monitor.
		Power off	Press and hold the joystick button once with your finger to turn off the monitor.
		Volume control	You can control the volume by moving the joystick button left/ right.
	▲/▼	Controls screen brightness	You can control the screen's brightness by moving the joystick button up/down.

Moving and Lifting the Monitor

When moving or lifting the monitor, follow these instructions to prevent the monitor from being scratched or damaged and to ensure safe transportation, regardless of its shape or size.

- Place the monitor in the original box or packing material before attempting to move it.
- Before moving or lifting the monitor, disconnect the power cord and all other cables.
- Hold the bottom and side of the monitor frame firmly. Do not hold the panel itself.
- When holding the monitor, the screen should face away from you to prevent it from being scratched.
- When transporting the monitor, do not expose the monitor to shock or excessive vibration.
- When moving the monitor, keep it upright and never turn the monitor on its side or tilt it sideways.






- Avoid touching the monitor screen as much as possible.
 - This may result in damage to the screen or some of the pixels used to create images.
- If you use the monitor panel without the stand base, its joystick button may cause the monitor to become unstable and fall, resulting in damage to the monitor or human injury. In addition, this may cause the joystick button to malfunction.

Installing on a Table


 Lift the monitor and place it on the table in an upright position. Place the monitor at least 100 mm (3.94 inches) away from the wall to ensure sufficient ventilation.



- Unplug the power cord before moving or installing the monitor. There is risk of electric shock.
- Make sure to use the power cord that is provided in the product package and connect it to a grounded power outlet.
- If you need another power cord, please contact your local dealer or the nearest retail store.

Adjusting the Stand Height

- 1 Place the monitor mounted on the stand base in an upright position.
- 2 Handle the monitor with both hands for safety.






• When adjusting the screen height, do not place your hand on the stand body to avoid injury to your fingers.

Adjusting the Angle

- 1 Place the monitor mounted on the stand base in an upright position.
- 2 Adjust the angle of the screen.

The angle of the screen can be adjusted forward or backward from -5° to 15° for a comfortable viewing experience.

To avoid injury to the fingers when adjusting the screen, do not hold the lower part
of the monitor's frame as illustrated below.




• Be careful not to touch or press the screen area when adjusting the angle of the monitor.



Pivot Feature

The pivot feature allows the monitor to rotate 90° clockwise.




- To avoid scratching the stand base, make sure that when rotating the monitor using the pivot feature, the stand does not make contact with the monitor.
- When using the Pivot function, do not rotate the monitor too fast or with excessive force.
- The head may come in contact with the stand and scratch the base.
- Be careful as you may injure your finger by jamming it between the head and the stand.

1 Raise the monitor to the maximum height.



2 Adjust the angle of the monitor in the direction of the arrow as shown in the figure.



3 Rotate the monitor clockwise as shown in the figure.



4 Complete the installation by rotating the monitor 90° as shown below.



• Be careful as you may injure your finger by jamming it between the head and the desk.


- · Auto Pivot feature of the display is not supported.
- The screen can be rotated easily using the screen pivot shortcut key provided with your Windows operating system. Note that some Windows versions and some graphics card drivers may use different settings for the screen pivot key or may not support the pivot key at all.

Using the Kensington Lock

The connector for the Kensington security system is located at the bottom of the monitor.

For more information on installation and usage, refer to the Kensington lock owner's manual or visit the website at *http://www.kensington.com*.

Connect the monitor to a table using the Kensington security system cable.





• The Kensington security system is optional. You can obtain optional accessories from most electronics stores.

Installing the Wall Mount Plate


This monitor meets the specifications for the wall mount plate or other compatible devices.

- Place the screen face down. To protect the monitor panel (screen), cover the surface with a soft cloth or the monitor protection pad included in the product package.
- 2 Remove the four screws tightened on the back of the monitor.
- 3 Place the wall mount plate onto the monitor and align it with the screw holes.
- 4 Tighten the four screws using a screwdriver to fix the plate to the monitor.

- The wall mount plate is sold separately.
- For more information on installation, refer to the wall mount plate's installation guide.
- Be careful not to apply too much force while mounting the wall mount plate as it may cause damage to the screen.

Installing on the Wall

Install the monitor at least 100 mm (3.94 inches) away from the wall and leave about 100 mm (3.94 inches) of space at each side of the monitor to ensure sufficient ventilation. Detailed installation instructions can be obtained from your local retail store. Alternatively, please refer to the manual for how to install and set up a tilting wall mounting bracket.



To install the monitor to a wall, attach a wall mounting bracket (optional) to the back of the monitor.

Make sure that the wall mounting bracket is securely fixed to the monitor and to the wall.


- 1 If you use screws longer than the standard length, it may damage the inside of the product.
- 2 A non-VESA standard screw may damage the product and cause the monitor to fall. LG Electronics is not liable for any accidents relating to the use of nonstandard screws.

Wall Mount (mm)	100 x 100
Standard screw	M4 x L10
Number of screws	4
Wall Mount Plate (Optional)	LSW 149

- · Use the screws specified by VESA standards.
- The wall mount kit includes the installation guide and all necessary parts.
- The wall mounting bracket is optional. You can obtain optional accessories from your local dealer.
- The length of the screw may differ for each wall mounting bracket. Be sure to use the proper length.
- For more information, please refer to the user manual for the wall mounting bracket.

- Unplug the power cord before moving or installing the monitor to avoid electric shock.
- Installing the monitor on the ceiling or on a slanted wall may result in the monitor falling off, which could lead to injury. Use an authorized LG wall mount and contact the local dealer or qualified personnel.
- Applying excessive force when tightening screws may cause damage to the monitor. Damage caused in this way will not be covered by the product warranty.

- Use the wall mounting bracket and screws that conform to VESA standards. Damage caused by the use or misuse of inappropriate components will not be covered by the product warranty.
- When measured from the back of the monitor, the length of each installed screw must be 8 mm (0.3 inches) or less.



Wall Mount Plate

USING THE MONITOR

- Illustrations in this manual may differ from the actual product. Press the joystick button, go to $\textbf{Settings} \to \textbf{Input}$, and then select the input option.

- Do not press the screen for a prolonged time. This may cause image distortion.
- Do not display a still image on the screen for a prolonged time. This may cause image retention. Use a screensaver if possible.

- When connecting the power cord to the outlet, use a grounded (3-hole) power strip or a grounded power outlet.
- The monitor may flicker when turned on in an area where the temperature is low. This is normal.
- Sometimes red, green, or blue spots may appear on the screen. This is normal.

Connecting to a PC

- This monitor supports the *Plug and Play feature.
- * Plug and Play: A feature that allows you to add a device to your computer without having to reconfigure anything or install any manual drivers.

HDMI Connection

Transmits digital video and audio signals from your PC to the monitor.

- Using a DVI to HDMI / DP (DisplayPort) to HDMI cable may cause compatibility issues.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI cable types
- Ultra High Speed HDMI®/ $^{\text{TM}}$ cable

DisplayPort Connection

Transmits digital video and audio signals from your PC to the monitor.

- There may be no video or audio output depending on the DP (DisplayPort) version of the PC.
- If you are using a Mini DisplayPort output graphics card, use a Mini DP to DP (Mini DisplayPort to DisplayPort) cable or gender that supports DisplayPort1.4. (sold separately)

Connecting AV Devices

HDMI Connection

HDMI transmits digital video and audio signals from your AV device to the monitor.

- Using a DVI to HDMI / DP (DisplayPort) to HDMI cable may cause compatibility issues.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI cable types
- Ultra High Speed HDMI®/TM cable

Connecting Peripherals

USB Device connection

The USB port on the product functions as a USB hub.

To use USB 3.0, connect the A-B type USB 3.0 cable of the product to the PC. Peripheral devices connected to the USB IN port can be controlled from the PC.

- It is recommended you install all Windows Updates to keep your Windows up-todate before connecting to the product for use.
- Peripheral devices are sold separately.
- A keyboard, mouse, or USB device can be connected to the USB port.
- The charging speed may vary depending on the device.

Cautions When Using a USB Device

- A USB device with an automatic recognition program installed, or that uses its own driver, may not be recognized.
- Some USB devices may not be supported or may not work properly.
- It is recommended to use a USB hub or hard disk drive with power supplied. (If the power supply is not adequate, the USB device may not be recognized properly.)


Connecting Headphones

Connect peripherals to the monitor via the headphones port.

- Peripheral devices are sold separately.
- If you use angled earphones, it may cause a problem with connecting another external device to the monitor. Therefore, it is recommended to use straight earphones.



• Depending on the audio settings of the PC and external device, headphones and speaker functions may be limited.



• Please connect the USB A to B cable to use a microphone function with headphones equipped with a microphone.


USER SETTINGS

18

- Your monitor's OSD (On Screen Display) may differ slightly from that shown in this manual.
- When **Beep Guide** is activated, pressing the joystick button will take you to **Settings** right away.

Activating the Main Menu

- 1 Press the joystick button on the bottom of the monitor.
- 2 Move the joystick up/down (▲ / ▼) and left/right (◄ / ►) to set the options.
- 3 Press the joystick button once more to exit the main menu.



Button	Menu Status		Description
Main menu disabled		enu disabled	Enables the main menu.
	Main menu enabled		Enters the Settings feature. (Holding down the button to turn off the monitor. You can turn off the monitor this way at any time, including when the OSD is on.)
		Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the Input feature.
		Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the Game Mode feature.
		Main menu disabled	Enters the Accessibility menu.
		Main menu enabled	Turns off the monitor.
	▼	Main menu disabled	Enters the Accessibility menu.
,		Main menu enabled	Exits the main menu.

Main Menu Features



Main Menu	Description			
Input	Sets input mode.			
Power Off	Turns off the monitor.			
Settings	Configures the screen settings.			
Game Mode	Sets the game mode for gaming.			
Exit	Exits the main menu.			

User Settings

20

Menu Settings

- 1 To view the OSD menu, press the joystick button at the bottom of the monitor and then enter the **Settings**.
- 2 Configure the options by moving the joystick up/down/left/right.
- 3 To return to the upper menu or set other menu items, move the joystick to ◀ or pressing (他) it.
- 4 If you want to exit the OSD menu, move the joystick to < until you exit.











General

Game Mode

Game Adjust

Picture Adjust

Input

Game Mode on SDR(Non-HDR)signal.

Settings > Game Mode		Description			
	Gamer 1	In this mode, users can customize elements including game-related options.			
	Gamer 2	Gamer 1 and Gamer 2 picture modes allow you to save two sets of customized display settings, including game-related setup options.			
	FPS	This mode is optimized for FPS games. It is suitable for very dark FPS games.			
	RTS	This mode is optimized for RTS games.			
	Vivid	Optimized the screen for vivid colors.			
	Reader	Optimizes the screen for viewing documents. You can brighten the screen in the OSD menu.			
Game Mode	HDR Effect	Optimizes the screen for high dynamic range.			
	sRGB	A standard RGB color space for the monitor and printer.			
	Color Weakness	This mode is for users who cannot distinguish between red and green. It enables users with color weakness to easily distinguish between the two colors.			
	Calibration 1				
	Calibration 2	Adjusts to the calibrated screen.			
	Calibration 1/Cali	ration 2 : Please install LG Calibration Studio to run calibration.			

Game Mode on HDR signal.

Settings > Game

-			
lode	Description		
Gamer 1	In this mode, users can customize elements including game-related options.		
Gamer 2	Gamer 1 and Gamer 2 picture modes allow you to save two sets of customized display settings, including game-related setup options.		
FPS	This mode is optimized for FPS games. It is suitable for very dark FPS games.		
RTS	This mode is optimized for RTS games.		
Vivid	Optimized the screen for vivid colors.		

Game Mode

- HDR content may not be operated properly depending on the Windows10 OS setting. Please check the HDR On / Off setting of Windows.
- When the HDR function is turned on, the characters or picture quality may be poor according to Graphic card performance.
- While the HDR function is on, screen flickering or cracking may occur when changing the monitor input or power on/off according to Graphic card performance.
- For information about whether the graphics card and game support HDR, visit their manufacture's website.

Settings > Game Adjust		Description		
Adaptive-Sync / VRR Game Adjust		CAUTIO Supported Inter Supported Grap Supported Versi	s and natural images by synchronizing the vertical frequency of the input signal with that of the output signal. IN face: DisplayPort (Adaptive-Sync), HDMI (Variable Refresh Rate). hic Card: A graphic card that supports NVIDIA's G-SYNC or AMD's FreeSync is necessary. ion: Make sure to update the graphic card to the latest driver. nation and requirement, refer to NVIDIA website (<i>www.nvidia.com</i>) and AMD website (<i>www.amd.com</i>).	
		Extended	Enables wider frequency range of Adaptive-Sync/VRR function than basic mode. The screen may flicker during the game play.	
		Basic	Enables basic frequency range of Adaptive-Sync/VRR function.	
		Off	Adaptive-Sync/VRR function off.	
	Black StabilizerYou can control the black contrast to have better visibility in dark scenes. You can easily distinguish objects on dark game screens.			

		Sets a response time for displayed pictures based on the speed of the screen.			
		For a normal environment, it is recommended that you use Fast .			
		For a fast-moving	picture, it is recommended that you use Faster .		
		Once Faster Mode is selected, Motion Blur may occur depending on the content.			
	Response Time	Faster	Sets the response time to Faster.		
		Fast	Sets the response time to Fast.		
		Normal	Sets the response time to Normal.		
		Off	Does not use the response time improvement feature.		
Game Adjust	Crosshair		Crosshair provides a mark on the center of the screen for First Person Shooter (FPS) games. Users can select the Crosshair that fits their gaming environment among four different Crosshairs.		
Game Adjust		On	The indicator is displayed on the upper left of the screen. It will reflect the actual frame rate that is received at the input. You can also adjust the position of FPS Counter. (upper left / upper right / lower right / lower left)		
	FPS Counter	Off	Does not use the FPS Counter feature.		
		• FPS Counter ar	nd Crosshair feature can not be used at the same time.		
		Returns game to the default settings.			
	Game Reset	No	Cancel the select.		
		Yes	Returns to the default settings.		

Settings > Picture Adjust			Description			
	Brightness	Adjusts the brightne	ess of the screen.			
	Contrast	Adjusts the contrast	Adjusts the contrast of the screen.			
	Sharpness	Adjusts the sharpne	Adjusts the sharpness of the screen.			
	Gamma	Mode 1, Mode 2, Mode 3	The higher the gamma value, the darker the image becomes. Likewise, the lower the gamma value, the lighter the image becomes.			
		Mode 4	If you do not need to adjust the gamma settings, select Mode 4.			
		Custom	The user can adjust it to red, green, or blue by customization.			
		Warm	Sets the screen color to a reddish tone.			
	Color Temp	Medium	Sets the screen color to between a red and blue tone.			
		Cool	Sets the screen color to a bluish tone.			
Picture Adjust		Manual	The user can fine - tune the color temperature.			
	R/G/B	You can customize t	You can customize the picture color using Red , Green , and Blue colors.			
			irements for colors by adjusting the hue and saturation of the six colors (Red, Green, Blue, Cyan, Magenta n saving the settings.			
	Six Color	Hue	Adjusts the tone of the screen colors.			
	Sat	Saturation	Adjusts the saturation of the screen colors. The lower the value, the less saturated and brighter the colors become.			
		Sets the offset leve • Offset: as a refe	el (for HDMI only). rence for a video signal, this is the darkest color the monitor can display.			
		High	Keeps the current contrast ratio of the screen.			
		Low	Lowers the black levels and raises the white levels from the current contrast ratio of the screen.			

		Provides extended contrast and gradation on a dark screen depending on game or video content.			
		Faster	Preferably for PC gaming experiences.		
		Fast	Preferably for console gaming experiences.		
		Normal	Preferably for playing video content and internet or word-processing.		
	Variable Backlight	Off	Disables the Variable Backlight feature.		
Picture Adjust	Variable Dacklight	 NOTE When these feature is enabled, a slight halo effect may be shown on dark backgrounds. This is normal and not a malfunction. When these feature is enabled, the screen flickering may occur intermittently. The function can only be used on HDR content. It is recommended to turn off when you are not using the gaming function. 			
	DFC	On	Adjusts the brightness automatically according to the screen.		
	DFC	Off	Disables the DFC feature.		
	Picture Reset	Do you want to reset your picture settings?			
		No	Cancel the select.		
		Yes	Returns to the default settings.		

Settings > Input		Description		
	Input List	Selects the input mode.		
		Adjusts the aspect ratio of the screen.		
Aspect Ratio		Full Wide	Displays the video in widescreen, regardless of the video signal input.	
Input		4:3	Displays the video in 4:3.	
When automatic input switch is set to On , display will automatically switch to n		ut switch is set to On , display will automatically switch to new input when connected.		
	Auto Input Switch	On	Enables Auto Input Switch.	
		Off	Disables Auto Input Switch.	

Settings > General		Description			
	Language	Sets the menu scree	Sets the menu screen to the desired language.		
	Hexagon Lighting	You can turn on or off the lighting on the back of the monitor, and you can also select or adjust the lighting color.			
	User-defined Key 1	You can customise	/ou can customise the main menu to access your preferred menu easily.		
	User-defined Key 2	User-definded Key 1 and User-definded Key 2 appear at the left/right of the main menu.			
		Enables the realizat	ion of three-dimensional sound with headphones or earphone.		
		Game	This mode is optimized for Game.		
	DTS Headphone:X	Entertainment	This mode is optimized for Entertainment.		
		Sports	This mode is optimized for Sports.		
		Off	Disables DTS Headhpone:X function.		
General	SMART ENERGY SAVING	High	Saves energy using the high-efficiency SMART ENERGY SAVING feature.		
General		Low	Saves energy using the low-efficiency SMART ENERGY SAVING feature.		
		Off	Disables the SMART ENERGY SAVING feature.		
	Deep Sleep Mode	When Deep sleep m	node is enabled, power consumption is minimized while the monitor is in standby mode.		
		On	Enables Deep sleep Mode.		
		Off	Disables Deep sleep Mode.		
	Power LED	Turns the power LEI	D on the bottom of the monitor on or off.		
		On	The power LED turns on automatically.		
		Off	The power LED turns off.		
	Automatic Standby	Feature that automatically turns off the monitor when there is no movement on the screen for a period of time. You can timer for the auto-off function. (8H, 6H, 4H and Off)			

	Input Compatibility	Please set the Input Compatibility Version to match the version of the connected external device.			
		номі	2.1(PC)/2.1(AV)/1.4		
			If you want to use the HDR, select the Input Compatibility Version to 2.1(PC) or 2.1(AV).		
		DisplayPort	1.4(DSC)/1.4/1.2		
	Version		If you want to use the HDR, select the Input Compatibility Version to 1.4(DSC) or 1.4.		
		 If the connected d 	evice supports 2.1 in HDMI but the screen or sound does not work properly, set this function to 2.1(AV).		
		This feature lets you set the sound generated from Buzzer when your monitor powers on.			
	Buzzer	On	Enables your monitor's Buzzer .		
General		Off	Disables your monitor's Buzzer .		
		This feature disables the configuration and adjustment of menus.			
	OSD Lock	On	Enables OSD Lock.		
		Off	Disables OSD Lock.		
		I NOTE			
		• All features are disabled except Brightness, Contrast in Picture Adjust, Input, OSD Lock and Information in General.			
	Information	The display information will be shown the Total Power On Time, Resolution.			
	Reset to Initial Settings	Do you want to reset your settings?			
		No	Cancel the reset.		
		Yes	Returns to the default settings.		

TROUBLESHOOTING

Nothing is displayed on the screen.		
Is the monitor's power cord plugged in?	Check if the power cord is correctly plugged into the power outlet.	
Is the power LED on?	Check the power cable connection and press the power button.	
Is the power on and the power LED displaying white?	 Check that the connected input is enabled (Settings > Input). 	
Is the power LED blinking?	 If the monitor is in sleep mode, move the mouse, or press any key on the keyboard, to switch the display on. Check if the computer is turned on. 	
Is the "The screen is not currently set to the recommended resolution. If you have no video or the screen flickers, see the troubleshooting guide in the product owner's manual." message being displayed?	 This occurs when signals transferred from the PC (graphics card) are out of the recommended horizontal or vertical frequency range of the monitor. Please see the Product Specification section of this manual to set the appropriate frequency. 	
Is the "No Signal" message being displayed?	• This is displayed when the signal cable between the PC and the monitor is missing or disconnected. Check the cable and reconnect it.	
Have you installed the display driver? • Be sure to install the display driver from our web site: http://www.lg.com. • Make sure to check if the graphics card supports Plug and Play function.		

Some features are disabled.		
Are some functions not available when you press the Menu button?	 The OSD is locked. Go to Settings > General and set OSD Lock to Off. 	

The screen retains an image.		
Does image sticking occur even when the	• Displaying a still image for a prolonged time may cause damage to the screen, resulting in the retention of the image.	
monitor is turned off?	 To extend the lifetime of the monitor, use a screensaver. 	

Screen display is unstable and shaky. / Images displayed on the monitor leave shadow trails.		
Did you select the appropriate resolution?	e resolution? • If the selected resolution is HDMI 1080i 60/50 Hz (interlaced), the screen may be flickering. Change the resolution to 1080p or the recommended resolution.	

3840 x 2160 resolution is not available in DisplayPort. (144 Hz)		
Is it connected to the correct input?	 In DisplayPort. (144 Hz) If it is connected with HDMI input, set it to DisplayPort input. Go to Settings > General > Input Compatibility Version and set the option to 1.4(DSC). Check if the graphics card supports the DSC (Display Stream Compression). Check if the graphics card driver has been updated to the latest version. 	

3840 x 2160 resolution is not available in HDMI. (144 Hz)		
Is it connected to the correct graphics • Check if the graphics card supports 3840 x 2160 / 144 Hz in HDMI. (NVIDIA RTX3000 Series, AMD RX6000 Se		
card?	 Check if the graphics card driver has been updated to the latest version. 	

- Vertical Frequency: In order to display an image, the screen must be refreshed dozens of times per second, like a fluorescent lamp. The number of times the screen is refreshed per second is called vertical frequency, or refresh rate, and is represented by Hz.
- Horizontal Frequency: The time it takes to display one horizontal line is called the horizontal cycle. If 1 is divided by the horizontal interval, the result is the number of horizontal lines displayed per second. This is called horizontal frequency and is represented by kHz.
- Check if the graphics card's resolution or frequency is within the range allowed by the monitor and set it to the recommended (optimal) resolution **Control Panel > Display > Settings** in Windows. (The settings may differ depending on the operating system (OS) you use.)
- Not setting the graphics card to the recommended (optimal) resolution may result in blurred text, a dimmed screen, a truncated display area or misalignment of the display.
- The setting methods may be different depending on the computer or operating system, and some resolutions may not be available depending on the performance of the graphics card. If this is the case, contact the manufacturer of the computer or graphics card for assistance.
- Some graphics cards may not support 3840 x 2160 resolution. If the resolution cannot be displayed, contact the manufacturer of your graphics card.

The display color is abnormal.	The display color is abnormal.		
Does the display appear discolored (16 colors)?	 Set the color to 24 bit (true color) or higher. In Windows, go to Control Panel > Display > Settings > Color Quality. (The settings may differ depending on the operating system (OS) you use.) 		
Does the display color appear unstable or monochrome?	• Check if the signal cable is connected properly. Reconnect the cable or reinsert the PC's graphics card.		
Are there spots on the screen?	• When using the monitor, pixilated spots (red, green, blue, white, or black) may appear on the screen. This is normal for an LCD screen. It is not an error, nor is it related to the monitor's performance.		

No sound from the headphone port.		
Are images displayed using DP (DisplayPort) or HDMI input without sound?	 Make sure that the headphone port connections are made properly. Try increasing the volume with the joystick. Set the audio output of the PC to the monitor you are using. On Microsoft Windows, go to Control Panel > Hardware and Sound > Sound > set the Monitor as default device. (The settings may differ depending on the operating system (OS) you use.) 	

PRODUCT SPECIFICATION

		1			
LCD Screen	Color Depth	HDMI	8-bit/10-bit color is supported.		
		DP (DisplayPort)	10-bit color is supported.		
Resolution	Max Resolution	3840 x 2160 @ 144 H	3840 x 2160 @ 144 Hz		
	Recommended Resolution	3840 x 2160 @ 144 H	Z		
Power Sources	Power Rating	19 V 5.0 A	19 V 5.0 A		
	Power Consumption (Typical)		On mode: 65 W (Typical)* Sleep Mode (Standby Mode) : ≤ 0.5 W ([Deep Sleep Mode]: [On])** Off Mode: < 0.3 W		
AC/DC Adapter	ADS-120QL-19A-3, manufactured Output: 19 V 5.79 A	manufactured by SHENZHEN HONOR ELECTRONIC 79 A			
Environmental Conditions	Operating Conditions	Temperature	0 °C to 40 °C (32 °F to 104 °F)		
		Humidity	Less than 80 %		
	Storing Conditions	Temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
		Humidity	Less than 85 %		
Dimensions Monitor Size (Width x Height x Depth)					
	With Stand		713.9 x 611.2 x 278 (mm) 28.1 x 24.0 x 10.9 (inches)		
	Without Stand	,	713.9 x 428.2 x 54 (mm) 28.1 x 16.8 x 2.1 (inches)		

Weight (Without Packaging)	With Stand	8.3 kg (18.2 lbs)
	Without Stand	6.0 kg (13.2 lbs)

Specifications are subject to change without notice.

The ~ symbol means alternating current, and the ____ symbol means direct current.

The Power Consumption level can be different by operating condition and monitor setting.

* The On mode power consumption is measured with LGE test standard (Full White pattern , Maximum resolution).

** The monitor goes to the Sleep Mode in a couple of minutes (Max 5 minutes).

Factory Support Mode

HDMI

Resolution	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Polarity (H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60.004	-/-	
1280 x 720	45	60	+/+	
1280 x 1024	79.976	75.025	+/+	
1920 x 1080	67.5	60	+/+	
1920 x 1080	66.587	59.934	+/-	
3840 x 2160	65.688	29.981	+/-	Recommended Timing - Input Compatibility Version: 1.4
1920 x 1080	166.688	144.052	+/-	
2560 x 1440	182.996	119.998	+/-	
3840 x 2160	133.313	59.997	+/-	Recommended Timing - Input Compatibility Version: 2.1(AV)
2560 x 1440	222.268	144.05	+/-	
3840 x 2160	333.33	144.05	+/-	Recommended Timing - Input Compatibility Version: 2.1(PC)

DisplayPort

Resolution	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Polarity (H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60.004	-/-	
1280 x 720	45	60	+/+	
1280 x 1024	79.976	75.025	+/+	
1920 x 1080	67.5	60	+/+	
1920 x 1080	166.587	143.981	+/-	
3840 x 2160	133.313	59.997	+/-	Recommended Timing - Input Compatibility Version: 1.2
2560 x 1440	222.151	143.973	+/-	
3840 x 2160	214.68	95.033	+/-	
3840 x 2160	268.438	119.999	+/-	Recommended Timing - Input Compatibility Version: 1.4
3840 x 2160	333.33	144.05	+/-	Recommended Timing - Input Compatibility Version: 1.4(DSC)

* DSC: Display Stream Compression.

* To display 144 Hz or over, make sure to use the graphics card that supports DSC (Display Stream Compression).



HDMI Timing (Video)

Factory support mode (Preset Mode)	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Remarks
480P	31.5	60	
720P	45	60	
1080P	67.5	60	
1080P	135	120	
2160P	135	60	
2160P	255	120	

Power LED

Mode	LED Color
On Mode	Red (For a few seconds)
Sleep Mode (Standby Mode)	Off
Off Mode	Off

Beep Guide

Menu	Location
Game Mode	1
Game Mode - Gamer1	11
Game Mode - Gamer2	12
Game Mode - FPS	13
Game Mode - RTS	14
Game Mode - Vivid	15
Game Mode - Reader	16
Game Mode - HDR Effect	17
Game Mode - sRGB	18
Game Mode - Color Weakness	19
Game Mode - Calibration 1	1 10
Game Mode - Calibration 2	1 1 1
Game Adjust	2
Game Adjust - VRR / Adaptive-Sync	2 1
Game Adjust - VRR / Adaptive-Sync - Extended	211
Game Adjust - VRR / Adaptive-Sync - Basic	212
Game Adjust - VRR / Adaptive-Sync - Off	213
Game Adjust - Black Stabilizer	2 2
Game Adjust - Black Stabilizer	2 2 1 Slider
Game Adjust - Response Time	2 3
Game Adjust - Response Time - Faster	231
Game Adjust - Response Time - Fast	232
Game Adjust - Response Time - Normal	233

Menu	Location
Game Adjust - Response Time - Off	234
Game Adjust - Crosshair	24
Game Adjust - Crosshair - Red Cross	241
Game Adjust - Crosshair - Green Cross	242
Game Adjust - Crosshair - Red Dot	243
Game Adjust - Crosshair - Green Dot	244
Game Adjust - Crosshair - Off	245
Game Adjust - FPS Counter	2 5
Game Adjust - FPS Counter - On	251
Game Adjust - FPS Counter - Off	252
Game Adjust - Game Reset	2 6
Game Adjust - Game Reset - No	261
Game Adjust - Game Reset - Yes	262
Picture Adjust	3
Picture Adjust - Brightness	31
Picture Adjust - Brightness	3 1 1 Slider
Picture Adjust - Contrast	3 2
Picture Adjust - Contrast	3 2 1 Slider
Picture Adjust - Sharpness	33
Picture Adjust - Sharpness	3 3 1 Slider
Picture Adjust - Gamma	34
Picture Adjust - Gamma - Mode 1	341
Picture Adjust - Gamma - Mode 2	342

Menu	Location
Picture Adjust - Gamma - Mode 3	343
Picture Adjust - Gamma - Mode 4	344
Picture Adjust - Color Temp	3 5
Picture Adjust - Color Temp - Custom	351
Picture Adjust - Color Temp - Warm	352
Picture Adjust - Color Temp - Medium	353
Picture Adjust - Color Temp - Cool	354
Picture Adjust - Color Temp - Manual	355
Picture Adjust - Color Temp - Manual	3 5 5 1 Slider
Picture Adjust - R/G/B	36
Picture Adjust - R/G/B - Red	361
Picture Adjust - R/G/B - Red	3 6 1 Slider
Picture Adjust - R/G/B - Green	362
Picture Adjust - R/G/B - Green	3 6 2 Slider
Picture Adjust - R/G/B - Blue	363
Picture Adjust - R/G/B - Blue	3 6 3 Slider
Picture Adjust - Six Color	37
Picture Adjust - Six Color - Red Hue	371
Picture Adjust - Six Color - Red Hue	3 7 1 Slider
Picture Adjust - Six Color - Red Saturation	372

Menu	Location
Picture Adjust - Six Color - Red	372
Saturation	Slider
Picture Adjust - Six Color - Green Hue	373
Picture Adjust - Six Color - Green Hue	373
,	Slider
Picture Adjust - Six Color - Green Saturation	374
Picture Adjust - Six Color - Green	374
Saturation	Slider
Picture Adjust - Six Color - Blue Hue	375
Disture Adjust Six Caler Dive Live	375
Picture Adjust - Six Color - Blue Hue	Slider
Picture Adjust - Six Color - Blue	376
Saturation	
Picture Adjust - Six Color - Blue	376
Saturation	Slider
Picture Adjust - Six Color - Cyan Hue	377
Picture Adjust - Six Color - Cyan Hue	377
	Slider
Picture Adjust - Six Color - Cyan	378
Saturation	
Picture Adjust - Six Color - Cyan	378
Saturation	Slider
Picture Adjust - Six Color - Magenta Hue	379
Picture Adjust - Six Color - Magenta Hue	379
	Slider
Picture Adjust - Six Color - Magenta Saturation	3710

Menu	Location
Picture Adjust - Six Color - Magenta	3710
Saturation	Slider
Picture Adjust - Six Color - Yellow Hue	3711
Picture Adjust - Six Color - Yellow Hue	3 7 11 Slider
Picture Adjust - Six Color - Yellow Saturation	3712
Picture Adjust - Six Color - Yellow Saturation	3 7 12 Slider
Picture Adjust - Black Level	38
Picture Adjust - Black Level - High	381
Picture Adjust - Black Level - Low	382
Picture Adjust - Variable Backlight	3 9
Picture Adjust - Variable Backlight - Faster	391
Picture Adjust - Variable Backlight - Fast	392
Picture Adjust - Variable Backlight - Normal	393
Picture Adjust - Variable Backlight - Off	394
Picture Adjust - DFC	3 10
Picture Adjust - DFC - On	3 10 1
Picture Adjust - DFC - Off	3 10 2
Picture Adjust - Picture Reset	3 1 1
Picture Adjust - Picture Reset - No	3 11 1
Picture Adjust - Picture Reset - Yes	3 11 2
Input	4
Input - Input List	4 1
Input - Input List - HDMI 1	411

Menu	Location
Input - Input List - HDMI 2	412
Input - Input List - DisplayPort	413
Input - Aspect Ratio	4 2
Input - Aspect Ratio - Full Wide	421
Input - Aspect Ratio - 4:3	422
Input - Auto Input Switch	43
Input - Auto Input Switch - On	431
Input - Auto Input Switch - Off	432
General	5
General - Language	5 1
General - Language - English	511
General - Language - German	512
General - Language - French	513
General - Language - Spanish	514
General - Language - Italian	515
General - Language - Swedish	516
General - Language - Finnish	517
General - Language - Portuguese	518
General - Language - Portuguese (Brazil)	519
General - Language - Polish	5110
General - Language - Russian	5111
General - Language - Turkish	5112
General - Language - Ukrainian	5113
General - Language - Chinese	5114
General - Language - Traditional Chinese	5115
General - Language - Japanese	5116
General - Language - Korean	5117

Menu	Location
General - Hexagon Lighting	5 2
General - Hexagon Lighting - Static 1	521
General - Hexagon Lighting - Static 1	5 2 1 Color Chip
General - Hexagon Lighting - Static 2	522
General - Hexagon Lighting - Static 2	5 2 2 Color Chip
General - Hexagon Lighting - Static 3	523
General - Hexagon Lighting - Static 3	5 2 3 Color Chip
General - Hexagon Lighting - Static 4	524
General - Hexagon Lighting - Static 4	5 2 4 Color Chip
General - Hexagon Lighting - Cycling	525
General - Hexagon Lighting - Off	526
General - User-defined Key 1	53
General - User-defined Key 1 - Input	531
General - User-defined Key 1 - Game Mode	532
General - User-defined Key 1 - Crosshair	533
General - User-defined Key 1 - Black Stabilizer	534
General - User-defined Key 1 - Response Time	535
General - User-defined Key 1 - FPS Counter	536
General - User-defined Key 1 - Hexagon Lighting	537
General - User-defined Key 2	54

Menu	Location
General - User-defined Key 2 - Input	541
General - User-defined Key 2 - Game Mode	542
General - User-defined Key 2 - Crosshair	543
General - User-defined Key 2 - Black Stabilizer	544
General - User-defined Key 2 - Response Time	545
General - User-defined Key 2 - FPS Counter	546
General - User-defined Key 2 - Hexagon Lighting	547
General - DTS Headphone:X	5 5
General - DTS Headphone:X - Game	551
General - DTS Headphone:X - Entertainment	552
General - DTS Headphone:X - Sports	553
General - DTS Headphone:X - Off	554
General - SMART ENERGY SAVING	56
General - SMART ENERGY SAVING - High	561
General - SMART ENERGY SAVING - Low	562
General - SMART ENERGY SAVING - Off	563
General - Deep Sleep Mode	57
General - Deep Sleep Mode - On	571
General - Deep Sleep Mode - Off	572
General - Power LED	58
General - Power LED - On	581

Menu	Location
General - Power LED - Off	582
General - Automatic Standby	5 9
General - Automatic Standby - 8H	591
General - Automatic Standby - 6H	592
General - Automatic Standby - 4H	593
General - Automatic Standby - Off	594
General - Input Compatibility Version	5 10
General - Input Compatibility Version - 2.1(PC) / 1.4(DSC)	5 10 1
General - Input Compatibility Version - 2.1(AV) / 1.4	5 10 2
General - Input Compatibility Version - 1.4 / 1.2	5 10 3
General - Buzzer	5 11
General - Buzzer - On	5 11 1
General - Buzzer - Off	5 11 2
General - OSD Lock	5 12
General - OSD Lock - On	5 12 1
General - OSD Lock - Off	5 12 2
General - Information	5 13
General - Reset to Initial Settings	5 14
General - Reset to Initial Settings - No	5 14 1
General - Reset to Initial Settings - Yes	5 14 2



Supplier's Declaration of Conformity		
Trade Name	LG	
Responsible Party	LG Electronics USA, Inc.	
Address	111 Sylvan Avenue, North Building,	
	Englewood Cliffs, NJ 07632	
E-mail	lg.environmental@lge.com	

The model and serial number of the product are located on the back and on one side of the product.

Record them below in case you ever need service.

Model _____

Serial No. _____