

# Owner's Manual



\* LG LED Monitor applies LCD screen with LED backlights.

Please read this manual carefully before operating your set and retain it for future reference.

49GR85DC

# **TABLE OF CONTENTS**

LICENSE3	USING THE MONITOR 13
OPEN SOURCE SOFTWARE NOTICE INFORMATION	- Connecting to a PC
- Moving and Lifting the Monitor6	Connecting Headphones
Installing on a Table	USER SETTINGS 16
Adjusting the Stand Height	- Activating the Main Menu16  Main Menu Features
Adjusting the Angle Using the Kensington Lock Installing the Wall Mount Plate	- User Settings18  Menu Settings
Installing on the Wall	TROUBLESHOOTING29
	PRODUCT SPECIFICATION 32
	- Factory Support Mode33
	- HDMI Timing (Video)35
	- Power LED35
	- Been Guide 36

# **LICENSE**

Each model has different licenses. Visit www.lq.com for more information on the license.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



The SuperSpeed USB Trident logo is a registered trademark of USB Implementers Forum, Inc.



VESA, VESA logo, DisplayPort compliance logo and DisplayPort compliance logo for dual-mode source devices are all registered trademarks of the Video Electronics Standards Association.



For DTS patents, see http://patents.dts.com.

Manufactured under license from DTS Licensing Limited. DTS, the Symbol, & DTS and the Symbol together, Headphone:X, and the DTS Headphone:X logo are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

# OPEN SOURCE SOFTWARE NOTICE INFORMATION

To obtain the source code under GPL, LGPL, MPL, and other open source licenses, that is contained in this product, please visit http://opensource.lge.com.

In addition to the source code, all referred license terms, warranty disclaimers and copyright notices are available for download.

LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping, and handling) upon email request to <code>opensource@lge.com</code>.

This offer is valid for a period of three years after our last shipment of this product. This offer is valid to anyone in receipt of this information.

# ASSEMBLING AND PREPARING

## **CAUTION**

- Always use genuine LG components to ensure safety and product performance.
- The product warranty will not cover damage or injury caused by the use of unauthorized components.
- It is recommended that use the supplied components.
- If you use generic cables not certified by LG, the screen may not display or there
  may be image noises.
- Illustrations in this document represent typical procedures, so they may look different from the actual product.
- Do not apply foreign substances (oils, lubricants, etc.) to the screw parts when assembling the product. (Doing so may damage the product.)

- Applying excessive force when tightening screws may cause damage to the monitor. Damage caused in this way will not be covered by the product warranty.
- Do not carry the monitor upside down by just holding the base. This may cause the monitor to fall off the stand and could result in personal injury.
- When lifting or moving the monitor, do not touch the monitor screen. The force applied to the monitor screen may cause damage to it.
- For wave pattern on appearance, unlike the general method of coating, it's applied
  to added glittering material in raw material. With no peeled-off appearance, it has
  good durability. Please use it with confidence because there is no problem in using
  the product at all.



#### NOTE


- The components may look different from those illustrated here.
- Without prior notice, all product information and specifications contained in this manual are subject to change to improve the performance of the product.
- To purchase optional accessories, visit an electronics store or an online shopping site, or contact the retailer from where you purchased the product.
- The power cord provided may differ depending upon the region.

# **Supported Drivers and Software**

You can download and install the latest version from the LGE website (www.lq.com).

Drivers and Software	Installation Priority
Monitor Driver	Recommended
OnScreen Control	Recommended
Dual Controller	Optional

# **Product and Button Description**



# How to Use the Joystick Button

You can easily control the functions of the monitor by pressing the joystick button or moving it left/right/up/down with your finger.


#### **Basic Functions**

	<b>4/▶</b>	Power on	Press the joystick button once with your finger to turn on the monitor.
		Power off	Press and hold the joystick button once with your finger to turn off the monitor.
		Volume control	You can control the volume by moving the joystick button left/ right.
		Controls screen brightness	You can control the screen's brightness by moving the joystick button up/down.

# **Moving and Lifting the Monitor**

When moving or lifting the monitor, follow these instructions to prevent the monitor from being scratched or damaged and to ensure safe transportation, regardless of its shape or size.

- Place the monitor in the original box or packing material before attempting to move it.
- Before moving or lifting the monitor, disconnect the power cord and all other cables.
- · Hold the bottom and side of the monitor frame firmly. Do not hold the panel itself.
- When holding the monitor, the screen should face away from you to prevent it from being scratched.
- When transporting the monitor, do not expose the monitor to shock or excessive vibration.
- When moving the monitor, keep it upright and never turn the monitor on its side or tilt it sideways.








- Avoid touching the monitor screen as much as possible.
  - This may result in damage to the screen or some of the pixels used to create images.
- If you use the monitor panel without the stand base, its joystick button may cause
  the monitor to become unstable and fall, resulting in damage to the monitor or
  human injury. In addition, this may cause the joystick button to malfunction.

# Installing on a Table

• Lift the monitor and place it on the table in an upright position. Place the monitor at least 100 mm (3.94 inches) away from the wall to ensure sufficient ventilation.



# **!** CAUTION

- Unplug the power cord before moving or installing the monitor. There is risk of electric shock.
- Make sure to use the power cord that is provided in the product package and connect it to a grounded power outlet.
- If you need another power cord, please contact your local dealer or the nearest retail store.

## Adjusting the Stand Height

- 1 Place the monitor mounted on the stand base in an upright position.
- 2 Handle the monitor with both hands for safety.

Max. 110.0 mm (4.3 inches)





#### WARNING

• When adjusting the screen height, do not place your hand on the stand body to avoid injury to your fingers.

# Adjusting the Angle

- 1 Place the monitor mounted on the stand base in an upright position.
- 2 Adjust the angle of the screen.

The angle of the screen can be adjusted forward or backward from -5° to 15° for a comfortable viewing experience.



### WARNING

To avoid injury to the fingers when adjusting the screen, do not hold the lower part
of the monitor's frame as illustrated below.







 Be careful not to touch or press the screen area when adjusting the angle of the monitor.




## Using the Kensington Lock

The connector for the Kensington security system is located at the bottom of the monitor.

For more information on installation and usage, refer to the Kensington lock owner's manual or visit the website at http://www.kensington.com.

Connect the monitor to a table using the Kensington security system cable.





 The Kensington security system is optional. You can obtain optional accessories from most electronics stores.

#### Installing the Wall Mount Plate

This monitor meets the specifications for the wall mount plate or other compatible devices.

- 1 Place the screen face down. To protect the monitor panel (screen), cover the surface with a soft cloth or the monitor protection pad included in the product package.
- 2 Remove the four screws tightened on the back of the monitor.
- 3 Place the wall mount plate onto the monitor and align it with the screw holes.
- 4 Tighten the four screws using a screwdriver to fix the plate to the monitor.




#### NOTE

- · The wall mount plate is sold separately.
- For more information on installation, refer to the wall mount plate's installation quide.
- Be careful not to apply too much force while mounting the wall mount plate as it may cause damage to the screen.

#### Installing on the Wall

Install the monitor at least 100 mm (3.94 inches) away from the wall and leave about 100 mm (3.94 inches) of space at each side of the monitor to ensure sufficient ventilation. Detailed installation instructions can be obtained from your local retail store. Alternatively, please refer to the manual for how to install and set up a tilting wall mounting bracket.



To install the monitor to a wall, attach a wall mounting bracket (optional) to the back of the monitor.

Make sure that the wall mounting bracket is securely fixed to the monitor and to the wall.

- 1 If you use screws longer than the standard length, it may damage the inside of the product.
- 2 A non-VESA standard screw may damage the product and cause the monitor to fall. LG Electronics is not liable for any accidents relating to the use of nonstandard screws.

Wall Mount (mm)	100 x 100
Standard screw	M4 x L10
Number of screws	4
Wall Mount Plate (Optional)	LSW 149




- · Use the screws specified by VESA standards.
- The wall mount kit includes the installation guide and all necessary parts.
- The wall mounting bracket is optional. You can obtain optional accessories from your local dealer.
- The length of the screw may differ for each wall mounting bracket. Be sure to use the proper length.
- For more information, please refer to the user manual for the wall mounting bracket.



### **CAUTION**

- Unplug the power cord before moving or installing the monitor to avoid electric shock.
- Installing the monitor on the ceiling or on a slanted wall may result in the monitor falling off, which could lead to injury. Use an authorized LG wall mount and contact the local dealer or qualified personnel.
- Applying excessive force when tightening screws may cause damage to the monitor. Damage caused in this way will not be covered by the product warranty.

- Use the wall mounting bracket and screws that conform to VESA standards.
   Damage caused by the use or misuse of inappropriate components will not be covered by the product warranty.
- When measured from the back of the monitor, the length of each installed screw must be 8 mm (0.3 inches) or less.



# **USING THE MONITOR**

Illustrations in this manual may differ from the actual product.
 Press the joystick button, go to Settings 

Input, and then select the input option.



# CAUTION

- Do not press the screen for a prolonged time. This may cause image distortion.
- Do not display a still image on the screen for a prolonged time. This may cause image retention. Use a screensaver if possible.



#### **NOTE**

- When connecting the power cord to the outlet, use a grounded (3-hole) power strip or a grounded power outlet.
- The monitor may flicker when turned on in an area where the temperature is low.
   This is normal.
- Sometimes red, green, or blue spots may appear on the screen. This is normal.

# Connecting to a PC

- · This monitor supports the \*Plug and Play feature.
- \* Plug and Play: A feature that allows you to add a device to your computer without having to reconfigure anything or install any manual drivers.

#### **HDMI Connection**

Transmits digital video and audio signals from your PC to the monitor.



### CAUTION

- Using a DVI to HDMI / DP (DisplayPort) to HDMI cable may cause compatibility issues.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI cable types
- Ultra High Speed  $\mathsf{HDMI}^{\text{\scriptsize B}}/^{\mathsf{TM}}$  cable

## **DisplayPort Connection**

Transmits digital video and audio signals from your PC to the monitor.



# NOTE

- There may be no video or audio output depending on the DP (DisplayPort) version of the PC.
- If you are using a Mini DisplayPort output graphics card, use a Mini DP to DP (Mini DisplayPort to DisplayPort) cable or gender that supports DisplayPort1.4. (sold separately)

# **Connecting AV Devices**

#### **HDMI Connection**

HDMI transmits digital video and audio signals from your AV device to the monitor.



# NOTE

- · Using a DVI to HDMI / DP (DisplayPort) to HDMI cable may cause compatibility issues.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI cable types
- Ultra High Speed HDMI®/™ cable

# **Connecting Peripherals**

#### **USB Device connection**

The USB port on the product functions as a USB hub.

To use USB 3.0, connect the A-B type USB 3.0 cable of the product to the PC. Peripheral devices connected to the USB IN port can be controlled from the PC.



- It is recommended you install all Windows Updates to keep your Windows up-todate before connecting to the product for use.
- · Peripheral devices are sold separately.
- · A keyboard, mouse, or USB device can be connected to the USB port.
- The charging speed may vary depending on the device.



Cautions When Using a USB Device

- A USB device with an automatic recognition program installed, or that uses its own driver, may not be recognized.
- · Some USB devices may not be supported or may not work properly.
- It is recommended to use a USB hub or hard disk drive with power supplied. (If the power supply is not adequate, the USB device may not be recognized properly.)

## **Connecting Headphones**

Connect peripherals to the monitor via the headphones port.



## NOTE


- · Peripheral devices are sold separately.
- If you use angled earphones, it may cause a problem with connecting another external device to the monitor. Therefore, it is recommended to use straight earphones.





Straight (Recommend)

 Depending on the audio settings of the PC and external device, headphones and speaker functions may be limited.



 Please connect the USB A to B cable to use a microphone function with headphones equipped with a microphone.


# **USER SETTINGS**



- Your monitor's OSD (On Screen Display) may differ slightly from that shown in this manual.
- When Beep Guide is activated, pressing the joystick button will take you to Settings right away.

# **Activating the Main Menu**

- 1 Press the joystick button on the bottom of the monitor.
- 2 Move the joystick up/down (▲ / ▼) and left/right (▼/ ▶) to set the options.
- 3 Press the joystick button once more to exit the main menu.



Button		Menu Status	Description
	Main menu disabled		Enables the main menu.
Main		enu enabled	Enters the <b>Settings</b> feature. (Holding down the button to turn off the monitor. You can turn off the monitor this way at any time, including when the OSD is on.)
		Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the <b>Input</b> feature.
	<b>•</b>	Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the <b>Game Mode</b> feature.
		Main menu disabled	Enters the <b>Accessibility</b> menu.
		Main menu enabled	Turns off the monitor.
		Main menu disabled	Enters the <b>Accessibility</b> menu.
,	<b>V</b>	Main menu enabled	Exits the main menu.

# Main Menu Features



Main Menu	Description			
Input	Sets input mode.			
Power Off	urns off the monitor.			
Settings	Configures the screen settings.			
Game Mode	Sets the game mode for gaming.			
Exit	Exits the main menu.			

# **User Settings**

### Menu Settings

- 1 To view the OSD menu, press the joystick button at the bottom of the monitor and then enter the **Settings**.
- 2 Configure the options by moving the joystick up/down/left/right.
- 3 To return to the upper menu or set other menu items, move the joystick to ◀ or pressing (டு) it.
- 4 If you want to exit the OSD menu, move the joystick to ◀ until you exit.







Game Adjust



Picture Adjust



Input



General

# Game Mode on SDR(Non-HDR)signal.

Settings > Game Mode		Description		
	Gamer 1	In this mode, users can customize elements including game-related options.		
	Gamer 2	Gamer 1 and Gamer 2 picture modes allow you to save two sets of customized display settings, including game-related setup options.		
	FPS	This mode is optimized for FPS games. It is suitable for very dark FPS games.		
RTS This mode is optimized for RTS games.  Game Mode Vivid Optimized the screen for vivid colors.		This mode is optimized for RTS games.		
		Optimized the screen for vivid colors.		
	Reader	Optimizes the screen for viewing documents. You can brighten the screen in the OSD menu.		
	HDR Effect	Optimizes the screen for high dynamic range.		
	sRGB	A standard RGB color space for the monitor and printer.		
Color Weakness		This mode is for users who cannot distinguish between red and green. It enables users with color weakness to easily distinguish between the two colors.		

# Game Mode on HDR signal.

Settings > Game Mod	de	Description			
	Gamer 1	In this mode, users can customize elements including game-related options.			
	Gamer 2	<b>Gamer 1</b> and <b>Gamer 2</b> picture modes allow you to save two sets of customized display settings, including game-related setup options.			
	FPS	This mode is optimized for FPS games. It is suitable for very dark FPS games.			
	RTS	This mode is optimized for RTS games.			
6	Vivid	Optimized the screen for vivid colors.			
Game Mode	When the HDR funct	ay not be operated properly depending on the Windows 10 OS setting. Please check the HDR On / Off setting of Windows. function is turned on, the characters or picture quality may be poor according to Graphic card performance. function is on, screen flickering or cracking may occur when changing the monitor input or power on/off according to Graphic card			

• For information about whether the graphics card and game support HDR, visit their manufacture's website.

Settings > Game Ad	just	Description		
Adaptive-Sync / VRR Game Adjust		• Supported Grapl • Supported Version	And natural images by synchronizing the vertical frequency of the input signal with that of the output signal.  N  Face: DisplayPort (Adaptive-Sync), HDMI (Variable Refresh Rate).  Thic Card: A graphic card that supports AMD's FreeSync is necessary.  Thic Card: A graphic card that supports AMD's FreeSync is necessary.  This card to the latest driver.  This card to the latest driver.  This card to AMD website (www.amd.com).	
		Extended	Enables wider frequency range of Adaptive-Sync/VRR function than basic mode.  The screen may flicker during the game play.	
		Basic	Enables basic frequency range of Adaptive-Sync/VRR function.	
		Off	Adaptive-Sync/VRR function off.	
Black Stabilizer  You can control the black contrast to have You can easily distinguish objects on dark g			ie black contrast to have better visibility in dark scenes. inguish objects on dark game screens.	

		Sets a response time for displayed pictures based on the speed of the screen.		
		For a normal environment, it is recommended that you use <b>Fast</b> .		
		For a fast-moving	picture, it is recommended that you use <b>Faster</b> .	
		Once Faster Mode	e is selected, <b>Motion Blur</b> may occur depending on the content.	
	Response Time	Faster	Sets the response time to Faster.	
		Fast	Sets the response time to Fast.	
		Normal	Sets the response time to Normal.	
		Off	Does not use the response time improvement feature.	
( rosshair		1	a mark on the center of the screen for First Person Shooter (FPS) games. Users can select the Crosshair that nvironment among four different Crosshairs.	
Guille Paguse	FPS Counter	On	The indicator is displayed on the upper left of the screen. It will reflect the actual frame rate that is received at the input. You can also adjust the position of FPS Counter. (upper left / upper right / lower right / lower left)	
		Off	Does not use the FPS Counter feature.	
		NOTE		
		• FPS Counter and Crosshair feature can not be used at the same time.		
	Game Reset	Returns game to the default settings.		
		No	Cancel the select.	
		Yes	Returns to the default settings.	

Settings > Picture Adjust		Description			
	Brightness	Adjusts the brightne	Adjusts the brightness of the screen.		
	Contrast	Adjusts the contrast	Adjusts the contrast of the screen.		
	Sharpness	Adjusts the sharpness of the screen.			
	Gamma	Mode 1, Mode 2, Mode 3	The higher the gamma value, the darker the image becomes. Likewise, the lower the gamma value, the lighter the image becomes.		
		Mode 4	If you do not need to adjust the gamma settings, select Mode 4.		
		Custom	The user can adjust it to red, green, or blue by customization.		
		Warm	Sets the screen color to a reddish tone.		
	Color Temp	Medium	Sets the screen color to between a red and blue tone.		
		Cool	Sets the screen color to a bluish tone.		
Picture Adjust		Manual	The user can fine - tune the color temperature.		
	R/G/B	You can customize t	You can customize the picture color using <b>Red</b> , <b>Green</b> , and <b>Blue</b> colors.		
		Meets the user requirements for colors by adjusting the hue and saturation of the six colors (Red, Green, Blue, Cyan, Magenta and Yellow) and then saving the settings.			
	Six Color	Hue	Adjusts the tone of the screen colors.		
		Saturation	Adjusts the saturation of the screen colors. The lower the value, the less saturated and brighter the colors become. The higher the value, the more saturated and darker the colors become.		
	Black Level	Sets the offset level (for HDMI only).  Offset: as a reference for a video signal, this is the darkest color the monitor can display.			
		High	Keeps the current contrast ratio of the screen.		
		Low	Lowers the black levels and raises the white levels from the current contrast ratio of the screen.		

	Local Dimming		rast ratio by making the bright areas of the screen brighter and the dark areas of the screen darker.  off may increase energy consumption.
		Faster	Sets the local dimming to faster.
Picture Adjust		Fast	Sets the local dimming to fast.
		Normal	Sets the local dimming to normal.
		Off	Does not use the local dimming improvement feature.
	DFC	On	Adjusts the brightness automatically according to the screen.
	DFC	Off	Disables the <b>DFC</b> feature.
	Picture Reset	Do you want to rese	t your picture settings?
		No	Cancel the select.
		Yes	Returns to the default settings.

Settings > Input		Description		
	Input List	Selects the input mo	de.	
		Adjusts the aspect ratio of the screen.		
		Full Wide	Displays the video in widescreen, regardless of the video signal input.	
		Original	Displays video according to the aspect ratio of the video signal input.	
		Just Scan	The aspect ratio is not adjusted from the original.	
	Aspect Ratio	Cinema 1	Enlarges the screen with an aspect ratio of 32:9.	
lament		Cinema 2	Enlarges the screen with an aspect ratio of 32:9, including the black box at the bottom for subtitles.	
Input		NOTE		
		• The display may look the same for <b>Full Wide</b> and <b>Original</b> options at the recommended resolution. (5120 x 1440)		
		<ul> <li>There is no Just Scan, Cinema 1, Cinema 2 menu on Adaptive-Sync/VRR Mode. (Go to Settings → Game Adjust → Adaptive-Sync/VRR, to set Adaptive-Sync/VRR Extended, Basic or Off)</li> </ul>		
	Auto Input Switch	When automatic input switch is set to <b>On</b> , display will automatically switch to new input when connected.		
		On	Enables <b>Auto Input Switch</b> .	
		Off	Disables Auto Input Switch.	

		You can select the various PBP or PIP combination.					
		PBP / PIP Connection		Sub Screen			
	DDD / DID			HDMI 1	HDMI 2	DP	
Input	PBP / PIP	Main Screen	HDMI 1	-	0	0	
			HDMI 2	0	-	0	
			DP	0	0	-	
	PIP Size	Sets the size of the PIP Sub window. ([Large] / [Small])					
	PIP Position	Sets the position of the PIP Sub window. (Bottom Right / Bottom Left / Top Left / Top Right)					
	Screen Switch	Switchs the main screen/sub-screen in PBP/PIP mode.					
	Sound Switch	Switch the main screen/sub-screen sound in PBP/PIP mode.					

Settings > General		Description			
	Language	Sets the menu scree	en to the desired language.		
	Hexagon Lighting	You can turn on or o	off the lighting on the back of the monitor, and you can also select or adjust the lighting color.		
	User-defined Key 1	You can customise t	the main menu to access your preferred menu easily.		
	User-defined Key 2	User-definded Key 1 and User-definded Key 2 appear at the left/right of the main menu.			
		Enables the realizat	ion of three-dimensional sound with headphones or earphone.		
		Game	This mode is optimized for Game.		
	DTS Headphone:X	Entertainment	This mode is optimized for Entertainment.		
		Sports	This mode is optimized for Sports.		
		Off	Disables DTS Headhpone:X function.		
General	SMART ENERGY SAVING	High	Saves energy using the high-efficiency SMART ENERGY SAVING feature.		
Concrat		Low	Saves energy using the low-efficiency SMART ENERGY SAVING feature.		
		Off	Disables the SMART ENERGY SAVING feature.		
	Deep Sleep Mode	When Deep sleep mode is enabled, power consumption is minimized while the monitor is in standby mode.			
		On	Enables <b>Deep sleep Mode</b> .		
		Off	Disables Deep sleep Mode.		
		Turns the power LEI	O on the bottom of the monitor on or off.		
	Power LED	On	The power LED turns on automatically.		
		Off	The power LED turns off.		
	Automatic Standby		atically turns off the monitor when there is no movement on the screen for a period of time. You can set a off function. (8H, 6H, 4H and Off)		

	Input Compatibility Version	Please set the Input	Compatibility Version to match the version of the connected external device.		
		HDMI	2.1(PC)/2.1(AV)/1.4		
			If you want to use the HDR, select the Input Compatibility Version to 2.1(PC) or 2.1(AV).		
		DisplayPort	1.4(DSC)/1.4/1.2		
		Display! Of C	If you want to use the HDR, select the Input Compatibility Version to 1.4(DSC) or 1.4.		
		This feature lets you	set the sound generated from Buzzer when your monitor powers on.		
	Buzzer	On	Enables your monitor's <b>Buzzer</b> .		
		Off	Disables your monitor's <b>Buzzer</b> .		
General	OSD Lock	This feature disables the configuration and adjustment of menus.			
General		On	Enables <b>OSD Lock</b> .		
		Off	Disables OSD Lock.		
		NOTE			
		All features are disabled except Brightness, Contrast in Picture Adjust, Input, OSD Lock and Information in General.			
	Information	The display information will be shown the Total Power On Time, Resolution.			
	Reset to Initial Settings	Do you want to reset your settings?			
		No	Cancel the reset.		
		Yes	Returns to the default settings.		

# **TROUBLESHOOTING**

Nothing is displayed on the screen.	
Is the monitor's power cord plugged in?	Check if the power cord is correctly plugged into the power outlet.
Is the power LED on?	Check the power cable connection and press the power button.
Is the power on and the power LED displaying red?	Check that the connected input is enabled (Settings > Input).
Is the power LED blinking?	<ul><li> If the monitor is in sleep mode, move the mouse, or press any key on the keyboard, to switch the display on.</li><li> Check if the computer is turned on.</li></ul>
Is the "The screen is not currently set to the recommended resolution." message being displayed?	This occurs when signals transferred from the PC (graphics card) are out of the recommended horizontal or vertical frequency range of the monitor. Please see the Product Specification section of this manual to set the appropriate frequency.
Is the <b>"No Signal"</b> message being displayed?	This is displayed when the signal cable between the PC and the monitor is missing or disconnected. Check the cable and reconnect it.
Have you installed the display driver?	<ul> <li>Be sure to install the display driver from our web site: http://www.lg.com.</li> <li>Make sure to check if the graphics card supports Plug and Play function.</li> </ul>

Some features are disabled.	Some features are disabled.				
Are some functions not available when you press the Menu button?	The OSD is locked. Go to <b>Settings</b> > <b>General</b> and set <b>OSD Lock</b> to <b>Off</b> .				

The screen retains an image.				
Does image sticking occur even when the	Displaying a still image for a prolonged time may cause damage to the screen, resulting in the retention of the image.			
monitor is turned off?	To extend the lifetime of the monitor, use a screensaver.			

w trails.
J

Did you select the appropriate resolution?

 If the selected resolution is HDMI 1080i 60/50 Hz (interlaced), the screen may be flickering. Change the resolution to 1080p or the recommended resolution.



# NOTE

- Vertical Frequency: In order to display an image, the screen must be refreshed dozens of times per second, like a fluorescent lamp. The number of times the screen is refreshed per second is called vertical frequency, or refresh rate, and is represented by Hz.
- Horizontal Frequency: The time it takes to display one horizontal line is called the horizontal cycle. If 1 is divided by the horizontal interval, the result is the number of horizontal lines displayed per second. This is called horizontal frequency and is represented by kHz.
- Check if the graphics card's resolution or frequency is within the range allowed by the monitor and set it to the recommended (optimal) resolution **Control Panel** > **Display** > **Settings** in Windows. (The settings may differ depending on the operating system (OS) you use.)
- Not setting the graphics card to the recommended (optimal) resolution may result in blurred text, a dimmed screen, a truncated display area or misalignment of the display.
- The setting methods may be different depending on the computer or operating system, and some resolutions may not be available depending on the performance of the graphics card. If this is the case, contact the manufacturer of the computer or graphics card for assistance.

The display color is abnormal.	The display color is abnormal.				
Does the display appear discolored (16 colors)?	Set the color to 24 bit (true color) or higher. In Windows, go to <b>Control Panel</b> > <b>Display</b> > <b>Settings</b> > <b>Color Quality</b> . (The settings may differ depending on the operating system (OS) you use.)				
Does the display color appear unstable or monochrome?	Check if the signal cable is connected properly. Reconnect the cable or reinsert the PC's graphics card.				
Are there spots on the screen?	When using the monitor, pixilated spots (red, green, blue, white, or black) may appear on the screen. This is normal for an LCD screen. It is not an error, nor is it related to the monitor's performance.				

No sound from the headphone port.			
Are images displayed using DP (DisplayPort) or HDMI input without sound?	<ul> <li>Make sure that the headphone port connections are made properly.</li> <li>Try increasing the volume with the joystick.</li> <li>Set the audio output of the PC to the monitor you are using. On Microsoft Windows, go to Control Panel &gt; Hardware and Sound &gt; Sound &gt; Sound &gt; set the Monitor as default device. (The settings may differ depending on the operating system (OS) you use.)</li> </ul>		

# **PRODUCT SPECIFICATION**

LCD Screen	Color Depth	HDMI	10-bit color is supported.		
		DP (DisplayPort)	10-bit color is supported.		
Resolution	Max Resolution	5120 x 1440 @ 240 Hz			
	Recommended Resolution	5120 x 1440 @ 240 Hz			
Power Sources	Power Rating	100 - 240 V~ 50/60 Hz 2	100 - 240 V~ 50/60 Hz 2.5 A		
(Typical) Sleep Mod		On mode: 90 W (Typical)* Sleep Mode (Standby Mod Off Mode: ≤ 0.3 W	eep Mode (Standby Mode) : ≤ 0.5 W		
Environmental Conditions	Operating Conditions	Temperature	0 °C to 40 °C (32 °F to 104 °F)		
		Humidity	Less than 80 %		
	Storing Conditions	Temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
		Humidity	Less than 85 %		
Dimensions	Monitor Size (Width x Height x Depth)				
	With Stand	1170 x 473.3 x 393.1 (mm) 46.0 x 18.6 x 15.4 (inches)			
	Without Stand	1170 x 373.1 x 236.4 (mm) 46.0 x 14.6 x 9.3 (inches)			
Weight (Without Packaging)	With Stand	15.1 kg (33.2 lbs)			
	Without Stand	12.1 kg (26.6 lbs)			

Specifications are subject to change without notice.

The  $\sim$  symbol means alternating current, and the  $\overline{\dots}$  symbol means direct current.

The Power Consumption level can be different by operating condition and monitor setting.

<sup>\*</sup> The On mode power consumption is measured with LGE test standard (Full White pattern , Maximum resolution).

<sup>\*\*</sup> The monitor goes to the Sleep Mode in a couple of minutes (Max 5 minutes).

# **Factory Support Mode**

# DisplayPort

Resolution	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Polarity (H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60	-/-	
1280 x 1024	79.976	75.025	+/+	
1920 x 1080	66.587	59.934	+/-	
5120 x 1440	388.54	239.99	+/-	DP1.4(DSC) Recommended Timing
5120 x 1440	222.16	143.98	+/-	DP1.4(DSC)
5120 x 1440	182.95	119.97	+/-	
5120 x 1440	111.88	74.99	+/-	DP1.2
5120 x 1440	88.83	59.98	+/-	
3840 x 1080	137.25	119.97	+/-	
3840 x 1080	113.25	99.96	+/-	
3440 x 1440	181.94	119.94	+/-	PBP(21:9)
2560 x 1440	183	120	+/-	PBP(16:9)
1680 x 1440	182.88	119.92	+/-	PBP(11:9)
1280 x 720	91.49	119.91	+/-	PIP(720P)
720 x 480	61.08	120	+/-	PIP(480P)

### HDMI

Resolution	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Polarity (H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60	-/-	
1280 x 720	91.49	119.91	+/-	
1280 x 1024	79.976	75.025	+/+	
1920 x 1080	66.587	59.934	+/-	
5120 x 1440	388.51	239.97	+/-	HDMI2.1 Recommended Timing
5120 x 1440	222.16	143.98	+/-	HDMI2.1
5120 x 1440	182.95	119.97	+/-	
5120 x 1440	88.83	59.98	+/-	
3840 x 1080	137.25	119.97	+/-	
3840 x 1080	66.62	59.97	+/-	
3440 x 1440	150.97	99.98	+/-	PBP(21:9)
3440 x 1440	73.68	49.99	+/-	PBP(21:9)
2560 x 1440	183	120	+/-	(Non PBP)
2560 x 1440	88.79	59.95	+/-	PBP(16:9)
2560 x 1440	183	120	+/-	PBP(16:9)
1680 x 1440	88.86	60	+/-	PBP(11:9)
1680 x 1440	182.88	119.92	+/-	PBP(11:9)
720 x 480	61.08	120	+/-	PIP(480P)
1280 x 720	91.49	119.91	+/-	PIP(720P)

# **HDMI Timing (Video)**

Preset Mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Remarks
480P	31.5	60	
720P	45	60	
1080P	67.5	60	
1080P	135	120	
2160P	135	60	
2160P	270	120	

# **Power LED**

Mode	LED Color
On Mode	Red (For a few seconds)
Sleep Mode (Standby Mode)	Off
Off Mode	Off

# **Beep Guide**

Menu	Location
Game Mode	1
Game Mode - Gamer 1	11
Game Mode - Gamer 2	12
Game Mode - FPS	13
Game Mode - RTS	1 4
Game Mode - Vivid	15
Game Mode - Reader	16
Game Mode - HDR Effect	17
Game Mode - sRGB	18
Game Mode - Color Weakness	19
Game Adjust	2
Game Adjust - VRR / Adaptive-Sync	2 1
Game Adjust - VRR / Adaptive-Sync - Extended	211
Game Adjust - VRR / Adaptive-Sync - Basic	212
Game Adjust - VRR / Adaptive-Sync - Off	213
Game Adjust - Black Stabilizer	2 2
Game Adjust - Black Stabilizer	2 2 1 Slider
Game Adjust - Response Time	2 3
Game Adjust - Response Time - Faster	231
Game Adjust - Response Time - Fast	232
Game Adjust - Response Time - Normal	233
Game Adjust - Response Time - Off	234
Game Adjust - Crosshair	2 4

Menu	Location
Game Adjust - Crosshair - Red Cross	2 4 1
Game Adjust - Crosshair - Green Cross	242
Game Adjust - Crosshair - Red Dot	243
Game Adjust - Crosshair - Green Dot	2 4 4
Game Adjust - Crosshair - Off	2 4 5
Game Adjust - FPS Counter	2 5
Game Adjust - FPS Counter - On	251
Game Adjust - FPS Counter - Off	252
Game Adjust - Game Reset	26
Game Adjust - Game Reset - No	261
Game Adjust - Game Reset - Yes	262
Picture Adjust	3
Picture Adjust - Brightness	3 1
Picture Adjust - Brightness	311
Picture Adjust - Brightness	Slider
Picture Adjust - Contrast	3 2
Picture Adjust - Contrast	3 2 1
Trecare Adjust Contrast	Slider
Picture Adjust - Sharpness	3 3
Picture Adjust - Sharpness	3 3 1
Trecare rajuse sharphess	Slider
Picture Adjust - Gamma	3 4
Picture Adjust - Gamma - Mode 1	3 4 1
Picture Adjust - Gamma - Mode 2	3 4 2
Picture Adjust - Gamma - Mode 3	3 4 3
Picture Adjust - Gamma - Mode 4	3 4 4

Menu	Location
Picture Adjust - Color Temp	3 5
Picture Adjust - Color Temp - Custom	3 5 1
Picture Adjust - Color Temp - Warm	352
Picture Adjust - Color Temp - Medium	353
Picture Adjust - Color Temp - Cool	3 5 4
Picture Adjust - Color Temp - Manual	355
Picture Adjust - Color Temp - Manual	3 5 5 1 Slider
Picture Adjust - R/G/B	3 6
Picture Adjust - R/G/B - Red	361
Picture Adjust - R/G/B - Red	3 6 1 1 Slider
Picture Adjust - R/G/B - Green	362
Picture Adjust - R/G/B - Green	3 6 2 1 Slider
Picture Adjust - R/G/B - Blue	363
Picture Adjust - R/G/B - Blue	3 6 3 1 Slider
Picture Adjust - Six Color	3 7
Picture Adjust - Six Color - Red Hue	371
Picture Adjust - Six Color - Red Hue	3 7 1 1 Slider
Picture Adjust - Six Color - Red Saturation	372
Picture Adjust - Six Color - Red Saturation	3 7 2 1 Slider
Picture Adjust - Six Color - Green Hue	373

Menu	Location
Picture Adjust - Six Color - Green Hue	3 7 3 1 Slider
Picture Adjust - Six Color - Green Saturation	374
Picture Adjust - Six Color - Green Saturation	3 7 4 1 Slider
Picture Adjust - Six Color - Blue Hue	375
Picture Adjust - Six Color - Blue Hue	3 7 5 1 Slider
Picture Adjust - Six Color - Blue Saturation	376
Picture Adjust - Six Color - Blue Saturation	3 7 6 1 Slider
Picture Adjust - Six Color - Cyan Hue	377
Picture Adjust - Six Color - Cyan Hue	3 7 7 1 Slider
Picture Adjust - Six Color - Cyan Saturation	378
Picture Adjust - Six Color - Cyan Saturation	3 7 8 1 Slider
Picture Adjust - Six Color - Magenta Hue	379
Picture Adjust - Six Color - Magenta Hue	3 7 9 1 Slider
Picture Adjust - Six Color - Magenta Saturation	3 7 10
Picture Adjust - Six Color - Magenta Saturation	3 7 10 1 Slider
Picture Adjust - Six Color - Yellow Hue	3 7 11

Menu	Location
Picture Adjust - Six Color - Yellow Hue	3 7 11 1 Slider
Picture Adjust - Six Color - Yellow Saturation	3 7 12
Picture Adjust - Six Color - Yellow Saturation	3 7 12 1 Slider
Picture Adjust - Black Level	38
Picture Adjust - Black Level - High	381
Picture Adjust - Black Level - Low	382
Picture Adjust - Local Dimming	3 9
Picture Adjust - Local Dimming - Faster	391
Picture Adjust - Local Dimming - Fast	392
Picture Adjust - Local Dimming - Normal	393
Picture Adjust - Local Dimming - Off	394
Picture Adjust - DFC	3 10
Picture Adjust - DFC - On	3 10 1
Picture Adjust - DFC - Off	3 10 2
Picture Adjust - Picture Reset	3 11
Picture Adjust - Picture Reset - No	3 11 1
Picture Adjust - Picture Reset - Yes	3 11 2
Input	4
Input - Input List	4 1
Input - Input List - HDMI 1	411
Input - Input List - HDMI 2	412
Input - Input List - DisplayPort	413
Input - Aspect Ratio	4 2
Input - Aspect Ratio - Full Wide	421
Input - Aspect Ratio - Original	422

Menu	Location
Input - Aspect Ratio - Just Scan	4 2 3
	423
Input - Aspect Ratio - Cinema 1	
Input - Aspect Ratio - Cinema 2	425
Input - Auto Input Switch	4 3
Input - Auto Input Switch - On	431
Input - Auto Input Switch - Off	432
Input - PBP/PIP	4 4
Input - PBP/PIP - Off	441
Input - PBP/PIP - Off - HDMI1	4411
Input - PBP/PIP - Off - HDMI2	4412
Input - PBP/PIP - Off - DisplayPort	4413
Input - PBP/PIP - PBP(16:9/16:9)	442
Input - PBP/PIP - PBP(21:9/11:9)	443
Input - PBP/PIP - PBP(11:9/21:9)	444
Input - PBP/PIP - PIP	4 4 5
Input - PIP Size	4 5
Input - PIP Size - Small	451
Input - PIP Size - Large	452
Input - PIP Position	4 6
Input - PIP Position - Bottom Right	461
Input - PIP Position - Bottom Left	462
Input - PIP Position - Top Left	463
Input - PIP Position - Top Right	464
Input - Screen Switch	47
Input - Screen Switch - OK	471
Input - Sound Switch	48
Input - Sound Switch - OK	481

Menu	Location
General	5
General - Language	5 1
General - Language - English	511
General - Language - German	512
General - Language - French	513
General - Language - Spanish	514
General - Language - Italian	515
General - Language - Swedish	516
General - Language - Finnish	517
General - Language - Portuguese	518
General - Language - Portuguese (Brazil)	519
General - Language - Polish	5 1 10
General - Language - Russian	5 1 11
General - Language - Turkish	5 1 12
General - Language - Ukrainian	5 1 13
General - Language - Chinese	5 1 14
General - Language - Traditional Chinese	5 1 15
General - Language - Japanese	5 1 16
General - Language - Korean	5 1 17
General - Hexagon Lighting	5 2
General - Hexagon Lighting - Static 1	5 2 1
Conoral Hoyagan Lighting Static 1	5 2 1
General - Hexagon Lighting - Static 1	Color Chip
General - Hexagon Lighting - Static 2	5 2 2
General - Hexagon Lighting - Static 2	5 2 2 Color Chip
General - Hexagon Lighting - Static 3	523

Menu	Location
General - Hexagon Lighting - Static 3	5 2 3 Color Chip
General - Hexagon Lighting - Static 4	5 2 4
General - Hexagon Lighting - Static 4	5 2 4 Color Chip
General - Hexagon Lighting - Cycling	5 2 5
General - Hexagon Lighting - Off	5 2 6
General - User-defined Key 1	5 3
General - User-defined Key 1 - Input	5 3 1
General - User-defined Key 1 - Game Mode	532
General - User-defined Key 1 - Crosshair	533
General - User-defined Key 1 - Black Stabilizer	5 3 4
General - User-defined Key 1 - Response Time	5 3 5
General - User-defined Key 1 - FPS Counter	536
General - User-defined Key 1 - Hexagon Lighting	537
General - User-defined Key 2 - PBP/PIP	538
General - User-defined Key 2	5 4
General - User-defined Key 2 - Input	5 4 1
General - User-defined Key 2 - Game Mode	5 4 2
General - User-defined Key 2 - Crosshair	543
General - User-defined Key 2 - Black Stabilizer	5 4 4

Menu	Location
General - User-defined Key 3 - Response Time	5 4 5
General - User-defined Key 2 - FPS Counter	5 4 6
General - User-defined Key 2 - Hexagon Lighting	5 4 7
General - User-defined Key 3 - PBP/PIP	5 4 8
General - DTS Headphone:X	5 5
General - DTS Headphone:X - Game	5 5 1
General - DTS Headphone:X - Entertainment	5 5 2
General - DTS Headphone:X - Sports	5 5 3
General - DTS Headphone:X - Off	5 5 4
General - SMART ENERGY SAVING	5 6
General - SMART ENERGY SAVING - High	5 6 1
General - SMART ENERGY SAVING - Low	562
General - SMART ENERGY SAVING - Off	563
General - Deep Sleep Mode	5 7
General - Deep Sleep Mode - On	571
General - Deep Sleep Mode - Off	572
General - Power LED	5 8
General - Power LED - On	5 8 1
General - Power LED - Off	582
General - Automatic Standby	5 9
General - Automatic Standby - 8H	5 9 1
General - Automatic Standby - 6H	592
General - Automatic Standby - 4H	593

Menu	Location
General - Automatic Standby - Off	5 9 4
General - Input Compatibility Version	5 10
General - Input Compatibility Version - 2.1(PC) / 1.4(DSC)	5 10 1
General - Input Compatibility Version - 2.1(AV) / 1.4	5 10 2
General - Input Compatibility Version - 1.4 / 1.2	5 10 3
General - Buzzer	5 11
General - Buzzer - On	5 11 1
General - Buzzer - Off	5 11 2
General - OSD Lock	5 12
General - OSD Lock - On	5 12 1
General - OSD Lock - Off	5 12 2
General - Information	5 13
General - Reset to Initial Settings	5 14
General - Reset to Initial Settings - No	5 14 1
General - Reset to Initial Settings - Yes	5 14 2



## Supplier's Declaration of Conformity

Trade Name LG

Responsible Party LG Electronics USA, Inc.

Address 111 Sylvan Avenue, North Building,

Englewood Cliffs, NJ 07632

E-mail lg.environmental@lge.com

The model and serial number of the product are located on the back and on one side of the product.

Record them below in case you ever need service.

Model	
Serial No	