## V7 L18500WS 19" LED Monitor 16:9



## **Key Features**

- Powerful built-in speakers
- Rich and vibrant visuals with 16.7 million colors
- Life-like detail and definition with 1,000,000 : 1 dynamic contrast ratio
- 1366 x 768 resolution
- Small desktop footprint with stylish slim-bezel design

## Overview

The V7 19" Class (18.5" Viewable) LED monitor provides superior image quality with vivid colors and lifelike images. The LED backlight technology saves you up to 40% energy and yields blacker blacks, pure white and more clearly defined grays for a vivid picture making it the perfect choice for home or office. Key specifications include: 1366x768 HD resolution, 16:9 aspect ratio, 200 nits brightness, reduced blur with 5 ms response time and customized picture settings to fit your needs. The L18500WS reduces clutter and provides more desk space while sitting in a black glossy bezel. The widescreen monitor is easily wall mountable and provides a tremendous price to performance value.



L18500WS-9E

## Specification

V7 Model #         L18500WS-9E           IM SKU #         J152563           EAN         0662919083460           Aspect Ratio         16:9           Brightness         200 cd/m²           Color Spectrum         16.7 million colors           Compliance         FCC, CE, WEEE, ROHS           Contrast Ratio         1,000,000:1 Dynamic           Country of Origin         China           Energy Efficiency Class         A+           Horizontal Frequency         30-60KHz           Max Resolution         1366 x 768           Monitor Dim (L/W/H)         47 x 442 x 270 mm without base and neck           Mounting Pattern         75x75 mm           Package dim. (L/W/H)         124 x 493 x 315 mm           Package Includes         Monitor, VGA Cable, Power cord, Warranty card, Manua           Package Weight         3.45 kg           Packaging type         Global Retail Full Color Box           Panel Size         18,5"   48cm           Power Requirements         AC 100 - 240V           Product dim. (L/W/H)         180 x 442 x 357 mm           Product Weight         2.65 kg           Response Time         5 ms           Signal Inputs         VGA	
EAN  Aspect Ratio  Brightness  200 cd/m²  Color Spectrum  16.7 million colors  Compliance  FCC, CE, WEEE, ROHS  Contrast Ratio  1,000,000:1 Dynamic  Country of Origin  Energy Efficiency Class  Horizontal Frequency  30-60KHz  Max Resolution  1366 x 768  Monitor Dim (L/W/H)  47 x 442 x 270 mm without base and neck  Mounting Pattern  Package dim. (L/W/H)  124 x 493 x 315 mm  Package Includes  Monitor, VGA Cable, Power cord, Warranty card, Manua  Package Weight  3.45 kg  Packaging type  Global Retail Full Color Box  Panel Size  18,5"   48cm  Power Requirements  AC 100 - 240V  Product dim. (L/W/H)  180 x 442 x 357 mm  Product Weight  2.65 kg  Response Time	
Aspect Ratio Brightness 200 cd/m² Color Spectrum 16.7 million colors  Compliance FCC, CE, WEEE, ROHS Contrast Ratio 1,000,000:1 Dynamic  Country of Origin Energy Efficiency Class Horizontal Frequency 30-60KHz Max Resolution 1366 x 768 Monitor Dim (L/W/H) 47 x 442 x 270 mm without base and neck Mounting Pattern 75x75 mm Package dim. (L/W/H) 124 x 493 x 315 mm  Package Includes Monitor, VGA Cable, Power cord, Warranty card, Manua Package Weight 3.45 kg Packaging type Global Retail Full Color Box Panel Size 18,5"   48cm Power Requirements AC 100 - 240V Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg Response Time 5 ms	
Brightness 200 cd/m² Color Spectrum 16.7 million colors  Compliance FCC, CE, WEEE, RoHS Contrast Ratio 1,000,000:1 Dynamic  Country of Origin China Energy Efficiency Class A+ Horizontal Frequency 30-60KHz Max Resolution 1366 x 768 Monitor Dim (L/W/H) 47 x 442 x 270 mm without base and neck Mounting Pattern 75x75 mm Package dim. (L/W/H) 124 x 493 x 315 mm  Package Includes Monitor, VGA Cable, Power cord, Warranty card, Manua Package Weight 3.45 kg Packaging type Global Retail Full Color Box Panel Size 18,5"   48cm Power Requirements AC 100 - 240V Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg Response Time 5 ms	
Color Spectrum  Compliance FCC, CE, WEEE, RoHS  Contrast Ratio 1,000,000:1 Dynamic  Country of Origin Energy Efficiency Class Horizontal Frequency 30-60KHz  Max Resolution 1366 x 768  Monitor Dim (L/W/H) 47 x 442 x 270 mm without base and neck  Mounting Pattern 75x75 mm Package dim. (L/W/H) 124 x 493 x 315 mm  Package Includes Monitor, VGA Cable, Power cord, Warranty card, Manua Package Weight 3.45 kg Packaging type Global Retail Full Color Box Panel Size 18,5"   48cm Power Requirements AC 100 - 240V Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg Response Time 5 ms	
Compliance FCC, CE, WEEE, RoHS  Contrast Ratio 1,000,000:1 Dynamic  Country of Origin China  Energy Efficiency Class A+  Horizontal Frequency 30-60KHz  Max Resolution 1366 x 768  Monitor Dim (L/W/H) 47 x 442 x 270 mm without base and neck  Mounting Pattern 75x75 mm  Package dim. (L/W/H) 124 x 493 x 315 mm  Package Includes Monitor, VGA Cable, Power cord, Warranty card, Manua  Package Weight 3.45 kg  Packaging type Global Retail Full Color Box  Panel Size 18,5"   48cm  Power Requirements AC 100 - 240V  Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg  Response Time 5 ms	
Contrast Ratio 1,000,000:1 Dynamic Country of Origin China Energy Efficiency Class A+ Horizontal Frequency 30-60KHz Max Resolution 1366 x 768 Monitor Dim (L/W/H) 47 x 442 x 270 mm without base and neck Mounting Pattern 75x75 mm Package dim. (L/W/H) 124 x 493 x 315 mm Package Includes Monitor, VGA Cable, Power cord, Warranty card, Manua Package Weight 3.45 kg Packaging type Global Retail Full Color Box Panel Size 18,5"   48cm Power Requirements AC 100 - 240V Product dim. (L/W/H) 180 x 442 x 357 mm Product Weight 2.65 kg Response Time 5 ms	
Country of Origin Energy Efficiency Class A+ Horizontal Frequency 30-60KHz Max Resolution 1366 x 768 Monitor Dim (L/W/H) 47 x 442 x 270 mm without base and neck Mounting Pattern 75x75 mm Package dim. (L/W/H) 124 x 493 x 315 mm Package Includes Monitor, VGA Cable, Power cord, Warranty card, Manual Package Weight 3.45 kg Packaging type Global Retail Full Color Box Panel Size 18,5"   48cm Power Requirements AC 100 - 240V Product dim. (L/W/H) 180 x 442 x 357 mm Product Weight 2.65 kg Response Time 5 ms	
Energy Efficiency Class A+ Horizontal Frequency 30-60KHz  Max Resolution 1366 x 768  Monitor Dim (L/W/H) 47 x 442 x 270 mm without base and neck  Mounting Pattern 75x75 mm  Package dim. (L/W/H) 124 x 493 x 315 mm  Package Includes Monitor, VGA Cable, Power cord, Warranty card, Manua  Package Weight 3.45 kg  Packaging type Global Retail Full Color Box  Panel Size 18,5"   48cm  Power Requirements AC 100 - 240V  Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg  Response Time 5 ms	
Horizontal Frequency  Max Resolution  1366 x 768  Monitor Dim (L/W/H)  47 x 442 x 270 mm without base and neck  Mounting Pattern  75x75 mm  Package dim. (L/W/H)  124 x 493 x 315 mm  Package Includes  Monitor, VGA Cable, Power cord, Warranty card, Manua  Package Weight  3.45 kg  Packaging type  Global Retail Full Color Box  Panel Size  18,5"   48cm  Power Requirements  AC 100 - 240V  Product dim. (L/W/H)  180 x 442 x 357 mm  Product Weight  2.65 kg  Response Time  5 ms	
Max Resolution1366 x 768Monitor Dim (L/W/H)47 x 442 x 270 mm without base and neckMounting Pattern75x75 mmPackage dim. (L/W/H)124 x 493 x 315 mmPackage IncludesMonitor, VGA Cable, Power cord, Warranty card, Manual Package WeightPackaging typeGlobal Retail Full Color BoxPanel Size18,5"   48cmPower RequirementsAC 100 - 240VProduct dim. (L/W/H)180 x 442 x 357 mmProduct Weight2.65 kgResponse Time5 ms	
Monitor Dim (L/W/H)  47 x 442 x 270 mm without base and neck  Mounting Pattern  75x75 mm  Package dim. (L/W/H)  124 x 493 x 315 mm  Monitor, VGA Cable, Power cord, Warranty card, Manua  Package Weight  3.45 kg  Packaging type  Global Retail Full Color Box  Panel Size  18,5"   48cm  Power Requirements  AC 100 - 240V  Product dim. (L/W/H)  180 x 442 x 357 mm  Product Weight  2.65 kg  Response Time  5 ms	
Mounting Pattern  Package dim. (L/W/H)  Package Includes  Monitor, VGA Cable, Power cord, Warranty card, Manua  Package Weight  3.45 kg  Packaging type  Global Retail Full Color Box  Panel Size  18,5"   48cm  Power Requirements  AC 100 - 240V  Product dim. (L/W/H)  180 x 442 x 357 mm  Product Weight  2.65 kg  Response Time  75x75 mm  Monitor, VGA Cable, Power cord, Warranty card, Manua  3.45 kg  Global Retail Full Color Box  18,5"   48cm  Power Requirements  AC 100 - 240V  Froduct Weight  2.65 kg	
Package dim. (L/W/H)  Package Includes  Monitor, VGA Cable, Power cord, Warranty card, Manual 3.45 kg  Package Weight  Packaging type  Global Retail Full Color Box  Panel Size  18,5"   48cm  Power Requirements  AC 100 - 240V  Product dim. (L/W/H)  180 x 442 x 357 mm  Product Weight  2.65 kg  Response Time  5 ms	
Package Includes  Monitor, VGA Cable, Power cord, Warranty card, Manua  3.45 kg  Packaging type  Global Retail Full Color Box  Panel Size  18,5"   48cm  Power Requirements  AC 100 - 240V  Product dim. (L/W/H)  180 x 442 x 357 mm  Product Weight  2.65 kg  Response Time  5 ms	
Package Weight 3.45 kg Packaging type Global Retail Full Color Box Panel Size 18,5"   48cm Power Requirements AC 100 - 240V Product dim. (L/W/H) 180 x 442 x 357 mm Product Weight 2.65 kg Response Time 5 ms	
Packaging type Global Retail Full Color Box  Panel Size 18,5"   48cm  Power Requirements AC 100 - 240V  Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg  Response Time 5 ms	CD
Panel Size 18,5"   48cm  Power Requirements AC 100 - 240V  Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg  Response Time 5 ms	
Power Requirements AC 100 - 240V Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg  Response Time 5 ms	
Product dim. (L/W/H) 180 x 442 x 357 mm  Product Weight 2.65 kg  Response Time 5 ms	
Product Weight 2.65 kg Response Time 5 ms	
Response Time 5 ms	
·	
Signal Inputs VGA	
Speaker 2 x 2W	
System Requirements Windows /XP/Vista/7/8 or above, Mac OSX	
Tilt (Degree) -5/15	
Vertical Frequency 55-75Hz	
Viewing Angle H/V 170°/160°	
Warranty 3 Year	















The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions, are disclaimed. Measurement standards and testing conditions, as per manufacturer definitions, are available on request.