

Data Sheet FUJITSU Display E22T-7 Pro

All-round Display: 54.6 cm (21.5-inch) widescreen Best energy saving solutions for office applications

The FUJITSU E22T-7 Pro all-round display is the cost-effective choice for your everyday office working requirements. With its size of 54.6 cm (21.5-inch), In-Plane Switching (IPS) technology, ease of use and reliability, this stylish all-rounder is perfect for your standard office tasks. Power saving features help to cut your energy bills.

In-Plane Switching (IPS) technology with 1920×1080 pixels resolution for pin sharp pictures

Flicker-free picture experience; ergonomic low blue light mode

Environment-friendly LED technology with unique, highly efficient energy saving solutions like ECO operation mode and ECO standby

Representative design providing a slender housing in ergonomic matt black with integrated speakers and power supply

Full support for FUJITSU Desktop ESPRIMO Q and FUJITSU Thin Clients FUTRO backpack solutions















Technical details

| Special features | |
|--------------------------------------|--|
| Special reactiles | Low blue light mode, In-Plane Switching (IPS) technology, Keep aspect ratio option, Eco button for Eco mode and |
| Francomic stand | 3-coloured Eco status LED, headset connector |
| Ergonomic stand | rama un bla |
| Stand | removable |
| Picture height over desk (min) | 70.8 mm |
| Tilt angle | -5°/+20° |
| Picture performance | |
| Panel and backlit | In-Plane Switching (IPS) technology/LED |
| Screen Surface Treatment | Anti-glare, 3H hard coating |
| Contrast - typical | 1,000:1 |
| Contrast - advanced | 20,000,000:1 |
| Response time gray to gray typical | 5 ms |
| Viewing angle (h/v) - typical | 178°/178° CR10:1 |
| Color performance | 16.7 million colors (Hi-FRC) |
| Brightness - typical | 250 cd/m2 |
| Size and resolution | |
| Aspect ratio | 16:9 |
| Diagonal Size | 54.6 cm (21.5-inch) |
| Resolution (native) | 1,920 x 1,080 pixel |
| Resolution (interpolated) | $1,680 \times 1,050$ pixel, $1,440 \times 900$ pixel, $1,366 \times 768$ pixel, $1,280 \times 1,024$ pixel, $1,280 \times 720$ pixel, $1,024 \times 768$ pixel, 800×600 pixel, 640×480 pixel |
| Display HD Support | 1080i/p, 720i/p, 576i/p, 480i/p |
| Picture size | 476 x 268 mm |
| Pixel Pitch | 0.248 mm |
| Frequencies | |
| Horizontal | 30 - 82 kHz |
| Vertical | 56 - 76 Hz |
| Frequencies - bandwidth | 165 Mhz |
| Connectivity | |
| HDMI | 1 x HDMI |
| DVI | 1 x DVI-D (HDCP) |
| VGA/D-SUB | 1 x D-SUB |
| Audio signal output | 3.5 mm stereo phone jack |
| Audio signal input | 3.5 mm stereo phone jack |
| Audio sound output | 2 x 1.5 W |
| HDMI audio | Yes |
| Ease-of-use menu | |
| Languages | Arabic, Chinese simply, Chinese traditional, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish |
| Brightness / Contrast | Brightness, Contrast, Black level, Auto level |
| Mode | Office, Photo, Video, sRGB |
| Color | 5000K, 6500K, 7500K, Native, Custom Color (R,G,B) |
| Image adjust | Clock, Phase, H-Position, V-Position, Expansion |
| Audio | Mute, Volume |
| Information | Model name, Serial number, Resolution/mode, Signal input |
| Setup | Input select, Language, DDC-CI, OSD-Timeout, Factory preset |
| Power consumption (typical, w/o sour | 1 3 3 3 7 7 7 |
| Soft switch off | 0.23 W |
| Power save mode | 0.27 W |
| Operating with EPA settings | 18.81 W |
| operating with LFA settings | TU.UT YY |

| Operating maximum brightness | 21.08 W |
|--|---|
| Power supply | integrated |
| Power notes | Speakers off |
| Electrical values | Diegweis uit |
| Rated voltage range | 100 V - 240 V |
| | 50 Hz - 60 Hz |
| Rated frequency range Protection class | |
| | 1 |
| Compliance | F22T 7 D |
| Product | E22T-7 Pro |
| Europe | Energy Efficiency Class: A, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration, EN 60601-1-2 |
| Model | DY22T-7 |
| Germany | TÜV GS |
| Russia | EAC |
| USA/Canada | FCC Class B, cUL |
| Australia/New Zealand | RCM |
| Japan | VCCI |
| South Korea | KC |
| Argentina | TÜV-S |
| Singapore | S-Mark |
| Taiwan | BSMI |
| China | |
| Saudi Arabia | SASO |
| Global | TCO Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) |
| Compliance link | http://globalsp.ts.fujitsu.com/sites/certificates |
| Quality and Reliability | |
| MTBF (demonstrated) | 70,000 h |
| Dimensions / Weight / Environmental | |
| Dimension without stand (W x D x H) | 516 x 62.8 x 316.1 mm |
| | 20.31 x 2.47 x 12.44 inch |
| Dimension with stand (W x D x H) | 516 x 213.9 x 359.3 mm |
| | 20.31 x 8.42 x 14.15 inch |
| Weight (packed) | 5.2 kg |
| | 11.46 lbs |
| Weight (unpacked) | 3.80 kg |
| | 8.38 lbs |
| Weight (Monitor only) | 3.27 kg |
| | 7.21 lbs |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F) |
| Miscellaneous | · · · · · · · · · · · · · · · · · · · |
| Miscellaneous | VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared |
| Color | Black |
| Package content | |
| Display delivered accessories | DVI-D Data cable 1.8 m Audio cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Getting Started Manual Warranty booklet |
| Display delivered accessories notes | Data cables and audio cable detachable on display Please note: cable length may vary by +/- 5 cm. |
| Order information | |
| Order Code | S26361-K1579-V160 |
| | |

| Order information | |
|-----------------------------|--|
| Country specific order code | BDL:K1579V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1579V160-CHN - with China power cable and CEL, mandatory for China BDL:K1579V160-ID - with Import label, mandatory for Indonesia BDL:K1579V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed |
| Accessories information | Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/ dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf |
| Warranty | |
| Warranty period | 3 years (depending on country) |
| Warranty type | Collect & Return Service (depending on country specific requirements) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display E22T-7 Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display E22T-7 Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2016-07-04 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2016 Fujitsu Technology Solutions GmbH