

Name Case color Type-model Panel Viewable image size Max view area (W x H) Native resolution Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD) Power supply Weight Limited warranty⁴ Available date	LT2024 Wide Flat Panel Monitor Business black 60B9HAR1US TFT-LCD, twisted nematic (TN), White LED backlight 20.0" (508mm) diagonal 17.4" x 9.8" (442.8mm x 249.1mm) 1600x900 16:9 .276mm 92 dpi 250 nits or cd/m² (typical) 1000:1 (typical) 5ms (typical) 72% 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt adjustable stand Sides: 0.567" (14.4mm) 13.68" H x 18.83" W x 6.33" D; 347.4mm H x 478.4mm W x 160.7mm D 19 watts typical, 22 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 6.75 lb; 3.07 kg 3 year (includes backlight) March 2014	Features • Widescreen 20-inch monitor • Supports 1600x900 resolution • Includes dual input connection for attachment to two systems concurrently (analog and digital) • Arsenic / Mercury free glass • EPEAT Gold certified • Support Lenovo Tiny PC and 3rd party thin client • Microsoft® Windows® 7 certified • Microsoft Windows 8 / Windows 8.1 certified
VESA-compliant² Power management Ergonomics Emission standards Environmental	VESA DDC2B/CI ENERGY STAR® qualified ISO 9241-307 FCC Class B TCO Displays 6.0, TCO Certified Edge 1.2, WEEE, RoHS, EPEAT™ Gold rating	 ThinkVision LT2024 Wide Monitor
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900	
Presets / user settings	Standard presets: 24 user settings: 24	
Viewing adjustments Rotating screen On screen display Control features Multiple input Monitor connectors Signal cables Mounting features Security	Tilt: 22° backward, -5° forward None On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, HDCP-compliant (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group	Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter black power cord	
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281		
Accessories Kensington MicroSaver Cable Lock73P2582 Kensington Twin Head Cable Lock45K1620 See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision		