ThinkCentre Tiny-In-One 24 Gen3 10QXPAT1++

Region EMEA

Machine Type 10QX

Color Black

Display Size 23.8"

Multi-touch 10-point Multi-touch

Resolution 1920x1080

Aspect Ratio 16:9

Pixel Pitch 0.2745 mm

Dot / Pixel Per Inch 92.6 dpi

Brightness 250 nits

Contrast Ratio 1000:1

Pixel Response Time 4-14 ms

Color Gamut 72% View Angle (H / V) 178 / 178

Stand Adjustable Stand

Power Comsuption (Typical / Maximum) 19W / 32W

Power Supply 90W 88% Adapter

Warranty 3-year

Ann Date (mm/yy) 07/17

Note: Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX -Hungary, CY - Cyprus, etc.), and "**" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifcations or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.



http://psref.lenovo.com

Visit psref website for the latest version of Product Specifcations Reference. © Lenovo, 2017. All rights reserved.



ThinkCentre Tiny-in-One (TIO) 24 Gen3

Product Specifications Reference (PSREF)

Model	Non-touch model: 10QYPAR1++/10QYPAT1++; 10QXPAR1++/10QXPAT1++ Tiny-in-One, offers a full All-In-One experience when optional Tiny slots into the back of TIO, clean cabling and effortless setup			Mounting features Adjustable stand	Wall or desk mounting using the extend arm or third-party accessories meeting the VESA FPMPMI® (100mm mount) <i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3° (110mm);		
Form factor							
Compatible Tiny:	M910 / M710 / M90 Chromebox Tiny	00 / M700 / M600 / M715	5 / M93/p* / M83 / M73* / M53 /		<i>swivel:</i> +/-45°; <i>Pivot:</i> clockwise 0° to 90°		
	* Non-TIO models		essing power button of TIO	Power supply	90 watts AC/DC adapter, 88% PSU, universal		
Panel	TFT-LCD, In-Plane Switching technology**, White LED backlight <i>Notes:</i> In-Plane Switching may refer to VA, PLS, and IPS panels 23.8" (604.7mm) diagonal 21.06" x 12.32" / 535.0mm x 313.0mm Top / Side: 2mm, Bottom: 22.1mm 1920x1080 Optional 10-point multi-touch, supports Wake on Touch 16:9 0.2745mm			Power consumption	19 watts typical, 32 watts maximum, <0.5 watts standby / suspend 3-years, Customer Carry-In or Mail-In via Rapid Replacement Service		
Viewable image size Max view area (W x H) Bezel Width Native resolution Multi-touch Aspect ratio Pixel pitch (mm)				VESA-compliant Ergonomics Emission standards Environmental Windows certifications	VESA DDC2B/CI, VESA DPMS-compliant ISO 9241-307, TUV Eye Comfort certified FCC Class B TCO 7.0, TCO Edge 2.0, WEEE, RoHS, ENERGY STAR® 7.0, EPEAT™ Gold rating, ULE Gold, TUV, VOC Windows 7 and Windows 10 certified		
Pixel pitch (mm) Dot/Pixel per Inch Brightness	92.6 dpi				TIO 24 (Monitor), detachable stand, AC/DC power adapter, power cord, user's guide and driver CD, quick start and safety poster		
Contrast ratio Pixel response time	1000:1 (typical)				For compatible accessories, please go to http://www.lenovoquickpick.com		
Color gamut	72%	5. GIVE IO HIIS, OIIIS	l				
Anti-reflective Viewing angle at 10:1 Cl	Anti-glare R178° (+/- 89°) horiz	ontal, 178° (+/- 89°) ver	tical		ThinkCentre Tiny-in-One 24 Gen3		
Preset resolutions	640x350 @ 70Hz 640x480 @ 60Hz, 67Hz, 72Hz, 75Hz 720x400 @ 70Hz 800x600 @ 60Hz, 72Hz, 75Hz 1024x768 @ 60Hz, 72Hz, 75Hz 1152x864 @75Hz 1280x800 @ 60Hz 1280x1024 @ 60Hz, 72Hz, 75Hz 1366x768 @ 60Hz 1440x900 @ 60Hz, 75Hz 1660x1200 @ 60Hz, 70Hz, 75Hz 1680x1050 @ 60Hz 1920x1080 @ 60Hz Presets: 25; user settings: 25			Model	M910 / M710 / M900 / M700 / M600 / M715 / M83 / M53 Tiny	M93/p Tiny, M73 Tiny	Chromebox
				Turn on TIO and Tiny together via Alt + P on USB KB	All models	All models	Not support
				Turn on TIO and Tiny together via TIO Power Button	All models	TIO models	All models
Presets / user settings							
On screen display	On screen display	with digital user controls	(8 languages)	•			
Control features	Ftont: Exit butto Right / B	on, Left / Mode-switching rightness button, Enter /	g button (TIO / monitor mode), Menu button, Power button				
Tiny-in-One Power On	Bottom: Volume up button, Volume down button Pressing Alt + P on keyboard or pressing Power button positioned on TIO can turn on both TIO and Tiny (only some Tiny support, see compatible list)						
Side ports (TIO)	One USB 3.1 Gen connected via USE <i>Notes:</i> The USB p	1 / USB 2.0 (when M73 o 3 upstream port)	or M53 installed or USB 2.0				
Side ports (Tiny) Rear ports 3-in-1 Cable	Side ports offered by installed Tiny (optional) One DisplayPort in port, one USB upstream port, one power connector Undetachable 3-in-1 cable (Power connecter, USB [supports USB 3.1 Gen1 / USB 2.0], DisplayPort), only for connecting to Tiny installed (optional) 1080p camera with dual microphone for VOIP, LED indicator 2 watt x2						
Camera Internal Speaker							
Security	Security keyhole fo compatible), locks offered by Tiny inst	optional Tiny with TIO to	cable lock (Kensington [®] lock ogether, more security features				
Mechanical	Dimensions	TIO without stand	TIO with stand				
	W x D x H (inch)	21.25 x 2.85 x 14.47	21.25 x 11.11 x 15.72 - 20.06				
	W x D x H (mm)	539.8 x 72.5 x 367.6	539.8 x 282.3 x 399.4 - 509.4				
	Weight (Approx.)	7.96 lb /3.61 kg	12.92 lb /5.86 kg				

ThinkCentre Tiny-In-One 24 Gen3











