

Widescreen display offers good value

With features like DVI and VGA inputs, SmartContrast and Energy efficiency, the 220V1 offers good value.

Good picture quality

- WSXGA+, wide format 1680x1050 resolution for sharper display
- 5ms fast response time
- SmartContrast: For incredible rich black details

Great convenience

- Dual input accepts both analog VGA and digital DVI signals
- Easy picture format control switching in wide and 4:3 format
- · Screen tilts to your ideal, individualized viewing angle

Environmentally friendly green design

- Eco-friendly materials that meets international standards
- Complies with RoHS standards to care for the environment
- EPEAT Silver ensures lower impact on environment

Philips

LCD widescreen monitor

56 cm (22") w V-line Format 16:10

220V1SB



Highlights

Eco-friendly materials

"Philips is committed to use sustainable, eco-friendly materials across its monitor range. All body plastic parts, metal chassis parts and packing materials use 100% recyclable materials. In some selected models we utilize upto 65% post consumer recycled plastics. Strict adherence to RoHS standards ensure substantial reduction or elimination of toxic substances like Lead, for example. Mercury content in monitors with CCFL backlight has been reduced significantly, while eliminated in monitors with LED backlight completely. Visit Philips @ http://www.asimpleswitch.com/global/to learn more.

Dual input





VGA connector

DM connector

Dual input provides connectors to accommodate input of both analog VGA and digital DVI signals.

Easy picture format control





Widesprea format

4:3 formati

Philips easy picture format control on OSD is to switch from the 4:3 aspect ratio to the widescreen mode and back again to match the display's aspect









Issue date 2017-07-28

Version: 5.0.7

12 NC: 8670 000 53402 EAN: 87 12581 48655 6 © 2017 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

ratio with your content for working with wide

native mode display of 4:3 ratio content.

Adjustable tilt

environment.

EPEAT Silver

documents without scrolling or viewing widescreen

media in the widescreen mode and distortion-free,

Adjustable tilt is backward and forward movement of

a screen on its base to achieve custom positioning for

an ideal viewing angle and more comfort for people

who spend long hours working on the computer.

Philips designs and produces display products in

compliance with strict Restriction of Hazardous

Philips EPEAT Silver certified monitors ensure

highly energy efficient ensuring low emissions of

helps purchasers evaluate, compare and select

Monitors based on 51 environmental criteria supported by US EPA. EPEAT Silver is valid only where

WSXGA+, wide format 1680x1050

Wide format, super extended graphics array is a

display specification that is capable of displaying 1680

x 1050 resolution or approximately 1.7 million pixels.

On-Off response time is the period required for a

liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured

in milliseconds. Faster is better: Lower response time

fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more

important measure in the display of business content

means faster transitions and, therefore, results in

Philips registers the product. Please visit

5ms on/off response time

like documents, graphs and photos.

protection for human health and environment, and are

climate changing green house gases. EPEAT program

www.epeat.net for registration status in your country.

Substances (RoHS) standards that restrict lead and other toxic substances that can harm the

Compliant with RoHS standards

www.philips.com

Specifications

Picture/Display

- LCD panel type: TFT-LCD
- Panel Size: 22 inch / 55.9 cm
- Aspect ratio: 16:10
- Pixel pitch: 0.282 x 0.282
- Brightness: 250 cd/m²
- SmartContrast: 20000:1
- Contrast ratio (typical): 1000:1
- Response time (typical): 5 ms
- Optimum resolution: 1680 x 1050 @ 60Hz
- Viewing angle: 176° (H) / 170° (V), @ C/R > 5
- Display colors: 16.7 M
- Scanning Frequency: 30 83 kHz (H) / 56 -75 Hz (V)
- sRGB

Connectivity

- Signal Input: VGA (Analog), DVI-D
- Sync Input: Separate Sync, Sync on Green

Convenience

- User convenience: Brightness, Menu, Input, Auto, Power On/Off
- OSD Languages: English, French, German, Spanish, Italian, Russian, Simplified Chinese, Portuguese, Turkish
- Other convenience: VESA mount (100x100mm), Kensington lock
- Plug & Play Compatibility: DDC/CI, Windows 98/ 2000/XP/Vista, sRGB

Stand

• Tilt: -5/+20 degree

Power

- On mode: 29.8 W
- Standby mode: <0.5 W
- Off mode: < 0.5 W
- Power LED indicator: Operation green, Stand by/ sleep - Amber
- Power supply: Built-in, 100-240VAC, 50/60Hz

Dimensions

- Product with stand (mm): $506 \times 403 \times 205$ mm
- Product without stand (mm): 506 x 347 x 62 mm
- Packaging in mm (WxHxD): 453 \times 570 \times 140 mm

Weight

- Product with stand (kg): 4.53 kg
- Product without stand (kg): 4.17 kg
- Product with packaging (kg): 6.29 kg

Operating conditions

- Temperature range (operation): 0-40 °C
- Temperature range (storage): -20-60 °C
- Relative humidity: 20%-80 %
- MTBF: 50,000 hour(s)

Sustainability

- Environmental and energy: EPEAT Silver, RoHS, EnergyStar 5.0
- Recyclable packaging material: 100 %

Compliance and standards

 Regulatory Approvals: CE Mark, FCC, Class B, UL/ cl II

Cabinet

- Color: Black
- Finish: Texture

