

Statement of Volatility - Dell P2219H Monitor

The purpose of this document is to certify that the Dell P2219H monitor will not save, retain, or reproduce a signal to any internal or external component after power has been removed and reapplied to the unit.

The Dell P2219H monitor contains both volatile and non-volatile (NV) memory ICs. Volatile memory(s) lose their data immediately upon removal of power. Non-volatile memory ICs continue to retain their data even after the power has been removed. However, no input video data is written into these memory ICs during operation.

List below contains volatile and non volatile memory ICs used in the Dell P2219H monitor.

System EEPROM	ST M24C16
Size	16Kbit
Type [e.g. Flash PROM, EEPROM]	EEPROM
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	OSD setting: Yes
Purpose	Storage of system setting (OSD)
How is data input to this memory?	Controls the OSD menu and changes OSD settings (ex. brightness, contrast, color settings) and the settings will be stored into system EEPROM.
How is this memory write protected?	Software write protected.

VGA EDID EEPROM	ROHM BR24G02
Size	2Kbit
Type [e.g. Flash PROM, EEPROM]	EEPROM
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	No
Purpose	Storage of VGA EDID

How is data input to this memory?	VGA EDID is embedded in the firmware, and copied to EEPROM after F/W programming. (or via customized EDID tool)
How is this memory write protected?	Hardware and software write protected

HDMI EDID EEPROM	ROHM BR24G02
Size	2Kbit
Type [e.g. Flash PROM, EEPROM]	EEPROM
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	No
Purpose	Storage of HDMI EDID
How is data input to this memory?	HDMI EDID is embedded in the firmware and copied to EEPROM after F/W programming. (or via customized EDID tool)
How is this memory write protected?	Hardware and software write protected

Flash ROM	ISSI PM25LQ040B
Size	4M bit
Type [e.g. Flash PROM, EEPROM]	Serial flash memory
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	No
Purpose	To store firmware.
How is data input to this memory?	Loading flash memory requires a vendor-provided tool and firmware.
How is this memory write protected?	Software write protected