

Name	P24q Wide Flat Panel Monitor	Features • 23.8-inch IPS LED backlit monitor • Supports 2560x1440 resolution • 5-Ports USB hub, support USB 3.0 • Support ThinkCentre Tiny • Supports optional soundbar • Microsoft® Windows® 7 certified • Microsoft Windows 10 certified						
Case color	Black							
Type-model	61A5GAR3US / 61A5GAT3EU							
Panel	TFT-LCD, IPS (In-Plane Switching), White LED backlight							
Viewable image size	23.8" (604.5mm) diagonal							
Max view area (W x H)	20.74" x 11.67" (526.85mm x 296.35mm)							
Optimum resolution	2560x1440							
Max pixel rate	300MHz							
Aspect ratio	16:9							
Pixel pitch (mm)	0.2058 x 0.2058mm							
Dot/Pixel per Inch	123 dpi							
Brightness	300 nits or cd/m² (typical)							
Contrast ratio	1000:1 (typical)							
Pixel response time	4ms							
Color gamut	99% sRGB							
Viewing angle at 10:1 CR	178° horizontal, 178° vertical							
Stand	Tilt, swivel, pivot, and height adjustable stand							
Bezel width	<i>Sides:</i> 0.08" (2mm)							
Dimensions	14.7" H x 21.26" W x 10.3" D;							
(HxWxD, including stand)	373.4mm H x 540.2mm W x 261.75mm D							
Power supply	24 watts typical, 67 watts maximum (with USB), <0.5 watts sleep/off; <0.5 watts switch off integrated (no external brick-like power supply)							
Weight	12.35 lb; 5.6kg (including stand)							
Limited warranty	3 year							
Available date	January 2017							
VESA-compliant	VESA DDC2B/CI	ThinkVision P24q Monitor						
Power management	ENERGY STAR® 7.0							
Ergonomics	ISO 9241-307							
Emission standards	FCC Class B							
Environmental	TCO Displays 7.0, RoHS, EPEAT™ Gold rating , ULE Gold							
Preset resolutions	VGA: 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080, 1920x1200 QHD: 2560x1440							
Presets / user settings	Standard presets: 20; user settings: 24							
Viewing adjustments	<i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.33" (110mm); <i>swivel:</i> +/-45° Screen pivots 90 degrees from landscape to portrait							
Rotating screen	On screen display with digital user controls (8 languages)							
On screen display	Direct access for menu, source switch, and brightness							
Control features	USB Hub: one USB 3.0 upstream port, four USB 3.0 downstream ports							
USB hub	Audio-out, optional sound bar supported							
Multimedia	None							
Camera	Support HDMI, DisplayPort, mini DisplayPort, DisplayPort-out							
Multiple input	(1) 2*HDMI (1.4), digital, HDCP-compliant							
Monitor connectors	(2) DisplayPort (1.2), digital, HDCP-compliant (3) Mini DisplayPort, digital, HDCP-compliant							
Signal cables	(1) detachable, mini DisplayPort to DisplayPort, digital, 1.8 meter							
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)							
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)							
Ship group	Monitor, detachable stand, Quick start and safety poster, 1.8 meter USB 3.0 cable, 1.8 meter mini DP to DP cable, 1.8 meter black power cord							
Limited Warranty See details at http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281		Accessories <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr></table> See details at www.lenovo.com/support/monitoraccessories See all monitors at www.lenovo.com/thinkvision	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303
Kensington MicroSaver Cable Lock	73P2582							
Kensington Twin Head Cable Lock	45K1620							
Lenovo Security Cable Lock	57Y4303							