Features & Technical Specifications

Alienware 25 Gaming Monitor

Viewable image size (diagonal)
(unage one (unagenai)
Active display area (horizontal x vertical)
Panel technology
Display Screen Coating
Maximum preset resolution
Typical viewing angles (vertical / horizontal)
Pixel pitch and Pixels Per Inch (PPI)
Aspect ratio
Brightness (typical)
Color gamut (typical)
Color depth
Contrast ratio (typical)
Response time (typical)
Backlight
ComfortView ¹
AlienFX Lighting
Connectivity
AMD FreeSync™
NVIDIA® G-SYNC™
Stand adjustability Stand features
VESA mount compatibity
Power AC input voltage/frequency/current Power consumption (typical/maximum)
Power consumption (standby/sleep mode)
Dimensions (HxWxD) Panel only Monitor head with stand (compressed/extended height)
Dimensions (HxWxD) Panel only Monitor head with stand (compressed/extended
Dimensions (HxWxD) Panel only Monitor head with stand (compressed/extended height) Weight Panel only (for VESA)
Dimensions (HxWxD) Panel only Monitor head with stand (compressed/extended height) Weight Panel only (for VESA) Monitor and cables with full packaging
Dimensions (HxWxD) Panel only Monitor head with stand (compressed/extended height) Weight Panel only (for VESA) Monitor and cables with full packaging Color Options
Dimensions (HxWxD) Panel only Monitor head with stand (compressed/extended height) Weight Panel only (for VESA) Monitor and cables with full packaging Color Options Compliance Standards

AW2521HF/HFL

62.23cm (24.5")
543.74mm x 302.62mm (21.41" x 11.91")
Fast IPS
Antiglare 25% with 3H Hardness
Full HD 1920 x 1080, 240 Hz (native)
178° / 178°
0.2832 mm x 0.2802 mm, 90 PPI
16:9
400 cd/m ²
99% sRGB
16.78 million colors
1,000 : 1
True 1ms (gray to gray) with overdrive in Extreme mode
LED edgelight system
Yes
Yes – 1 zone, 3 lights (Logo, Power Button, Rear Light Strip)
2x HDMI 2.0, DP 1.2, USB 3.0 upstream, 4x USB 3.0 downstream (1 with Power Charge), 1x Headphone-out jack, 1 x Audio Line-out jack
AMD FreeSync Premium
G-SYNC Compatible
Height adjustable stand up to 130 mm, Tilt (-5° to 21°), Swivel (-20° to 20°), Pivot (-90° to 90°) Built in cable-management
Yes, 100 mm x 100 mm, with quick release button
100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.5 A (typical) 24W / 73W <0.3 W
328.24 mm x 556.29 mm x 72.95 mm (12.92" x 21.90" x 2.87") 421.21mm - 526.08mm x 556.29 mm x 251.92mm (16.58" – 20.71" x 21.90" x 9.92")
3.55kg (7.81lbs) 11.22kg (24.91lbs)
2521HF - Dark Side of the Moon / 2521HFL - Lunar Light
Product Safety, EMC and Environmental Datasheets Dell Regulatory Compliance Home Page Dell and the Environment
3-year Advanced Exchange Service ² & Premium Panel Exchange
Monitor panel, Stand riser, Stand base, Cable Cover, Power cable, 1x HDMI cable, 1x DisplayPort cable, 1x USB 3.0 (upstream) cable, Quick setup guide, Drivers and documentation media, Safety Information

¹ComfortView feature reduces blue light emission and optimizes eye comfort.
²Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis.
Fee charged for failure to return defective unit. Availability varies. Other conditions apply.
³For a copy of the Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see Dell.com/warranty. Technical specifications subject to change without prior notice. Product availability varies by country. Please contact your Dell representative for more information.

Copyright 2020 Dell Inc. All rights reserved. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their

products. Dell disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without express written permission from Dell Inc. is strictly forbidden.



.