# A DISPLAY OF HIGH PERFORMANCE

## Space-saving 19.5" display that's built for productivity

ThinkVision T2054p is a real productivity-builder for business. The brilliant 19.5" wide-angle IPS display is perfect for everything from tiny text to complex images, and the compact design is a real space-saver. It's perfect for any user with lift-tilt-swivel stand and support for a ThinkCentre Tiny PC bracket. Fully Green-certified, it pairs seamlessly to virtually any device with VGA, DisplayPort1.2 and HDMI1.4 ports.



## WHY YOU SHOULD BUY THE THINKVISION T2054p MONITOR



#### Brilliant Screen Performance

The 1440 x 900 IPS screen displays crisp images from centre to sides with a 16:10 wide-angle view. 16.7M colors, 250 nits brightness and 1000:1 contrast ensure a truly vivid display.



#### Compact, Space-saving Design

This compact monitor fits anywhere you need it, and adjusts for any user with lift-tilt-swivel stand and support for a ThinkCentre Tiny PC clamp bracket.

## THE THINKVISION T2054P MONITOR IS BEST SUITED FOR



Businesses and office users seeking outstanding display performance to ramp up productivity.



Public reception areas or other customer-facing uses where compact design and sleek good looks are important.



o(:::::)o

#### Seamless Connectivity

Use the T2054p seamlessly with virtually any system or device, thanks to VGA, HDMI1.4 and DisplayPort 1.2 connectivity.

Windows

#### Business situations where space is at a premium, yet user comfort and productivity is important.



# ThinkVision T2054p Monitor

19.5″

WLED

262.35 x 418.61

0.0969 x 0.2915

VGA, HDMI, DisplayPort

1440 x 900

178° / 178° 250 cd/m<sup>2</sup>

IPS

19.5"

16:10

1000.1

87.3

72% 16.7 M 7 ms Yes

VGA

1.8 m

No

No

14.5 W

21 W

N/A

0.3 W

0.3 W

49.45 Btu/h

71.61 Btu/h

47 - 63 Hz

Internal

## **SPECIFICATIONS**

### DISPLAY

Panel Size
Panel Type
Backlit
Viewable Area (Diagonal)
Screen Dimensions (W x H) (mm)
Resolution
Aspect Ratio
Viewing Angle (H/V at CR 10:1)
Maximum Brightness (Typical)
Contrast Ratio (Typical)
Pixel Pitch (W x H) (mm)
Dot/Pixel Per Inch (DP / PPI)
Color Gamut (CIE 1931)
Number of Colors
Response Time
Anti-Glare

### SIGNAL INPUT

Video Input Signals Video Cables Supplied Video Cable Length USB Hub USB Cable Supplied

### POWER CONSUMPTION

#### Power Consumption Typical Max. without USB Hub Max. with USB Hub Sleep-Mode Off-Mode Heat Dissipation Typical Max. Power Supply Power Voltage Voltage Dynamic Frequency

#### DIMENSIONS (W X D X H)

Size Packed (mm) (inches) Size Unpacked with Stand (mm) (inches) Size Unpacked without Stand (Head Only) (mm)(inches) Distance from Table to Panel Lowest Pixel at Bottom of Screen Highest Pixel at Top of Screen Stand Base Footprint Area (mm / inches) Weight Packed

Unpacked Monitor Head 509 x 176 x 368 20.04" x 6.93" x 14.49"

90 - 264 VAC, 1.5 A

454.2 x 242.6 x 345.9 ~ 455.9 17.88" x 9.55" x 13.62" ~ 17.95'

454.2 x 53 x 297.9 17.88" x 2.09" x 11.73"

(mm / inches) 65.8 / 2.59" 328.2 / 12.92"

Diameter 240 / 9.45"

Starting at 10.8 lbs (4.9 kg) Starting at 8.15 lbs (3.7 kg) Starting at 4.85 lbs (2.2 kg)

### MECHANICAL

Tilt Angle (Front / Back)	-5° ~ 22°
Swivel Angle (Left / Right)	-45° - 45°
Lift (mm)	110
Pivot	No
VESA Mount (mm)	100 x 100
Kensington Lock Slot	Yes
Cable Management	Yes
Ambient Light Sensor	No
Control Buttons	Yes
Bezel Color	Raven Black
Bezel Width (Side) (mm / inches)	17 / 0.67"
Bezel Width (Top / Bottom) (mm / inches)	17 / 0.67"

#### SIGNAL INTERFACE / PERFORMANCE

Horizontal Frequency Vertical Frequency Native Resolution Maximum Pixel Clock Speed / Bandwidth

Default Color Temperature Preset Display Modes User-defined Display Modes **OSD** Buttons **OSD** Languages

## COMPLIANCE

FPFAT **ENERGY STAR Rating** ULE TCO TCO Edge TUV GREENGUARD RoHS (EU 2002/95/EC) Windows Certification

Silver 8.0 Gold 6.0 2.0 Yes No Yes Windows 7, Windows 8, Windows 8.1, Windows 10 Tier 1

30 kHz - 81 kHz 50 Hz - 75 Hz

: 150 MHz

: 150 MHz

DisplayPort: 150 MHz

1440 x 900

VGA

HDMI

7200K

22

16

5

8

China Energy Efficiency Standard

### **ENVIRONMENTAL**

Temperature Operating	0 °C - 45 °C	
Non-operating	-20 °C - 60 °C (non-condensing)	
Humidity		
Operating	10% - 80%	
Non-operating	5% - 95% (non-condensing)	
Altitude		
Operating	8,000 ft	
Non-operating	40,000 ft	
Arsenic-free Glass	Yes	
PVC Free	Yes	
Mercury Free	Yes	
PCC % of Plastic Resins	85%	
Low Halogen	No	

### WARRANTY AND AVAILABILITY

Warranty Geography Availability ThinkVision Logo Global Model

3 Years World Wide Yes Yes





©2020 Lenovo. All rights reserved. Availability: Offers, prices, specifications and availability may change without notice. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC, 27709, Attr. Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkServer, ThinkVantage and ThinkVision are trademarks or registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Atom and Intel Atom Inside are trademarks. of Intel Corporation in the U.S. and/or other countries. Other company, product and service names may be trademarks or service marks of others. Visit Lenovo.com/safecomputing periodically for the latest information on safe and effective computing