

ViewSonic® LED DISPLAY VG2748

Key Features

- vDisplay Manager (gratis download)
- Smalle bezel
- HDMI-, DisplayPort- en VGA-ingangen
- SuperClear® IPS-technologie
- Veelzijdige voet



Product Description



1. VESA Compatible(Wall mount 100mm x 100mm)
2. Menu Control Panel
3. USB down stream x 2
4. AC In
5. DisplayPort
6. HDMI
7. VGA
8. USB up stream
9. USB down stream x 2

Visit Us  www.viewsonic.com

DISPLAY

Monitor Size:	27"W (27" Viewable) LCD monitor
Panel Technology:	SuperClear® IPS TFT LCD
Resolution:	FHD 1920 x 1080
Display Area:	597.9(H) x 336.3(V) mm
Aspect Ratio:	16:9
Brightness:	300 cd/m² (Typ.)
Contrast Ratio:	1000:1 (Typ.)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angles:	178 degrees (Typ.) / 178 degrees (Typ.)
Response Time:	GTG: 5ms (Typ.)
Pixel Size:	0.311 (H) x 0.311 (W) mm

INPUT SIGNAL

Frequency:	Analog: Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz Digital: Fh = 24 ~ 82KHz ; Fv = 24 ~ 75Hz
Sync:	Separate Sync / Composite Sync / Sync on Green / TMDs / PCI-E

COMPATIBILITY

PC:	Windows 7, Windows 8, Windows 8.1, Windows 10 certified
Mac®:	Power Mac tested

CONNECTOR

Input:	VGA x 1, HDMI x 1 (v1.4 compatible), DisplayPort 1.2 x 1
--------	--

AUDIO

Speaker:	2W x 2
----------	--------

USB

Upstream:	USB 3.0 Type B x 1
Downstream:	USB 3.0 Type A x 4

POWER

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	29.15W
Optimize:	23.06W
Conserve:	18.50W

ERGONOMICS

Tilt:	40 ~ -5 degrees
Swivel:	+/-60 degrees
Pivot:	+/-90 degrees

SPECIAL FEATURES

Eye Care:	Blue light filter, Flicker Free
-----------	------------------------------------

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	620.7mm (W) x 537.2mm (H) x 202.2 mm (D)
Physical without stand (mm):	620.7 mm (W) x 366.1mm (H) x 51.1 mm (D)
Packaging (mm):	692 mm (W) x 430 mm (H) x 218 mm (D)

WEIGHT

Net with stand:	7.3kg
Net without stand:	4.9kg
Gross:	10.1 kg

REGULATIONS

cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC, UkrSEPRO, GS, RCM, GEMS

PACKAGE CONTENTS

LCD Display Power Cable (1.8m) DP to DP Cable (1.8m) USB3.0 Upstream Cable (1.8m) Quick Start Guide
