

ViewSonic LCD DISPLAY VP3256-4K

Key Features

- **Lifelike True Beauty:** International color standard Pantone validated and 100% sRGB wide color gamut
- **Precise Color:** ColorPro Verified with pre-factory calibration for overwhelmed Delta E < 2 color accuracy
- **Multimedia Devices:** Support USB-C with 60W high-speed charging, plus HDMI 1.4, DisplayPort 1.2a, USB3.2
- **Unlimited Flexibility:** Auto Pivot & Ergonomic Stand with tilt, swivel, pivot, and height adjustments
- **The Visible Difference:** 4K UHD(3840* 2160) resolution IPS panel with 32" frameless design



Product Description

Designed with creative professionals in mind, the ViewSonic VP3256-4K delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us  www.viewsonic.com

DISPLAY		WALL MOUNT	
Display Size (in.):	32	VESA Compatible:	100 x 100 mm
Viewable Area (in.):	31.5	INPUT SIGNAL	
Panel Type:	IPS Technology	Frequency Horizontal:	15 ~ 136KHz
Resolution:	3840 x 2160	Frequency Vertical:	24 ~ 75Hz
Resolution Type:	UHD	VIDEO INPUT	
Static Contrast Ratio:	1,000:1 (typ)	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
Dynamic Contrast Ratio:	20M:1	ERGONOMICS	
Light Source:	LED	Height Adjust (mm):	130
Brightness:	350 cd/m² (typ)	Swivel:	120°
Colors:	1.07B	Tilt (Forward/Back):	-5° / 21°
Color Space Support:	10 bit (8 bit + A-FRC)	Pivot (Right/Left):	90° / 90°
Aspect Ratio:	16:9	WEIGHT (IMPERIAL)	
Response Time (Typical GTG):	5ms	Net (lbs):	24
Response Time (GTG w/OD):	5ms	Net Without Stand (lbs):	15.8
Viewing Angles:	178° horizontal, 178° vertical	Gross (lbs):	33.7
Backlight Life (Hours):	30000 Hrs (Min)	WEIGHT (METRIC)	
Curvature:	Flat	Net (kg):	10.9
Refresh Rate (Hz):	60	Net Without Stand (kg):	7.2
Adaptive Sync:	Yes	Gross (kg):	15.3
Blue Light Filter:	Yes	DIMENSIONS (IMPERIAL) (WXHxD)	
Flicker-Free:	Yes	Packaging (in.):	33.1 x 20.5 x 12.8
Color Gamut:	Adobe RGB: 95% size / 82% coverage (Typ)DCI-P3: 95% size / 90% coverage (Typ)EBU: 127% size / 100% coverage (Typ)REC709: 128% size / 100% coverage (Typ)SMPTE-C: 139% size / 100% coverage (Typ)NTSC: 91% size (Typ)sRGB: 128% size / 100% coverage (Typ)	Physical (in.):	28.2 x 20.23~25.35 x 10.4
		Physical Without Stand (in.):	28.2 x 16.7 x 2.6
Pixel Size:	0.182 mm (H) x 0.182 mm (V)	DIMENSIONS (METRIC) (WXHxD)	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Packaging (mm):	840 x 520 x 326
COMPATIBILITY		Physical (mm):	715 x 513.8~643.8 x 265
PC Resolution (max):	3840x2160	Physical Without Stand (mm):	715 x 423 x 66
Mac® Resolution (max):	3840x2160	GENERAL	
PC Operating System:	Windows 7/8/8.1/10 certified; macOS tested	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, CCC, China RoHS, China Energy Label
Mac® Resolution (min):	3840x2160	PACKAGE CONTENTS:	VP3256-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
CONNECTOR		Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
USB 3.2 Type A Down Stream:	2	Warranty:	*Warranty offered may differ from market to market
USB 3.2 Type B Up Stream:	1	Power Management:	Energy Star standards, EPEAT
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1		
HDMI 2.0 (with HDCP 2.2):	2		
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	3Watts x2		
POWER			
Eco Mode (Conserve):	32W		
Eco Mode (optimized):	39W		
Consumption (typical):	46W		
Consumption (max):	50W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		