



SPECIFICATIONS

Panel Size	31.5"
Active Display Area (mm)	697.344(H) x 392.256(V)
Curvature	1000R
Panel Type	Rapid VA
Panel Resolution	2560x1440 (WQHD)
Pixel Pitch (H x V)	0.2724(H) x 0.2724(V)
Aspect Ratio	16:9
Brightness (nits)	400
Contrast Ratio	4000 : 1 (Typ.)
DCR	100000000:1
Signal Frequency	91.2~386.2 KHz(H) / 48~240 Hz(V)
ACTIVATED RANGE	48 ~ 240Hz
Refresh Rate	240Hz
Response time	1ms (GTG)
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive sync support
HDR Support	DisplayHDR 400
Video ports	2x HDMI™ 2.0 (Supports WQHD@144Hz) 1x DisplayPort 1.4a (Supports WQHD@240Hz as specified in DisplayPort) 1x USB Type-C (DP alt. w/ PD Charging 15W)
USB ports	2x USB 2.0 Type A 1x USB 2.0 Type B
Audio ports	1x Earphone out
Viewing Angle	178° (H) / 178° (V)
Adobe RGB / DCI-P3 / sRGB	99% / 91% / 115%
Surface Treatment	Anti-glare
Display Colors	1.07B (8 bits + FRC)
Power Type	External Adaptor 20V 6A
Power Input	100~240V, 50/60Hz
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Height)	0 ~ 100mm
Kensington Lock	Yes
Dimension (W x D x H)	701.4 x 270.1 x 579.2 mm 701.4 x 128.4 x 428.0 mm (without stand)
Carton Dimension (W X D X H)	WW carton: 970 x 198 x 513 mm Outer: 985 x 213 x 538 mm
Frameless Design	Yes

FEATURES



Rapid VA

Provide ultra-fast 1ms GTG response time, make sure the intensity and purity of colors when gaming.



1000R

Enjoy the most immersive gameplay with 1000R curvature rate.



240Hz Extremely High Refresh Rate

Experience smooth gaming with a blazing fast 240Hz refresh rate, that gives you the upper hand in fast moving games.



WQHD High Resolution

Game titles will even look better, displaying more details.



Fast Response Time

Eliminate screen tearing and choppy frame rates with 1ms GTG response time.



VEASA DisplayHDR True Black 400

It has passed the VESA DisplayHDR True Black 400 Certification, meaning it can provide a display with the most realistic colors.

PIP / PBP Function	N/A
VESA Mounting	100 x 100 mm
Note	Display Port: 2560x1440 (Up to 170Hz by DP overclocking)
	HDMI™: 2560x1440 (Up to 144Hz)
	*sRGB and DCI-P3 follow CIE1976 standard

CONNECTIONS



1. 5-Way Joystick Navigator
2. 1 x Power Jack
3. 1 x DisplayPort (1.4a)
4. 2 x HDMI™ (2.0)
5. 1 x USB Type C (DisplayPort Alternate)
6. 1 x Earphone out
7. 1 x USB 2.0 Type B
8. 2 x USB 2.0 Type A