

# Optix Series

## *LCD Monitor*

---

Optix MAG321CURV (3DA2)

Optix MAG322CQRV (3DA4)

# Contents

Copyright and Trademarks Notice .....	iii
Revision .....	iii
Technical Support .....	iii
Safety Instructions.....	iv
CE Conformity.....	vi
FCC-B Radio Frequency Interference Statement.....	vi
WEEE Statement.....	vii
Chemical Substances Information .....	vii
RoHS Statement .....	vii
<b>1. Getting Started .....</b>	<b>1 - 1</b>
Package Contents.....	1-2
Installing the Monitor Stand.....	1-3
Adjusting the Monitor .....	1-4
Monitor Overview .....	1-5
Connecting the Monitor to PC .....	1-7
<b>2. OSD Setup .....</b>	<b>2 - 1</b>
Navi Key.....	2-2
OSD Setup via Navi Key .....	2-6
<b>Appendix .....</b>	<b>A - 1</b>
Specifications .....	A-2
Preset Display Modes .....	A-4
Troubleshooting .....	A-6

## Copyright and Trademarks Notice

Copyright © Micro-Star Int'l Co., Ltd. All rights reserved. The MSI logo used is a registered trademark of Micro-Star Int'l Co., Ltd. All other marks and names mentioned may be trademarks of their respective owners. No warranty as to accuracy or completeness is expressed or implied. MSI reserves the right to make changes to this document without prior notice.

## Revision

Revision	Date
V1.0	2019/06

## Technical Support

If a problem arises with your product and no solution can be obtained from the user's manual, please contact your place of purchase or local distributor. Alternatively, please visit <https://www.msi.com/support/> for further guidance.

# Safety Instructions



- Read the safety instructions carefully and thoroughly.
- All cautions and warnings on the device or user's manual should be noted.
- Refer servicing to qualified personnel only.



Keep the User's Guide that comes with the package for future reference.




To prevent fire or shock hazard, keep this device away from humidity and high temperature.



Lay this device on a reliable flat surface before setting it up.



- Make sure that the power voltage is within its safety range and has been adjusted properly to the value of 100~240V before connecting the device to the power outlet. Do not disable the protective earth pin from the plug. The device must be connected to an earthed mains socket-outlet.
- Always disconnect the power cord or switch the wall socket off if the device would be left unused for a certain time to achieve zero energy consumption.



The ventilator on the device is used for air convection and to prevent the device from overheating. Do not cover the ventilator.



Do not leave the device in an unconditioned environment with a storage temperature above 60°C or below -20°C, which may damage the device.

**NOTE:** The maximum operating temperature is around 40°C.



When cleaning the device, be sure to remove the power plug. Use a piece of soft cloth rather than industrial chemical to clean the device. Never pour any liquid into the opening; that could damage the device or cause electric shock.



Place the power cord in a way that people are unlikely to step on it. Do not place anything on the power cord.



Always keep strong magnetic or electrical objects away from the device.



If any of the following situations arises, get the device checked by service personnel:

- The power cord or plug is damaged.
- Liquid has penetrated into the device.
- The device has been exposed to moisture.
- The device does not work well or you can not get it work according to user's manual.
- The device has dropped and damaged.
- The device has obvious sign of breakage.



#### Green Product Features

- Reduced energy consumption during use and stand-by
- Limited use of substances harmful to the environment and health
- Easily dismantled and recycled
- Reduced use of natural resources by encouraging recycling
- Extended product lifetime through easy upgrades
- Reduced solid waste production through take-back policy

#### Environmental Policy

- The product has been designed to enable proper reuse of parts and recycling and should not be thrown away at its end of life.
- Users should contact the local authorized point of collection for recycling and disposing of their end-of-life products.
- Visit the MSI website and locate a nearby distributor for further recycling information.
- Users may also reach us at [gpccontdev@msi.com](mailto:gpccontdev@msi.com) for information regarding proper disposal, take-back, recycling, and disassembly of MSI products.

V

★ Warning! Overuse of screens is likely to affect eyesight.

★ Recommendations:

1. Take a 10-minute break for every 30 minutes of screen time.
2. Children under 2 years of age should have no screen time. For children aged 2 years and over, screen time should be limited to less than one hour per day.

# CE Conformity

This device complies with the requirements set out in the Council Directive on the Approximation of the Laws of the Member States relating to Electromagnetic Compatibility (2014/30/EU), Low-voltage Directive (2014/35/EU), ErP Directive (2009/125/EC) and RoHS directive (2011/65/EU).



This product has been tested and found to comply with the harmonized standards for Information Technology Equipment published under Directives of Official Journal of the European Union.

# FCC-B Radio Frequency Interference Statement



This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the measures listed below:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/television technician for help.

## Notice 1

The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

## Notice 2

Shielded interface cables and AC power cord, if any, must be used in order to comply with the emission limits.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. this device may not cause harmful interference, and
2. this device must accept any interference received, including interference that may cause undesired operation.

## MSI Computer Corp.

901 Canada Court, City of Industry, CA 91748, USA

(626) 913-0828

[www.msi.com](http://www.msi.com)

## WEEE Statement

Under the European Union ("EU") Directive on Waste Electrical and Electronic Equipment, Directive 2012/19/EU, products of "electrical and electronic equipment" cannot be discarded as municipal waste anymore and manufacturers of covered electronic equipment will be obligated to take back such products at the end of their useful life.



## Chemical Substances Information

In compliance with chemical substances regulations, such as the EU REACH Regulation (Regulation EC No. 1907/2006 of the European Parliament and the Council), MSI provides the information of chemical substances in products at:

[https://www.msi.com/html/popup/csr/evmtprt\\_pcm.html](https://www.msi.com/html/popup/csr/evmtprt_pcm.html)

## RoHS Statement

### Japan JIS C 0950 Material Declaration

A Japanese regulatory requirement, defined by specification JIS C 0950, mandates that manufacturers provide material declarations for certain categories of electronic products offered for sale after July 1, 2006.

[https://www.msi.com/html/popup/csr/cemm\\_jp.html](https://www.msi.com/html/popup/csr/cemm_jp.html)

[https://tw.msi.com/html/popup/csr\\_tw/cemm\\_jp.html](https://tw.msi.com/html/popup/csr_tw/cemm_jp.html)

vii

### India RoHS

This product complies with the "India E-waste (Management and Handling) Rule 2011" and prohibits use of lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers in concentrations exceeding 0.1 weight % and 0.01 weight % for cadmium, except for the exemptions set in Schedule 2 of the Rule.

### Turkey EEE Regulation

Conforms to the EEE Regulations of the Republic Of Turkey

### Ukraine Restriction of Hazardous Substances

The equipment complies with requirements of the Technical Regulation, approved by the Resolution of Cabinet of Ministry of Ukraine as of December 3, 2008 № 1057, in terms of restrictions for the use of certain dangerous substances in electrical and electronic equipment.

### Vietnam RoHS

As from December 1, 2012, all products manufactured by MSI comply with Circular 30/2011/TT-BCT temporarily regulating the permitted limits for a number of hazardous substances in electronic and electric products.



# 1

---

## Getting Started

This chapter provides you with the information on hardware setup procedures. While connecting devices, be careful in holding the devices and use a grounded wrist strap to avoid static electricity.

### **IMPORTANT**

- *The illustrations are for reference only. Your monitor may vary in appearance.*
- *Do not use any sharp objects on the monitor.*

## Package Contents

- 1. Monitor
- 2. Stand
- 3. Stand Base with Screw
- 4. Power Adapter & Power Cord
- 5. HDMI Cable
- 6. DisplayPort Cable
- 7. USB Upstream Cable (to enable the USB ports on the monitor)
- 8. Quick Start Guide
- 9. Warranty Card

\* Contact your place of purchase or local distributor if any of the items is damaged or missing.  
\* Package contents may vary by country.


# Installing the Monitor Stand

1. Fit the stand to the monitor.
2. Tighten the stand with the stand screws.
3. Connect the base to the stand and tighten the base screw to secure the base.


## **IMPORTANT**

*Place the monitor on a soft, protected surface to avoid scratching the display panel.*

**1**




**2**



**1-3**

**3**




## Adjusting the Monitor


This monitor is designed to maximize your viewing comfort with its adjustment capabilities.

### **IMPORTANT**

*Avoid touching the display panel when adjusting the monitor.*



# Monitor Overview

**1**

Power Button

**2**

Navi Key

**3**

Power Jack

**4**

HDMI Port   
HIGH-DEFINITION MULTIMEDIA INTERFACE

**5**

DisplayPort

**6**

**USB Type-C Port (For Optix MAG321CURV)**

This port supports DisplayPort Alternate (DP Alt) Mode and up to 5V/3A (15W) power delivery. It only carries video signals and doesn't support data transmission function.


**7**

**USB Type B Upstream Port**

For USB Upstream Cable.

**IMPORTANT**

*Check the package for USB Upstream Cable and connect it to the PC and monitor. Once this cable is connected, the USB Type A Downstream Ports on the monitor will be ready for use.*



1-6

**8**

Headphone Jack

**9**


USB Type A Downstream Port


**10**

Kensington Lock

## Connecting the Monitor to PC

1. Turn off your computer.
2. Connect the HDMI/DisplayPort cable from the monitor to your computer.
3. Assemble the monitor power adapter & power cord. (Figure A)
4. Connect the power adapter to the monitor power jack. (Figure B)
5. Plug the power cord into the electrical outlet. (Figure C)
6. Turn on the monitor. (Figure D)
7. Select your Input Source at OSD menu and power on the computer.





# 2

---

## OSD Setup


This chapter provides you with essential information on OSD Setup.

### **IMPORTANT**

*All information is subject to change without prior notice.*

## Navi Key

The monitor comes with a Navi Key, a multi-directional control that helps navigate the On-Screen Display (OSD) menu.



The Navi Key default settings are as follows.

Navi Key	Hot Key (When OSD menu is OFF)	Basic Operations (When OSD menu is ON)
Middle Button	OSD Main Menu  Optix MAG321CURV  Optix MAG322CQRV 	<ul style="list-style-type: none"> <li>Entering submenus</li> <li>Confirming a selection or setting</li> </ul>
Up	Game Mode 	<ul style="list-style-type: none"> <li>Press Middle Button to confirm selection and exit.</li> <li>Press Up and Down Buttons to adjust.</li> <li>Press Left Button to cancel preview and exit without applying mode effect.</li> <li>Selecting function menus and items</li> <li>Allowing upward adjustment in function values</li> </ul>
Down	Screen Assistance 	<ul style="list-style-type: none"> <li>Press Middle Button to confirm selection and exit.</li> <li>Press Up and Down Buttons to adjust.</li> <li>Press Left Button to cancel preview and exit.</li> <li>Selecting function menus and items</li> <li>Allowing downward adjustment in function values</li> </ul>

Navi Key	Hot Key (When OSD menu is OFF)	Basic Operations (When OSD menu is ON)
Left 	Alarm Clock 	<ul style="list-style-type: none"> <li>■ Press Middle Button to confirm selection and exit.</li> <li>■ Press Up and Down Buttons to select.</li> <li>■ Press Left Button to cancel preview and exit.</li> </ul>
Right 	Input Source Optix MAG321CURV  Optix MAG322CQRV 	<ul style="list-style-type: none"> <li>■ Press Middle Button to confirm selection and exit.</li> <li>■ Press Up and Down Buttons to select.</li> <li>■ Press Left Button to exit.</li> </ul>

Users may enter the OSD Menu to customize their own Navi Key Hot Keys.

More Hot Key options are as below.

Navi Key Hot Key Options	Operations	
Brightness		<ul style="list-style-type: none"><li>■ Press Middle Button to save value and exit.</li><li>■ Press Up and Down Buttons to adjust.</li><li>■ Press Left Button to cancel preview and exit.</li></ul>
PIP/PBP		<ul style="list-style-type: none"><li>■ Press Middle Button to confirm selection and exit.</li><li>■ Press Up and Down Buttons to adjust.</li><li>■ Press Left Button to cancel preview and exit.</li></ul>
Refresh Rate		<ul style="list-style-type: none"><li>■ Press Middle Button to confirm selection and exit.</li><li>■ Press Right Button to turn on and Left Button to turn off the Refresh Rate.</li></ul>

## OSD Setup via Navi Key


Press the Middle button of Navi Key to launch the On-Screen Display (OSD) main menu. Use the Up, Down, Left, Right buttons to tune the desired function menus to suit your personal preferences.

Optix MAG321CURV






2-6

Optix MAG322CQRV



## ► GAMING

1st Level Menu	2nd/3rd Level Menu	Description	
Game Mode	User	Default mode. All items can be adjusted by users.	
	FPS	All items can be adjusted by users.	
	Racing		
	RTS		
	RPG		
<ul style="list-style-type: none"> <li>■ Use Up or Down Button to select and preview mode effects.</li> <li>■ Press the Middle Button to confirm and apply your mode type.</li> </ul>			
Night Vision	OFF	This function optimizes background brightness and is recommended for FPS games.	
	Normal		
	Strong		
	Strongest		
	A.I.		
Response Time	Normal	<ul style="list-style-type: none"> <li>■ Users can adjust Response Time in any Mode.</li> </ul>	
	Fast	<ul style="list-style-type: none"> <li>■ Response Time will be grayed out while Anti Motion Blur is enabled.</li> </ul>	
	Fastest	<ul style="list-style-type: none"> <li>■ Response Time has to be set to Fast after Anti Motion Blur is disabled.</li> </ul>	
Anti Motion Blur (For Optix MAG322CQRV)	<input checked="" type="checkbox"/> (OFF) <input type="checkbox"/> (ON)	<ul style="list-style-type: none"> <li>■ Brightness cannot be adjusted when Anti Motion Blur is set to ON.</li> <li>■ When Anti Motion Blur is enabled, HDR and Brightness cannot be enabled and will be grayed out.</li> <li>■ Response time will be grayed out while Anti Motion Blur is enabled.</li> <li>■ Anti Motion Blur will be grayed out while Adaptive Sync or PIP/PBP is set to ON.</li> <li>■ 1:1 of Screen Size will be grayed out while Anti Motion Blur is set to ON.</li> </ul>	
Zero Latency	<input checked="" type="checkbox"/> (OFF) <input type="checkbox"/> (ON)	<ul style="list-style-type: none"> <li>■ Zero Latency default is ON.</li> <li>■ Zero Latency helps to reduce the signal throughput timing.</li> </ul>	
Refresh Rate	Location	Left Top	<ul style="list-style-type: none"> <li>■ Users can adjust Refresh Rate in any Mode.</li> </ul>
		Right Top	<ul style="list-style-type: none"> <li>■ Default Refresh Rate Location is Left Bottom. Location is adjustable in OSD Menu. Press the Middle Button to confirm and apply your Refresh Rate Location.</li> </ul>
		Left Bottom	<ul style="list-style-type: none"> <li>■ This monitor follows and works at the Operating System's preset Screen Refresh Rate.</li> </ul>
		Right Bottom	
	OFF		
	ON		

1st Level Menu	2nd/3rd Level Menu	Description																											
Alarm Clock	<table border="1"> <tr> <td>Location</td> <td>Left Top</td> <td>■ Users can adjust Alarm Clock in any Mode.</td></tr> <tr> <td></td> <td>Right Top</td> <td>■ After setting the time, press the Middle Button to activate the timer.</td></tr> <tr> <td></td> <td>Left Bottom</td> <td>■ Default Alarm Clock Location is Left Top. Users can select their own location.</td></tr> <tr> <td></td> <td>Right Bottom</td> <td></td></tr> <tr> <td></td> <td>OFF</td> <td></td></tr> <tr> <td></td> <td>15:00</td> <td></td></tr> <tr> <td></td> <td>30:00</td> <td></td></tr> <tr> <td></td> <td>45:00</td> <td></td></tr> <tr> <td></td> <td>60:00</td> <td></td></tr> </table>	Location	Left Top	■ Users can adjust Alarm Clock in any Mode.		Right Top	■ After setting the time, press the Middle Button to activate the timer.		Left Bottom	■ Default Alarm Clock Location is Left Top. Users can select their own location.		Right Bottom			OFF			15:00			30:00			45:00			60:00		<ul style="list-style-type: none"> <li>■ Users can adjust Alarm Clock in any Mode.</li> <li>■ After setting the time, press the Middle Button to activate the timer.</li> <li>■ Default Alarm Clock Location is Left Top. Users can select their own location.</li> </ul>
Location	Left Top	■ Users can adjust Alarm Clock in any Mode.																											
	Right Top	■ After setting the time, press the Middle Button to activate the timer.																											
	Left Bottom	■ Default Alarm Clock Location is Left Top. Users can select their own location.																											
	Right Bottom																												
	OFF																												
	15:00																												
	30:00																												
	45:00																												
	60:00																												
Screen Assistance	<table border="1"> <tr> <td>None</td> <td>■ Users can adjust Screen Assistance in any Mode.</td></tr> <tr> <td>  </td> <td>■ Screen Assistance default is None.</td></tr> </table>	None	■ Users can adjust Screen Assistance in any Mode.		■ Screen Assistance default is None.	<ul style="list-style-type: none"> <li>■ Users can adjust Screen Assistance in any Mode.</li> <li>■ Screen Assistance default is None.</li> </ul>																							
None	■ Users can adjust Screen Assistance in any Mode.																												
	■ Screen Assistance default is None.																												
Adaptive Sync (For Optix MAG322CQRV)	<table border="1"> <tr> <td><input checked="" type="checkbox"/> (OFF)</td> <td>■ Adaptive Sync prevents screen tearing.</td></tr> <tr> <td><input type="checkbox"/> (ON)</td> <td>■ DisplayPort or HDMI default is ON and can be adjusted ON/OFF in any mode, any resolution, any input source and any screen refresh rate.</td></tr> <tr> <td></td> <td>■ Anti Motion Blur, PIP/PBP and 1:1 of Screen Size will be grayed out if Adaptive Sync is enabled.</td></tr> </table>	<input checked="" type="checkbox"/> (OFF)	■ Adaptive Sync prevents screen tearing.	<input type="checkbox"/> (ON)	■ DisplayPort or HDMI default is ON and can be adjusted ON/OFF in any mode, any resolution, any input source and any screen refresh rate.		■ Anti Motion Blur, PIP/PBP and 1:1 of Screen Size will be grayed out if Adaptive Sync is enabled.	<ul style="list-style-type: none"> <li>■ Adaptive Sync prevents screen tearing.</li> <li>■ DisplayPort or HDMI default is ON and can be adjusted ON/OFF in any mode, any resolution, any input source and any screen refresh rate.</li> <li>■ Anti Motion Blur, PIP/PBP and 1:1 of Screen Size will be grayed out if Adaptive Sync is enabled.</li> </ul>																					
<input checked="" type="checkbox"/> (OFF)	■ Adaptive Sync prevents screen tearing.																												
<input type="checkbox"/> (ON)	■ DisplayPort or HDMI default is ON and can be adjusted ON/OFF in any mode, any resolution, any input source and any screen refresh rate.																												
	■ Anti Motion Blur, PIP/PBP and 1:1 of Screen Size will be grayed out if Adaptive Sync is enabled.																												

## ► Professional

1st Level Menu	2nd Level Menu	Description
Pro Mode	User	Default mode. All items can be adjusted by users.
	Reader	All items can be adjusted by users.
	Cinema	
	Designer	
	<ul style="list-style-type: none"> <li>■ Use Up or Down Button to select and preview mode effects.</li> <li>■ Press the Middle Button to confirm and apply your mode type.</li> </ul>	
Eye Saver	<input checked="" type="checkbox"/> (OFF)	<ul style="list-style-type: none"> <li>■ Eye Saver protects your eyes against blue light. When enabled, Eye Saver adjusts the screen color temperature to a more yellow glow.</li> <li>■ Users can adjust Eye Saver in any Mode.</li> <li>■ When Pro Mode is set to Reader, it is mandatory to enable Eye Saver.</li> </ul>
	<input type="checkbox"/> (ON)	
HDCR	<input checked="" type="checkbox"/> (OFF)	<ul style="list-style-type: none"> <li>■ HDCR default is OFF. Users can adjust HDCR in any Mode.</li> <li>■ HDCR enhances image quality by increasing the contrast of images.</li> <li>■ When HDCR is set to ON, Brightness will be grayed out.</li> <li>■ HDCR and Anti Motion Blur cannot be enabled simultaneously.</li> </ul>
	<input type="checkbox"/> (ON)	
Anti Motion Blur (For Optix MAG322CQRV)	<input checked="" type="checkbox"/> (OFF)	<ul style="list-style-type: none"> <li>■ Brightness cannot be adjusted when Anti Motion Blur is set to ON.</li> <li>■ When Anti Motion Blur is enabled, HDCR and Brightness cannot be enabled and will be grayed out.</li> <li>■ Response time will be grayed out while Anti Motion Blur is enabled.</li> <li>■ Anti Motion Blur will be grayed out while Adaptive Sync or PIP/PBP is set to ON.</li> <li>■ 1:1 of Screen Size will be grayed out while Anti Motion Blur is set to ON.</li> </ul>
	<input type="checkbox"/> (ON)	
Image Enhancement	OFF	<ul style="list-style-type: none"> <li>■ Image Enhancement enhances image edges to improve their acutance.</li> <li>■ Users can adjust Image Enhancement in any Mode.</li> </ul>
	Weak	
	Medium	
	Strong	
	Strongest	

## ► Image

1st Level Menu	2nd/3rd Level Menu	Description										
Brightness	0-100	<ul style="list-style-type: none"> <li>■ Users can adjust Brightness in User, RTS, RPG and Reader mode.</li> <li>■ Brightness will be grayed out when Anti Motion Blur, HDR or HDCR is enabled. (HDR for Optix MAG321CURV only)</li> </ul>										
Contrast	0-100	<ul style="list-style-type: none"> <li>■ Contrast default is 50.</li> <li>■ Users can adjust Contrast in any Mode.</li> </ul>										
Sharpness	0-5	<ul style="list-style-type: none"> <li>■ Sharpness default is 0. Users can adjust Sharpness in any Mode.</li> <li>■ Sharpness improves clarity and details of images.</li> </ul>										
Color Temperature	<table border="1" style="width: 100px; margin-left: auto; margin-right: auto;"> <tr><td>Cool</td></tr> <tr><td>Normal</td></tr> <tr><td>Warm</td></tr> <tr><td>Customization</td></tr> <tr><td>R (0-100)</td></tr> <tr><td>G (0-100)</td></tr> <tr><td>B (0-100)</td></tr> </table>	Cool	Normal	Warm	Customization	R (0-100)	G (0-100)	B (0-100)	<ul style="list-style-type: none"> <li>■ Color Temperature default is Normal.</li> <li>■ Use Up or Down Button to select and preview mode effects.</li> <li>■ Press the Middle Button to confirm and apply your mode type.</li> <li>■ Users can adjust Color Temperature in Customization mode.</li> <li>■ Customization mode default is 50/50/50.</li> </ul>			
Cool												
Normal												
Warm												
Customization												
R (0-100)												
G (0-100)												
B (0-100)												
Screen Size	<table border="1" style="width: 100px; margin-left: auto; margin-right: auto;"> <tr><td>Optix MAG321CURV</td></tr> <tr><td>19"</td></tr> <tr><td>24"</td></tr> <tr><td>4:3</td></tr> <tr><td>16:9</td></tr> <tr><td>Optix MAG322CQRV</td></tr> <tr><td>Auto</td></tr> <tr><td>4:3</td></tr> <tr><td>16:9</td></tr> <tr><td>1:1</td></tr> </table>	Optix MAG321CURV	19"	24"	4:3	16:9	Optix MAG322CQRV	Auto	4:3	16:9	1:1	<ul style="list-style-type: none"> <li>■ Screen Size default is 16:9.</li> <li>■ Users can adjust Screen Size in any mode, any resolution and any screen refresh rate.</li> </ul> <ul style="list-style-type: none"> <li>■ Screen Size default is Auto.</li> <li>■ Anti Motion Blur and Zero Latency will be grayed out when Screen Size is set to 1:1.</li> <li>■ If users set Screen Size to 1:1 and then enable PIP, Screen Size will be reset to Auto and 1:1 will be grayed out.</li> <li>■ 1:1 will be grayed out when PIP, Anti Motion Blur or Adaptive Sync is enabled.</li> <li>■ Screen Size will be grayed out when PBP is enabled.</li> </ul>
Optix MAG321CURV												
19"												
24"												
4:3												
16:9												
Optix MAG322CQRV												
Auto												
4:3												
16:9												
1:1												

2-10

## ► Input Source

1st Level Menu	Description
HDMI1	Users can adjust Input Source in any Mode.
HDMI2	
DP	
Type-C (For Optix MAG321CURV)	

## ► PIP/ PBP

1st Level Menu	2nd/3rd Level Menu	Description
OFF		
PIP	Source	<ul style="list-style-type: none"> <li>HDMI1</li> <li>HDMI2</li> <li>DP</li> <li>Type-C (For Optix MAG321CURV)</li> </ul>
	PIP Size	<ul style="list-style-type: none"> <li>Small</li> <li>Medium</li> <li>Large</li> </ul>
	Location	<ul style="list-style-type: none"> <li>Left Top</li> <li>Right Top</li> <li>Left Bottom</li> <li>Right Bottom</li> </ul>
	Display Switch	
	Audio Switch	
PBP	Source	<ul style="list-style-type: none"> <li>HDMI1</li> <li>HDMI2</li> <li>DP</li> <li>Type-C (For Optix MAG321CURV)</li> </ul>
	Display Switch	
	Audio Switch	

2-11

## ► Navi Key

1st Level Menu	2nd Level Menu	Description
Up / Down / Left / Right	OFF	<ul style="list-style-type: none"> <li>Up Button default is Game Mode.</li> <li>Down Button default is Screen Assistance.</li> <li>Left Button default is Alarm Clock.</li> <li>Right Button default is Input Source.</li> <li>All Navi Key items can be adjusted via OSD Menu.</li> </ul>
	Brightness	
	Game Mode	
	Screen Assistance	
	Alarm Clock	
	Input Source	
	PIP/PBP	
	Refresh Rate	

## ► Setting



1st Level Menu	2nd Level Menu	Description
Language	繁體中文 English Français Deutsch Italiano Español 한국어 日本語 Русский Português 简体中文 ไทย Bahasa Indonesia Türkçe (More languages coming soon)	<ul style="list-style-type: none"> <li>■ Language factory default is English.</li> <li>■ Users have to press the Middle Button to confirm and apply the Language setting.</li> <li>■ Language is an independent setting. Users' own language setting will override the factory default. When users set Reset to Yes, Language will not be changed.</li> </ul>
Transparency	0~5	Transparency default is 0. Users can adjust Transparency in any Mode.
OSD Time Out	5-30s	OSD Time Out default is 20s. Users can adjust OSD Time Out in any Mode.
RGB LED	OFF ON	RGB LED default is On. Users can adjust RGB LED to On or Off.
Reset	YES NO	Users can Reset and restore settings to original OSD Default in any Mode.

# A

---

## Appendix

### **IMPORTANT**

*All information is subject to change without prior notice.*

# Specifications

Model	Optix MAG321CURV (3DA2)	Optix MAG322CQRV (3DA4)
Size	31.5 inch	
Curvature	1500R	
Panel Type	VA	
Resolution	3840 x 2160 @ 60Hz	2560 x 1440 @144Hz
Aspect Ratio	16:9	
Brightness (nits)	300	
Brightness : USB Type-C Power Delivery	<ul style="list-style-type: none"> <li>■ 0~79% : 5V/3A</li> <li>■ 80~89% : 5V/2A</li> <li>■ 90~100% : 5V/1A</li> </ul>	
Contrast Ratio	2500:1	3000:1
Refresh Rate	60Hz	144Hz
Response Time	4ms (GTG)	1ms (MPRT)
Input Interface	HDMI x2, DP x1, Type-C x1	HDMI x2, DP x1
I/O	<ul style="list-style-type: none"> <li>■ USB 2.0 Type A x 2</li> <li>■ USB Type-C (DP Alt Mode) x 1 (Up to 5V/3A (15W) power delivery)</li> <li>■ USB 3.0 Type B x 1 (for PC to Monitor)</li> <li>■ Headphone Jack x 1</li> </ul>	<ul style="list-style-type: none"> <li>■ USB 2.0 Type A x 2</li> <li>■ USB 3.0 Type B x 1 (for PC to Monitor)</li> <li>■ Headphone Jack x 1</li> </ul>
View Angles	178°(H), 178°(V)	
sRGB / DCI-P3*	96.6% / 77.0%	99.1% / 78.9%
Surface Treatment	Anti-glare	
Display Colors	16.7M	
Power Type	External Adapter	
Adapter Manufacturer	Asian Power Devices Inc., Model: DA-90J19	
Power Consumption (Typical)	53W	50W
Power Input	AC 100-240V, 50-60Hz	
Power Output	19V ■■■ 4.74A	
Adjustment (Tilt)	-5° ~ 20°	
Adjustment (Height)	0 ~ 130mm	
Kensington Lock	Yes	

A-2

Model	Optix MAG321CURV (3DA2)	Optix MAG322CQRV (3DA4)
<b>VESA Mounting</b>		<ul style="list-style-type: none"> <li>■ Plate Type: 100 x 100mm</li> <li>■ Screw Type: M4 x 12mm           <ul style="list-style-type: none"> <li>▶ Thread Diameter: 4mm</li> <li>▶ Thread Pitch: 0.7mm</li> <li>▶ Thread Length: 12mm</li> </ul> </li> </ul>
<b>Dimension (W x H x D)</b>		710 x 513.6 x 266.5 mm
<b>Net Weight</b>		7.0 kg (15.42 lb)
<b>Environment</b>	<b>Operating</b>	<ul style="list-style-type: none"> <li>■ Temperature: 0°C to 40°C</li> <li>■ Humidity: 20% to 90%, non-condensing</li> <li>■ Altitude: 0 ~ 5000m</li> </ul>
	<b>Storage</b>	<ul style="list-style-type: none"> <li>■ Temperature: -20°C to 60°C</li> <li>■ Humidity: 10% to 90%, non-condensing</li> </ul>

\* Based on CIE1976 test standards.

# Preset Display Modes

Resolution		Optix MAG321CURV (3DA2)		Optix MAG322CQRV (3DA4)
		HDMI	DP / Type-C	HDMI / DP
640x480	@60Hz	V	V	V
	@66Hz	V	V	
	@72Hz	V	V	
	@75Hz	V	V	V
720x400	@70Hz			V
800x600	@56Hz	V	V	
	@60Hz	V	V	V
	@72Hz	V	V	
	@75Hz	V	V	V
832x624	@75Hz	V	V	V
1024x768	@60Hz	V	V	V
	@70Hz	V	V	
	@75Hz	V	V	V
1152x864	@75Hz	V	V	V
1280x720	@60Hz	V	V	V
1280x768	@60Hz	V	V	
1280x800	@60Hz	V	V	V
1280x960	@60Hz	V	V	
1280x1024	@60Hz	V	V	V
	@75Hz	V	V	V
1360x768	@60Hz	V		
1366x768	@60Hz		V	
1440x900	@60Hz	V	V	V
1600x1200	@60Hz	V	V	
1680x1050	@60Hz	V	V	V
1920x1080	@60Hz	V	V	V
	@100Hz			V
	@120Hz			V
	@144Hz			V

A-4

Resolution		Optix MAG321CURV (3DA2)		Optix MAG322CQRV (3DA4)
		HDMI	DP / Type-C	HDMI / DP
2560x1440	@60Hz	V	V	V
	@120Hz			V
	@144Hz			V
3840x2160	@30Hz	V	V	
	@60Hz	V	V	

A-5

# Troubleshooting

## The power LED is off.

- Press the monitor power button again.
- Check if the monitor power cable is properly connected.

## No image.

- Check if the computer graphics card is properly installed.
- Check if the computer and monitor are connected to electrical outlets and are turned on.
- Check if the monitor signal cable is properly connected.
- The computer may be in Standby mode. Press any key to activate the monitor.

## The screen image is not properly sized or centered.

Refer to Preset Display Modes to set the computer to a setting suitable for the monitor to display.

## No Plug & Play.

- Check if the monitor power cable is properly connected.
- Check if the monitor signal cable is properly connected.
- Check if the computer and graphics card are Plug & Play compatible.

A-6

## The icons, font or screen are fuzzy, blurry or have color problems.

- Avoid using any video extension cables.
- Adjust brightness and contrast.
- Adjust RGB color or tune color temperature.
- Check if the monitor signal cable is properly connected.
- Check for bent pins on the signal cable connector.

## The monitor starts flickering or shows waves.

- Change the refresh rate to match the capabilities of your monitor.
- Update your graphics card drivers.
- Keep the monitor away from electrical devices that may cause electromagnetic interference (EMI).