

### Philips Monitor USB-C monitor

### **3000 series** 27" (68.6 cm) 1920 x 1080 (Full HD)

### 27E1N3300A

# Simplify your connections with USB-C

This Philips USB-C multipurpose monitor offers clutter-free setup. With a single cable you can view smooth high-resolution video, transfer data, and charge your laptop. A true hub for mobile professionals.

### Single cable USB-C connection

• Connect your notebook with one USB-C cable

### **Superb Picture Quality**

- IPS LED wide view technology for image and color accuracy
- Effortlessly smooth gameplay with AMD FreeSync<sup>™</sup> technology
- 1ms (MPRT) fast response for crisp image and smooth gameplay
- · SmartImage game mode optimized for gamers
- SmartContrast for rich black details

### Features designed for you

- LowBlue mode and Flicker-free easy-on-the eyes viewing
- · EasyRead mode for a paper-like reading experience
- · Built-in stereo speakers for multimedia
- · Cable management reduces cable clutter for neat workspace
- · EasySelect menu toggle key for quick on-screen menu access

## PHILIPS

### 27E1N3300A/61

### Highlights

### **USB-C** connection



This Philips display features a USB type-C connector with power delivery. With intelligent and flexible power management, you can power charge your compatible device directly. Its slim, reversible USB-C allows for easy, one-cable connection. You can watch high resolution video and transfer data at a super-speed, while powering up and recharging your compatible device at the same time.

### Ultra-smooth gaming



NR PASSOR

Gaming shouldn't be a choice between choppy gameplay or broken frames. With the new Philips monitor it doesn't have to be. Get fluid, artifact-free performance at virtually any framerate with AMD FreeSync<sup>™</sup> technology, smooth quick refresh and ultra-fast response time.

### **1ms MPRT fast response**



MPRT (motion picture response time) is more intuitive way to describe the response time,

which directly refers the duration from seeing blurry noise to clean and crisp images. Philips gaming monitor with 1 ms MPRT effectively eliminates smearing and motion blur, delivers shaper and precise visuals to enhance gaming experience. Best choice for playing thrilling and twitch-sensitive games.

### SmartImage Game mode



The new Philips gaming display has quick access OSD fine tuned for gamers, offering you multiple options. "FPS" mode (First person shooting) improves dark themes in games, allowing you to see hidden objects in dark areas. "Racing" mode adapts display with fastest response time, high color, along with image adjustments. "RTS" mode (Real time strategy) has a special SmartFrame mode which enables highlighting of specific area and allows for size and image adjustments. Gamer 1 and Gamer 2 enable you to save personal customized settings based on different games, ensuring best performance.

### LowBlue Mode & Flicker-free



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

### **Built-in stereo speakers**



A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

### **Cable management**



Cable management is an intimate design that maintains tidy workspace by organizing cables and wires required for the operation of a display device.

### EasyRead mode



EasyRead mode for a paper-like reading experience















Lassificad



### Specifications

### **Picture/Display**

- LCD panel type: IPS technology
- Backlight type: W-LED system
- Panel Size: 27 inch / 68.6 cm
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
  Effective viewing area: 597.888 (H) x 336.312 (V)
- Aspect ratio: 16:9
- Maximum resolution: 1920 x 1080 @ 75 Hz\*
- Pixel Density: 81.59 PPI
- Response time (typical): 4 ms (Gray to Gray)\*
- MPRT: 1 ms
- Brightness: 300 cd/m<sup>2</sup>
- Contrast ratio (typical): 1000:1
- SmartContrast: Mega Infinity DCR
- Pixel pitch: 0.3114 x 0.3114 mm
  Viewing angle: 178° (H) / 178° (V), @ C/R > 10 Flicker-free
- · Picture enhancement: SmartImage game • Color gamut (typical): NTSC 106.2%\*, sRGB
- 122.8%
- Display colors: 16.7 M
- Scanning Frequency: 30 85 kHz (H) / 48 75 Hz (V)
- LowBlue Mode
- EasyRead
- sRGB
- AMD FreeSync<sup>™</sup> technology

### Connectivity

- Signal Input: HDMI 1.4 x 1, USB-C 3.2 Gen 1 x 1 (upstream, Power Delivery up to 65W)
- USB:: USB 3.2 x 4 (downstream with 1 fast charge B.C 1.2)
- Sync Input: Separate Sync
- Audio (In/Out): Audio out

### USB

- USB-C: Reversible plug connector
- Super speed: Data and Video transfer
- DP: Built-in Display Port Alt mode
- Power delivery: USB PD version 3.0
- USB-C max. power delivery: Up to 65W (5V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A)

### Convenience

- Built-in Speakers: 3 W x 2
- User convenience: Power On/Off, Menu, Volume, Input, SmartImage Game
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish,

### Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian

- · Other convenience: Kensington lock, VESA mount (100x100mm)
- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

### Stand

• Tilt: -5/20 degree

### Power

- On mode: 25.1 W (typ.)
- Standby mode: 0.5 W (typ.)
- Off mode: 0.3 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: Internal, 100-240VAC, 50-60Hz

### **Dimensions**

- Product with stand(max height): 612 x 456 x 197 mm
- Product without stand (mm): 612 x 365 x 55 mm
- Packaging in mm (WxHxD): 780 x 525 x 186 mm
- Product with stand (kg): 6.06 kg
- Product without stand (kg): 4.20 kg
- Product with packaging (kg): 10.14 kg

- Temperature range (storage): -20 to 60 °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF: 50,000 hrs (excluding backlight) hour(s)

### Sustainability

- Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- · Specific Substances: Mercury free, PVC / BFR free housing

### **Compliance and standards**

• Regulatory Approvals: CB, CE Mark, CU-EAC, EAEU RoHS, FCC Class B, ICES-003, TUV/ ISO9241-307, TUV-BAUART, KC, KCC

### Cabinet

- Color: Black
- Finish: Textured

\* "IPS" word mark / trademark and related patents on technologies belong to their respective owners.

- \* The maximum resolution works for HDMI input only.
- \* For best output performance, please always ensure that your graphic card is capable of achieving the maximum resolution and refresh rate of this Philips display.
- Response time value equal to SmartResponse

E1N3300A/61

- \* MPRT is to adjust brightness for blur reduction, so cannot adjust brightness while MPRT is turned on. To reduce motion blur, LED backlight will strobe synchronously with screen refresh, which may
- \* MPRT is gaming-optimized mode. Turn on MPRT may cause noticeable screen flickering. It is recommended to turn off when you are not using the gaming function. \* NTSC Area based on CIE1976 \* sRGB Area based on CIE1931

- \* 2020 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, AMD FreeSync<sup>™</sup> and combinations thereof are trademarks of Advanced Micro Devices, Inc. Other product names used in this publication are for identification purposes only and may be trademarks of their respective companies. \* For USB-C power and charging function, your Notebook/device
- must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details
- \* For Video transmission via USB-C, your Notebook/device must support USB-C DP Alt mod
- \* The monitor may look different from feature images.

12 NC: 8670 001 81945 EAN: 87 12581 78565 9

DHIID

Issue date 2022-06-22 Version: 3.1.1

© 2022 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

Weight

### **Operating conditions**

• Temperature range (operation): 0 to 40 °C