

**PHILIPS**

Momentum

559M1

Sound by  
Bowers & Wilkins



[www.philips.com/welcome](http://www.philips.com/welcome)

|    |                            |    |
|----|----------------------------|----|
| EN | User manual                | 1  |
|    | Customer care and warranty | 31 |
|    | Troubleshooting & FAQs     | 35 |

# Table of Contents

|                                                            |    |
|------------------------------------------------------------|----|
| 1. Important .....                                         | 1  |
| 1.1 Safety precautions and maintenance .....               | 1  |
| 1.2 Notational Descriptions .....                          | 3  |
| 1.3 Disposal of product and packing material .....         | 4  |
| 2. Setting up the display .....                            | 5  |
| 2.1 Installation .....                                     | 5  |
| 2.2 Operating the display .....                            | 8  |
| 2.3 Remove the Base Assembly for VESA Mounting .....       | 13 |
| 2.4 MultiView .....                                        | 15 |
| 3. Ambiglow .....                                          | 17 |
| 4. Image Optimization .....                                | 18 |
| 4.1 SmartImage .....                                       | 18 |
| 4.2 SmartContrast .....                                    | 20 |
| 4.3 HDR Settings in Windows 10 system .....                | 21 |
| 4.4 Adaptive Sync .....                                    | 22 |
| 5. Sound by Bowers & Wilkins .....                         | 23 |
| 6. Power Delivery and Smart Power .....                    | 24 |
| 7. Technical Specifications .....                          | 25 |
| 7.1 Resolution & Preset Modes ...                          | 28 |
| 8. Power Management .....                                  | 30 |
| 9. Customer care and warranty ..                           | 31 |
| 9.1 Philips' Flat Panel Displays Pixel Defect Policy ..... | 31 |
| 9.2 Customer Care & Warranty .....                         | 34 |
| 10. Troubleshooting & FAQs .....                           | 35 |
| 10.1 Troubleshooting .....                                 | 35 |
| 10.2 General FAQs .....                                    | 37 |
| 10.3 Multiview FAQs .....                                  | 39 |

# 1. Important

This electronic user's guide is intended for anyone who uses the Philips display. Take time to read this user manual before you use your display. It contains important information and notes regarding operating your display.

The Philips guarantee applies provided the product is handled properly for its intended use, in accordance with its operating instructions and upon presentation of the original invoice or cash receipt, indicating the date of purchase, dealer's name and model and production number of the product.

## 1.1 Safety precautions and maintenance

### Warnings

Use of controls, adjustments or procedures other than those specified in this documentation may result in exposure to shock, electrical hazards and/or mechanical hazards.

Read and follow these instructions when connecting and using your computer monitor.

Excessive sound pressure from earphones and headphones can cause hearing loss. Adjustment of the equalizer to maximum increases the earphones and headphones output voltage and therefore the sound pressure level.

### Operation

- Please Keep the monitor out of direct sunlight, very strong bright lights and away from any other heat source. Lengthy exposure to this type of environment may result in discoloration and damage to the monitor.
- Keep the display away from oil. Oil may damage the plastic cover of the display and void the warranty.
- Remove any object that could fall into ventilation holes or prevent proper cooling of the monitor's electronics.
- Do not block the ventilation holes on the cabinet.
- When positioning the monitor, make sure the power plug and outlet are easily accessible.
- If turning off the monitor by detaching the power cable or DC power cord, wait for 6 seconds before attaching the power cable or DC power cord for normal operation.
- Please use approved power cord provided by Philips all the time. If your power cord is missing, please contact with your local service center. (Please refer to Service contact information listed in Important information manual.)
- Operate under the specified power supply. Be sure to operate the monitor only with the specified power supply. Use of an incorrect voltage will cause malfunction and may cause fire or electric shock.
- Protect the cable. Do not pull or bend the power cable and signal cable. Do not place the monitor or any other heavy objects on the cables, if damaged, the cables may cause fire or electric shock.
- Do not subject the monitor to severe vibration or high impact conditions during operation.
- To avoid potential damage, for example the panel peeling from the bezel, ensure that the monitor does not tilt downward by more than -5 degrees. If the -5 degree downward

## 1. Important

tilt angle maximum is exceeded, the monitor damage will not be covered under warranty.

- Do not knock or drop the monitor during operation or transportation.
- The USB Type-C port could only be connected to specify equipment with fire enclosure in compliance with IEC 62368-1 or IEC 60950-1.
- If provided with a 3-pin attachment plug on the power cord, plug the cord into a grounded (earthed) 3-pin outlet. Do not disable the power cord grounding pin, for example, by attaching a 2-pin adapter. The grounding pin is an important safety feature.
- Excessive usage of monitor can cause eye discomfort, it's better to take shorter breaks more often at your workstation than longer breaks and less often; for example a 5-10 minute break after 50-60-minute continuous screen use is likely to be better than a 15-minute break every two hours. Try to keep your eyes from eye strain while using the screen for a constant period of time by :
  - Looking at something varying distances after a long period focusing on the screen.
  - Conscious Blinking often while you work.
  - Gently closing and rolling your eyes to relax.
  - Reposition your screen to appropriate height and angle according to your height.
  - Adjusting the brightness and contrast to appropriate level.
  - Adjusting the environment lighting similar to that of your screen brightness, avoid the fluorescent

lighting, and surfaces that don't reflect too much light.

- Seeing a doctor if your symptoms.

## Maintenance

- To protect your monitor from possible damage, do not put excessive pressure on the LCD panel. When moving your monitor, grasp the frame to lift; do not lift the monitor by placing your hand or fingers on the LCD panel.
- Oil-based cleaning solutions may damage the plastic parts and void the warranty.
- Unplug the monitor if you are not going to use it for an extensive period of time.
- Unplug the monitor if you need to clean it with a slightly damp cloth. The screen may be wiped with a dry cloth when the power is off. However, never use organic solvent, such as, alcohol, or ammonia-based liquids to clean your monitor.
- To avoid the risk of shock or permanent damage to the set, do not expose the monitor to dust, rain, water, or excessive moisture environment.
- If your monitor gets wet, wipe it with dry cloth as soon as possible.
- If foreign substance or water gets in your monitor, please turn the power off immediately and disconnect the power cord. Then, remove the foreign substance or water, and send it to the maintenance center.
- Do not store or use the monitor in locations exposed to heat, direct sunlight or extreme cold.
- In order to maintain the best performance of your monitor and use it for a longer lifetime, please use the monitor in a location

## 1. Important

that falls within the following temperature and humidity ranges.

- Temperature: 0–40°C 32–104°F
- Humidity: 20–80% RH

### Important information for Burn-in/ Ghost image

- Always activate a moving screen saver program when you leave your monitor unattended. Always activate a periodic screen refresh application if your monitor will display unchanging static content. Uninterrupted display of still or static images over an extended period may cause “burn-in”, also known as “after-imaging” or “ghost imaging”, on your screen.
- “Burn-in”, “after-imaging”, or “ghost imaging” is a well-known phenomenon in LCD panel technology. In most cases, the “burn-in” or “after-imaging” or “ghost imaging” will disappear gradually over a period of time after the power has been switched off.

### Warning

Failure to activate a screen saver, or a periodic screen refresh application may result in severe “burn-in” or “after-imaging” or “ghost image” symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

### Service

- The casing cover should be opened only by qualified service personnel.
- If there is any need for any document for repair or integration, please contact with your local service center. (Please refer to Service contact information listed in Important information manual.)

- For transportation information, please refer to “Technical Specifications”.
- Do not leave your monitor in a car/trunk under direct sun light.

### Note

Consult a service technician if the monitor does not operate normally, or you are not sure what procedure to take when the operating instructions given in this manual have been followed.

---

## 1.2 Notational Descriptions

The following subsections describe notational conventions used in this document.

### Notes, Cautions and Warnings

Throughout this guide, blocks of text may be accompanied by an icon and printed in bold or italic type. These blocks contain notes, cautions or warnings. They are used as follows:

### Note

This icon indicates important information and tips that help you make better use of your computer system.

### Caution

This icon indicates information that tells you how to avoid either potential damage to hardware or loss of data.

### Warning

This icon indicates the potential for bodily harm and tells you how to avoid the problem.

Some warnings may appear in alternate formats and may not be accompanied by an icon. In such cases, the specific presentation of the warning is mandated by the relevant regulatory authority.

## 1.3 Disposal of product and packing material

Waste Electrical and Electronic Equipment-WEEE



This marking on the product or on its packaging illustrates that, under European Directive 2012/19/EU governing used electrical and electronic appliances, this product may not be disposed of with normal household waste. You are responsible for disposal of this equipment through a designated waste electrical and electronic equipment collection. To determine the locations for dropping off such waste electrical and electronic, contact your local government office, the waste disposal organization that serves your household or the store at which you purchased the product.

Your new display contains materials that can be recycled and reused. Specialized companies can recycle your product to increase the amount of reusable materials and to minimize the amount to be disposed of.

All redundant packing material has been omitted. We have done our utmost to make the packaging easily separable into mono materials.

Please find out about the local regulations on how to dispose of your old display and packing from your sales representative.

### Taking back/Recycling Information for Customers

Philips establishes technically and economically viable objectives to optimize the environmental performance of the organization's product, service and activities.

From the planning, design and production stages, Philips emphasizes the importance of making products that can easily be recycled. At Philips, end-of-life management primarily entails participation in national take-back initiatives and recycling programs whenever possible, preferably in cooperation with competitors, which recycle all materials (products and related packaging material) in accordance with all Environmental Laws and taking back program with the contractor company.

Your display is manufactured with high quality materials and components which can be recycled and reused.

To learn more about our recycling program please visit :


<http://www.philips.com/a-w/about/sustainability.html>

## 2. Setting up the display


### 2.1 Installation

#### 1 Unpacking


1. Open the the top flap and remove clips on the bottom of the package.



2. Remove the upper package.




3. Lift up the display from the packaging cushion, a shown in the image below.



#### ⚠ Warning

- This display is heavy, so two people are required to lift up the display.
- Do not press on the panel to avoid any accidental damage.

#### 2 Package contents




\*Different according to region

\*Battery: Zinc carbon AAA R03 1.5V


#### 3 Prevent Tipping

When using the display, fasten the LCD to a wall using a cord or chain that can support the weight of the monitor in order to prevent the monitor from falling.




## 2. Setting up the display

### 4 Connecting to your PC



USB hub



1. AC power input
2. USB C
3. DisplayPort input
4. HDMI-1 input
5. HDMI-2 input
6. HDMI-3 input
7. AUDIO OUT
8. USB UP
9. USB downstream/USB fast charger
10. USB downstream
11. USB downstream/USB fast charger
12. USB downstream
13. Kensington anti-theft lock

### Connect to PC

1. Connect the power cord to the back of the display firmly.
2. Turn off your computer and unplug its power cable.
3. Connect the display signal cable to the video connector on the back of your computer.
4. Plug the power cord of your computer and your display into a nearby outlet.
5. Turn on your computer and display. If the display displays an image, installation is complete.

### 5 USB hub

To comply with International energy standards, the USB hub/ports of this display are disabled during Standby and Off modes.

Connected USB devices will not work in this state.

To permanently put the USB function in “ON” state, please go to OSD Menu, then select “USB standby mode”, and switch it to “ON” state.

### 6 USB charging

This display has USB ports capable of standard power output including some with USB Charging function (identifiable with power icon ). You can use these ports to charge your Smart phone or power your external HDD, for example. The display must be powered ON at all times to be able to use this function.

Some select Philips displays may not Power or Charge your device when it enters to “Sleep/Standby” mode (Red power LED breathing). In that case, please enter to OSD Menu and select “USB Standby Mode”, then, turn the function to “ON” mode (default=OFF).

## 2. Setting up the display

This will then keep the USB power and charging functions active even when the monitor is in sleep/standby mode.

|             |                         |     |   |
|-------------|-------------------------|-----|---|
| SmartSize   | Resolution Notification | On  | ✓ |
|             | USB Standby Mode        | Off |   |
| Audio       | Smart Power             |     |   |
|             | CEC                     |     |   |
| Color       | Reset                   |     |   |
|             | Information             |     |   |
| Language    |                         |     |   |
|             |                         |     |   |
| OSD Setting |                         |     |   |
|             |                         |     |   |
| Setup       |                         |     |   |

### Note

If you Turn OFF your monitor via the power switch at any given time, all the USB ports will power OFF.

### Warning


USB 2.4Ghz wireless devices, such as, wireless mouse, keyboard, and headphones, maybe have interference by USB3.2 or higher version, the high-speed signal devices, which may result in a decreased efficiency of the radio transmission. Should this happen, please try the following methods to help reduce the effects of interference.

- Try to keep USB2.0 receivers away from USB3.2 or higher version of connection port.
- Use a standard USB extension cable or USB hub to increase the space between your wireless receiver and the USB3.2 or higher version of connection port.

## 7 The remote control is powered by two 1.5V AAA batteries.

To install or replace batteries:

1. Press and then slide the cover to open it.
2. Align the batteries according to the (+) and (−) indications inside the battery compartment.
3. Replace the cover.




### Note

The incorrect use of batteries can result in leaks or bursting. Be sure to follow these instructions:

- Place “AAA” batteries matching the (+) and (−) signs on each battery to the (+) and (−) signs of the battery compartment.
- Do not mix battery types.
- Do not combine new batteries with used ones. It causes shorter life or leakage of batteries.
- Remove the dead batteries immediately to prevent them from liquid leaking in the battery compartment. Don't touch exposed battery acid, as it can damage your skin.
- If you do not intend to use the remote control for a long period, remove the batteries.

2.2 Operating the display


1 Description of the control buttons



|   |  |                                                                                                                                                                                                                                                                                                                                                                     |
|---|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 |  | Press to switch power on.<br>Press more than 3 seconds to switch power off.                                                                                                                                                                                                                                                                                         |
| 2 |  | Access the OSD menu.<br>Confirm the OSD adjustment.                                                                                                                                                                                                                                                                                                                 |
| 3 |  | Change the Sound Mode.<br>Adjust the OSD menu.                                                                                                                                                                                                                                                                                                                      |
| 4 |  | Change the signal input source.<br>Adjust the OSD menu.                                                                                                                                                                                                                                                                                                             |
| 5 |  | SmartImage Game menu.<br>There are multiple selections: Xbox, FPS, Racing, RTS, Gamer 1, Gamer 2, Movie, Economy, LowBlue Mode, SmartUniformity, Off.<br>When the monitor receives HDR signal, SmartImage will show HDR menu. There are multiple selections: Xbox, HDR Game, HDR Movie, HDR Photo, DisplayHDR 1000, Personal, Off.<br>Return to previous OSD level. |

2. Setting up the display

2 Description of the remote control buttons



|   |  |                                   |
|---|--|-----------------------------------|
| 1 |  | Press to switch power on and off. |
| 2 |  | Mute                              |
| 3 |  | Access the OSD menu.              |

|    |     |                                                                                                                                                                                                                                                                                                                              |
|----|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4  |     | Change the signal input source.                                                                                                                                                                                                                                                                                              |
| 5  |     | Adjust the OSD menu/ Turn up the values.                                                                                                                                                                                                                                                                                     |
| 6  |     | Adjust the OSD menu / Return to previous OSD level.                                                                                                                                                                                                                                                                          |
| 7  | OK  | Confirm the OSD adjustment.                                                                                                                                                                                                                                                                                                  |
| 8  |     | Access the OSD menu. Confirm the OSD adjustment.                                                                                                                                                                                                                                                                             |
| 9  |     | Adjust the OSD menu / Turn down the values.                                                                                                                                                                                                                                                                                  |
| 10 |     | Access Sound Mode menu.                                                                                                                                                                                                                                                                                                      |
| 11 |     | SmartImage Game menu. There are multiple selections: Xbox, FPS, Racing, RTS, Gamer 1, Gamer 2, Movie, Economy, LowBlue Mode, SmartUniformity, Off. When the monitor receives HDR signal, SmartImage will show HDR menu. There are multiple selections: Xbox, HDR Game, HDR Movie, HDR Photo, DisplayHDR 1000, Personal, Off. |
| 12 |     | Return to previous OSD level                                                                                                                                                                                                                                                                                                 |
| 13 |     | Adjust brightness value                                                                                                                                                                                                                                                                                                      |
| 14 | VOL | Adjust volume.                                                                                                                                                                                                                                                                                                               |

## 2. Setting up the display

### 3 EasyLink (CEC)

What is it?

HDMI is a single cable to carry both picture and audio signals from your devices to your monitor, saving you from cable clutter. It carries uncompressed signals, ensuring that you have the highest quality from source to screen. HDMI-connected monitors with Philips EasyLink (CEC) allow you to control functions of multiple connected devices with one remote control. Enjoy high quality picture and sound without clutter or fuss.

How to enable EasyLink (CEC)

|             |                         |     |   |
|-------------|-------------------------|-----|---|
| SmartSize   | Resolution Notification | On  | ✓ |
|             | USB Standby Mode        | Off |   |
| Audio       | Smart Power             |     |   |
|             | CEC                     |     |   |
| Color       | Reset                   |     |   |
|             | Information             |     |   |
| Language    |                         |     |   |
| OSD Setting |                         |     |   |
| Setup       |                         |     |   |

1. Connect an HDMI-CEC compliant device through HDMI.
2. Configure the HDMI-CEC compliant device properly.
3. Switch on EasyLink(CEC) of this display by toggling to the right to enter OSD.
4. Select [Setup] > [CEC].
5. Select [On], and then confirm the selection.
6. Now, you can turn on or off both your device and this display using the same remote control.

### Note

1. The EasyLink-compliant device must be switched on and selected as the source.
2. Philips does not guarantee 100% interoperability with all HDMI CEC devices.


### 4 Description of the On Screen Display

What is On-Screen Display (OSD)?

On-Screen Display (OSD) is a feature in all Philips LCD displays. It allows an end user to adjust screen performance or select functions of the displays directly through an on-screen instruction window. A user friendly on screen display interface is shown as below:

|                   |                 |                |
|-------------------|-----------------|----------------|
| Ambiglow          | Follow Video    |                |
|                   | Follow Audio    |                |
| Game Setting      | Color Shift     | Clockwise      |
|                   | Color Wave      | Clockwise      |
| LowBlue Mode      | Color Breathing |                |
|                   | Starry Night    |                |
| Input             | Static Mode     |                |
|                   | Your Color      | Blue           |
| HDMI Refresh Rate | Light Position  | Top/Right/Left |
|                   | Speed           | Low            |
| Picture           | Brightness      | Bright         |
|                   | Off             |                |

Basic and simple instruction on the control keys



To access the OSD menu on this Philips display simply use the single toggle button on the backside of the display. The single button operates like a joystick. To move the cursor, simply toggle the button in four directions. Press the button to select desired option.

## 2. Setting up the display

### The OSD Menu

Below is an overall view of the structure of the On-Screen Display. You can use this as a reference when you want to work your way around the different adjustments later on.

| Main menu         | Sub menu                                                                                                                                                                                                         |                                                                                                                                                                     |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambilight         | Follow Video                                                                                                                                                                                                     |                                                                                                                                                                     |
|                   | Follow Audio                                                                                                                                                                                                     |                                                                                                                                                                     |
|                   | Color Shift                                                                                                                                                                                                      | — Clockwise, Anticlockwise                                                                                                                                          |
|                   | Color Wave                                                                                                                                                                                                       | — Clockwise, Anticlockwise                                                                                                                                          |
|                   | Color Breathing                                                                                                                                                                                                  |                                                                                                                                                                     |
|                   | Starry Night                                                                                                                                                                                                     |                                                                                                                                                                     |
|                   | Static Mode                                                                                                                                                                                                      |                                                                                                                                                                     |
|                   | Your Color                                                                                                                                                                                                       | — Rainbow, White, Red, Rose, Magenta, Violet, Blue, Azure, Cyan, Aquamarine, Green, Chartreuse, Yellow, Orange                                                      |
|                   | Light Position                                                                                                                                                                                                   | — Top-Right-Left, Right-Left                                                                                                                                        |
|                   | Speed                                                                                                                                                                                                            | — Low, Normal, High                                                                                                                                                 |
| Game Setting      | Brightness                                                                                                                                                                                                       | — Bright, Brighter, Brightest                                                                                                                                       |
|                   | Off                                                                                                                                                                                                              |                                                                                                                                                                     |
|                   | Adaptive Sync                                                                                                                                                                                                    | — On, Off                                                                                                                                                           |
|                   | Crosshair                                                                                                                                                                                                        | — On, Off                                                                                                                                                           |
|                   | Low Input Lag                                                                                                                                                                                                    | — On, Off                                                                                                                                                           |
|                   | SmartResponse                                                                                                                                                                                                    | — Off, Fast, Faster, Fastest                                                                                                                                        |
|                   | SmartFrame                                                                                                                                                                                                       | — On, Off                                                                                                                                                           |
|                   |                                                                                                                                                                                                                  | — Size (1,2,3,4,5,6,7)                                                                                                                                              |
|                   |                                                                                                                                                                                                                  | — Brightness (0-100)                                                                                                                                                |
|                   |                                                                                                                                                                                                                  | — Contrast (0-100)                                                                                                                                                  |
| LowBlue Mode      | On                                                                                                                                                                                                               |                                                                                                                                                                     |
|                   | Off                                                                                                                                                                                                              | — 1, 2, 3, 4                                                                                                                                                        |
| Input             | 1 HDMI 2.1                                                                                                                                                                                                       |                                                                                                                                                                     |
|                   | 2 HDMI 2.1                                                                                                                                                                                                       |                                                                                                                                                                     |
|                   | 3 HDMI 2.1                                                                                                                                                                                                       |                                                                                                                                                                     |
|                   | DisplayPort                                                                                                                                                                                                      |                                                                                                                                                                     |
|                   | USB C                                                                                                                                                                                                            |                                                                                                                                                                     |
| HDMI Refresh Rate | Auto                                                                                                                                                                                                             |                                                                                                                                                                     |
|                   | HDMI 1                                                                                                                                                                                                           | — 120Hz, 144Hz                                                                                                                                                      |
|                   | HDMI 2                                                                                                                                                                                                           | — 120Hz, 144Hz                                                                                                                                                      |
| Picture           | HDMI 3                                                                                                                                                                                                           | — 120Hz, 144Hz                                                                                                                                                      |
|                   | SmartImage                                                                                                                                                                                                       | — Xbox/ FPS/ Racing/ RTS/ Gamer1/ Gamer2/ Movie/ Economy/ LowBlue Mode/ SmartUniformity/ Off                                                                        |
|                   | SmartImage HDR                                                                                                                                                                                                   | — Xbox/ HDR Game/ HDR Movie/ HDR Photo/ DisplayHDR 1000/ Personal/ Off                                                                                              |
|                   | Brightness                                                                                                                                                                                                       | — 0-100                                                                                                                                                             |
|                   | Contrast                                                                                                                                                                                                         | — 0-100                                                                                                                                                             |
|                   | Sharpness                                                                                                                                                                                                        | — 0-100                                                                                                                                                             |
|                   | Saturation                                                                                                                                                                                                       | — 0-100                                                                                                                                                             |
|                   | SmartContrast                                                                                                                                                                                                    | — On, Off                                                                                                                                                           |
|                   | Gamma                                                                                                                                                                                                            | — 1.8, 2.0, 2.2, 2.4, 2.6                                                                                                                                           |
|                   | Over Scan                                                                                                                                                                                                        | — On, Off                                                                                                                                                           |
| PBP               | PBP Mode                                                                                                                                                                                                         | — Off, PBP                                                                                                                                                          |
|                   | PBP Input                                                                                                                                                                                                        | — 1 HDMI 2.1, 2 HDMI 2.1, 3 HDMI 2.1, DisplayPort, USB C                                                                                                            |
| SmartSize         | Swap                                                                                                                                                                                                             |                                                                                                                                                                     |
|                   | Panel Size                                                                                                                                                                                                       | — 17" (5-4), 19" (5-4), 19" W (16-10), 22" W (16-10), 18.5" W (16-9), 19.5" W (16-9), 20" W (16-9), 21.5" W (16-9), 23" W (16-9), 24" W (16-9), 27" W (16-9), 55" W |
| Audio             | 11 Aspect                                                                                                                                                                                                        |                                                                                                                                                                     |
|                   | Volume                                                                                                                                                                                                           | — 0-60                                                                                                                                                              |
|                   | Mute                                                                                                                                                                                                             | — On, Off                                                                                                                                                           |
|                   | Audio Source                                                                                                                                                                                                     | — HDMI1, HDMI2, HDMI3, DisplayPort, USB C                                                                                                                           |
|                   | Audio Mode                                                                                                                                                                                                       | — Sport & Racing/ RPG and Adventure/ Shooting and Action/ Movie Watching/ Music/ Personal                                                                           |
| Color             | EQ                                                                                                                                                                                                               | — 100Hz, 300Hz, 1KHz, 3KHz, 10KHz                                                                                                                                   |
|                   | Monitor Placement                                                                                                                                                                                                | — Stand, Wall                                                                                                                                                       |
| Language          | Color Temperature                                                                                                                                                                                                | — Native, 5000K, 6500K, 7500K, 8200K, 9300K, 11500K                                                                                                                 |
|                   | sRGB                                                                                                                                                                                                             |                                                                                                                                                                     |
|                   | User Define                                                                                                                                                                                                      | — Red: 0-100<br>— Green: 0-100<br>— Blue: 0-100                                                                                                                     |
| OSD Setting       | English, Deutsch, Español, <b>한국어</b> , Français, Italiano, Magyar, Nederlands, Português, Português do Brasil, Polski, <b>Русский</b> , Svenska, Suomi, Türkçe, Čeština, Українська, 繁體中文, 繁體中文, 繁體中文, 日本語, 한국어 |                                                                                                                                                                     |
|                   | Horizontal                                                                                                                                                                                                       | — 0-100                                                                                                                                                             |
|                   | Vertical                                                                                                                                                                                                         | — 0-100                                                                                                                                                             |
|                   | Transparency                                                                                                                                                                                                     | — Off, 1, 2, 3, 4                                                                                                                                                   |
| Setup             | OSD Time Out                                                                                                                                                                                                     | — 5s, 10s, 20s, 30s, 60s                                                                                                                                            |
|                   | Resolution Notification                                                                                                                                                                                          | — On, Off                                                                                                                                                           |
|                   | USB Standby Mode                                                                                                                                                                                                 | — On, Off                                                                                                                                                           |
|                   | SmartPower                                                                                                                                                                                                       | — On, Off                                                                                                                                                           |
|                   | CEC                                                                                                                                                                                                              | — On, Off                                                                                                                                                           |
|                   | Reset                                                                                                                                                                                                            | — Yes, No                                                                                                                                                           |
| Information       | Information                                                                                                                                                                                                      |                                                                                                                                                                     |

### Note

Xbox: Level up your gaming experience while playing Xbox games, you can even control the connected Xbox console using the remote control.


### 5 Resolution notification

This display is designed for optimal performance at its native resolution, 3840 x 2160. When the display is powered on at a different resolution, an alert is displayed on screen: Use 3840 x 2160 for best results.

Display of the native resolution alert can be switched off from Setup in the OSD (On Screen Display) menu.

### 6 Physical Function


#### Tilt



## 2. Setting up the display

### 7 Ideal setting position for optimal acoustic performance


For optimal acoustic performance when table-mounting the monitor, please ensure the screen is not tilted and the speaker enclosure is facing front, parallel with the table.




### 2.3 Remove the Base Assembly for VESA Mounting

Before you start disassembling the display base, please follow the instructions below to avoid any possible damage or injury.


1. Place the display face down on a smooth surface. Pay attention not to scratch or damage the screen. Use a screwdriver to lift up the hinge cover.




2. Loosen the assembly screws, then detach the stand from the display.



3. Recover the hinge cover.




4. Due to the display rear design, make sure to secure 4 spacer nuts (provided in the box) before installing the wall mount bracket over the hinge cover.




#### Note

This monitor accepts a 200mm x 200mm VESA-Compliant mounting interface. VESA Mounting Screw M6. Always contact manufacturer for wall-mount installation.



## 2. Setting up the display



### Tips on Placement

- Position the display where light does not shine directly on the screen.
- Dim lighting conditions in the room for best Ambiglow effect.
- For optimal acoustic performance when wall-mounting the monitor, please ensure the speaker enclosure is a minimum of 35mm from the wall.


### ⚠ Caution

Wall mounting the display requires special skills and should only be performed by qualified personnel.

The display wall mounting should meet safety standards according to the display's weight.

Also read the safety precautions before positioning the display.

Philips bears no responsibility for improper mounting or any mounting that results in accident or injury.




\* Display design may differ from those illustrated.

### ⚠ Warning

- To avoid potential screen damage, such as panel peeling, ensure that the monitor does not tilt downward by more than -5 degrees.
- Do not press the screen while adjusting the angle of the monitor. Grasp only the bezel.

2.4 MultiView



1 What is it?

Multiview enables active variety connect and view so that you can work with multiple devices like PC and Notebook side-by-side simultaneously, making complex multi-tasking work a breeze.

2 Why do I need it?

With the ultra high resolution Philips MultiView display, you can experience a world of connectivity in a comfortable way in the office or at home. With this display, you can conveniently enjoy multiple content sources at one screen. For example: You may want to keep an eye on the live news video feed with audio in the small window, while working on your latest blog, or you may want to edit an Excel file from your Ultrabook, while logged into secured company intranet to access files from a desktop.

3 How to enable MultiView by OSD menu?

|  |                   |           |     |
|--|-------------------|-----------|-----|
|  | Ambilight         | PBP Mode  | Off |
|  | Game Setting      | PBP Input | PBP |
|  | LowBlue Mode      | Swap      |     |
|  | Input             |           |     |
|  | HDMI Refresh Rate |           |     |
|  | Picture           |           |     |
|  | PBP               |           |     |

1. Toggle to the right to enter OSD Menu Screen.
2. Toggle to the up or down to select main menu [PBP], then toggle to the right to confirm.
3. Toggle to the up or down to select [PBP Mode], then toggle to the right.
4. Toggle to the up or down to select [PBP], then toggle to the right to confirm your selection.
5. Now you can move backward to set the [PBP Mode], [PBP Input], or [Swap].
6. Toggle to the right to confirm your selection.

2. Setting up the display

4 MultiView in OSD menu

[PBP]: Picture by Picture

Open up a sub-window side-by-side of another signal source.



When the sub source is not detected:



Note

The black strip shows on the top and the bottom of the screen for the correct aspect ratio when in the PBP mode. If you expect to see full screen side by side, adjust your devices resolution as pop up attention resolution, and make sure graphic card's resolution is set to '1920 x 2160 at 60Hz'.

[PBP Input]: There are 5 different video inputs to choose as the sub display source: [1 HDMI 2.1], [2 HDMI 2.1], [3 HDMI 2.1], [DisplayPort], [USB C].

| MultiView        | Inputs      | SUB SOURCE POSSIBILITY (x1) |        |        |             |       |
|------------------|-------------|-----------------------------|--------|--------|-------------|-------|
|                  |             | HDMI 1                      | HDMI 2 | HDMI 3 | DisplayPort | USB C |
| MAIN SOURCE (x1) | HDMI 1      | •                           | •      | •      | •           | •     |
|                  | HDMI 2      | •                           | •      | •      | •           | •     |
|                  | HDMI 3      | •                           | •      | •      | •           | •     |
|                  | DisplayPort | •                           | •      | •      | •           | •     |
|                  | USB C       | •                           | •      | •      | •           | •     |

[Swap]: The main picture source and the sub picture source swapped on the display.

Swap A and B source in [PBP] mode:




- Off: Stop MultiView function.

Note

When you do the SWAP function, the video and its audio source will swap at the same time.

# 3. Ambiglow



## 1 What is it?

Ambiglow adds a new dimension to your viewing experience. The innovative Ambiglow processor continuously adjusts the overall color and brightness of the light to match the on screen image. Whether you are playing games, or watching movies, Philips Ambiglow offers you a unique and immersive viewing experience.

## 2 How does it work?

It is recommended that you dim the lighting conditions in your room for maximum effect. Ensure that Ambiglow is set to “on” mode. Start a movie, or play a game from your computer. The monitor will react with appropriate colors creating a halo effect, overall matching the image on the screen. You can also manually select Bright, Brighter, Brightest mode or ambiglow function off mode depending on your preference which helps reduce eye fatigue under prolonged usage.

## 3 How to enable Ambiglow

Ambiglow function can be selected through OSD menu by pressing right button to choose and pressing right button again to confirm the selection:

1. Press right button.
2. To switch Ambiglow off, or select [Follow Video], [Follow Audio], [Color Shift], [Color Wave], [Color Breathing], [Starry Night], [Static Mode], [Your Color], [Light Position], [Speed], [Brightness], [Off].

|                                                                                     |                   |                 |                |
|-------------------------------------------------------------------------------------|-------------------|-----------------|----------------|
|    | Ambiglow          | Follow Video    |                |
|                                                                                     |                   | Follow Audio    |                |
|   | Game Setting      | Color Shift     | Clockwise      |
|                                                                                     |                   | Color Wave      | Clockwise      |
|  | LowBlue Mode      | Color Breathing |                |
|                                                                                     |                   | Starry Night    |                |
|  | Input             | Static Mode     |                |
|                                                                                     |                   | Your Color      | Blue           |
|  | HDMI Refresh Rate | Light Position  | Top/Left/Right |
|                                                                                     |                   | Speed           | Low            |
|  | Picture           | Brightness      | Bright         |
|                                                                                     |                   | Off             |                |
| ▼                                                                                   |                   |                 |                |

## 4. Image Optimization

### 4.1 SmartImage

#### 1 What is it?

SmartImage provides presets that optimize display for different types of content, dynamically adjusting brightness, contrast, color and sharpness in real time. Whether you're working with text applications, displaying images or watching a video, Philips SmartImage delivers great optimized display performance.


#### 2 Why do I need it?

You want a display that delivers optimized display all your favorite types of content, SmartImage software dynamically adjust brightness, contrast, color and sharpness in real time to enhance your display viewing experience.

#### 3 How does it work?

SmartImage is an exclusive, leading edge Philips technology that analyzes the content displayed on your screen. Based on a scenario you select, SmartImage dynamically enhances the contrast, color saturation and sharpness of images to enhance the contents being displayed - all in real time with the press of a single button.


#### 4 How to enable SmartImage?



1. Toggle to the left to launch the SmartImage on screen display.

2. Toggle to the up or down to select between the SmartImage modes.
3. The SmartImage on screen display will remain on screen for 5 seconds or you can also toggle to the right to make confirmation.

There are multiple selections: Xbox, FPS, Racing, RTS, Gamer 1, Gamer 2, Movie, Economy, LowBlue Mode, SmartUniformity, Off.




- **Xbox:** Level up your gaming experience while playing Xbox games, you can even control the connected Xbox console using the remote control.
- **FPS:** For playing FPS (First Person Shooters) games. Improves dark theme black level details.
- **Racing:** For playing Racing games. Provides fastest response time and high color saturation.
- **RTS:** For playing RTS (Real Time Strategy) games, a user-selected portion can be highlighted for RTS games (through SmartFrame). The picture quality can be adjusted for the highlighted portion.
- **Gamer 1:** User's preference settings saved as Gamer 1.
- **Gamer 2:** User's preference settings saved as Gamer 2.

## 4. Image Optimization

- **Movie:** Ramped up luminance, deepened color saturation, dynamic contrast and razor sharpness displays every details in darker areas of your videos without color washout in brighter areas maintaining a dynamic natural values for the ultimate video display.
- **Economy:** Under this profile, brightness, contrast are adjusted and backlighting finetuned for just right display of everyday office applications and lower power consumption.
- **LowBlue Mode:** LowBlue Mode for easy on-the-eyes productivity. Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.
- **SmartUniformity:** Fluctuations in brightness on different parts of a screen are a common phenomenon among LCD displays. Typical uniformity is measured around 75-80%. By enabling Philips SmartUniformity feature, display uniformity is increased to above 95%. This produces more consistent and true images.
- **Off:** No optimization by SmartImage.

When this display receives HDR signal from the connected device, select a picture mode that best fits your needs.

There are multiple selections: Xbox, HDR Game, HDR Movie, HDR Photo, DisplayHDR 1000, Personal, and Off.



- **Xbox:** Level up your gaming experience while playing Xbox games, you can even control the connected Xbox console using the remote control.
- **HDR Game:** Ideal setting to optimize for playing video games. With brighter white and darker black, the gaming scene is vivid and revealing more details, easily spot enemies hiding in the dark corner and shadows.
- **HDR Movie:** Ideal setting for watching HDR movie. Deliver better contrast and brightness for more realistic and immerse viewing experience.
- **HDR Photo:** Enhancing red, green, and blue for true-to-life visuals.
- **DisplayHDR 1000:** Meet VESA DisplayHDR 1000 standard
- **Personal:** Customize available settings in picture menu.
- **Off:** No optimization by SmartImage HDR.

### Note

To switch off HDR function, please disable from Input device and its content.

Inconsistent HDR settings between input device and monitor may cause unsatisfying images.

### 4.2 SmartContrast

#### 1 What is it?

Unique technology that dynamically analyzes displayed content and automatically optimizes a display's contrast ratio for maximum visual clarity and viewing enjoyment, stepping up backlighting for clearer, crisper and brighter images or dimming backlighting for clear display of images on dark backgrounds.

#### 2 Why do I need it?

You want the very best visual clarity and viewing comfort for every type of content. SmartContrast dynamically controls contrast and adjusts backlighting for clear, crisp, bright gaming and video images or displays clear, readable text for office work. By reducing your display's power consumption, you save on energy costs and extend the lifetime of your display.

#### 3 How does it work?

When you activate SmartContrast, it will analyse the content you are displaying in real time to adjust colors and control backlight intensity. This function will dynamically enhance contrast for a great entertainment experience when viewing videos or playing games.

## 4. Image Optimization

### 4.3 HDR Settings in Windows 10 system

#### Steps


1. Right click on the desktop, enter to display settings.
2. Select the display/monitor.
3. Adjust resolution to 3840 x 2160.
4. Turn the “HDR and WCG” to on mode.
5. Adjust Brightness for SDR content.

#### Note

Windows 10 edition is required, always upgrade to the most updated version.

Below linkage is for the further more information from microsoft official website.


<https://support.microsoft.com/en-au/help/4040263/windows-10-hdr-advanced-color-settings>



#### Note

To switch off HDR function, please disable from Input device and its content.

Inconsistent HDR settings between input device and monitor may cause unsatisfying images.



### 4.4 Adaptive Sync



#### Adaptive Sync

PC gaming has long been an imperfect experience because GPUs and monitors update at different rates. Sometimes a GPU can render many new pictures during a single update of the monitor, and the monitor will show pieces of each picture as a single image. This is called “tearing.” Gamers can fix tearing with a feature called “v-sync,” but the image can become jerky as the GPU waits on the monitor to call for an update before delivering new pictures.

The responsiveness of mouse input and overall frames per second are reduced with v-sync, too. AMD Adaptive Sync technology eliminates all of these problems by letting the GPU update the monitor the moment a new picture is ready, leaving gamers with unbelievably smooth, responsive, tearing-free games.

## 5. Sound by Bowers & Wilkins

The new Philips Momentum display boasts sound by legendary audio experts Bowers & Wilkins. Its speaker system, created exclusively for Philips by Bowers & Wilkins, delivers a thrilling performance with incredible dynamic range. Bass is rich and full while details are pristine, even at low volume. Take your sensory experience and immersion one level deeper by selecting audio modes to optimize your sound for both gaming and entertainment.


- **Volume:** Adjust the volume level.
- **Mute:** Mute the sound or restore it.
- **Audio source:** Select audio source from connected devices. (HDMI 1/HDMI 2/HDMI 3/DisplayPort/USB C)
- **Audio mode:** Select one of the six sound modes to best suit your gaming, viewing or listening experience.
  - **Sport & Racing:** Create a realistic, being-there experience when enjoying sports or racing games.
  - **RPG and Adventure:** Immerse yourself in spacious and atmospheric sound.
  - **Shooting and Action:** Experience punchy, impactful sound for maximum excitement and realism.
  - **Movie Watching:** Enhance movie soundtracks for an immersive, cinematic listening experience.
  - **Music:** True Sound by Bowers & Wilkins, delivering the performance as the artist intended.
  - **Personal:** Access the EQ menu to adjust the sound to your specific requirements.

- **EQ:** Adjust equalizer level for audio.
- **Monitor placement:** Select 'Stand' or 'Wall' to have the best sound reproduction according to the setting.

# 6. Power Delivery and Smart Power

Smart Power is an exclusive Philips technology that provides flexible power delivery options. With Smart Power, you can still charge your device without sacrificing the screen brightness, even set your screen as VESA DisplayHDR 1000.

## 1 How to enable Smart Power?



- 1. Connect the device to the USB C port.
- 2. Press right button, and select [Setup].
- 3. Select [Smart Power], and turn on or off.

| SmartImage mode                                              | Power Delivery from USB C | Ambiglow |
|--------------------------------------------------------------|---------------------------|----------|
| SmartImage                                                   | Smart Power<br>On: 65W    | On       |
|                                                              | Smart Power<br>Off: 65W   | On       |
| SmartImage HDR<br>(HDR Game, HDR Movie, HDR Photo, Personal) | Smart Power<br>On: 65W*   | On       |
|                                                              | Smart Power<br>Off: 65W   | On       |
| SmartImage HDR<br>(VESA DisplayHDR 1000)                     | Smart Power<br>On: 45W*   | Off      |
|                                                              | Smart Power<br>Off: 0W    | On       |

### Note

- If DFP (Downstream Facing Port) is using more than 5W, then [Smart Power] will be turned off.

## 7. Technical Specifications

| Picture/Display       |                                                                                                                                                                                |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display Panel Type    | VA                                                                                                                                                                             |
| Backlight             | W-LED                                                                                                                                                                          |
| Panel Size            | 55" (139.7 cm)                                                                                                                                                                 |
| Pixel Pitch           | 0.315 (H) mm x 0.315 (V) mm                                                                                                                                                    |
| Aspect Ratio          | 16:9                                                                                                                                                                           |
| Contrast ratio (typ.) | 4,000:1                                                                                                                                                                        |
| Optimum Resolution    | 3840x2160 @ 144Hz (HDMI/DP)<br>3840x2160 @ 120Hz (USB C)                                                                                                                       |
| Viewing Angle         | 178° (H) / 178° (V) @ C/R > 10                                                                                                                                                 |
| Picture Enhancement   | SmartImage Game / SmartImage HDR                                                                                                                                               |
| Display Colors        | 1.07G                                                                                                                                                                          |
| Vertical Refresh Rate | 48-144Hz (HDMI/DP)<br>48-120Hz (USB C)                                                                                                                                         |
| Horizontal Frequency  | 30-135KHz (HDMI)<br>30-254KHz (DP)<br>30-254KHz (USB C)                                                                                                                        |
| sRGB                  | YES                                                                                                                                                                            |
| Color Gamut           | YES                                                                                                                                                                            |
| SmartUniformity       | YES                                                                                                                                                                            |
| Delta E               | YES                                                                                                                                                                            |
| LowBlue Mode          | YES                                                                                                                                                                            |
| HDR                   | VESA Certified DisplayHDR™ 1000                                                                                                                                                |
| Adaptive Sync         | YES                                                                                                                                                                            |
| Flicker-free          | YES                                                                                                                                                                            |
| Ambiglow              | Yes (3-sides Ambiglow)                                                                                                                                                         |
| Connectivity          |                                                                                                                                                                                |
| Connectors            | 1 x USB-C (DP ALT mode, PD 65W)<br>1 x DisplayPort 1.4<br>3 x HDMI 2.1 (HDCP 2.2)<br>4 x USB-A, downstream with x2 fast charge BC 1.2<br>1 x USB-B (upstream)<br>1 x Audio out |
| Power Delivery        | USB-C: up to 65W (5V/3A, 7V/3A, 9V/3A, 10V/3A, 12V/3A, 15V/3A, 20V/3.25A)<br>USB-A: x2 fast charge BC 1.2, up to 7.5W (5V/1.5A)                                                |
| Sync input            | Separate Sync                                                                                                                                                                  |
| Convenience           |                                                                                                                                                                                |
| Speaker               | 2.1 channel speaker ( Middle High 10Wx2, Woofer 20Wx1 )                                                                                                                        |
| MultiView             | PBP mode (2 x devices)                                                                                                                                                         |

## 7. Technical Specifications

|                           |                                                                                                                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OSD Languages             | English, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean |
| Other Convenience         | VESA mount(200x200 mm), Kensington Lock                                                                                                                                                                                   |
| Plug & Play Compatibility | DDC/CI, sRGB, Windows 10/8.1/8/7, Mac OSX                                                                                                                                                                                 |

| Power                |                                                                                                   |                                   |                                   |
|----------------------|---------------------------------------------------------------------------------------------------|-----------------------------------|-----------------------------------|
| Consumption          | AC Input Voltage at 100VAC , 50Hz                                                                 | AC Input Voltage at 115VAC , 60Hz | AC Input Voltage at 230VAC, 50Hz  |
| Normal Operation     | 95.5 W (typ.)                                                                                     | 95.3 W (typ.)                     | 96.3 W (typ.)                     |
| Sleep (Standby mode) | 0.5 W                                                                                             | 0.5 W                             | 0.5 W                             |
| Off mode             | 0.3 W                                                                                             | 0.3 W                             | 0.3 W                             |
| Heat Dissipation*    | AC Input Voltage at 100VAC , 50Hz                                                                 | AC Input Voltage at 115VAC , 60Hz | AC Input Voltage at 230VAC , 50Hz |
| Normal Operation     | 325.94 BTU/hr (typ.)                                                                              | 325.26 BTU/hr (typ.)              | 328.67 BTU/hr (typ.)              |
| Sleep (Standby mode) | 1.71 BTU/hr                                                                                       | 1.71 BTU/hr                       | 1.71 BTU/hr                       |
| Off mode             | 1.02 BTU/hr                                                                                       | 1.02 BTU/hr                       | 1.02 BTU/hr                       |
| Power LED indicator  | On mode: LED light turns off<br>Standby/Sleep mode: Red light (breathing)<br>Power off: Red light |                                   |                                   |
| Power Supply         | Built-in, 100-240VAC, 50-60Hz                                                                     |                                   |                                   |

| Dimensions                     |                     |
|--------------------------------|---------------------|
| Product with stand (WxHxD)     | 1232 x 834 x 308 mm |
| Product without stand (WxHxD)  | 1232 x 715 x 102 mm |
| Product with packaging (WxHxD) | 1390 x 990 x 376 mm |

| Weight                 |          |
|------------------------|----------|
| Product with stand     | 26.80 kg |
| Product without stand  | 23.00 kg |
| Product with packaging | 34.61 kg |

| Operating Condition              |                |
|----------------------------------|----------------|
| Temperature range (operation)    | 0°C to 40 °C   |
| Relative humidity (operation)    | 20% to 80%     |
| Atmospheric pressure (operation) | 700 to 1060hPa |

## 7. Technical Specifications

|                                         |                |
|-----------------------------------------|----------------|
| Temperature range<br>(Non-operation)    | -20°C to 60°C  |
| Relative humidity<br>(Non-operation)    | 10% to 90%     |
| Atmospheric pressure<br>(Non-operation) | 500 to 1060hPa |

| Environmental       |                           |
|---------------------|---------------------------|
| ROHS                | YES                       |
| Packaging           | 100% recyclable           |
| Specific Substances | 100% PVC BFR free housing |
| Cabinet             |                           |
| Color               | Black                     |
| Finish              | Glossy and texture        |

### Note

1. This data is subject to change without notice. Go to [www.philips.com/support](http://www.philips.com/support) to download the latest version of leaflet.
2. SmartUniformity and Delta E information sheets are included in the box.
3. The version of HDMI and DisplayPort comply with the Compliance Test Specification (CTS).

## 7.1 Resolution & Preset Modes

- 1** Maximum Resolution  
3840 x 2160 @ 144 Hz (HDMI/DP)  
3840 x 2160 @ 120 Hz (USB C)

- 2** Recommended Resolution  
3840 x 2160 @ 60 Hz

| H. freq (kHz) | Resolution            | V. freq (Hz) |
|---------------|-----------------------|--------------|
| 31.47         | 720 x 400             | 70.09        |
| 31.47         | 640 x 480             | 59.94        |
| 35.00         | 640 x 480             | 66.67        |
| 37.86         | 640 x 480             | 72.81        |
| 37.50         | 640 x 480             | 75.00        |
| 37.88         | 800 x 600             | 60.32        |
| 46.88         | 800 x 600             | 75.00        |
| 48.36         | 1024 x 768            | 60.00        |
| 60.02         | 1024 x 768            | 75.03        |
| 44.77         | 1280x 720             | 59.86        |
| 63.89         | 1280 x 1024           | 60.02        |
| 79.98         | 1280 x 1024           | 75.03        |
| 67.50         | 1920 x 1080           | 60.00        |
| 135.00        | 1920 x 1080           | 120.00       |
| 133.29        | 1920x2160 (PBP)       | 59.98        |
| 183.00        | 2560x1440             | 120.00       |
| 67.50         | 3840 x 2160           | 30.00        |
| 112.50        | 3840 x 2160           | 50.00        |
| 135.00        | 3840 x 2160           | 60.00        |
| 222.20        | 3840 x 2160 (HDMI/DP) | 98.00        |
| 266.65        | 3840 x 2160           | 120.00       |
| 319.94        | 3840 x 2160 (HDMI/DP) | 144.00       |

## 3 Video Timing

| Resolution   | V. freq (Hz) |
|--------------|--------------|
| 640 x 480p   | 60Hz 4:3     |
| 720x 480p    | 60Hz 4:3     |
| 720 x 480p   | 60Hz 16:9    |
| 1280x 720p   | 60Hz         |
| 1920x 1080i  | 60Hz         |
| 1920x 1080p  | 60Hz         |
| 720 x 576p   | 50Hz 4:3     |
| 720 x 576p   | 50Hz 16:9    |
| 1280x 720p   | 50Hz         |
| 1920 x 1080i | 50Hz         |
| 1920 x 1080p | 50Hz         |
| 3840 x 2160p | 50Hz         |
| 3840 x 2160p | 60Hz         |


### Note

1. Please notice that your display works best at native resolution of 3840 x 2160. For best output performance, please always ensure that your graphic card is capable of achieving the maximum resolution and refresh rate of this Philips display.
2. The default resolution through HDMI is 3840 x 2160 @120Hz for optimal HDMI 2.1 console gameplay. If you want to run 4K UHD with 144Hz, please go to OSD menu, select [HDMI Refresh Rate], and change to [144Hz].


## 7. Technical Specifications

3. If you feel the texts in your display is a little fade away, you can adjust your fonts setting in your PC/ Notebook as following steps.

### Step 1: Control panel/All Control Panel Items/Fonts



### Step 2: Adjust Clear Type Text



### Step 3: Uncheck "Clear Type"



# 8. Power Management

If you have VESA DPM compliance display card or software installed in your PC, the display can automatically reduce its power consumption when not in use. If an input from a keyboard, mouse or other input device is detected, the display will 'wake up' automatically. The following table shows the power consumption and signaling of this automatic power saving feature:

| Power Management Definition |       |        |        |                                 |                 |
|-----------------------------|-------|--------|--------|---------------------------------|-----------------|
| VESA Mode                   | Video | H-sync | V-sync | Power Used                      | LED Color       |
| Active                      | ON    | Yes    | Yes    | 95.3 W (typ.)<br>444.7 W (max.) | Off             |
| Sleep (Standby mode)        | OFF   | No     | No     | 0.5 W                           | Red (breathing) |
| Off mode                    | OFF   | -      | -      | 0.3 W                           | Red             |

The following setup is used to measure power consumption on this display.


- Native resolution: 3840 x 2160
- Contrast: 50%
- Brightness: 70%
- Color temperature: 6500k with full white pattern

 **Note**  
This data is subject to change without notice.

## 9. Customer care and warranty

### 9.1 Philips' Flat Panel Displays Pixel Defect Policy

Philips strives to deliver the highest quality products. We use some of the industry's most advanced manufacturing processes and practice stringent quality control. However, pixel or sub pixel defects on the TFT display panels used in flat panel displays are sometimes unavoidable. No manufacturer can guarantee that all panels will be free from pixel defects, but Philips guarantees that any display with an unacceptable number of defects will be repaired or replaced under warranty. This notice explains the different types of pixel defects and defines acceptable defect levels for each type. In order to qualify for repair or replacement under warranty, the number of pixel defects on a TFT display panel must exceed these acceptable levels. For example, no more than 0.0004% of the sub pixels on a display may be defective. Furthermore, Philips sets even higher quality standards for certain types or combinations of pixel defects that are more noticeable than others. This policy is valid worldwide.



#### Pixels and Sub pixels


A pixel, or picture element, is composed of three sub pixels in the primary colors of red, green and blue. Many pixels together form an image. When all sub pixels of a pixel are lit, the three colored sub pixels together appear as a single white pixel. When all are dark, the three colored sub pixels together appear as a single black pixel. Other combinations of lit and dark sub pixels appear as single pixels of other colors.

#### Types of Pixel Defects


Pixel and sub pixel defects appear on the screen in different ways. There are two categories of pixel defects and several types of sub pixel defects within each category.

#### Bright Dot Defects

Bright dot defects appear as pixels or sub pixels that are always lit or 'on'. That is, a bright dot is a sub-pixel that stands out on the screen when the display displays a dark pattern. There are the types of bright dot defects.




One lit red, green or blue sub pixel.



Two adjacent lit sub pixels:  
- Red + Blue = Purple

## 9. Customer care and warranty

- Red + Green = Yellow
- Green + Blue = Cyan (Light Blue)





Three adjacent lit sub pixels (one white pixel).

### Note

A red or blue bright dot must be more than 50 percent brighter than neighboring dots while a green bright dot is 30 percent brighter than neighboring dots.

### Black Dot Defects

Black dot defects appear as pixels or sub pixels that are always dark or 'off'. That is, a dark dot is a sub-pixel that stands out on the screen when the display displays a light pattern. These are the types of black dot defects.



### Pixel Defect Tolerances

In order to qualify for repair or replacement due to pixel defects during the warranty period, a TFT display panel in a Philips flat panel display must have pixel or sub pixel defects exceeding the tolerances listed in the following tables.

### Proximity of Pixel Defects

Because pixel and sub pixels defects of the same type that are near to one another may be more noticeable, Philips also specifies tolerances for the proximity of pixel defects.

9. Customer care and warranty

| BRIGHT DOT DEFECTS                             | ACCEPTABLE LEVEL |
|------------------------------------------------|------------------|
| 1 lit subpixel                                 | 2                |
| 2 adjacent lit subpixels                       | 0                |
| 3 adjacent lit subpixels (one white pixel)     | 0                |
| Total bright dot defects of all types          | 2                |
| BLACK DOT DEFECTS                              | ACCEPTABLE LEVEL |
| 1 dark subpixel                                | 10 or fewer      |
| 2 adjacent dark subpixels                      | 2 or fewer       |
| 3 adjacent dark subpixels                      | 1 or fewer       |
| Distance between two black dot defects*        | >=5mm            |
| Total black dot defects of all types           | 10 or fewer      |
| TOTAL DOT DEFECTS                              | ACCEPTABLE LEVEL |
| Total bright or black dot defects of all types | 10 or fewer      |

 **Note**  
1 or 2 adjacent sub pixel defects = 1 dot defect

9.2 Customer Care & Warranty

For warranty coverage information and additional support requirements valid for your region, please visit [www.philips.com/support](http://www.philips.com/support) website for details or contact your local Philips Customer Care Center.

For Warranty Period please refer to Warranty Statement in Important Information Manual.

For extended warranty, if you would like to extend your general warranty period, an Out of Warranty service package is offered via our Certified Service Center.

If you wish to make use of this service, please be sure to purchase the service within 30 calendar days of your original purchase date. During the extended warranty period, the service includes pickup, repair and return service, however the user will be responsible for all costs accrued.

If the Certified Service Partner cannot perform the required repairs under the offered extended warranty package, we will find alternative solutions for you, if possible, up to the extended warranty period you have purchased.

Please contact our Philips Customer Service Representative or local contact center (by Consumer care number) for more details.

Philips Customer Care Center number listed below.

|                                  |                            |                                     |
|----------------------------------|----------------------------|-------------------------------------|
| • Local Standard Warranty Period | • Extended Warranty Period | • Total Warranty Period             |
| • Depend on different Regions    | • + 1 Year                 | • Local Standard warranty period +1 |
|                                  | • + 2 Years                | • Local Standard warranty period +2 |
|                                  | • + 3 Years                | • Local Standard warranty period +3 |

\*\*Proof of original purchase and extended warranty purchase required.

 Note

Please refer to important information manual for regional service hotline, which is available on the [Philips website support page](#).

## 10. Troubleshooting & FAQs

### 10.1 Troubleshooting

This page deals with problems that can be corrected by a user. If the problem still persists after you have tried these solutions, contact Philips customer service representative.

#### 1 Common Problems

##### No Picture (Power LED not lit)

- Make sure the power cord is plugged into the power outlet and into the back of the display.
- First, ensure that the power button on the rear side of the display is in the OFF position, then press it to the ON position.

##### No Picture (Power LED is Red)

- Make sure the computer is turned on.
- Make sure the signal cable is properly connected to your computer.
- Make sure the display cable has no bent pins on the connect side. If yes, repair or replace the cable.
- The Energy Saving feature may be activated

##### Screen says

Check cable connection

- Make sure the display cable is properly connected to your computer. (Also refer to the Quick Start Guide).
- Check to see if the display cable has bent pins.
- Make sure the computer is turned on.

##### AUTO button doesn't function

- The auto function is applicable only in VGA-Analog mode. If the result is not satisfactory, you can do manual adjustments via the OSD menu.



#### Note

The Auto Function is not applicable in DVI-Digital mode as it is not necessary.

##### Visible signs of smoke or sparks

- Do not perform any troubleshooting steps
- Disconnect the display from mains power source immediately for safety
- Contact with Philips customer service representative immediately.

#### 2 Imaging Problems

##### Image is not centered

- Adjust the image position using the "Auto" function in OSD Main Controls.
- Adjust the image position using the Phase/Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

##### Image vibrates on the screen

- Check that the signal cable is properly securely connected to the graphics board or PC.

##### Vertical flicker appears



- Adjust the image using the "Auto" function in OSD Main Controls.
- Eliminate the vertical bars using the Phase/Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

##### Horizontal flicker appears



## 10. Troubleshooting & FAQs

- Adjust the image using the "Auto" function in OSD Main Controls.
- Eliminate the vertical bars using the Phase/Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

Image appears blurred, indistinct or too dark

- Adjust the contrast and brightness on On-Screen Display.

An "after-image", "burn-in" or "ghost image" remains after the power has been turned off.

- Uninterrupted display of still or static images over an extended period may cause "burn-in", also known as "after-imaging" or "ghost imaging", on your screen. "Burn-in", "after-imaging", or "ghost imaging" is a well-known phenomenon in LCD panel technology. In most cases, the "burn-in" or "after-imaging" or "ghost imaging" will disappear gradually over a period of time after the power has been switched off.
- Always activate a moving screen saver program when you leave your display unattended.
- Always activate a periodic screen refresh application if your LCD display will display unchanging static content.
- Failure to activate a screen saver, or a periodic screen refresh application may result in severe "burn-in" or "after-imaging" or "ghost image" symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

Image appears distorted. Text is fuzzy or blurred.

- Set the PC's display resolution to the same mode as display's recommended screen native resolution.

Green, red, blue, dark, and white dots appears on the screen

- The remaining dots are normal characteristic of the liquid crystal used in today's technology, Please refer the pixel policy for more detail.

## 10.2 General FAQs

**Q1: When I install my display what should I do if the screen shows 'Cannot display this video mode'?**

**Ans.:** Recommended resolution for this display: 3840 x 2160.

- Unplug all cables, then connect your PC to the display that you used previously.
- In the Windows Start Menu, select Settings/Control Panel. In the Control Panel Window, select the display icon. Inside the display Control Panel, select the 'Settings' tab. Under the setting tab, in box labelled 'desktop area', move the sidebar to 3840 x 2160 pixels.
- Open 'Advanced Properties' and set the Refresh Rate to 60 Hz, then click OK.
- Restart your computer and repeat step 2 and 3 to verify that your PC is set at 3840 x 2160 @ 60 Hz.
- Shut down your computer, disconnect your old display and reconnect your Philips LCD display.
- Turn on your display and then turn on your PC.

**Q2: What are the .inf and .icm files on the CD-ROM? How do I install the drivers (.inf and .icm)?**

**Ans.:** These are the driver files for your monitor. Follow the instructions in your user manual to install the drivers. Your computer may ask you for monitor drivers (.inf and .icm files) or a driver disk when you first install your monitor. Follow the instructions to insert the ( companion CD-ROM) included in this package. Monitor drivers (.inf and .icm files) will be installed automatically.

**Q3: How do I adjust the resolution?**

**Ans.:** Your video card/graphic driver and display together determine the available resolutions. You can select the desired resolution under Windows® Control Panel with the "Display properties".

**Q4: What if I get lost when I am making display adjustments via OSD?**

**Ans.:** Simply press the ➡ button, then select 'Reset' to recall all of the original factory settings.

**Q5: Is the LCD screen resistant to scratches?**

**Ans.:** In general it is recommended that the panel surface is not subjected to excessive shocks and is protected from sharp or blunt objects. When handling the display, make sure that there is no pressure or force applied to the panel surface side. This may affect your warranty conditions.

**Q6: How should I clean the LCD surface?**

**Ans.:** For normal cleaning, use a clean, soft cloth. For extensive cleaning, please use isopropyl alcohol. Do not use other solvents such as ethyl alcohol, ethanol, acetone, hexane, etc.

**Q7: Can I change the color setting of my display?**

**Ans.:** Yes, you can change your color setting through OSD control as the following procedures,

- Press "➡" to show the OSD (On Screen display) menu
- Press "↓" to select the option "Color" then press "➡" to enter

color setting, there are three settings as below.

1. **Color Temperature:** The 7 settings are Native, 5000K, 6500K, 7500K, 8200K, 9300K and 11500K. With settings in the 5000K range the panel appears "warm, with a red-white color tone", while a 11500K temperature yields "cool, bluishwhite toning".
2. **sRGB:** This is a standard setting for ensuring correct exchange of colors between different device (e.g. digital cameras, displays, printers, scanners, etc).
3. **User Define:** The user can choose his/her preference color setting by adjusting red, green blue color.

### Note

A measurement of the color of light radiated by an object while it is being heated. This measurement is expressed in terms of absolute scale, (degrees Kelvin). Lower Kelvin temperatures such as 2004K are red; higher temperatures such as 9300K are blue. Neutral temperature is white, at 6504K.

**Q8: Can I connect my LCD display to any PC, workstation or Mac?**

**Ans.:** Yes. All Philips LCD displays are fully compatible with standard PCs, Macs and workstations. You may need a cable adapter to connect the display to your Mac system. Please contact your Philips sales representative for more information.

**Q9: Are Philips LCD displays Plug-and- Play?**

**Ans.:** Yes, the displays are Plug-and-Play compatible with Windows 10/8.1/8/7.

**Q10: What is Image Sticking, or Image Burn-in, or After Image, or Ghost Image in LCD panels?**

**Ans.:** Uninterrupted display of still or static images over an extended period may cause "burn-in", also known as "after-imaging" or "ghost imaging", on your screen. "Burn-in", "after-imaging", or "ghost imaging" is a well-known phenomenon in LCD panel technology. In most cases, the "burn-in" or "after-imaging" or "ghost imaging" will disappear gradually over a period of time after the power has been switched off.

Always activate a moving screen saver program when you leave your display unattended.

Always activate a periodic screen refresh application if your LCD display will display unchanging static content.

### Warning


Failure to activate a screen saver, or a periodic screen refresh application may result in severe "burn-in" or "after-imaging" or "ghost image" symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

**Q11: Why is my display not showing sharp text, and is displaying jagged characters?**


**Ans.:** Your LCD display works best at its native resolution of 3840 x 2160. For best display, please use this resolution.

**Q12: How to unlock/lock my hot key?**

Ans.: Please press **↓** for 10 seconds to unlock/lock the hot key, by doing so, your display pops out “Attention” to show the unlock/lock status as shown below illustrators.



Display controls unlocked



Display controls locked

Q13: **Why the fonts are indistinct?**

Ans.: Please follow the process on page 29 to improve it.

Q14: **Where can I find Important Information manual mentioned in EDFU?**

Ans.: Important Information manual can be download on the Philips website support page.

---

### 10.3 Multiview FAQs

Q1: **How to listen to Audio, independent of video?**

Ans.: Normally the audio source is linked to the main picture source. If you want to change audio-source input, you can press **➡** to enter OSD menu. Select your preferred [Audio Source] option from the [Audio] main menu.

Please note that the next time you turn on your display, the display will by default select the audio source you chose last time. In case you want to change it again, you need to go through the above steps to select your new preferred audio source, which then will become the “default” mode.

Q2: **Why the sub-windows flickers when I enable PBP.**

Ans.: It's because the sub-windows video source is interlace timing (i-timing), please change sub-window signal source to be progressive timing (3P-timing).



2021 © TOP Victory Investments Ltd. All rights reserved.

This product has been manufactured by and is sold under the responsibility of Top Victory Investments Ltd., and Top Victory Investments Ltd. is the warrantor in relation to this product. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. and are used under license.

Specifications are subject to change without notice.

Version: 559MICE1T