



Philips  
LCD Indoor Touch Totem

107 cm (42")

multimedia  
Full HD

BDT4251TX

## More audience interaction

with the multi-touch Totem LCD Display

Deliver vital information or marketing messages to your audience in startling clarity. And thanks to the interactive touch screen, you can also engage your customer much more closely than ever before.

### **Operational flexibility**

- Capacitive Touch
- 2 Touch Points
- Software Independent

### **Optimised for public touch**

- Full HD LCD display, 1920 x 1080p
- Slim bezel design for a stylish look

### **Lower total cost of ownership**

- SmartPower for energy saving

### **Sustainable and safe**

- Temperature sensor measures the health condition
- Complies with RoHS standards of care for the environment

# PHILIPS

# Specifications

## Picture/Display

- Diagonal screen size: 42 inch / 107 cm
- Panel resolution: 1920 x 1080p
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 700 cd/m<sup>2</sup>
- Contrast ratio (typical): 1100:1
- Response time (typical): 9 ms
- Aspect ratio: 16:9
- Viewing angle: 178° (H)/178° (V)
- Pixel pitch: 0.485 x 0.485
- Display colours: 1.06 Billion
- Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement

## Supported Display Resolution

### Computer formats

Resolution	Refresh rate
640 x 480	60, 67, 72, 75 Hz
800 x 600	56, 60, 72, 75 Hz
1024 x 768	60 Hz
1280 x 768	60 Hz
1280 x 800	60 Hz
1280 x 1024	60 Hz
1360 x 768	60 Hz
1366 x 768	60 Hz
1440 x 900	60 Hz
1600 x 1200	60 Hz
1920 x 1080	60 Hz
1920 x 1200	60 Hz

### Video formats

Resolution	Refresh rate
480i	60 Hz
480p	60 Hz
576i	50 Hz
576p	50 Hz
720p	50, 60 Hz
1080i	50, 60 Hz
1080p	50, 60 Hz

## Connectivity

- PC: VGA-in D-Sub 15HD, VGA-out D-Sub 15HD, DVI-D x 1, RS232 D-Sub9, RS232 D-sub9 output, 3.5 mm PC audio input x 1
- AV input: HDMI x 1, Component (YPbPr) x 1, Composite (RCA) x 1, Composite (BNC) x 1, S-video x 1, Audio (L/R) x 1
- AV output: Composite (BNC) x 1, Audio (L/R) x 1
- Touch Screen: USB
- Other connections: AC-out, External loudspeaker connector

## Convenience

- Placement: Portrait

- Picture in picture: PBP, PIP, POP
- Screen-saving functions: Pixel shift, Low bright
- Keyboard control: Hidden, Lockable
- Remote control signal: Lockable
- Ease of installation: AC Out
- Energy-saving functions: Ambient light sensor, Smart Power
- Safety control functions: Heat Control, Temperature Sensor
- Picture performance: Advanced colour control
- Network controllability: RS232

## Dimensions

- Totem: 598 x 201 x 154 mm
- Plate: 598 x 8 x 450.6 mm
- Packaging dimensions (WxHxD): 1 x Euro pallet: 1200 x 2200 x 800 mm

## Operating conditions

- Temperature range (operation): 0 - 40 °C
- Relative humidity: 5 - 90 %
- MTBF: 50,000 hour(s)

## Power

- Mains power: 90-264 VAC, 50/60 Hz
- Consumption (On mode): Typ. 133 W
- Standby power consumption: < 1 W

## Accessories

- Included accessories: Remote Control, Batteries for remote control, AC Power Cord, VGA cable, User manual on CD-ROM, Owner's Manual, Touch Driver on USB
- Optional accessories: Software Omnitapps BMT1909/00

## Miscellaneous

- Warranty: Europe 2 years
- On-Screen Display Languages: English, French, German, Italian, Polish, Russian, Simplified Chinese, Turkish
- Regulatory approvals: CCC, CE, FCC, Class B, RoHS, UL/cUL
- Totem: black, RAL 9005F13

## Packaging Data

- Tare weight: 80 kg
- Number of products included: 1

## Interactivity

- Multi-touch technology: 2 Touch Points simultaneously, USB connection, 5-mm safety glass, Capacitive touch

# Highlights

## Capacitive Touch

This capacitive touch has 5-mm tempered glass. Therefore it is perfectly practical for public use and easy to clean.

## 2 Touch Points

Enjoy the interactivity of multi-touch functionality. It has the advantages of a more robust touch screen combined with the multi-touch gestures for using more versatile touch software.

## Full HD LCD display

Full HD LCD display, 1920 x 1080p

## Slim bezel

A slim bezel design adds a stylish look to a Touch Screen to nicely blend in most environments.

## SmartPower

The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

## Software Independent

Our touch screens are software independent and work with most touch-screen software commercially available, including Windows XP/7 and Mac OS, Omnitapps – BMT1909/00. Connect via USB to a PC or laptop.

## Temperature sensor

This multi-user Touch Screen contains a temperature sensor to monitor the internal health condition. If the internal temperature surpasses the pre-set threshold, two internal fans will be automatically activated to cool down the display to normal conditions.

## Compliant with RoHS standards

Philips designs and produces display products in compliance with strict Restriction of Hazardous Substances (RoHS) standards that restrict lead and other toxic substances that can harm the environment.



Issue date 2019-05-09

Version: 1.0.1

12 NC: 8670 000 87687  
EAN: 87 12581 63764 4

© 2019 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)