



## www.philips.com/welcome

ΕN	User manual	
	Customer care and warranty	31
	Troubleshooting & FAQs	36



## Table of Contents

1.	Impo	ortant1
		Safety precautions and
		maintenance1
		Notational Descriptions2
		Disposal of product and packing
		material3
2.	Sett	ing up the monitor4
	2.1	Installation4
		Operating the monitor5
		MHL (Mobile High-Definition Link)
		introduction8
		Bluetooth
		(275C5QHAB/275C5QHAW)9
3.	Imag	ge Optimization10
		SmartImage10
		SmartKolor11
		SmartContrast11
	3.4	Philips SmartControl Premium11
4.	Tech	nical Specifications19
	4.1	Resolution & Preset Modes
5.	Pow	er Management23
5.	1000	
6.	Reg	ulatory Information24
7.	Cus	tomer care and warranty
		Philips' Flat Panel Monitors Pixel
		Defect Policy
	7.2	Customer Care & Warranty
8.	Trou	ubleshooting & FAQs
	8.1	Troubleshooting
		SmartControl Premium FAQs
		General FAQs
		MHL FAQs40
	8.5	Bluetooth FAQs41

## 1. Important

This electronic user's guide is intended for anyone who uses the Philips monitor. Take time to read this user manual before you use your monitor. It contains important information and notes regarding operating your monitor.

The Philips guarantee applies provided the product is handled properly for its intended use, in accordance with its operating instructions and upon presentation of the original invoice or cash receipt, indicating the date of purchase, dealer's name and model and production number of the product.

## 1.1 Safety precautions and maintenance

### Warnings

Use of controls, adjustments or procedures other than those specified in this documentation may result in exposure to shock, electrical hazards and/or mechanical hazards.

Read and follow these instructions when connecting and using your computer monitor.

### Operation

- Please Keep the monitor out of direct sunlight, very strong bright lights and away from any other heat source. Lengthy exposure to this type of environment may result in discoloration and damage to the monitor.
- Remove any object that could fall into ventilation holes or prevent proper cooling of the monitor's electronics.
- Do not block the ventilation holes on the cabinet.
- When positioning the monitor, make sure the power plug and outlet are easily accessible.
- If turning off the monitor by detaching the power cable or DC power cord, wait for 6 seconds before attaching the power cable or DC power cord for normal operation.

- Please use approved power cord provided by Philips all the time. If your power cord is missing, please contact with your local service center. (Please refer to Customer Care Consumer Information Center)
- Do not subject the monitor to severe vibration or high impact conditions during operation.
- Do not knock or drop the monitor during operation or transportation.

### Maintenance

- To protect your monitor from possible damage, do not put excessive pressure on the LCD panel. When moving your monitor, grasp the frame to lift; do not lift the monitor by placing your hand or fingers on the LCD panel.
- Unplug the monitor if you are not going to use it for an extensive period of time.
- Unplug the monitor if you need to clean it with a slightly damp cloth. The screen may be wiped with a dry cloth when the power is off. However, never use organic solvent, such as, alcohol, or ammonia-based liquids to clean your monitor.
- To avoid the risk of shock or permanent damage to the set, do not expose the monitor to dust, rain, water, or excessive moisture environment.
- If your monitor gets wet, wipe it with dry cloth as soon as possible.
- If foreign substance or water gets in your monitor, please turn the power off immediately and disconnect the power cord. Then, remove the foreign substance or water, and send it to the maintenance center.
- Do not store or use the monitor in locations exposed to heat, direct sunlight or extreme cold.
- In order to maintain the best performance of your monitor and use it for a longer lifetime, please use the monitor in a location that falls within the following temperature and humidity ranges.

- Temperature: 0-40°C 32-95°F
- Humidity: 20-80% RH

## Important information for Burn-in/Ghost image

- Always activate a moving screen saver program when you leave your monitor unattended. Always activate a periodic screen refresh application if your monitor will display unchanging static content. Uninterrupted display of still or static images over an extended period may cause "burn in", also known as "after-imaging" or "ghost imaging", on your screen.
- "Burn-in", "after-imaging", or "ghost imaging" is a well-known phenomenon in LCD panel technology. In most cases, the "burned in" or "after-imaging" or "ghost imaging" will disappear gradually over a period of time after the power has been switched off.

### Warning

Failure to activate a screen saver, or a periodic screen refresh application may result in severe "burn-in" or "after-image" or "ghost image" symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

### Service

- The casing cover should be opened only by qualified service personnel.
- If there is any need for any document for repair or integration, please contact with your local service center. (please refer to the chapter of "Consumer Information Center")
- For transportation information, please refer to "Technical Specifications".
- Do not leave your monitor in a car/trunk under direct sun light.

### Note

Consult a service technician if the monitor does not operate normally, or you are not sure what procedure to take when the operating instructions given in this manual have been followed.

## 1.2 Notational Descriptions

The following subsections describe notational conventions used in this document.

### Notes, Cautions and Warnings

Throughout this guide, blocks of text may be accompanied by an icon and printed in bold or italic type. These blocks contain notes, cautions or warnings. They are used as follows:

## Solution Note

This icon indicates important information and tips that help you make better use of your computer system.

## Caution

This icon indicates information that tells you how to avoid either potential damage to hardware or loss of data.

### (1) Warning

This icon indicates the potential for bodily harm and tells you how to avoid the problem.

Some warnings may appear in alternate formats and may not be accompanied by an icon. In such cases, the specific presentation of the warning is mandated by the relevant regulatory authority.

## 1.3 Disposal of product and packing material

Waste Electrical and Electronic Equipment-WEEE



This marking on the product or on its packaging illustrates that, under European Directive 2012/19/EU governing used electrical and electronic appliances, this product may not be disposed of with normal household waste. You are responsible for disposal of this equipment through a designated waste electrical and electronic equipment collection. To determine the locations for dropping off such waste electrical and electronic, contact your local government office, the waste disposal organization that serves your household or the store at which you purchased the product.

Your new monitor contains materials that can be recycled and reused. Specialized companies can recycle your product to increase the amount of reusable materials and to minimize the amount to be disposed of.

All redundant packing material has been omitted. We have done our utmost to make the packaging easily separable into mono materials.

Please find out about the local regulations on how to dispose of your old monitor and packing from your sales representative.

## Taking back/Recycling Information for Customers

Philips establishes technically and economically viable objectives to optimize the environmental performance of the organization's product, service and activities.

From the planning, design and production stages, Philips emphasizes the important of making products that can easily be recycled. At Philips, end-of-life management primarily entails participation in national take-back initiatives and recycling programs whenever possible, preferably in cooperation with competitors, which recycle all materials (products and related packaging material) in accordance with all Environmental Laws and taking back program with the contractor company.


Your display is manufactured with high quality materials and components which can be recycled and reused.

To learn more about our recycling program please visit: <u>http://www.philips.</u> <u>com/sites/philipsglobal/about/sustainability/</u> <u>ourenvironment/productrecyclingservices.page</u>.

## 2. Setting up the monitor

## 2.1 Installation

### 1 Package contents







#### AC/DC Adapter





\*VGA





Cable management

\*HDMI (275C5QHS)

### \*Depends on the country

### Solution Note

Use only the AC/DC adapter model: Philips ADPC1945(275C5QSB/QSW) ADPC1965(275C5QHAB/QHAW) ADS-65LSI-19-1 19065G(275C5QHAB/ QHAW)


### Warnings




Do not rip off panel film

2 Connecting to your PC

Model 275C5QSB, 275C5QSW:



Model 275C5QHAB, 275C5QHAW:



- 1 AC/DC power input
- **2** VGA input
- 3 HDMI inputs (HDMI1, HDMI2)
- 4 HDMI or MHL input
- **5** Earphone output
- 6 Audio input
- Kensington anti-theft lock

#### 2. Setting up the monitor


### Connect to PC

- 1. Connect the power cord to the back of the monitor firmly.
- 2. Turn off your computer and unplug its power cable.
- 3. Connect the monitor signal cable to the video connector on the back of your computer.
- 4. Plug the power cord of your computer and your monitor into a nearby outlet.
- 5. Turn on your computer and monitor. If the monitor displays an image, installation is complete.


### 2.2 Operating the monitor

1 Front view product description

### Model 275C5QSB, 275C5QSW:



### Model 275C5QHAB, 275C5QHAW:



0	ወ	Switch monitor's power ON and OFF.
2	■/OK	Access the OSD menu.
3	◀	Return to previous OSD level.
4	м	Adjust the speaker volume.
6		Adjust the OSD menu.
6	Ð	Change the signal input source.
Ø	đ	SmartImage hot key. There are 7 modes to select: Text, Office, Photo, Movie, Game, Economy and Off.
8	۲	Bluetooth hot key.

### 2 Description of the On Screen Display

### What is On-Screen Display (OSD)?

On-Screen Display (OSD) is a feature in all Philips LCD monitors. It allows an end user to adjust screen performance or select functions of the monitors directly through an on-screen instruction window. A user friendly on screen display interface is shown as below:

### Model 275C5QSB, 275C5QSW:

Input	VGA -
Picture	
Color	
Language	
OSD Settings	
•	

### Model 275C5QHAB,275C5QHAW:

Input	HDMI1	•
Picture		
Audio		
<b>*</b> ®		
Color		
•		

## Basic and simple instruction on the control keys

In the OSD shown above, you can press ▼ ▲ buttons at the front bezel of the monitor to move the cursor, and press OK button to confirm the choice or change.

### The OSD Menu

Below is an overall view of the structure of the On-Screen Display. You can use this as a reference when you want to work your way around the different adjustments later on.

Main menu	Sub menu
Input	- VGA
	<ul> <li>DVI (available for selective models)</li> </ul>
	HDMI1 (available for selective models)
	HDMI2 (available for selective models)
	MHL-HDMI (available for selective models)
- Picture	Picture Format — Wide Screen, 4:3
, iccur e	Brightness — 0~100
	Contrast 0~100
	— SmartKolor — On, Off
	SmartTxt On, Off
	SmartResponse Off, Fast, Faster, Fastest
	- SmartContrast - On, Off
	- Gamma - 1.8, 2.0, 2.2, 2.4, 2.6
	Pixel Orbiting On, Off
	<ul> <li>Over Scan — On, Off (available for selective models)</li> </ul>
— Audio	Volume — 0~100
	(available for selective models)
	<ul> <li>Stand-Alone On, Off (available for selective models)</li> </ul>
	Mute On, Off
	MuteOn, Off (available for selective models) Audio SourceAudio In HDMI1
	(available for HDMI2, MHL-HDMI
	selective models)
	Treble On, Off (available for selective models)
	Bass On Off
	(available for selective models) SRS WOW HD™ On Off
	SRS WOW HD™ On, Off (available for selective models)
	<ul> <li>Incredible Surround On, Off (available for selective models)</li> </ul>
	EQ 100Hz: 0~100
	(available for 330Hz: 0~100
	selective models) 1KHz: 0~100 3.3KHz: 0~100
	3.3KHz: 0~100 10KHz: 0~100
Bluetooth (available for s	Bluetooth On, Off elective models)
Color	Color Temperature 5000K, 6500K, 7500K,
	- sRGB 8200K, 9300K, 11500K
	User Define Red: 0~100
	Green: 0~100 Blue: 0~100
Language	— English, Deutsch, Español, Ελληνική, Français,
	Italiano, Maryar, Nederlands, Português, Português do Brazil, Polski, Русский "Svenska,
	Suomi、Türkçe、Čeština、Українська, 简体中文,
	繁體中文, 日本語, 한국어
- OSD Settings	Horizontal — 0~100
	Transparency         Off, 1, 2, 3, 4           OSD Time Out         5s, 10s, 20s, 30s, 60s
Setup	- OSD Time Out - SS, TOS, 205, 505
Secup	
	Phase - 0~100
	Clock — 0~100
	Resolution Notification — On, Off
	Reset Yes, No
	Information


### 3 Resolution notification

This monitor is designed for optimal performance at its native resolution, 1920  $\times$  1080 @ 60 Hz. When the monitor is powered on at a different resolution, an alert is displayed on screen: Use 1920  $\times$  1080 @ 60 Hz for best results.

Display of the native resolution alert can be switched off from Setup in the OSD (On Screen Display) menu.

### 4 Physical Function

### Tilt



### 2.3 MHL (Mobile High-Definition Link) introduction

### 1 What is it?

Mobile High Definition Link (MHL) is a mobile audio/video interface for directly connecting mobile phones and other portable devices to high-definition displays.

An optional MHL cable allows you to simply connect your MHL capable mobile device to this large Philips MHL display, and watch your HD videos come to life with full digital sound. Now not only you can enjoy your mobile games, photos, movies, or other apps on its big screen, you can simultaneously charge your mobile device so you never run out of power half way.


### 2 How do I use the MHL function?

To use the MHL function, you need an MHL-Certified mobile device. To find a list of MHLcertified devices, visit the official MHL website (http://www.mhlconsortium.org)

You also need a optional MHL certified special cable in order to use this function.

### 3 How does it work? (how do I connect?)

Connect the Optional MHL cable to the mini USB port on the mobile device side, and the [MHL-HDMI] marked port on the monitor side. You are now ready to view the images on your big screen display and operate all function on you the mobile device such as internet surfing, game playing, photo browsing...etc. if your monitor has speaker function, then you will be able to hear accompanying sound too. When the MHL cable is disconnected or the mobile device is turned off, the MHL function will be automatically disabled.



### Note

- The port marked [MHL-HDMI] is the only port on the monitor that supports the MHL function when the MHL cable is used. Note that the MHL certified cable is different than a standard HDMI cable.
- A mobile device with MHL certification must be purchased separately
- You may have to manually switch the monitor to MHL-HDMI mode in order to activate the monitor, if you have other devices already working and connected to available inputs
- Standby/Off energy saving of ErP is not applicable for the MHL charging functionality
- This Philips display is MHL certified. However, in case your MHL device does not connect or work correctly, check with your MHL device FAQ or vendor directly for direction. The policy of your device manufacturer may require you to purchase their brand specific MHL cable or adapter in order to work with other brand MHL devices. Note that this is not a fault of this Philips display.

### 2.4 Bluetooth (245C5QHAB/245C5QHAW)

### 1 What is it?

This Philips display with Bluetooth , you can transfer music from your mobile phone. It requires no cables or network connection to play your audio content over Bluetooth to share music using Bluetooth on this Philips display.

### 2 Why do I need it?

We have embraced music on our devices. There is so much great content on mobile phone to take advantage but the small volume doesn't work well for enjoying the music. And if you have a call, you can talk through microphone on the Philips display instead of mobile phone.

### 3 How it works?

Bluetooth function can be selected by simply pressing the **hotkey** of the Philips Monitor:

- 1. On your device, open Bluetooth to start scanning for other Bluetooth devices.
- Press hotkey (\*) on the front bezel of display, your monitor pops out "Attention" as shown below illustrators.



 Select your Philips monitor on the list to connect. Now the music on the device can be played on your Philips display.

Besides of simply press the hotkey, Bluetooth preferences can be also selected through OSD menu:

- 1. Press 🗐 button.
- Keep pressing hotkey ▲ ▼ to select [Bluetooth]>[Bluetooth]>[On], Then press "OK" button to make confirmation for your selection.

Tanan I	Bluetooth	On
		• Off
Picture		
Audio		
Bluetooth		
8		
Color		
<b>•</b>		

### Note

- 1. The source device must be Bluetooth enabled.
- 2. This Philips display is Bluetooth CERTIFIED. The source device must be with Bluetooth function, however, in case your source device does not connect or work correctly, check with your device FAQ or vendor directly for direction.
- If output is not smooth during Bluetooth connection, please adjust the distance between your device and Philips display.
- 4. When you open the Bluetooth, the "Attention" pops out and stay for a few senconds, that is OK.
- 5. When playing music, you have a call, Philips display will stop the music. And you can talk through microphone on the Philips display.

### 3.1 SmartImage

### 1 What is it?

SmartImage provides presets that optimize display for different types of content, dynamically adjusting brightness, contrast, color and sharpness in real time. Whether you're working with text applications, displaying images or watching a video, Philips SmartImage delivers great optimized monitor performance.


### 2 Why do I need it?

You want a monitor that delivers optimized display all your favorite types of content, SmartImage software dynamically adjust brightness, contrast, color and sharpness in real time to enhance your monitor viewing experience.

### 3 How does it work?

SmartImage is an exclusive, leading edge Philips technology that analyzes the content displayed on your screen. Based on a scenario you select, SmartImage dynamically enhances the contrast, color saturation and sharpness of images to enhance the contents being displayed - all in real time with the press of a single button.

### 4 How to enable SmartImage?



- 1. Press 🗇 to launch the SmartImage on screen display.
- Keep pressing ▼ ▲ to toggle among Text, Office, Photo, Movie, Game, Economy and Off.

3. The SmartImage on screen display will remain on screen for 5 seconds, or you can also press "OK" to make confirmation.

There are seven modes to select: Text, Office, Photo, Movie, Game, Economy and Off.

SmartImage
Text
Office
Photo
Movie
Game
Economy
Off

- Text: Helps improve reading of text based application like PDF ebooks. By using a special algorithm which increases the contrast and boundary sharpness of text content, the display is optimized for a stress-free reading by adjusting the brightness, contrast and color temperature of the monitor.
- Office: Enhances text and dampens brightness to increase readability and reduce eye strain. This mode significantly enhances readability and productivity when you're working with spreadsheets, PDF files, scanned articles or other general office applications.
- **Photo:** This profile combines color saturation, dynamic contrast and sharpness enhancement to display photos and other images with outstanding clarity in vibrant colors all without artifacts and faded colors.
- Movie: Ramped up luminance, deepened color saturation, dynamic contrast and razor sharpness displays every details in darker areas of your videos without color washout in brighter areas maintaining a dynamic natural values for the ultimate video display.
- Game: Turn on over drive circuit for best response time, reduce jaggy edges for fast

moving objects on screen, enhance contrast ratio for bright and dark scheme, this profile delivers the best gaming experience for gamers.

- Economy: Under this profile, brightness, contrast are adjusted and backlighting finetuned for just right display of everyday office applications and lower power consumption.
- Off: No optimization by SmartImage.

### 3.2 SmartKolor

### 1 What is it?

SmartKolor is a special color extension technology that is able to enhance visual color range to deliver vivid and rich picture performance.

### 2 Why do I need it?

You want the rich, vibrant images for experiencing the outstanding photos or videos.

### 3 How does it work?

SmartKolor will dynamically enhance color saturation and extend visual color range to enrich color quality and performance of your viewing images. SmartKolor is turned off automatically; for example, in Text mode or Office mode, where it is not required.

### 3.3 SmartContrast

### 1 What is it?

Unique technology that dynamically analyzes displayed content and automatically optimizes a Monitor's contrast ratio for maximum visual clarity and viewing enjoyment, stepping up backlighting for clearer, crisper and brighter images or dimming backlighting for clear display of images on dark backgrounds.

### 2 Why do I need it?

You want the very best visual clarity and viewing comfort for every type of content. SmartContrast dynamically controls contrast and adjusts backlighting for clear, crisp, bright gaming and video images or displays clear, readable text for office work. By reducing your monitor's power consumption, you save on energy costs and extend the lifetime of your monitor.

### 3 How does it work?

When you activate SmartContrast, it will analyse the content you are displaying in real time to adjust colors and control backlight intensity. This function will dynamically enhance contrast for a great entertainment experience when viewing videos or playing games.

### 3.4 Philips SmartControl Premium

The new SmartControl Premium software by Phillips allows you to control your monitor via an easy to use on-screen graphic interface. Complicated adjustments are a thing of the past as this user friendly software guides you through fine-tuning resolution, Color calibration, Clock/Phase adjustments, RGB White point adjustment, etc.

Equipped with latest technology in core algorithm for fast processing and response, this Windows 7 compliant eye catching animated lcon based software is ready to enhance your experience with Philips monitors!

### 1 Installation

- Follow the instruction and complete the installation.
- You can launch after installation is completed.
- If you want to launch later, you can either click the shortcut on desktop or toolbar.



### First launch -Wizard

- The first time after installation of SmartControl Premium, it will automatically go to Wizard for first time launch.
- The wizard will guide you through adjustment your monitor performance step by step.
- You can go to Plug-in menu to launch wizard later on as well.
- You can adjust more options without wizard by Standard pane.



### 2 Start with Standard pane

### Adjust menu

- Adjust Menu allow you to adjust Brightness, Contrast, Focus, Position and Resolution.
- You can follow the instruction and do the adjustment.
- Cancel prompts user if you want to cancel installation.





### Color menu


- Color Menu allow you to adjust RGB, Black Level, White Point, Color Calibration, and SmartImage (Please refer to SmartImage section).
- You can follow the instruction and do the adjustment.
- Refer to below table for sub-menu item base on your input.
- Example for Color Calibration.





- 1. "Show Me" starts color calibration tutorial.
- 2. Start starts the 6-step color calibration sequence.
- 3. Quick View loads the before/after images.
- 4. To return to Color home pane, click the Cancel button.
- Enable color calibration by default is on. If unchecked, does not allow for color calibration to happen, dimes out start and quick view buttons.
- 6. Must have patent info in calibration screen.

### First Color Calibration Screen



- Previous button is disabled until the second color screen.
- Next goes to the succeeding target (6-targets).
- Finally go to File > Presets pane.
- Cancel closes the UI and returns to the plug in page.

### SmartImage

Allows user to change setting for better display setting based on content.

When Entertainment is set, SmartContrast and SmartResponse are enabled.



### ECO menu



### Options menu

Theft Deterrence Pane will only be active when selecting Theft Deterrence Mode from the drop-down Plug Ins menu.



To enable Theft Deterrence, clicking Enable Theft Deterrence Mode button brings up the following screen:

- User can enter PIN between 4 and 9 digits numbers only.
- After entering PIN, Accept button takes user to the pop-up dialog box on the following page.
- Minimum minutes set to 5. Slider set to 5 by default.

• Does not require the display be attached to a different host to go into Theft Deterrence mode.

After creating PIN, the Theft Deterrence pane will indicate Theft Deterrence Enabled and provide PIN Options button:

- Theft Deterrence Enabled is displayed.
- Disable Theft Deterrence Mode opens pane screen on next page.
- PIN Options button only available after user creates PIN, button opens secure PIN web site.

**Options>Preferences** - Will only be active when selecting Preferences from the dropdown Options menu. On a non-supported display capable of DDC/CI, only the Help and Options tabs are available.

Station .	40
StratControl Fremium	PHILIPS
🥶 <u>e</u>	Note-arous Program in the second second second response Program is the second second second Program is the second second Program is the second second second second Program is the second second second second second Program is the second second second second second second Program is the second s
	A second and a sec
🧐 📫	
New Conce	

- Displays current preference settings.
- A checked box enables the feature. The check box is a toggle.
- Enable Context Menu on desktop is checked (On) by default. Enable Context menu displays SmartControl Premium selections for Select Preset and Tune Display in the desktop right-click context menu. Disabled removes SmartControl Premium from the right click context menu.
- Enable Task Tray icon is checked (On) by default. Enable context menu shows the task tray menu for SmartControl Premium.

A right click on the task tray icon displays the menu options for Help, Technical Support. Check for Update, About, and Exit. When Enable task tray menu is disabled, the task tray icon will only display EXIT.

- Run at Startup is checked (On) by default. When disabled, SmartControl Premium will not launch at start or be in the task tray. The only way to launch SmartControl Premium is either from the desktop short cut or from the program file. Any preset set to run at startup will not load when this box is unchecked (Disabled).
- Enable transparency mode (Windows 7, Vista, XP). Default is 0% Opaque.

**Options>Input** - Will only be active when selecting Input from the drop-down Options menu. On a non-supported display capable of DDC/CI, only the Help and Options tabs are available. All other SmartControl Premium tabs are not available.



- Display the Source instruction pane and current input source setting.
- On single input displays, this pane will not be visible.

**Options>Audio** - Will only be active when selecting Audio from the drop-down Options menu.

On a non-supported display capable of DDC/ Cl, only the Help and Options tabs are available.



### **Option>Auto Pivot**

Star See	10
StratControl Fremium	PHILIPS
	Auto See: The Auto Sector Control of Control The Auto Sector Sector Sector Sector Auto Sector Sector Sector Biological Sector Biological Sector S
1 . Car	

### Help menu

Help>User Manual - Will only be active when selecting User Manual from the drop-down Help menu. On a non-supported display capable of DDC/Cl, only the Help and Options tabs are available.




Help>Version - Will only be active when selecting Version from the drop- down Help menu. On a non-supported display capable of DDC/Cl, only the Help and Options tabs are available.



### Context Sensitive menu

The Context Sensitive menu is Enabled by default. If Enable Context Menu has been checked in the Options>Preferences pane, then the menu will be visible.



The Context Menu has four entries:

- SmartControl Premium When selected the About screen is displayed.
- Select Preset Provides a hierarchical menu of saved presets for immediate use. A check mark shows the currently selected preset. Factory Preset can also be called from the drop-down menu.
- **Tune Display** Opens the SmartControl Premium control panel.
- SmartImage Check current settings: Off, Office, Photo, Movie, Text, Game, Economy.

### Task Tray Menu Enabled

The task tray menu can be displayed by rightclicking on the SmartControl Premium icon from the task tray. Left Click will launch the application.



The task tray has five entries:

- Help Access to User Manual file: Open User Manual file using the default browser window.
- Technical Support Displays the tech support page.
- Check for Update Takes the user to PDI Landing and checks the user's version against the most current available.
- About Displays detailed reference information: product version, release information, and product name.
- Exit Close SmartControl Premium.

To run SmartControl Premium again, either select SmartControl Premium from Program menu, double-click the desktop PC icon, or restart the system.



### Task Tray Menu Disabled

When the Task Tray is disabled in the preference folder, only the Exit selection is available. To completely remove SmartControl Premium from the task tray, disable Run at Startup in Options>Preferences.

### 

All the illustrations in this section are for reference only. SmartControl software version might be changed without notification. Please always check official Portrait website <u>www.</u> <u>portrait.com/dtune/phl/enu/index</u> to download the latest version of SmartControl software.

# 4. Technical Specifications 4. Technical Specifications

Monitor Panel Type         AH-IPS LCD           Backlight         LED           Panel Size         27"W (68.6 cm)           Aspect Ratio         16:9           Pixel Pitch         0.3114(H) mm x 0.3114(V) mm           Brightness         250 cd/m²           SmartContrast         20.000/01           Contrast Ratio (typ.)         1000:1           Response Time (typ.)         14 ms           SmartResponse Time (typ.)         5 ms(GG)           Optimum Resolution         1920 × 1080 @ 60 Hz           Viewing Angle         178° (H) / 178° (V) @ CR > 10           Display Colors         16.7 M           Vertical Refresh Rate         56 Hz - 76 Hz           Horizontal Frequency         30 kHz - 83 kHz           MHL         1080P @ 30 Hz           sRGB         YES           Connectivity         275CSQSB 275CSQAW: DVI (Digital, MCP), MHL-HDMI (Digital, HDCP)           Input Signal         Separate Sync, Sync on Green           Audio Out         275CSQSB, 275CSQAW: VPC audio-in, Earphone out           Convenience         Imput No grata Sync, Sync on Green           Juser Convenience         Imput Nagrain, Spraish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Polsh, 275CSQAW:           OSD Languages         Impid Nagrain, Sprais	Picture/Display		
Danel Size27" W (68.6 cm)Aspect Ratio16.9Pixel Pitch0.3114(H) mm x 0.3114(V) mmBrightness250 cd/m²SmartContrast20.000,000:1Contrast Ratio (typ.)1000:1Response Time (typ.)14 msSmartResponse Time (typ.)5 ms(GtG)Optimum Resolution1920 x 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ C/R > 10Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivity275C5QSB, 275C5QSW: DVI (Digital),VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDMI1(Digital,HDCP), HDMI2(Digital,HDCP), MHL-HDMI (Digital,HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275C5QHAB, 275C5QHAW: PC audio-in, Earphone outConvenience7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)User Convenience7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)OSD LanguagesT/W $< 0/$ $< 1/$ $< 0/$ $< 1/$ $< 0/$ $< 1/$ $< 0/$ $< 1/$ $< 0/$ $< 0/$ Other ConvenienceEnglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, LinuxStandDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Monitor Panel Type	AH-IPS LCD	
Aspect Ratio16.9Pixel Pitch0.3114(H) mm × 0.3114(V) mmBrightness250 cd/m²SmartContrast20,000,000:1Contrast Ratio (typ.)1000:1Response Time (typ.)5 ms(GtG)Optimum Resolution1920 × 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ C/R > 10Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 HHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal Input275C5QSB, 275C5QSW: DVI (Digital), VGA (Analog), 275C5QHAB, 275C5QHAW: VGA(Analog), HDMI1 (Digital, HDCP), HDMI2 (Digital, HDCP), MHL-HDMI (Digital, HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275C5QSB, 275C5QW: PC audio-in, Earphone outConvenience7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)User Convenience7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)OSD Languages7 W×2 Bluetooth speaker, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, LinuxStandDD/C/L, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Backlight	LED	
Pixel Pitch0.3114(H) mm × 0.3114(V) mmBrightness250 cd/m²SmartContrast20,000,000:1Contrast Ratio (typ.)1000:1Response Time (typ.)14 msSmartResponse Time (typ.)5 ms(GtG)Optimum Resolution1920 × 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ C/R > 10Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 Hz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal Input275CSQSB, 275CSQSW: DVI (Digital), VGA (Analog), 275CSQHAB, 275CSQHAW: VGA(Analog), HDM11(Digital, HDCP), HDM12(Digital, HDCP), MHL-HDM1 (Digital, HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275CSQHAB, 275CSQHAW: PC audio-in, Earphone outConvenience $\mathbb{P}/4$ $\mathbb{A}/\mathbb{P}$ Built-in speaker7 W×2 Bluetooth speaker (245CSQHAB, 245CSQHAW)QSD Languages $\mathbb{P}/4$ $\mathbb{A}/\mathbb{P}$ OSD LanguagesEnglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/Cl, sRGB, Windows 8/7/Vista/XP, Mac OSX, LinuxStand	Panel Size	27" W (68.6 cm)	
Brightness250 cd/m²SmartContrast20,000,000:1Contrast Ratio (typ.)1000:1Response Time (typ.)14 msSmartResponse Time (typ.)5 ms(GrG)Optimum Resolution1920 x 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ C/R > 10Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal Input275C5QHAB, 275C5QHAW: VGA(Analog), HDM11(Digital,HDCP), HDM12(Digital,HDCP), MHL-HDM1 (Digital, HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275C5QHAB, 275C5QHAW: PC audio-in, Earphone outConvenience170/4Built-in speaker7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)QSD LanguagesCiplish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Aspect Ratio	16:9	
SmartContrast20,000,00:1Contrast Ratio (typ.)1000:1Response Time (typ.)14 msSmartResponse Time (typ.)5 ms(GtG)Optimum Resolution1920 × 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ $C/R > 10$ Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal Input275C5QSB, 275C5QSW: DVI (Digital), VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDM1(Digital, HDCP), HDM12(Digital, HDCP), MHL-HDM1 (Digital, HDCP)Input SignalSeparate Sync, Sync on Green Audio OutAudio Out275C5QSB, 275C5QSW: 275C5QHAB, 275C5QHAW: PC audio-in, Earphone outConvenience7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW) 275C5QSB, 275C5QSW: $@P/4 @ P/A @ P/A @ /oK @275C5QHAB, 275C5QHAW:User ConvenienceEnglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch,Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish,Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese,Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux$	Pixel Pitch	0.3114(H) mm x 0.3114(V) mm	
Contrast Ratio (typ.)1000:1Response Time (typ.)14 msSmartResponse Time (typ.)5 ms(GtG)Optimum Resolution1920 × 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ C/R > 10Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal Input275C5QSH, 275C5QSW: DVI (Digital), VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDM1(Digital, HDCP), HDM12(Digital, HDCP), MHL-HDMI (Digital, HDCP)Input SignalSeparate Sync, Sync on Green Audio OutAudio Out275C5QSB, 275C5QSW: PC audio-in, Earphone outConvenience7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)User Convenience7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)OSD LanguagesEnglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Brightness	250 cd/m <sup>2</sup>	
Response Time (typ.)14 msSmartResponse Time (typ.)5 ms(GtG)Optimum Resolution1920 x 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ C/R > 10Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal Input275CSQSB, 275CSQSW: DVI (Digital), VGA (Analog) 275CSQHAB, 275CSQHAW: VGA(Analog), HDMI1(Digital, HDCP), HDMI2(Digital, HDCP), MHL-HDMI (Digital, HDCP), HDMI2(Digital, HDCP), MHL-HDMI (Digital, HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275CSQHAB, 275CSQSW:Convenience7W×2 Bluetooth speaker (245CSQHAB), 245CSQHAW)User Convenience $@/                                    $	SmartContrast	20,000,000:1	
SmartResponse Time (typ.)5 ms(GtG)Optimum Resolution1920 x 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ C/R > 10Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal Input275C5QSB, 275C5QSW: DVI (Digital), VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDM11 (Digital, HDCP), HDM12(Digital, HDCP), MHL-HDMI (Digital, HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275C5QSHAB, 275C5QHAW: PC audio-in, Earphone outConvenience10 × 275C5QSB, 275C5QSW:Built-in speaker7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)User Convenience275C5QHAB, 275C5QHAW:OSD LanguagesEnglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Contrast Ratio (typ.)	1000:1	
Optimum Resolution1920 × 1080 @ 60 HzViewing Angle178° (H) / 178° (V) @ $C/R > 10$ Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ 30HzsRGBYESConnectivitySignal InputSignal Input275C5QSB, 275C5QSW: DVI (Digital),VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDM11(Digital,HDCP), HDM12(Digital,HDCP), MHL-HDMI (Digital,HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275C5QHAB, 275C5QSW:ConvenienceBuilt-in speaker7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)Q75C5QSB, 275C5QSW:User Convenience $\overline{\mathbb{P}}/4$ $\overline{\mathbb{P}}/\Phi$ OSD LanguagesEnglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean $\overline{\mathbb{P}}/V$ Other ConvenienceKensington LockPlay CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, LinuxStand	Response Time (typ.)	14 ms	
Viewing Angle $178^{\circ}$ (H) / $178^{\circ}$ (V) @ $C/R > 10$ Display Colors16.7 MVertical Refresh Rate56 Hz - 76 HzHorizontal Frequency30 kHz - 83 kHzMHL1080P @ $30$ HzsRGBYESConnectivitySignal Input275C5QSB, 275C5QSW: DVI (Digital),VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDM11 (Digital,HDCP), HDM12(Digital,HDCP), MHL-HDM1 (Digital,HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275C5QHAB, 275C5QHAW: PC audio-in, Earphone outConvenienceBuilt-in speaker7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)275C5QSB, 275C5QSW: $\textcircled{D}/4$ $\textcircled{A}/ \textcircled{O}/2$ User Convenience $\fbox{D}/4$ $\textcircled{A}/ \textcircled{O}/2$ $\textcircled{O}/4$ $\textcircled{O}/2$ OSD LanguagesEnglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, KoreanOther ConvenienceKensington LockPlug & Play CompatibilityDDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, LinuxStand	SmartResponse Time (typ.)	5 ms(GtG)	
Display Colors       16.7 M         Vertical Refresh Rate       56 Hz - 76 Hz         Horizontal Frequency       30 kHz - 83 kHz         MHL       1080P @ 30Hz         sRGB       YES         Connectivity       275C5QSB, 275C5QSW: DVI (Digital), VGA (Analog)         Signal Input       275C5QAHAB, 275C5QHAW: VGA(Analog), HDMI1 (Digital, HDCP), HDMI2(Digital, HDCP), MHL-HDMI         Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         0SD Languages       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         0SD Languages       Freglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean         Other Convenience       Kensington Lock         Plug & Play Compatibility       DDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Optimum Resolution	1920 × 1080 @ 60 Hz	
Vertical Refresh Rate       56 Hz - 76 Hz         Horizontal Frequency       30 kHz - 83 kHz         MHL       1080P @ 30Hz         sRGB       YES         Connectivity         Signal Input       275C5QSB, 275C5QSW: DVI (Digital), VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDMI1 (Digital, HDCP), HDMI2(Digital, HDCP), MHL-HDMI (Digital, HDCP)         Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience       7W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7V×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         0SD Languages       Finglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean         Other Convenience       Kensington Lock         Plug & Play Compatibility       DDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Viewing Angle	178° (H) / 178° (V) @ C/R > 10	
Horizontal Frequency       30 kHz - 83 kHz         MHL       1080P @ 30Hz         sRGB       YES         Connectivity       275C5QSB, 275C5QSW: DVI (Digital),VGA (Analog)         Signal Input       275C5QHAB, 275C5QHAW: VGA(Analog), HDMI1 (Digital,HDCP), HDMI2(Digital,HDCP), MHL-HDMI (Digital,HDCP)         Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7 VV×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         0SD Languages       English, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean         Other Convenience       Kensington Lock         Plug & Play Compatibility       DDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Display Colors	16.7 M	
MHL       1080P @ 30Hz         sRGB       YES         Connectivity       275C5QSB, 275C5QSW: DVI (Digital),VGA (Analog)         Signal Input       275C5QHAB, 275C5QHAW: VGA(Analog),         HDMI1 (Digital,HDCP), HDMI2(Digital,HDCP), MHL-HDMI       (Digital,HDCP)         Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience       275C5QSB, 275C5QSW:         Built-in speaker       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         275C5QSB, 275C5QSW:       10/4         (Diser Convenience       10/4         OSD Languages       English, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean         Other Convenience       Kensington Lock         Plug & Play Compatibility       DDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Vertical Refresh Rate	56 Hz - 76 Hz	
sRGB       YES         Connectivity       275C5QSB, 275C5QSW: DVI (Digital), VGA (Analog)         Signal Input       275C5QHAB, 275C5QHAW: VGA(Analog),         HDMI1 (Digital, HDCP), HDMI2(Digital, HDCP), MHL-HDMI       (Digital, HDCP)         Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience       7W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         User Convenience       7V×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         0SD Languages       Finglish, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean         Other Convenience       Kensington Lock         Plug & Play Compatibility       DDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	Horizontal Frequency	30 kHz - 83 kHz	
Connectivity       275C5QSB, 275C5QSW: DVI (Digital), VGA (Analog)         Signal Input       275C5QHAB, 275C5QHAW: VGA(Analog),         HDMI1 (Digital, HDCP), HDMI2(Digital, HDCP), MHL-HDMI       (Digital, HDCP)         Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Built-in speaker       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         275C5QSB, 275C5QSW:       1/1 ≤)/0K          Were Convenience       275C5QHAB, 275C5QHAW:         User Convenience       275C5QHAB, 275C5QHAW:         OSD Languages       English, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean         Other Convenience       Kensington Lock         Plug & Play Compatibility       DDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux	MHL	1080P @ 30Hz	
Signal Input275C5QSB, 275C5QSW: DVI (Digital),VGA (Analog) 275C5QHAB, 275C5QHAW: VGA(Analog), HDMI1(Digital,HDCP), HDMI2(Digital,HDCP), MHL-HDMI (Digital,HDCP)Input SignalSeparate Sync, Sync on GreenAudio Out275C5QHAB, 275C5QHAW: PC audio-in, Earphone outConvenienceBuilt-in speaker7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)275C5QSB, 275C5QSW:Imput Signal7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)Over the provide the speaker (245C5QHAB, 245C5QHAW)275C5QSB, 275C5QSW:Imput SignalImput SignalImput SignalOver the provide the speaker (245C5QHAB, 245C5QHAW)275C5QSB, 275C5QSW:Imput SignalImput SignalImput SignalOver the provide the speaker (245C5QHAB, 245C5QHAW)275C5QSB, 275C5QSW:Imput SignalImput SignalImput SignalOver tolspan="4">Imput SignalImput SignalOver tolspan="4">Imput SignalImput SignalImput SignalImput SignalOver tolspan="4">Imput SignalSeparate Sync, Sync on GreenImput SignalImput SignalOver tolspan="4" Imput SignalImput Signal <td>sRGB</td> <td>YES</td>	sRGB	YES	
Signal Input       275C5QHAB, 275C5QHAW: VGA(Analog), HDMI1(Digital,HDCP), HDMI2(Digital,HDCP), MHL-HDMI (Digital,HDCP)         Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience         Built-in speaker       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         275C5QSB, 275C5QSW:       Import         Import       Import         User Convenience       Import         Import       Separate Sync, Sync on Green         Import       Import         Import       Import <tr< td=""><td>Connectivity</td><td></td></tr<>	Connectivity		
Input Signal       Separate Sync, Sync on Green         Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience       7W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         Built-in speaker       7W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         275C5QSB, 275C5QSW:       275C5QHAB, 245C5QHAW)         User Convenience       @/<	Signal Input	275C5QHAB, 275C5QHAW: VGA(Analog), HDMI1(Digital,HDCP), HDMI2(Digital,HDCP), MHL-HDMI	
Audio Out       275C5QHAB, 275C5QHAW: PC audio-in, Earphone out         Convenience         Built-in speaker       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         275C5QSB, 275C5QSW:       275C5QSB, 275C5QSW:         Image: Convenience       Image: Convenience         Convenience       English, German, Spanish, Greek, French, Italian, Hungarian, Dutch, Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean         Other Convenience       Kensington Lock         Plug & Play Compatibility       DDC/Cl, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux         Stand       Image: Conventibility	Input Signal		
Convenience         Built-in speaker       7 W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)         275C5QSB, 275C5QSW:       275C5QSB, 275C5QSW:         Imp/<			
275C5QSB, 275C5QSW:         Imp/<	Convenience		
Image: bit is the second se	Built-in speaker	7W×2 Bluetooth speaker (245C5QHAB, 245C5QHAW)	
OSD Languages     Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finnish, Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chinese, Japanese, Korean       Other Convenience     Kensington Lock       Plug & Play Compatibility     DDC/CI, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux       Stand     Ventor	User Convenience	ID / ▲ ▲/▼ ⊕/▲ ■/OK () 275C5QHAB, 275C5QHAW:	
Plug & Play Compatibility DDC/Cl, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux Stand	OSD Languages Portuguese, Brazil Portuguese, Polish, Russian, Swedish, Finn Turkish, Czech, Ukranian, Simplified Chinese, Traditional Chin		
Stand	Other Convenience		
	Plug & Play Compatibility DDC/Cl, sRGB, Windows 8/7/Vista/XP, Mac OSX, Linux		
Tilt -5 / +20	Stand		
	Tilt	-5 / +20	

### 275C5QSB, 275C5QSW:

Power	
On Mode	23.80 W (typ.), 26.65 W (max.)
Sleep (Standby)	0.5 W
Off	0.3 W
Power LED indicator	On mode: White, Standby/Sleep mode: White (blinking)
Power Supply	External, 100-240 VAC, 50-60 Hz

### 275C5QHAB, 275C5QHAW:

Power	
On Mode	23.39 W (typ.), 42.78 W (max.)
Sleep (Standby)	0.5 W
Off	0.3 W
Power LED indicator	On mode: White, Standby/Sleep mode: White (blinking)
Power Supply	External, 100-240 VAC, 50-60 Hz

Dimension	
Product with stand (W×H×D)	613 x 467 x 238 mm
Weight	
Product with stand	5.67 kg
Product with packaging	7.31 kg
Operating Condition	
Temperature range (operation)	0°C to 40 °C
Temperature range (Non-operation)	-20°C to 60°C
Relative humidity	20% to 80%
MTBF	30,000 hrs
Environmental	
ROHS	YES
EPEAT	Silver ( <u>www.epeat.net</u> )
Packaging	100% recyclable
Specific Substances	100% PVC BFR free housing
Energy Star	YES
Compliance and standards	
Regulatory Approvals	CE Mark, FCC Class B, CU, SEMKO, TCO Certified, ETL, BSMI, ISO9241-307, CB, MEPS, SASO, KUCAS, EPA
Cabinet	
Color	275C5QSW, 275C5QHAW: White 275C5QSB, 275C5QHAB: Black
Finish	Glossy

### Note

1. EPEAT Gold or Silver is valid only where Philips registers the product. Please visit <u>www.epeat.net</u>

for registration status in your country.

- 2. This data is subject to change without notice. Go to <u>www.philips.com/support</u> to download the latest version of leaflet.
- 3. Smart response time is the optimum value from either GtG or GtG (BW) tests.

## 4.1 Resolution & Preset Modes

### 1 Maximum Resolution

1920 × 1080 @ 60 Hz (analog input) 1920 × 1080 @ 60 Hz (digital input)

### 2 Recommended Resolution

1920 × 1080 @ 60 Hz (digital input)

H. freq (kHz)	Resolution	V. freq (Hz)
31.47	720 × 400	70.09
31.47	640 × 480	59.94
35.00	640 × 480	66.67
37.86	640 × 480	72.81
37.50	640 × 480	75.00
37.88	800 × 600	60.32
46.88	800 × 600	75.00
48.36	1024 × 768	60.00
60.02	1024 × 768	75.03
63.89	1280 x 1024	60.02
79.98	1280 x 1024	75.03
55.94	1440 × 900	59.89
70.64	1440 × 900	74.98
65.29	1680 x 1050	59.95
67.50	1920 × 1080	60.00

### Note

Please notice that your display works best at native resolution of  $1920 \times 1080$  @ 60Hz. For best display quality, please follow this resolution recommendation.

## 5. Power Management

If you have VESA DPM compliance display card or software installed in your PC, the monitor can automatically reduce its power consumption when not in use. If an input from a keyboard, mouse or other input device is detected, the monitor will 'wake up' automatically.The following table shows the power consumption and signaling of this automatic power saving feature:

### 275C5QSB, 275C5QSW:

Power Management Definition					
VESA Mode	Video	H-sync	V-sync	Power Used	LED Color
Active	ON	Yes	Yes	23.80 W (typ.) 26.65 W (max.)	White
Sleep (Standby)	OFF	No	No	0.5 W (typ.)	White (blink)
Switch Off	OFF	-	-	0.3 W (typ.)	OFF

### 275C5QHAB, 275C5QHAW:

Power Management Definition					
VESA Mode	Video	H-sync	V-sync	Power Used	LED Color
Active	ON	Yes	Yes	23.39 W (typ.) 42.78 W (max.)	White
Sleep (Standby)	OFF	No	No	0.5 W (typ.)	White (blink)
Switch Off	OFF	-	-	0.3 W (typ.)	OFF

The following setup is used to measure power consumption on this monitor:

- Native resolution: 1920 × 1080
- Contrast: 50%
- Brightness: 250 nits
- Color temperature: 6500k with full white pattern

### Solution Note

This data is subject to change without notice.

## 6. Regulatory Information

### Congratulations!

This product is designed for both you and the planet!

TCO Development works for sustainable IT - manufacture, use and recycling of IT products

reflecting environmental, social and economic responsibility.

TCO Certified is a third party verified program, where every product model is tested by an accredited impartial test laboratory.TCO Certified represents one of the toughest certifications for ICT products worldwide.

### Some of the Usability features of TCO Certified Displays:

- Visual Ergonomics for image quality is tested to ensure top performance and reduce sight and strain problems. Important parameters are Resolution, Luminance, Contrast, Reflection and Colour characteristics
- Products are tested according to rigorous safety standards at impartial laboratories
- Electric and magnetic fields emissions as low as normal household background levels
- Workload ergonomics to ensure a good physical environment

## Some of the Environmental features of TCO Certified Displays:

- Production facilities have an Environmental Management System (EMAS or ISO 14001)
- Low energy consumption to minimize
   climate impact
- Restrictions on Chlorinated and Brominated flame retardants, plasticizers, plastics and heavy metals such as cadmium, mercury and lead (RoHS compliance)
- Both product and product packaging is prepared for recycling
- The brand owner offers take-back options

### Corporate Social Responsibility

 The brand owner demonstrates the product is manufactured under working practices that promote good labour relations and working conditions.

The Criteria Document can be downloaded from our web site. The criteria included in this label have been developed by TCO Development in co-operation with scientists, experts, users as well as manufacturers all over the world. Since the end of the 1980s TCO has been involved in influencing the development of IT equipment in a more user and environmentally friendly direction. Our ICT product labeling system began in 1992 and is now requested by users and ICT-manufacturers all over the world.

For displays with glossy bezels, the user should consider the placement of the display as the bezel may cause disturbing reflections from surrounding light and bright surfaces.

For more information, please visit: www.tcodevelopment.com



(Only for selective models)

### Lead-free Product



Lead free display promotes environmentally sound recovery and disposal of waste from electrical and electronic equipment. Toxic

substances like Lead has been eliminated and compliance with European community's stringent RoHs directive mandating restrictions on hazardous substances in electrical and electronic equipment have been adhered to in order to make Philips monitors safe to use throughout its life cycle.

### EPEAT

(www.epeat.net)



The EPEAT (Electronic Product Environmental Assessment Tool) program evaluates computer

desktops, laptops, and monitors based on 51 environmental criteria developed through an extensive stakeholder consensus process supported by US EPA.

EPEAT system helps purchasers in the public and private sectors evaluate, compare and select desktop computers, notebooks and monitors based on their environmental attributes. EPEAT also provides a clear and consistent set of performance criteria for the design of products, and provides an opportunity for manufacturers to secure market recognition for efforts to reduce the environmental impact of its products.

### Benefits of EPEAT

Reduce use of primary materials Reduce use of toxic materials

Avoid the disposal of hazardous waste EPEAT'S requirement that all registered products meet ENERGY STAR's energy efficiency specifications, means that these products will consume less energy throughout their life.

### CE Declaration of Conformity

This product is in conformity with the following standards

- EN60950-1:2006+A11:2009+A1: 2010+A12:2011 (Safety requirement of Information Technology Equipment).
- EN55022:2010(Radio Disturbance requirement of Information Technology Equipment).
- EN55024:2010 (Immunity requirement of Information Technology Equipment).
- EN61000-3-2:2006+A1:2009+A2:2009 (Limits for Harmonic Current Emission).
- EN61000-3-3:2008 (Limitation of Voltage Fluctuation and Flicker) following provisions of directives applicable.
- 2006/95/EC (Low Voltage Directive).
- 2004/108/EC (EMC Directive).
- 2009/125/EC (ErP Directive, EC No. 1275/2008 Implementing Directive for Standby and Off mode power consumption)

And is produced by a manufacturing organization on ISO9000 level.

- ISO9241-307:2008 (Ergonomic requirement, Analysis and compliance test methods for electronic visual displays).
- GS EK1-2000:2011 (GS mark requirement).
- prEN50279:1998 (Low Frequency Electric and Magnetic fields for Visual Display).
- MPR-II (MPR:1990:8/1990:10 Low Frequency Electric and Magnetic fields).
- TCO CERTIFIED (Requirement for Environment Labeling of Ergonomics, Energy, Ecology and Emission, TCO: Swedish Confederation of Professional Employees) for TCO versions.

#### 6. Regulatory Infomation

### **Energy Star Declaration**

(www.energystar.gov)



As an ENERGY STAR<sup>®</sup> Partner, we have determined that this product meets the ENERGY STAR<sup>®</sup> guidelines for energy efficiency.

### Solution Note

We recommend you switch off the monitor when it is not in use for a long time.

### Federal Communications Commission (FCC) Notice (U.S. Only)

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Use only RF shielded cable that was supplied with the monitor when connecting this monitor to a computer device.

To prevent damage which may result in fire or shock hazard, do not expose this appliance to rain or excessive moisture.

THIS CLASS B DIGITAL APPARATUS MEETS ALL REQUIREMENTS OF THE CANADIAN INTERFERENCE-CAUSING EQUIPMENT REGULATIONS.

### FCC Declaration of Conformity

Declaration of Conformity for Products Marked with FCC Logo,

### United States Only



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## Commission Federale de la Communication (FCC Declaration)

Cet équipement a été testé et déclaré conforme auxlimites des appareils numériques de class B,aux termes de l'article 15 Des règles de la FCC. Ces limites sont conçues de façon à fourir une protection raisonnable contre les interférences nuisibles dans le cadre d'une installation résidentielle.

CET appareil produit, utilise et peut émettre des hyperfréquences qui, si l'appareil n'est pas installé et utilisé selon les consignes données, peuvent causer des interférences nuisibles aux communications radio.

Cependant, rien ne peut garantir l'absence d'interférences dans le cadre d'une installation particulière. Si cet appareil est la cause d'interférences nuisibles pour la réception des signaux de radio ou de télévision, ce qui peut être décelé en fermant l'équipement, puis en le remettant en fonction, l'utilisateur pourrait essayer de corriger la situation en prenant les mesures suivantes:

- Réorienter ou déplacer l'antenne de réception.
- Augmenter la distance entre l'équipement et le récepteur.
- Brancher l'équipement sur un autre circuit que celui utilisé par le récepteur.
- Demander l'aide du marchand ou d'un technicien chevronné en radio/télévision.
- Toutes modifications n'ayant pas reçu l'approbation des services compétents en matière de conformité est susceptible d'interdire à l'utilisateur l'usage du présent équipement.

N'utiliser que des câbles RF armés pour les connections avec des ordinateurs ou périphériques.

CET APPAREIL NUMERIQUE DE LA CLASSE **B RESPECTE TOUTES LES EXIGENCES DU** REGIEMENT SUR LE MATERIEL BROUILLEUR DU CANADA.

### EN 55022 Compliance (Czech Republic Only)

The overall being the calling  $r_{\rm p}$  is device an obtained in EM 20002,  $r_{\rm s}$  when the spectrum planet final time that  $r_{\rm s}$  and  $r_{\rm s}$  and  $r_{\rm s}$  and  $r_{\rm s}$  are the following approximation of the following approximation of the second state of protocol up to at the second state of the second state of protocol up to at the second state of the s denote is ablight to take all stage necessary to service equipped of any tenance to sale contrustonion prodel: devices.

Palas di suar tran legensian di bina problada secolaren, Banquinia ata da vilaj A proba 86 AV200, openal antarea teng da Bary II yante 764 86029. Pre estimat enterente en Bary il otare nat - construction (see the PATRATE paint active spirit Degler 1.1 in Acrel to be reacting which is not an implet Saffarent (and Safety processing accelve fallows) age (by 1.2 alog actual) and the rit.

### Polish Center for Testing and Certification Notice

The equipment should draw power from a socket with an attached protection circuit (a three-prong socket). All equipment that works together (computer, monitor, printer, and so on) should have the same power supply source.

The phasing conductor of the room's electrical installation should have a reserve short-circuit protection device in the form of a fuse with a nominal value no larger than 16 amperes (A).

To completely switch off the equipment, the power supply cable must be removed from the power supply socket, which should be located near the equipment and easily accessible.

A protection mark "B" confirms that the equipment is in compliance with the protection usage requirements of standards PN-93/T-42107 and PN-89/E-06251.

#### Wymegenia Polskiego Centrum Badań i Certyfikocji

Device is particular by the interpolation productory of solar action and a solar opportunity of initial solar Modern approximation and accepted a dampate, makes that the particular particular any composition.

Invalidação de la vecera paralecencente provinse survivaira, provensión de aveças esterar as primar prevel estantiante ve para el hereita cultur e vanoriei conservante de arte aveça de 16.5 temperios: We de vallew is provident a statistical a viet data and a statistical el we was table. En la graph o general de la Maria previone angla serie de la viet data de la statistica de agos. Zoak hop: see fature. IN some or he special/complexes or any rescanced herse beneficial any itse many computer Prior in the Prior P

#### Pozostale Instrukcje bezpieczeństwa

- b is easierly edge and we provide and provide the form of the limit of an element space we provide the definition of the edge space of the edge of
- Per antinense ar ong ming a single gen pada anglesis de allergens serantani lab què la contra serantani lab què la contra page della contra page de la co
- Manufacty and and applying and implicitly in plants are given hangements;
- <sup>4</sup> Microbioly report to balance production of a strendy reprint transmission page page to the inspectational point (dependentic page), provide an activity demonstrative proceedings).
- <sup>1</sup> System experiments are not an investigated as a data of size while it is due of a formula, in some biddens denotes we it for each bidden while it can be obtained as compared as a second method of the state of the second of the second size of compared and second size of the second size of the second size of the second size of the second size.

### North Europe (Nordic Countries) Information

### Placering/Ventilation

### VARNING:

FÖRSÄKRA DIG OM ATT HUVUDBRYTARE OCH UTTAG ÄR LÄTÅTKOMLIGA, NÄR DU STÄLLER DIN UTRUSTNING PÅPLATS.

Placering/Ventilation

### ADVARSEL:

SØRG VED PLACERINGEN FOR, AT NETLEDNINGENS STIK OG STIKKONTAKT ER NEMTTILGÆNGELIGE.

Paikka/Ilmankierto

### VAROITUS:

SIJOITA LAITE SITEN, ETTÄ VERKKOJOHTO VOIDAAN TARVITTAESSA HELPOSTI IRROTTAA PISTORASIASTA.

### Plassering/Ventilasjon

### ADVARSEL:

NÅR DETTE UTSTYRET PLASSERES, MÅ DU PASSE PÅ AT KONTAKTENE FOR STØMTILFØRSEL ER LETTE Å NÅ.

### BSMI Notice (Taiwan Only)

符合乙類資訊畫品之標準

### Ergonomie Hinweis (nur Deutschland)

Der von uns gelieferte Farbmonitor entspricht den in der "Verordnung über den Schutz vor Schäden durch Röntgenstrahlen" festgelegten Vorschriften.

Auf der Rückwand des Gerätes befindet sich ein Aufkleber, der auf die Unbedenklichkeit der Inbetriebnahme hinweist, da die Vorschriften über die Bauart von Störstrahlern nach Anlage III ¤ 5 Abs. 4 der Röntgenverordnung erfüllt sind.

Damit Ihr Monitor immer den in der Zulassung geforderten Werten entspricht, ist darauf zu achten, daß

- 1. Reparaturen nur durch Fachpersonal durchgeführt werden.
- 2. nur original-Ersatzteile verwendet werden.
- 3. bei Ersatz der Bildröhre nur eine bauartgleiche eingebaut wird.

Aus ergonomischen Gründen wird empfohlen, die Grundfarben Blau und Rot nicht auf dunklem Untergrund zu verwenden (schlechte Lesbarkeit und erhöhte Augenbelastung bei zu geringem Zeichenkontrast wären die Folge). Der arbeitsplatzbezogene Schalldruckpegel nach DIN 45 635 beträgt 70dB (A) oder weniger.

ACHTUNG: BEIM AUFSTELLEN DIESES GERÄTES DARAUF ACHTEN, DAß NETZSTECKER UND NETZKABELANSCHLUß LEICHT ZUGÄNGLICH SIND.

#### 6. Regulatory Infomation

### EU Energy Label



The European Energy Label informs you on the energy efficiency class of this product. The greener the energy efficiency class of this product is the lower the energy it consumes.

On the label, you can find the energy efficiency class, the average power consumption of this product in use and the average energy consumption for 1 year.

### Note

The EU Energy Label will be ONLY applied on the models bundling with HDMI and TV tuners.

### China RoHS

The People's Republic of China released a regulation called "Management Methods for Controlling Pollution by Electronic Information Products" or commonly referred to as China RoHS. All products produced and sold for China market have to meet China RoHS request.

中国电子信息产品污染控制标识要求(中国 RoHS法规标示要求)产品中有毒有害物质或 元素的名称及含量

	有毒有害物质或元素					
部件名称	铅 (Pb)	汞 (Hg)	뗾 (Cd)	六价铬 (Cr6+)	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
外壳	0	0	0	0	0	0
液晶显示屏/灯管	×	0	0	0	0	0
电路板组件*	×	0	0	0	0	0
电源适配线	×	0	0	0	0	0
电源线/连接线	×	0	0	0	0	0

- \*: 电路板组件包括印刷电路板及其构成的零部件,如电阻、电容、集成电路、连接器等。
- O:表示该有毒有害物质在该部件所有均质材料中的含量均在《电子信息产品 中有毒有害物质的限量要求标准》规定的限量要求以下。
- X: 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出《电子信息产品中有毒有害物质的限量要求标准》规定的限量要求;但是上表中打 "X"的部件,符合欧盟RoHS法规要求(属于豁免的部分)。



此标识指期限(十年),电子信息产品中含有的有 毒有害物质或元素在正常使用的条件下不会发生 外泄或突变,电子信息产品用户使用该电子信息 产品不会对环境造成严重污染或对其人身、财产 造成严重损害的期限。

#### 中国教教教率标识

根据中国大陆《建筑东南桥积管理办法》不且示器符合以下设试:

開始改革(34W) 2023年12 2023年12	> 1.06
#\$2里信	115
\$6316.8	G8/21520-2008

#### 详细有关信息项目的中国影响和识别:http://www.energy/abs/gow.on

《废弃电器电子产品回收处理管理条例》提示性 说明

为了更好地关爱及保护地球,当用户不再需要此 产品或产品寿命终止时,请遵守国家废弃电器电 子产品回收处理相关法律法规,将其交给当地具 有国家认可的回收处理资质的厂商进行回收处 理。



### VCCI-B

この装置は、クラスB情報技術装置です。 この装置は、家庭環境で使用することを目 的としていますが、この装置がラジオやテ レビジョン受信機に近接して使用される と、受信障害を引き起こすことがありま す。

\$P17545	×	化学物質表					
粗分類	ų	Pb	Hg	Cd	Cr6+	PBBs	PBDEs
前面ベゼル		0	0	0	0	0	0
背面カバー		0	0	0	0	0	0
スタンド		0	0	0	0	0	0
LCDパネル	WLED	適用除 外の	0	0	0	0	0
LCD/\\$/	CCFL	適用除 外の	適用除 外の	0	0	0	0
РСВА		適用除 外の	0	0	0	0	0
ケーブル&ワイヤ		適用除 外の	0	0	0	0	0
リモコン		適用除 外の	0	0	0	0	0
740 100000000000000000000000000000000000							

とされた項目に対応することを意味します。


JIS C 0950

取扱説明書に従って正しい取り扱いをし て下さい。

# 7. Customer care and warranty

## 7.1 Philips' Flat Panel Monitors Pixel Defect Policy

Philips strives to deliver the highest quality products. We use some of the industry's most advanced manufacturing processes and practice stringent quality control. However, pixel or sub pixel defects on the TFT Monitor panels used in flat panel monitors are sometimes unavoidable. No manufacturer can guarantee that all panels will be free from pixel defects, but Philips guarantees that any monitor with an unacceptable number of defects will be repaired or replaced under warranty. This notice explains the different types of pixel defects and defines acceptable defect levels for each type. In order to qualify for repair or replacement under warranty, the number of pixel defects on a TFT Monitor panel must exceed these acceptable levels. For example, no more than 0.0004% of the sub pixels on a monitor may be defective. Furthermore, Philips sets even higher quality standards for certain types or combinations of pixel defects that are more noticeable than others. This policy is valid worldwide.



### Pixels and Sub pixels


A pixel, or picture element, is composed of three sub pixels in the primary colors of red, green and blue. Many pixels together form an image. When all sub pixels of a pixel are lit, the three colored sub pixels together appear as a single white pixel. When all are dark, the three colored sub pixels together appear as a single black pixel. Other combinations of lit and dark sub pixels appear as single pixels of other colors.

### Types of Pixel Defects


Pixel and sub pixel defects appear on the screen in different ways. There are two categories of pixel defects and several types of sub pixel defects within each category.

### Bright Dot Defects

Bright dot defects appear as pixels or sub pixels that are always lit or 'on'. That is, a bright dot is a sub-pixel that stands out on the screen when the monitor displays a dark pattern. There are the types of bright dot defects.



One lit red, green or blue sub pixel.



Two adjacent lit sub pixels:

- Red + Blue = Purple
- Red + Green = Yellow
- Green + Blue = Cyan (Light Blue)




Three adjacent lit sub pixels (one white pixel).

### Note

A red or blue bright dot must be more than 50 percent brighter than neighboring dots while a green bright dot is 30 percent brighter than neighboring dots.


### Black Dot Defects

Black dot defects appear as pixels or sub pixels that are always dark or 'off'. That is, a dark dot is a sub-pixel that stands out on the screen when the monitor displays a light pattern. These are the types of black dot defects.



### Proximity of Pixel Defects

Because pixel and sub pixels defects of the same type that are near to one another may be more noticeable, Philips also specifies tolerances for the proximity of pixel defects.



### Pixel Defect Tolerances

In order to qualify for repair or replacement due to pixel defects during the warranty period, a TFT Monitor panel in a Philips flat panel monitor must have pixel or sub pixel defects exceeding the tolerances listed in the following tables.

BRIGHT DOT DEFECTS	ACCEPTABLE LEVEL
1 lit subpixel	3
2 adjacent lit subpixels	1
3 adjacent lit subpixels (one white pixel)	0
Distance between two bright dot defects*	>15mm
Total bright dot defects of all types	3
BLACK DOT DEFECTS	ACCEPTABLE LEVEL
1 dark subpixel	5 or fewer
2 adjacent dark subpixels	2 or fewer
3 adjacent dark subpixels	0
Distance between two black dot defects*	>15mm
Total black dot defects of all types	5 or fewer
TOTAL DOT DEFECTS	ACCEPTABLE LEVEL
Total bright or black dot defects of all types	5 or fewer

### Note

- 1. 1 or 2 adjacent sub pixel defects = 1 dot defect
- 2. This monitor is ISO9241-307 compliant(ISO9241-307: Ergonomic requirement , analysis and compliance test methods for electronic visual displays)
- 3. ISO9241-307 is the successor of formerly known ISO13406 standard, which is withdrawn by the International Organisation for Standardisation (ISO) per: 2008-11-13.

## 7.2 Customer Care & Warranty

For warranty coverage information and additional support requirement valid for your region, please visit <u>www.philips.com/support</u> website for details. You may also contact your local Philips Customer Care Center number listed below.

Country	CSP	Hotline Number	Price	Opening Hours
Austria	RTS	+43 0810 000206	€ 0.07	Mon to Fri : 9am - 6pm
Belgium	Ecare	+32 078 250851	€ 0.06	Mon to Fri : 9am - 6pm
Cyprus	Alman	800 92 256	Free of charge	Mon to Fri : 9am - 6pm
Denmark	Infocare	+45 3525 8761	Local call tariff	Mon to Fri : 9am - 6pm
Finland	Infocare	+358 09 2290 1908	Local call tariff	Mon to Fri : 9am - 6pm
France	Mainteq	+33 082161 1658	€ 0.09	Mon to Fri : 9am - 6pm
Germany	RTS	+49 01803 386 853	€ 0.09	Mon to Fri : 9am - 6pm
Greece	Alman	+30 00800 3122 1223	Free of charge	Mon to Fri : 9am - 6pm
Ireland	Celestica	+353 01 601 1161	Local call tariff	Mon to Fri : 8am - 5pm
Italy	Anovo Italy	+39 840 320 041	€ 0.08	Mon to Fri : 9am - 6pm
Luxembourg	Ecare	+352 26 84 30 00	Local call tariff	Mon to Fri : 9am - 6pm
Netherlands	Ecare	+31 0900 0400 063	€ 0.10	Mon to Fri : 9am - 6pm
Norway	Infocare	+47 2270 8250	Local call tariff	Mon to Fri : 9am - 6pm
Poland	MSI	+48 0223491505	Local call tariff	Mon to Fri : 9am - 6pm
Portugal	Mainteq	800 780 902	Free of charge	Mon to Fri : 8am - 5pm
Spain	Mainteq	+34 902 888 785	€ 0.10	Mon to Fri : 9am - 6pm
Sweden	Infocare	+46 08 632 0016	Local call tariff	Mon to Fri : 9am - 6pm
Switzerland	ANOVO CH	+41 02 2310 2116	Local call tariff	Mon to Fri : 9am - 6pm
United Kingdom	Celestica	+44 0207 949 0069	Local call tariff	Mon to Fri : 8am - 5pm

### Contact Information for WESTERN EUROPE region:

### Contact Information for China:

Country	Call center	Consumer care number
China	PCCW Limited	4008 800 008

### Contact Information for NORTH AMERICA :

Country	Call center	Consumer care number
U.S.A.	EPI-e-center	(877) 835-1838
Canada	EPI-e-center	(800)479-6696

#### 7. Customer care and warranty

### Contact Information for CENTRAL AND EASTERN EUROPE region:

Country	Call center	CSP	Consumer care number	
Belarus	NA	IBA	+375 17 217 3386 +375 17 217 3389	
Bulgaria	NA	LAN Service	+359 2 960 2360	
Croatia	NA	MR Service Ltd	+385 (01) 640 1111	
Czech Rep.	NA	Asupport	420 272 188 300	
Estonia	NA	FUJITSU	+372 6519900(General) +372 6519972(workshop)	
Georgia	NA	Esabi	+995 322 91 34 71	
Hungary	NA	Profi Service	+36 1 814 8080(General) +36 1814 8565(For AOC&Philips only)	
Kazakhstan	NA	Classic Service I.I.c.	+7 727 3097515	
Latvia	NA	ServiceNet LV	+371 67460399 +371 27260399	
Lithuania	NA	UAB Servicenet	+370 37 400160(general) +370 7400088 (for Philips)	
Macedonia	NA	AMC	+389 2 3125097	
Moldova	NA	Comel	+37322224035	
Romania	NA	Skin	+40 21 2101969	
Russia	NA	CPS	+7 (495) 645 6746	
Serbia&Montenegro	NA	Kim Tec d.o.o.	+381 11 20 70 684	
Slovakia	NA	Datalan Service	+421 2 49207155	
Slovenia	NA	PC H.and	+386 1 530 08 24	
the republic of Belarus	NA	ServiceBy	+ 375 17 284 0203	
Turkey	NA	Tecpro	+90 212 444 4 832	
Ukraine	NA	Тораz	+38044 525 64 95	
Ukraine	NA	Comel	+380 5627444225	

### Contact Information for LATIN AMERICA region:

Country	Call center	Consumer care number	
Brazil		0800-7254101	
Argentina	Vermont	0800 3330 856	

### Contact Information for APMEA region:

Country	ASP	Consumer care number	Opening hours
Australia	AGOS NETWORK PTY LTD	1300 360 386	Mon.~Fri. 9:00am-5:30pm
New Zealand	Visual Group Ltd.	0800 657447	Mon.~Fri. 8:30am-5:30pm
Hong Kong Macau	Company: Smart Pixels Technology Ltd.	Hong Kong: Tel: +852 2619 9639 Macau:Tel: (853)-0800-987	Mon.~Fri. 9:00am-6:00pm Sat. 9:00am-1:00pm
India	REDINGTON INDIA LTD	Tel: 1 800 425 6396 SMS: PHILIPS to 56677	Mon.~Fri. 9:00am-5:30pm
Indonesia	PT. CORMIC SERVISINDO PERKASA	+62-21-4080-9086 (Customer Hotline) +62-8888-01-9086 (Customer Hotline)	Mon.~Thu. 08:30-12:00; 13:00-17:30 Fri. 08:30-11:30; 13:00-17:30
Korea	Alphascan Displays, Inc	1661-5003	Mon.~Fri. 9:00am-5:30pm Sat. 9:00am-1:00pm
Malaysia	R-Logic Sdn Bhd	+603 5102 3336	Mon.~Fri. 8:15am-5:00pm Sat. 8:30am-12:30am
Pakistan	TVONICS Pakistan	+92-213-6030100	Sun.~Thu. 10:00am-6:00pm
Singapore	Philips Electronics Singapore Pte Ltd (Philips Consumer Care Center)	(65) 6882 3966	Mon.~Fri. 9:00am-6:00pm Sat. 9:00am-1:00pm
Taiwan	FETEC.CO	0800-231-099	Mon.~Fri. 09:00 - 18:00
Thailand	Axis Computer System Co., Ltd.	(662) 934-5498	Mon.~Fri. 8:30am~05:30pm
South Africa	Computer Repair Technologies	011 262 3586	Mon.~Fri. 8:00am~05:00pm
Israel	Eastronics LTD	1-800-567000	Sun.~Thu. 08:00-18:00
Vietnam	FPT Service Informatic Company Ltd Ho Chi Minh City Branch	+84 8 38248007 Ho Chi Minh City +84 5113.562666 Danang City +84 5113.562666 Can tho Province	Mon.~Fri. 8:00-12:00, 13:30- 17:30,Sat. 8:00-12:00
Philippines	EA Global Supply Chain Solutions ,Inc.	(02) 655-7777; 6359456	Mon.~Fri. 8:30am~5:30pm
Armenia Azerbaijan Georgia Kyrgyzstan Tajikistan	Firebird service centre	+97 14 8837911	Sun.~Thu. 09:00 - 18:00
Uzbekistan	Soniko Plus Private Enterprise Ltd	+99871 2784650	Mon.~Fri. 09:00 - 18:00
Turkmenistan	Technostar Service Centre	+(99312) 460733, 460957	Mon.~Fri. 09:00 - 18:00
Japan	フィリップスモニター・サ ポ ートセンター	0120-060-530	Mon.~Fri. 10:00 - 17:00

## 8. Troubleshooting & FAQs

### 8.1 Troubleshooting

This page deals with problems that can be corrected by a user. If the problem still persists after you have tried these solutions, contact Philips customer service representative.

### 1 Common Problems

### No Picture (Power LED not lit)

- Make sure the power cord is plugged into the power outlet and into the back of the monitor.
- First, ensure that the power button on the front of the monitor is in the OFF position, then press it to the ON position.

### No Picture (Power LED is White)

- Make sure the computer is turned on.
- Make sure the signal cable is properly connected to your computer.
- Make sure the monitor cable has no bent pins on the connect side. If yes, repair or replace the cable.
- The Energy Saving feature may be activated

### Screen says



- Make sure the monitor cable is properly connected to your computer. (Also refer to the Quick Start Guide).
- Check to see if the monitor cable has bent pins.
- Make sure the computer is turned on.

### AUTO button doesn't function

• The auto function is applicable only in VGA-Analog mode. If the result is not satisfactory, you can do manual adjustments via the OSD menu.

### Note

The Auto Function is not applicable in DVI-Digital mode as it is not necessary.

### Visible signs of smoke or sparks

- Do not perform any troubleshooting steps
- Disconnect the monitor from mains power source immediately for safety
- Contact with Philips customer service representative immediately.

### 2 Imaging Problems

### Image is not centered

- Adjust the image position using the "Auto" function in OSD Main Controls.
- Adjust the image position using the Phase/ Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

### Image vibrates on the screen

• Check that the signal cable is properly securely connected to the graphics board or PC.

### Vertical flicker appears



- Adjust the image using the "Auto" function in OSD Main Controls.
- Eliminate the vertical bars using the Phase/ Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

### Horizontal flicker appears

-	·
-	

- Adjust the image using the "Auto" function in OSD Main Controls.
- Eliminate the vertical bars using the Phase/ Clock of Setup in OSD Main Controls. It is valid only in VGA mode.

#### 8. Troubleshooting & FAQs

### Image appears blurred, indistinct or too dark

• Adjust the contrast and brightness on On-Screen Display.

## An "after-image", "burn-in" or "ghost image" remains after the power has been turned off.

- Uninterrupted display of still or static images over an extended period may cause "burn in", also known as "after-imaging" or "ghost imaging", on your screen. "Burnin", "after-imaging", or "ghost imaging" is a well-known phenomenon in LCD panel technology. In most cases, the "burned in" or "after-imaging" or "ghost imaging" will disappear gradually over a period of time after the power has been switched off.
- Always activate a moving screen saver program when you leave your monitor unattended.
- Always activate a periodic screen refresh application if your LCD monitor will display unchanging static content.
- Failure to activate a screen saver, or a periodic screen refresh application may result in severe "burn-in" or "after-image" or "ghost image" symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

## Image appears distorted. Text is fuzzy or blurred.

• Set the PC's display resolution to the same mode as monitor's recommended screen native resolution.

## Green, red, blue, dark, and white dots appears on the screen

• The remaining dots are normal characteristic of the liquid crystal used in today's technology, Please refer the pixel policy for more detail.

## The "power on" light is too strong and is disturbing

 You can adjust "power on" light using the power LED Setup in OSD main Controls. For further assistance, refer to the Consumer Information Centers list and contact Philips customer service representative.

### 8.2 SmartControl Premium FAQs

- Q1. I change the monitor on a PC to a different one and the SmartControl Premium becomes un-usable, what do I do?
- Ans.: Restart your PC and see if SmartControl Premium can work. Otherwise, you will need to remove and re-install SmartControl Premium to ensure proper driver is installed.

### Q2. The SmartControl Premium functions worked well before, but it does not work anymore, what can I do?

- Ans.: If the following actions were executed, the monitor driver may need to be reinstalled.
- Changed video graphic adapter to another one
- Updated video driver
- Activities on OS, such as service pack or patch
- Run Windows Update and updated monitor and/or video driver
- Windows was booted with the monitor power off or disconnected.
- To find out, please right click My Computer and click on Properties->Hardware-> Device Manager.
- If you see "Plug and Play Monitor" shows under Monitor, then you need to re-install. Simply remove SmartControl Premium and re-install it.

#### 8.Troubleshooting & FAQs

- Q3. After installing SmartControl Premium, when clicking on SmartControl Premium tab, nothing shows up after a while or a failure message shows, what happened?
- Ans.: It might be your graphic adaptor is not compatible with the SmartControl Premium. If your graphic adaptor is one of the above mentioned brands, try to download the most updated graphic adaptor driver from corresponding companies' web site. Install the driver. Remove SmartControl Premium, and re-install it once more.

If it is still not working, we are sorry that the graphic adaptor is not supported. Please visit Philips website and check if an updated SmartControl Premium driver is available.

- Q4. When I click on Product Information, only partial information is shown, what happened?
- Ans.: It might be your graphic card adaptor driver is not the most updated version which fully supporting DDC/ Cl interface. Please try to download the most updated graphic adaptor driver from corresponding companies' web site. Install the driver. Remove SmartControl Premium and re-install it once more.



### Q5. I forgot my PIN for Theft Deterrence Function. How can I do?

Ans.: Philips Service center has a right to ask for legitimate identification and authorization, in order to establish ownership of the monitor.

### 8.3 General FAQs

### Q1: When I install my monitor what should I do if the screen shows 'Cannot display this video mode'?

- Ans.: Recommended resolution for this monitor: 1920 × 1080 @ 60 Hz.
- Unplug all cables, then connect your PC to the monitor that you used previously.
- In the Windows Start Menu, select Settings/ Control Panel. In the Control Panel Window, select the Display icon. Inside the Display Control Panel, select the 'Settings' tab. Under the setting tab, in box labelled 'desktop area', move the sidebar to 1920 × 1080 pixels.
- Open 'Advanced Properties' and set the Refresh Rate to 60 Hz, then click OK.
- Restart your computer and repeat step 2 and 3 to verify that your PC is set at 1920 x 1080 @ 60 Hz.
- Shut down your computer, disconnect your old monitor and reconnect your Philips LCD monitor.
- Turn on your monitor and then turn on your PC.

## Q2: What is the recommended refresh rate for LCD monitor?

- Ans.: Recommended refresh rate in LCD monitors is 60 Hz, In case of any disturbance on screen, you can set it up to 75 Hz to see if that removes the disturbance.
- Q3: What are the .inf and .icm files on the CD-ROM? How do I install the drivers (.inf and .icm)?
- Ans.: These are the driver files for your monitor. Follow the instructions in your user manual to install the drivers. Your computer may ask you for monitor drivers (.inf and .icm files) or a driver disk when you first install your monitor. Follow the instructions to insert the (

companion CD-ROM) included in this package. Monitor drivers (.inf and .icm files) will be installed automatically.

### Q4: How do I adjust the resolution?

Ans.: Your video card/graphic driver and monitor together determine the available resolutions. You can select the desired resolution under Windows® Control Panel with the "Display properties".

## Q5: What if I get lost when I am making monitor adjustments via OSD?

Ans.: Simply press the OK button, then select 'Reset' to recall all of the original factory settings.

## Q6: Is the LCD screen resistant to scratches?

Ans.: In general it is recommended that the panel surface is not subjected to excessive shocks and is protected from sharp or blunt objects. When handling the monitor, make sure that there is no pressure or force applied to the panel surface side. This may affect your warranty conditions.

### Q7: How should I clean the LCD surface?

Ans.: For normal cleaning, use a clean, soft cloth. For extensive cleaning, please use isopropyl alcohol. Do not use other solvents such as ethyl alcohol, ethanol, acetone, hexane, etc.

## Q8: Can I change the color setting of my monitor?

- Ans.: Yes, you can change your color setting through OSD control as the following procedures,
- Press "OK" to show the OSD (On Screen Display) menu
- Press "Down Arrow" to select the option "Color" then press "OK" to enter color setting, there are three settings as below.

- 1. Color Temperature; The six settings are 5000K, 6500K, 7500K, 8200K, 9300K and 11500K. With settings in the 5000K range the panel appears "warm, with a red-white color tone", while a 11500K temperature yields "cool, bluewhite toning".
- 2. sRGB; this is a standard setting for ensuring correct exchange of colors between different device (e.g. digital cameras, monitors, printers, scanners, etc)
- User Define; the user can choose his/ her preference color setting by adjusting red, green blue color.

### Note

A measurement of the color of light radiated by an object while it is being heated. This measurement is expressed in terms of absolute scale, (degrees Kelvin). Lower Kevin temperatures such as 2004K are red; higher temperatures such as 9300K are blue. Neutral temperature is white, at 6504K.

## Q9: Can I connect my LCD monitor to any PC, workstation or Mac?

Ans.: Yes. All Philips LCD monitors are fully compatible with standard PCs, Macs and workstations. You may need a cable adapter to connect the monitor to your Mac system. Please contact your Philips sales representative for more information.

### Q10: Are Philips LCD monitors Plug-and-Play?

Ans.: Yes, the monitors are Plug-and-Play compatible with Windows 8/7/Vista/XP/ NT, Mac OSX, Linux

### Q11: What is Image Sticking, or Image Burnin, or After Image, or Ghost Image in LCD panels?

Ans.: Uninterrupted display of still or static images over an extended period

#### 3. Troubleshooting & FAQs

may cause "burn in", also known as "after-imaging" or "ghost imaging", on your screen. "Burn-in", "after-imaging", or "ghost imaging" is a well-known phenomenon in LCD panel technology. In most cases, the "burned in" or "atter-imaging" or "ghost imaging" will disappear gradually over a period of time after the power has been switched off.

Always activate a moving screen saver program when you leave your monitor unattended.

Always activate a periodic screen refresh application if your LCD monitor will display unchanging static content.

### Warning

Failure to activate a screen saver, or a periodic screen refresh application may result in severe "burn-in" or "after-image" or "ghost image" symptoms that will not disappear and cannot be repaired. The damage mentioned above is not covered under your warranty.

- Q12: Why is my Display not showing sharp text, and is displaying jagged characters?
- Ans.: Your LCD monitor works best at its native resolution of 1920 × 1080 @ 60 Hz. For best display, please use this resolution.

### Q13: How to unlock/lock my hot key?

Ans.: Please press ≡/OK for 10 seconds to unlock/lock the hot key, by doing so, your monitor pops out "Attention" to show the unlock/lock status as shown below illustrators.



### 8.4 MHL FAQs

## Q1: I cannot see my mobile device image on the monitor screen

#### Ans.:

- Please check if your mobile device is MHL certified.
- You also need to have a MHL certified cable to connect the devices.
- Make sure that you have connected to the MHL-HDMI port, and that correct input is selected on the Monitor via the input selector (front bezel or OSD)
- The product is officially MHL-certified. As this monitor is a passive display, if you encounter any unexpected troubles when using the MHL input, please refer to the mobile device's user manual or contact the manufacturer of the mobile device.



- Make sure your mobile device has not entered standby (sleep) mode. If it has, then you will see a notification message on the display. Once the mobile device wakes up, the monitor's display will wake and show the images. You may need to make sure that the correct input is selected if in between you have used or connected any other device
- Q2. Why is the image on the monitor display of poor quality? My mobile device looks far better.

### Ans.:

- The MHL standard defines fixed 1080p@30hz for output, and input. This monitor complies with this standard.
- The image quality depends on the quality of the original contents. If the content is of high resolution (example HD or 1080p), then it will appear in HD or 1080p on this

#### 8.Troubleshooting & FAQs

monitor display. If the original content is in low resolution (example QVGA) it may look good on the mobile device due to its small screen size, but will look to be of lower quality on the large screen monitor display.

## Q3. I cannot hear sound from the monitor display.

### Ans.:

- Make sure your monitor display has builtin speakers and the volume is turned on the monitor side, and also on the mobile device side. You may also want to use optional headphones.
- If your monitor display does not have in built speakers, then you can connect optional headphones to the output on the monitor. Please ensure that the volume is turned on the monitor side, and also on the mobile device side.

## For further information or FAQ, please visit official website of MHL org:

### http://www.mhlconsortium.org

### 8.5 Bluetooth FAQs

- Q1: My device doesn't have Bluetooth; can I use Bluetooth on this Philips display?
- Ans.: This Philips display receives the signal via Bluetooth technology. To enjoy this Bluetooth function, your source device has to be certified for Bluetooth.

# Q2: My devices are with Bluetooth, why can I not use Bluetooth on the Philips display?

Ans.: In case your source device does not connect or work correctly, check with your device FAQ or vendor directly for direction. Note that this is not a fault of this Philips display.

## Q3: Do I need any cables to enable the Bluetooth on this Philips display?

Ans.: No, to enable the Bluetooth function, it does not require cables to transfer your music to this Philips display.



© 2014 Koninklijke Philips N.V. All rights reserved.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. and are used under license from Koninklijke Philips N.V.

Specifications are subject to change without notice.

Version: M5275CE1T