

Philips LCD monitor

V Line

20 (Viewable 19.5" / 49.4 cm)

206V6QSB

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Equipped with SmartContrast, it's a great choice!

Vivid pictures every time

- · AH-IPS display gives awesome images with wide viewing angles
- SmartContrast for rich black details

Great choice

- Compact design saves space
- Mercury Free eco-friendly display
- · VESA mount allows for flexibility



Highlights

63

AH-IPS displays use an advanced technology which

almost any angle. Unlike standard TN panels, AH-IPS

displays gives you remarkably crisp images with vivid

colors, making it ideal not only for Photos, movies

and web browsing, but also for professional applications which demand color accuracy and

consistent brightness at all times.

SmartContrast

gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from

AH-IPS technology

Specifications

Picture/Display

- LCD panel type: AH-IPS LCD
- · Backlight type: W-LED system
- Panel Size: 19.45 inch / 49.4 cm
- Effective viewing area: 418.61 (H) x 262.35 (V)
- Aspect ratio: 16:10
- Optimum resolution: 1440 x 900 @ 60 Hz
- Response time (typical): 14 (GtG) ms
- Brightness: 250 cd/m²
- SmartContrast: 10,000,000:1
- Contrast ratio (typical): 1000:1
- Pixel pitch: 0.291 x 0.291 mm
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Display colors: 16.7 M
- Scanning Frequency: 30 -83 kHz (H) / 56 -76 Hz (V)
- sRGB

Connectivity

- Signal Input: VGA (Analog), DVI-D (digital, HDCP)
- Sync Input: Separate Sync, Sync on Green

Convenience

- User convenience: Power On/Off, Menu/OK, Brightness/Back, 4:3 Wide/Up, Auto/Down
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukranian
- · Other convenience: Kensington lock, VESA mount (100x100mm)
- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 7, Windows 8

Stand

• Tilt: -5/20 degree













Power

- On mode: 17.17 W (typ.), 18.1 W (max.)
- Standby mode: 0.5 W (typ.)
- Off mode: 0.5 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: External, 100-240VAC, 50-60Hz

Dimensions

- Product with stand (mm): 452 x 371 x 200 mm
- Product without stand (mm): $452 \times 304 \times 40 \text{ mm}$
- Packaging in mm (WxHxD): 508 x 432 x 111 mm

Weight

- Product with stand (kg): 2.28 kg
- Product without stand (kg): 2.00 kg
- Product with packaging (kg): 3.70 kg

Operating conditions

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF: 50,000 (excluding backlight) hour(s)

Sustainability


- · Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Compliance and standards

· Regulatory Approvals: CE Mark, WEEE, CECP, CCC

Cabinet

- · Color: Black
- Finish: Glossy (front bezel) / Texture (rear cover)



Mercury Free Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

SmartContrast is a Philips technology that analyzes

adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and videos or when playing games where dark hues are displayed. When Economy mode is selected, contrast is adjusted and backlighting fine-


the contents you are displaying, automatically



© 2016 Koninklijke Philips N.V. All Rights reserved.

12 NC: 8670 001 40867 EAN: 87 12581 74169 3 Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com



Smart response time is the optimum value from either GtG or GtG (BW) tests.

