

Philips FHD LCD monitor with USB-C dock

B Line 24 (23.8" / 60.5 cm diag.) Full HD (1920 x 1080)



241B7QUPBEB

Simplify your connections

with revolutionary USB-C

Simple USB-C connection and crystal-clear IPS images. The Philips B line monitor with USB-C connector allows simple notebook docking via one cable for fast data and video to full HD IPS display, and even notebook charging.

Designed for people

- All your connections through one USB-C cable
- Narrow border display for seamless appearance
- SmartErgoBase enables people-friendly ergonomic adjustments
- Less eye fatigue with Flicker-free technology
- LowBlue Mode for easy on-the-eyes productivity
- EasyRead mode for a paper-like reading experience

Excellent performance

• IPS technology for full colors and wide viewing angles

Easy to experience

• Built-in stereo speakers for multimedia

Sustainable Eco-friendly solution

• PowerSensor saves up to 80% energy costs



FHD LCD monitor with USB-C dock B Line 24 (23.8" / 60.5 cm diag.), Full HD (1920 x 1080)

Highlights

USB-C Docking



SmartErgoBase



The new USB 3.1 Type-C cable with features a slim and reversible connector and offers easy one-cable-docking. With USB 3.1 you get the fastest data speeds, 20 times as fast as USB 2.0, allowing you to transfer data from a HDD to your PC faster than ever. Simplify by connecting all your peripherals to your monitor as a dock with one cable to the notebook, including high resolution video output from your PC to monitor. Additionally, USB-C with power delivery, can even enable you to power and charge your notebook from the monitor, eliminating the need for extra power cables.

UltraNarrow Border



The new Philips displays feature ultra-narrow borders which allow for minimal distractions and maximum viewing size. Especially suited for multi-display or tiling setup like gaming, graphic design and professional applications, the ultra-narrow border display gives you the feeling of using one large display. The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base's people-friendly height, swivel, tilt and rotation angle adjustments position the monitor for maximum comfort that can ease the physical strains of a long workday; cable management reduces cable clutter and keeps the workspace neat and professional.

Flicker-free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue

light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

EasyRead mode



EasyRead mode for a paper-like reading experience

IPS technology



IPS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle - even in 90 degree Pivot mode! Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

Built-in stereo speakers

A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

















241B7QUPBEB/75

Specifications

Picture/Display

- LCD panel type: IPS technology
- Backlight type: W-LED system
- Panel Size: 23.8 inch / 60.5 cm
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
 Effective viewing area: 527 x 296.5 mm
- Aspect ratio: 16:9
- Optimum resolution: 1920 x 1080 @ 60Hz
- Pixel Density: 93 PPI
- Response time (typical): 5 ms (Gray to Gray)*
- Brightness: 250 cd/m²
- Contrast ratio (typical): 1,000:1
- SmartContrast: 20,000,000:1
- Pixel pitch: 0.275 x 0.275 mm
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10 Flicker-free
- Picture enhancement: SmartImage
- Display colors: 16.7 M
- Color gamut (typical): NTSC 85%*, sRGB 102%*
- Scanning Frequency: 30 83 kHz (H) / 56 76 Hz (V)
- sRGB
- LowBlue Mode
- EasyRead

Connectivity

- Signal Input: VGA (Analog), DisplayPort 1.2 x 1, HDMI 1.4 x 1, USB-C 3.1 Gen 2 x 1 (upstream, power delivery up to 60 W), USB 3.0×2 (downstream, w/ fast charging)
- Signal Output: DisplayPort out
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): PC audio-in, Headphone out
- RJ45: Ethernet LAN (10M/100M/1G)

USB docking

- USB-C: Reversible plug connector
- · Super speed: Data and Video transfer
- DP: Built-in DisplayPort Alt mode
- USB-C power delivery: USB PD version 2.0
- USB-C max. power delivery: Upto 60 watts (5V/ 3A; 7V/3A; 9V/3A; 12V/3A; 15V/3A; 20V/3A)

Convenience

- Built-in Speakers: 2 W x 2
- User convenience: SmartImage, Input,
- PowerSensor, Menu, Power On/Off
- Control software: SmartControl
- OSD Languages: English, French, German, Italian, Portuguese, Russian, Simplified Chinese, Spanish,

Korean, Brazil Portuguese, Czech, Dutch, Finnish, Greek, Hungarian, Japanese, Polish, Swedish, Traditional Chinese, Turkish, Ukranian

- Other convenience: Kensington lock, VESA mount (100x100mm)
- Plug & Play Compatibility: DDC/CI (VGA only),
- Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

Stand

• Height adjustment: 150 mm

• Pivot: 90 degree

- Swivel: -175/175 degree
- Tilt: -5/30 degree

Power

- ECO mode: 11.8 W (typ.)
- On mode: 15.4 W (typ.) (EnergyStar 7.0 test method)
- Standby mode: <0.7 W (typ.)
- Off mode: <0.3 W (typ.)
- Energy Label Class: A
- · Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: External, 100-240VAC, 50-60Hz

Dimensions

- Product with stand(max height): 541 x 527 x
- 257 mm
- Product without stand (mm): 541 x 332 x 57 mm • Packaging in mm (WxHxD): 603 x 492 x 224 mm

Weight

- Product with stand (kg): 5.72 kg
- Product without stand (kg): 3.29 kg
- Product with packaging (kg): 8.94 kg

Operating conditions

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF (demonstrated): 70,000 hrs (excluded backlight)

Sustainability

- Environmental and energy: EnergyStar 7.0, PowerSensor, EPEAT Gold*, TCO edge, RoHS
- Recyclable packaging material: 100 %



I/O back panel connector diagram



Issue date 2019-03-11

© 2019 Koninklijke Philips N.V. All Rights reserved.

www.philips.com

Version: 3.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 48755 EAN: 87 12581 74822 7

- "IPS" word mark / trademark and related patents on technologies belong to their respective owners. * For Video transmission via USB-C, your Notebook/device must
- support USB-C DP Alt mode
- * For USB-C power and charging function, your Notebook/device must support USB-C standard Power Delivery specifications. Please check with your Notebook user manual or manufacturer for more details
- * Activities such as screen sharing, on-line streaming video and audio over the Internet can impact your network performance. Your hardware, network bandwidth and its performance will determine overall audio and video quality.
- NTSC Area based on CIE1976
- * sRGB Area based on CIE 1931 * Response time value equal to SmartResponse
- * EPEAT Gold or Silver is valid only where Philips registers the product. Please visit www.epeat.net for registration status in your country.
- * The notebook, keyboard, mouse as shown are for illustration
- purpose only, not included in the product. * The monitor may look different from feature images.

241B7OUPBEB/75

- Post consumer recycled plastic: 85%
- · Specific Substances: PVC / BFR free housing, Mercury free, Lead free

SEMKO, cETLus, CU-EAC, TCO edge, TUV Ergo,

TUV/GS, EPA, WEEE, UKRAINIAN, ICES-003,

Compliance and standards • Regulatory Approvals: CE Mark, FCC Class B,

RCM, VCCI

Front bezel: Black

· Rear cover: Black • Foot: Black

• Finish: Texture

Cabinet