

Philips Brilliance LED-backlit LCD monitor with PowerSensor

B Line 23" (58.4 cm) Full HD (1920 x 1080)







# Crisp images, efficient performance

# with PowerSensor saves energy

The Philips PowerSensor LED display using 65% post consumer recycled plastics and PVC, BFR free housing is ideal for eco-friendly productivity

# **Excellent performance**

- IPS technology for full colors and wide viewing angles
- DisplayPort offers audio and video over a single, long cable
- · Built-in stereo speakers for multimedia

# **Designed for people**

- SmartErgoBase enables people-friendly ergonomic adjustments
- Low bezel-to-table height for maximum reading comfort

# **Easy to experience**

- · SmartImage presets for easy optimized image settings
- USB Hub with 2 ports for easy connections

# Sustainable Eco-design

- PowerSensor saves up to 80% energy costs
- · Zero power consumption with 0 watt hard switch
- 65% post consumer recycled plastics with TCO Edge



# LED-backlit LCD monitor B Line 23" (58.4 cm), Full HD (1920 x 1080)

# Highlights

### **IPS** technology



IPS displays use an advanced technology which gives you extra wide viewing angles of 178/178 degree, making it possible to view the display from almost any angle - even in 90 degree Pivot mode! Unlike standard TN panels, IPS displays gives you remarkably crisp images with vivid colors, making it ideal not only for Photos, movies and web browsing, but also for professional applications which demand color accuracy and consistent brightness at all times.

# **DisplayPort**

DisplayPort is a digital link from PC to Monitor without any conversion. With higher capabilities than DVI standard, it is fully capable to support up to 15meter cables and 10.8 Gbps/sec data transfer. With this high performance and zero latency, you get the fastest imaging and refresh rates - making DisplayPort the best choice for not only general office or home use, but also for the demanding gaming and movies, video editing and more. It also keeps interoperability in mind via use of various adapters.

#### **Built-in stereo speakers**

A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

#### **SmartErgoBase**



The SmartErgoBase is a monitor base that delivers ergonomic display comfort and provides cable management. The base's peoplefriendly height, swivel, tilt and rotation angle adjustments position the monitor for maximum comfort that can ease the physical strains of a long workday; cable management reduces cable clutter and keeps the workspace neat and professional.

### Low bezel-to-table height



The Philips monitor, thanks to its advanced SmartErgoBase, can be lowered down almost to desk level for a comfortable viewing angle. Low bezel-to-table height is the perfect solution if you use bifocals, trifocals or progressive lens glasses for your computing work. Additionally, it allows for users with greatly different heights to

use the monitor in their preferred angle and height settings, helping them reduce fatigue and strain.

#### **S**martImage



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

# 2 Ports USB 2.0 HUB

USB Hub allows user to conveniently connect their plug and play multimedia devices such as USB memory devices, camera, portable HDD, Web camera, PDA, Printer and many other devices which has USB connection available. The conveniently located USB 2.0 Hub on the monitor allows USB 2.0 signals to pass thru to the computer. Note that many devices like cameras and HDD may need to be powered On independently, as they have higher power requirements than the monitor USB Hub can provide.



















# Specifications

# **Picture/Display**

- LCD panel type: IPS LCD
- Backlight type: W-LED system
- Panel Size: 23 inch / 58.4 cm
- Effective viewing area: 509.18 (H)  $\times$  286.41 (V)
- Aspect ratio: 16:9
- Optimum resolution: 1920 x 1080 @ 60Hz
- Response time (typical): 7 ms (GTG\_BW)\*
- Brightness: 250 cd/m<sup>2</sup>
- Contrast ratio (typical): 1000:1
- SmartContrast: 20,000,000:1
- Pixel pitch: 0.265 x 0.265 mm
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Picture enhancement: SmartImage
- Display colors: 16.7 M
- Scanning Frequency: 30 83 kHz (H) / 56 75 Hz (V) • sRGB

# Connectivity

- Signal Input: DisplayPort, DVI-D (digital, HDCP), VGA (Analog)
- USB: USB 2.0 x 2
- Sync Input: Separate Sync, Sync on Green
- Audio (In/Out): PC audio-in, Headphone out

#### Convenience

- Built-in Speakers: 1.5W x 2
- User convenience: SmartImage, Volume, PowerSensor, Menu, Power On/Off
- Control software: SmartControl Premium
- OSD Languages: English, French, German, Italian, Portuguese, Russian, Simplified Chinese, Spanish
- Other convenience: Kensington lock, VESA mount (100x100mm)
- Plug & Play Compatibility: DDC/CI, Mac OS X, sRGB, Windows 8.1 / 8 / 7

#### Stand

- Height adjustment: 110 mm
- Pivot: 90 degree
- Swivel: -65/65 degree
- Tilt: -5/20 degree

### Power

- ECO mode: 13.7 W (typ.)
- On mode: 20.2 W (typ.) (EnergyStar 6.0 test method)
- Standby mode: <0.3 W (typ.)
- Off mode: Zero watts with AC switch

- Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: 100-240VAC, 50-60Hz, Built-in

#### Dimensions

- Product with stand(max height): 547 x 507 x 227 mm
- Product with stand(max height): 21.5 x 20.0 x 8.9 inch
- Product without stand (mm):  $547 \times 343 \times 60$  mm
- Product without stand in inch:  $21.5 \times 13.5 \times 2.4$  inch
- Packaging in mm (WxHxD): 620 x 401 x 167 mm
  Packaging in inch (WxHxD): 24.4 x 15.8 x 6.6 inch
- Fackaging in inch (\*\*xHxD): 24.4 x 15.6 x 6

#### Weight

- Product with stand (kg): 5.70 kg
- Product with stand (lb): 12.54 lb
- Product without stand (kg): 3.90 kg
- Product without stand (lb): 8.58 lb
- Product with packaging (kg): 7.82 kg
- Product with packaging (Ib): 17.20 lb

#### **Operating conditions**

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF: 30,000 (backlight) hour(s)

#### **Sustainability**

- Environmental and energy: PowerSensor, EnergyStar
- 6.0, EPEAT Gold\*, TCO edge, RoHS
- Recyclable packaging material: 100 %
  Post consumer recycled plastic: 65%
- Post consumer recycled plastic: 65%
   Specific Substances: PVC / BFR free housing,
- Specific Substances: PVC / BFR free housing, Mercury free, Lead free

#### **Compliance and standards**

 Regulatory Approvals: BSMI, CE Mark, cETLus, FCC Class B, GOST, SASO, SEMKO, TCO 6.0, TUV Ergo, TUV/GS, WEEE

#### Cabinet

- Front bezel: Black
- Rear cover: Black
- Foot: Black
- Finish: Texture



Issue date 2018-03-26

© 2018 Koninklijke Philips N.V. All Rights reserved.

www.philips.com

Version: 3.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 20832 UPC: 6 09585 24432 0 \* EPEAT Gold is valid only where Philips registers the product. Please visit www.epeat.net for registration status in your country.

- \* "IPS" word mark / trademark and related patents on technologies belong to their respective owners.
- \* Response time value equal to SmartResponse
- e Philips N.V. \* EPEAT Gold is va