





VG2456V

Key Features


The ViewSonic® VG2456V is a 24" (23.8" viewable) docking monitor with premium video conferencing features such as a pop-up webcam, adjustable LED lighting and more to help you look your best when calling into a meeting. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB-C connectivity makes dual-monitor setup a breeze and provides up to 90W power delivery to your laptop. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need—whether you are working in the office, or from home.



24
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION



Product Description

The ViewSonic® VG2456V is a 24" (23.8" viewable) docking monitor with premium video conferencing features such as a pop-up webcam, adjustable LED lighting and more to help you look your best when calling into a meeting. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB-C connectivity makes dual-monitor setup a breeze and provides up to 90W power delivery to your laptop. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need—whether you are working in the office, or from home.

Specifications

More Information	
Display Size (in.)	24

Viewable Area (in.)	23.8
Panel Type	IPS
Resolution	1920 x 1080
Resolution Type	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80M:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit + Hi-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Flicker-Free	Yes
Blue Light Filter	Yes
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
USB Type A	2
USB Type B	1
USB Type C	1
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	136
Eco Mode (optimized)	137
Consumption (typical)	139
Consumption (max)	165
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5
Power Supply	Internal
Cable Organization	Yes
Headphone Hook	No

Microphone	noise-cancelling microphone array
Kensington Lock Slot	1
Webcam	Yes
Physical Controls	Key 1 (audio focus), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Conference Mode, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 85 KHz
Frequency Vertical	50 ~ 75 Hz
Height Adjust	110 mm / 4.3 in
Swivel	60°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 40°
Net (lbs)	15
Net Without Stand (lbs)	10
Gross (lbs)	20.9
Net (kg)	6.8
Net Without Stand (kg)	4.5
Gross (kg)	9.5
Packaging (in.)	23.9 " (W) x 16.2 " (H) x 8.3 " (D)
Physical (in.)	21.2 " (W) x 15.82~20.15 " (H) x 8 " (D)
Physical Without Stand (in.)	21.2 " (W) x 13.7 " (H) x 2.2 " (D)
Packaging (mm)	606 mm (W) x 411 mm (H) x 210 mm (D)
Physical (mm)	539 mm (W) x 401.83~511.83 mm (H) x 202 mm (D)
Physical Without Stand (mm)	539 mm (W) x 349 mm (H) x 56 mm (D)
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy
PACKAGE CONTENTS	LCD Display, Power Cable, HDMI Cable, USB Type C cable, USB A/B Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)

888.881.8781 
email: salesinfo@viewsonic.com 