

22" (21.5" viewable) Full HD SuperClear® IPS LED Monitor



Frameless Bezel Design and Advanced HDMI® Connectivity

VA2259-smh



Available for this model:
**Privacy Filter
Screen Protector**
VSPF2150
(Sold Separately)

With flexible connectivity, wide-angle viewing, and amazing screen performance, the ViewSonic® VA2259-smh delivers solid multimedia features and a sleek design at a great value. Featuring SuperClear IPS panel technology, the VA2259-smh delivers stunning color and contrast at nearly any viewing angle. A minimalistic design, edge-to-edge screen, and frameless bezel make this an ideal monitor for nearly seamless multi-screen setups. Whether for working at the office, or enjoying entertainment at home, the VA2259-smh also features an HDMI port for flexible connectivity to PCs, laptops, gaming consoles, and other multimedia devices. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, makes the VA2259-smh a great overall value choice.

Key Features:

SuperClear IPS panel technology

Frameless design

Versatile connectivity

Full HD 1080p resolution

Superior color rendering and intuitive settings

Designed for:

Business

Home

22" (21.5" viewable) Full HD SuperClear® IPS LED Monitor



VA2259-smh



Specifications

LCD PANEL	Type	IPS Type, a-si TFT Active Matrix LCD
	Display Area	18.8" horizontal x 10.6" vertical; 21.5" diagonal
	Optimum Resolution	1920x1080
	Brightness	250 cd/m ² (typ.)
	Contrast Ratio	1000:1 (typ.)
	Dynamic Contrast Ratio	50M:1
	Viewing Angles	178° horizontal, 178° vertical
	Colors	16.7M (6bit + A-FRC)
	Response Time	5ms (GTG)
	Backlight	White-light LED
VIDEO INPUT	Digital	HDMI
	Analog	VGA
AUDIO OUTPUT	Frequency	Fh: 24~82kHz, Fv: 50~75Hz
	Sync	Separate Sync, Composite Sync, Sync on Green, TMDS
COMPATIBILITY	Speakers	2-watt (x2)
	PC	Up to 1920x1080 non-interlaced
CONNECTOR	Mac®	Up to 1920x1080
	Video In	HDMI, VGA
CONTROLS	Audio In	3.5mm mini jack
	Headphones	3.5mm mini jack
	Power	3-pin plug (CEE22)
	Front Panel Buttons	1, 2, Down, Up, Power
	OSD	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

ERGONOMICS	Tilt	Forward 5° / Back 22°
POWER	Voltage	AC 100–240V (universal), 50 / 60Hz
	Consumption	25W (typ.) / 27W (max.)
	Optimize	20W (typ.)
	Conserve	16W (typ.)
OPERATING CONDITIONS	Temperature	32–104° F (0–40° C)
	Humidity	20–90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with Stand	19.7 x 14.8 x 7.9 in. / 499.7 x 375.1 x 200 mm
	Physical without Stand	19.7 x 11.9 x 1.8 in. / 499.7 x 301.9 x 45.5 mm
	Packaging	22.1 x 17.4 x 6.1 in. / 562 x 443 x 155 mm
WEIGHT	Net with Stand	6.3 lb. / 2.8 kg
	Net without Stand	5.5 lb. / 2.5 kg
	Gross	9.5 lb. / 4.3 kg
WALL MOUNT	VESA compatible	100 x 100 mm
REGULATIONS		CE EMC, CB, RoHS Green BOM & RoHS DoC, REACH SVHC List and DoC, ErP, WEEE, US NRTL w/ CA, FCC-B w/ ICES003, ENERGY STAR, EPEAT Silver, Mexico CoC, Mexico Energy
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state, or federal laws
WARRANTY		Three-year limited warranty on parts, labor and backlight

Optional Accessories

HDMI to DVI cable 6FT	CB-00008948
Desktop Display Wall Mount Kit	LCD-WMK-001

What's in the box?

VA2259-smh monitor, Power cable, Audio cable, VGA cable, Quick Start Guide, ViewSonic Wizard CD

